PCoIP Management Console

25.06

Table of contents

PCoIP Management Console Overview	8
About PCoIP Management Console Releases	9
PCoIP Management Console Modes	10
PCoIP Management Console Free	11
PCoIP Management Console Enterprise	11
Quick Links	12
What's New in this Release	13
New Features and Changes	13
System Requirements	14
Management Console Formats	14
MC Upgrade Dependency Packages for Online and Darksite	14
System Configuration and Requirements	15
Licensing for PCoIP Management Console	16
Port Numbers	16
Network	16
Browser Compatibility	17
PCoIP Endpoint Firmware	17
Where to Find Information about Other Components	18
Installation Guide	19
Installing the PCoIP Management Console and Configuring Your System	19
Installation Overview	19
Using IPv6 with Management Console	20
Management Console Host Requirements	20
Limitations	20
Installing PCoIP Management Console using vSphere	22

Generate and Create a Management Console AMI	24
Install the Management Console after the VMDK Import	24
Install the Management Console during VMDK generation	29
Management Console as an RPM	34
Management Console RPM Installation and Removal	35
Remove Management Console	37
Moving to a New Version of Management Console	39
Running Different PCoIP Management Console Versions in Parallel	40
Administrators' Guide	42
PCoIP Management Console Administrators' Guide	42
Getting Started	43
Log In to the PCoIP Management Console Web User Interface	43
Understanding the PCoIP Management Console Dashboard	47
Managing Licenses Online	51
Managing Licenses Offline	57
Uploading Endpoint Firmware to the PCoIP Management Console	62
Setting up Security	63
Active Directory Authentication	66
Identity Provider (IDP) Integration with Management Console (Enterprise)	72
Securing User Passwords	78
Securing PCoIP Management Console User Passwords	78
Accessing the PCoIP Management Console Virtual Machine Console	79
Changing the PCoIP Management Console Web Interface Default Password	83
Changing the PCoIP Management Console Virtual Machine Default 'Root' Password	86
Moving to a Newer Version	87
Migrating PCoIP Management Console to a Newer Release Using OVA	87
Upgrading using RPM	93
Moving Between IPv4 and IPv6	98
Migrating from PCoIP Management Console 1	107

Managing Firmware	113
Managing PCoIP Zero Client and Remote Workstation Card Firmware	113
Upgrading Endpoints to Firmware 5.0 or Later	114
Downgrading Endpoints to an Older Firmware	117
Discovering Endpoints	121
Discovery Process Overview	121
Configuring DHCP for Endpoints that use Auto Discovery	127
Configuring DNS for Endpoints that use Autodiscovery	131
Discovering Endpoints Manually from PCoIP Management Console	138
Managing Endpoints	141
Managing Endpoints	141
Managing Profiles	142
Organizing Endpoints into Groups	155
Auto Configuring Endpoints (Enterprise)	160
Auto Naming Endpoints	165
Requesting Endpoint Certificates Using SCEP (Enterprise)	167
Managing Schedules (Enterprise)	174
Hidden Endpoint Settings	182
Remote Endpoint Management (Enterprise)	202
Using the Endpoints Page	213
Endpoints Page Overview	213
Displaying Endpoint Properties	215
Using the ENDPOINT DETAILS Page	231
Performing Power Management	238
Powering Down PCoIP Zero Clients	238
Renaming Endpoints	241
Deleting Endpoints	242
Searching an Endpoint Table	243
Filtering the Endpoint List	244

	Exporting an Endpoint List	247
	Managing the Console	248
	Creating and Managing User Roles	248
	Managing Users	253
	Managing PCoIP Management Console Logs	260
	Creating and Managing PCoIP Management Console Certificates	263
	Updating PCoIP Management Console Certificates after Endpoint Discovery	278
	Uploading the PCoIP Management Console Certificate to an Endpoint	284
	Configuring the Console Settings	287
	Configuring PCoIP Management Console Session Timeout (Enterprise)	287
	Configuring PCoIP Management Console web UI Time Zone	288
	Default Rocky Linux Configuration for PCoIP Management Console	289
	Changing the Default Network Configuration	293
	Configuring an Endpoint Manager Manually from an Endpoint	301
	Managing PCoIP Management Console Databases	305
R	eferences	311
	PCoIP Management Console 1 Profile Properties Renamed or Not Migrated	311
	Time Zone Definitions for PCoIP Management Console 1 or later releases	326
	Expanding the PCoIP Management Console Disk Size	330
	Using your Virtual Machine Console to Administer Licenses when Connected to the Internet	332
	Activating Licenses	332
	Viewing Installed Licenses	333
	View installed licenses via the command prompt:	334
	Deactivating Licenses	334
	Deactivating Your PCoIP Management Console License	335
	HTTP Strict Transport Security	337
	Configure Crypto Policy to Disable CBC and sha1 hash	340
	Chrony NTP Configuration	342
	Disabling the Chrony	346

SSH Security Considerations	347
Disable Root Login	347
Limit User Logins	347
Disable SSH Protocol 1	348
Use Public/Private Keys for authentication and disable Password Authentication	348
Identity Provider(IDP) Integrations	350
Create Self-Signed Certificate	350
Okta Reference	353
Smartcard Authentication with SSO	366
PingFederate Installation Reference	390
PingFederate Configuration for Management Console	391
Firewall References	424
Configuring firewalld for New Installs of Management Console 20.04 or newer	424
Configuring firewalld after a Management Console Upgrade	434
Migrating PCoIP Management Console to a Newer Release Using firewalld	455
Removing Management Console iptables Configuration	460
Deleted Data When Migrating between IP Protocols	463
Troubleshooting	466
Troubleshooting	466
Troubleshooting Endpoints in Recovery Mode	467
Locating Endpoints in Recovery Mode	467
Recovery Mode Causes and Solutions	468
Recovery Mode Examples	469
Troubleshooting DNS	470
Viewing License Information via Command Line	473
Deactivating and Activating Licenses via Command Line	473
FAQ	474
FAQs	474

Support	
Contacting Support	475
Finding the PCoIP Management Console Release Number	476

PCoIP Management Console Overview

Welcome to the PCoIP® Management Console Administrators' Guide. This documentation explains how to install and use your PCoIP Management Console to discover, configure, and manage your PCoIP Zero Client and Remote Workstation Card endpoints.

PCoIP® Management Console manages PCoIP Zero Clients and Remote Workstation Cards using the Tera2 chipset. For more information about these PCoIP endpoints, see the PCoIP Zero Client Firmware Administrators' Guide and Remote Workstation Card Firmware Administrators' Guide.

Support for PCoIP Zero Client and Remote Workstation Card firmware 4.x and earlier

If you are using PCoIP firmware 4.x or earlier, the corresponding PCoIP Management Console is version 1.x. See PCoIP Management Console 1.x User Manual for details.

PCoIP Management Console provides IT administrators with a browser-based console for managing PCoIP endpoints. You can quickly provision new endpoints, configure settings, and update firmware.

Based on Teradici's Management Protocol, the PCoIP Management Console delivers a secure and reliable way to configure and manage the endpoints in your PCoIP deployment.

PCoIP Management Console enables you to organize and manage PCoIP endpoints and their configurations in groups. Using PCoIP Management Console, you can:

- Display the status, health, and activity of your PCoIP deployment at a glance
- Discover endpoints in a variety of ways and automatically name and configure them
- Organize endpoints into multi-level groups
- · Schedule firmware and configuration updates to endpoints based on their groups
- Reset endpoints to factory defaults and control their power settings
- Use custom certificates to secure your PCoIP system

PCoIP Management Console is packaged in a variety of formats for easy deployment. These formats are:

- OVA: An Open Virtual Appliance (OVA) format for quick and easy deployment on a Omnissa Horizon ESXi host
- RPM: Red Hat Package Manager (RPM) format to allow for efficient updates using any one of a variety of Linux operating system.

Note

PCoIP Management Console has discontinued the distribution of pre-built AMIs. If you require a Management Console AMI, please follow the manual process for creating your own custom AMIs as outlined in the <u>Generate and Create a Management Console AMI - PCoIP Management Console</u> 25.06 Administrators Guide.

About PCoIP Management Console Releases

PCoIP Management Console underwent an architecture change since release 2.0 which is not compatible with all releases of endpoint firmware.

The following information identifies which firmware versions to use with your PCoIP Management Console deployment.

- PCoIP Management Console 3.x and higher manages PCoIP Zero Clients and Remote Workstation Cards using firmware 20.01 or higher.
- PCoIP Management Console 1.10.manages PCoIP Zero Clients and Remote Workstation Cards using firmware up to and including 4.9.
- We recommend using the latest firmware versions available at the time of the Management Console release.

PCoIP Management Console Release	Recommended PCoIP Zero Client Firmware	Recommended Remote Workstation Card Firmware
20.01+	20.01+	20.01+
2.0 - 19.11	5.x - 19.11	5.x - 19.11

PCoIP Management Console Release	Recommended PCoIP Zero Client Firmware	Recommended Remote Workstation Card Firmware
1.10 (end of life)	Up to 4.8.2	Up to 4.9

In this guide, references to PCoIP Management Console will refer to the current release unless other releases are specifically identified.


PCoIP Management Console Modes

PCoIP Management Console is one product that operates in two modes—Enterprise and Free. PCoIP Management Console Enterprise requires activating a valid license to operate in Enterprise mode. The banner on the PCoIP Management Console's web interface identifies which mode you are running.

This document discusses both modes of operation and indicates differences in the features as they are introduced.

For information about PCoIP Management Console Free, license offers, term lengths, trial licenses, and the Support and Maintenance program see PCoIP Management Console on our web site. For more information about the differences between the two modes of operation. See Comparison of PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and PCoIP Management Console Enterprise and <

The Web User Interface provides the user with some useful information that new users to Management Console will find helpful.



PCoIP Management Console PCoIP Management Console Free

PCoIP Management Console Free

PCoIP Management Console Free enables a single administrative user to manage a basic deployment of up to 100 endpoints, as well as to upgrade firmware, manage configuration profiles, and discover endpoints.

PCoIP Management Console Enterprise

PCoIP Management Console Enterprise enables large enterprise deployments to manage up to 20,000 endpoints from a single console as well as to upgrade firmware, manage configuration profiles, discover endpoints, schedule actions and configure remote endpoints. PCoIP Management Console Enterprise supports multiple administration users and includes the assurance of support and maintenance for Tera2 endpoint firmware. PCoIP Management Console Enterprise is available through HP Anyware subscriptions. PCoIP Management Console Enterprise reverts to Free mode when all licenses expire.

Comparison of PCoIP Management Console Enterprise and PCoIP Management Console Free

Feature Comparison	Enterprise	Free
Price	See All Access Plans	\$0
Multi-device support	Up to 20,000 PCoIP Zero Clients & PCoIP Remote Workstation Cards	Up to 100 PCoIP Zero Clients & PCoIP Remote Workstation Cards
Apply firmware updates		
Device profile, filtering/delete		
Power down/reset		
Deployment dashboard		
Multi-level group organization		
Device factory reset		
One-time & recurring schedules		
Auto discovery & configuration		
SCEP Support		

PCoIP Management Console Quick Links

Feature Comparison	Enterprise	Free
Multiple administrator accounts		
Role-based access with granular permissions		
Active Directory support		
Concurrent user access		
Inventory reporting		
Remote device management		
Zero Client / Workstation Card peering		
Export / Import endpoint group profiles		
Offline license activation		
Support & Maintenance: Software, Zero Client Firmware and Remote Workstation Card Firmware		

Quick Links

The following links contain information you will need when you first download and install the PCoIP Management Console:

- For information about deployment platforms, system specifications, browser compatibility, and PCoIP endpoint firmware specifications, see <u>System Requirements</u>.
- For instructions on how to activate your license, see Managing Licenses Online.
- For instructions on how to get up and running quickly, see <u>Installing the PCoIP Management</u> <u>Console and Configuring Your System.</u>
- For instructions on how to migrate your PCoIP Management Console 1 to PCoIP Management Console 1 to PCoIP Management Console 1.

PCoIP Management Console What's New in this Release

What's New in this Release

PCoIP Management Console version **25.06** is a release with new features, and security updates over release **25.03.1**.

New Features and Changes

- In the MC profile, a new property called Friendly Name has been added under the Session
 (Advanced) → Session Connection Type → Broker Address Cache List tab for the CLIENT DUAL
 and CLIENT QUAD profiles. For more information, see <u>Friendly Name</u>.
- Upgraded the Flexera libraries from 11.19.6.0 to 11.19.8.0.
- In the MC profile, the following audio-related properties have been renamed:
 - Local USB Audio Driver → Enable Local USB Audio Driver
 - Dual Audio Output → Enable Dual Audio Output
 - Opus Audio Codec → Enable Opus Audio Codec
 - Audio Line In → Enable Audio Line In
- UI validation has been introduced for the **Enable Audio** property and its dependent properties in the CLIENT and HOST profiles.
 - · Enable Local USB Audio Driver
 - · Enable Dual Audio Output
 - · Enable Opus Audio Codec
 - · Enable Analog Audio Input
 - · Enable Audio Line In

For more information, see **Enabling Audio and its Properties**.

MC AMIs will not be available from MC 25.06 onwards; to create an AMI for a region, follow <u>Steps</u> to Generate and Create a Management Console AMI.

PCoIP Management Console System Requirements

System Requirements

The PCoIP Management Console is intended for deployment within a secured corporate network for the management of PCoIP endpoints that are internal or external (Enterprise) to the network.

✓ Note: PCoIP Management Console must not be accessible from unsecured networks

The PCoIP Management Console must only be accessible by endpoints from the open Internet as described within this guide. Any other exposure to the open Internet is an unsupported use of the product and will void any warranty.

Management Console Formats

PCoIP Management Console is released in two formats, both featuring Rocky Linux 8 (64-bit) as the installation operating system. The first format is an Open Virtual Appliance (OVA), which supports deployment on VMware ESXi 7.0 and 8.0. The second format is an RPM package, a standard used by Linux administrators to manage software installations. Please note that pre-built AMIs are no longer distributed. If you require a Management Console AMI, please follow the manual process for creating a custom AMI as outlined in the Generate and Create a Management Console AMI - PCoIP Management Console 25.06 Administrators Guide.

MC Upgrade Dependency Packages for Online and Darksite

RPM formatted versions of PCoIP Management Console may require additional steps for MC RPM upgrades or licensing. Upgrades occasionally require dependency updates to your Management Console host operating system before using the Management Console RPM.

If you are an Online or Dark Site user, you must have all the available MC RPM dependencies installed in the Management Console host operating system prior to the RPM upgrade.

The following RPM packages have been provided for download and are included in installation and upgrade instructions when needed to get you up and running quickly.

- RHEL and Rocky Linux MC Upgrade dependency package: This package contains Java 17, PostgreSQL 15, Python 3.9, and upgrade scripts.
- For installations that require licensing when there is no internet access see Managing Licenses Offline.

System Configuration and Requirements



Update your software to the current release

From time to time, updates may be made available from support, or the OS developers. While we recommend staying current on releases, it is also recommended that you test updates on a test system prior to upgrading your production system or back up a snapshot of the PCoIP Management Console before running the update.

PCoIP Management Console requires the following minimum system configuration and requirements:

OVA format	AMI format	RPM format
• 4 CPUs	• 4 vCPUs	• 4 CPUs or vCPUs
• 12 GB RAM	• 12 GB RAM	• 12 GB RAM
• 62 GB hard drive	 62 GB hard drive space 	· 20 GB free hard drive
space	 Recommended instance type: 	space ¹
	m5.xlarge	Rocky Linux 8.10 and 9.6
		 RHEL 8.10 and 9.6



Caution: Lowering minimum system requirements

Changing minimum system requirements, such as lowering RAM to 4 GB may produce error messages such as Waiting for the server to start. Please refresh the page to try again

Minimum requirements help ensure you have the greatest chance for a successful deployment.

Licensing for PCoIP Management Console

PCoIP Management Console requires access to the activation server on the Internet, directly on port 443 or via a proxy, in order to activate a license. For more information, please see <u>Managing Licenses</u> Online.

Port Numbers

The PCoIP Management Console uses the following ports with both formats:

- Inbound port 443: HTTPS for access to the web interface (administrative interface)
- Inbound port 5172: PCoIP Management Protocol (management interface)
- Outbound port 5172: PCoIP Management Protocol required for manual discovery only
- Outbound port 443: HTTPS (licensing interface)
- Inbound port 8080: Redirects port 80 to 8080
- Inbound port 8443: Redirects port 443 to 8443
- Inbound port 22: TCP (for SSH)

Network

· IP Address Configuration

The PCoIP Management Console supports both pure-IPv4 and pure-IPv6 networks, and can join any network that is using DHCP. The PCoIP Management Console also supports static IP addressing. HP recommends giving the PCoIP Management Console a fixed IP address, either through a DHCP reservation or by assigning a static IP address. See <u>Assigning a Static IP Address</u> and <u>Using IPv6</u> for further details.

Network Latency

PCoIP Management Console supports networks with latency under 100 ms.

PCoIP Management Console Browser Compatibility

Browser Compatibility

PCoIP Management Console supports the release of each browser available at the time of product release, with the exception of Internet Explorer:

- Firefox
- Chrome
- · Microsoft Edge

PCoIP Endpoint Firmware

HP recommends using the latest version of firmware for PCoIP endpoints. For the latest information on current and supported versions, see the <u>HP Support Center</u> for your product page.

PCoIP Management Console requires PCoIP endpoints have a minimum firmware release installed

Management Console 20.xx can manage PCoIP Zero Client firmware 5.x and newer. Check release notes for any special considerations when managing firmware with Management Console.

1. Minimum 20 GB of FREE disk space dedicated specifically to Management Console use. You can increase this recommended size by the space necessary for the Rocky Linux operating system and any other files required on your Linux system. ←

Where to Find Information about Other Components

This guide describes the PCoIP Management Console.

For tips and suggestions to get the best experience from your PCoIP endpoint deployment:

• PCoIP Session Planning Guide

For more information about PCoIP endpoints managed by PCoIP Management Console, see either of the following:

- PCoIP Zero Client Administrators' Guide
- · Remote Workstation Card Administrators' Guide.

PCoIP Management Console Installation Guide

Installation Guide

Installing the PCoIP Management Console and Configuring Your System

The topics in this section contain information to help you get up and running quickly.

Topics that refer to specific versions of PCoIP Management Console will be identified by the release number.

Migrating, upgrading, or downgrading from other versions

If you are migrating to a new PCoIP Management Console version see <u>Migrating to a Newer Version</u>. If you need to downgrade endpoints from firmware 20.01 or higher to an older version, see <u>Downgrading Endpoints to Older Firmware</u>.

Installation Overview

PCoIP Management Console is released in two formats. The first called Open Virtual Appliance (OVA) format with supported hypervisor platforms of VMware ESXi 7.0 and 8.0. The second format is RPM which is one standard for Linux Administrators to manage software installations.

OVA installation contain all dependencies required for Management Console and provide for an easy first time install.

RPM upgrade may require the installation of a dependency package for RHEL 8, Rocky Linux 8, RHEL 9 and Rocky Linux 9 deployments. If required, these packages will be available from the support site download area and may change with each release. To obtain a supported download, go to the version of Management Console you require and download the available download required for your deployment.

Using IPv6 with Management Console

Management Console 20.07 and newer versions support pure IPv4 or pure IPv6 networks; hybrid or dual stacked networks are not supported. In a pure IP deployment, Management Console only stores and displays the PCoIP endpoint data that is relevant to the IP version of the Management Console NIC. This means that when migrating between networks, data that is not relevant to the new network is permanently deleted. Please see <u>Deleted Data When Migrating between IP Protocols</u> for details.

Management Console will automatically display the IP information such as ip addresses relative to it's configured NIC. For example, if the NIC is configured for IPv6, all endpoint properties will display their IPv6 information. Searching for PCoIP endpoints will only display properties for endpoints in IP-only networks.

Management Console supports DHCPv6 with and without SLAAC configurations. The Web UI can be accessed by either a manual, DHCPv6, or SLAAC IPv6 address depending on the network configuration and the Management Console NIC configuration.

Management Console Host Requirements

- Only one NIC can be configured with one IP version
- Must be able to ping and communicate with PCoIP endpoints
- · Must have an internet connection
- Firewall must be configured before installing Management Console
- PCoIP endpoints must be using firmware 20.07 or higher

Limitations

In an environment with DHCPv6 without SLAAC, there is a limitation between the caching systems of the Management Console VM host operating system and administrators using Windows-based

PCoIP Management Console Limitations

clients to access the Web UI. This limitation prevents a connection on the initial connection to the Management Console Web UI. This limitation requires any of two work arounds to fix the issue.

1. Configure a static route from the Management Console VM host operating system to Windows host (MC Client). This can be done by issuing a command similar to:

sudo ip -6 route add via link local address of Windows host dev Ethernet name in Management Console VM host operating system.

Example:

```
sudo ip -6 route add 3505:b900:9000:19::/64 via fe80::e887:4e5d:fab7:cc dev eth0
```

2. From the Management Console host operating system, ping the administrators Windows computer that is accessing the Management Console Web UI prior to the first connection.

Information on IPv6 is included in the Installation and Migration topics for all formats of Management Console.

Installing PCoIP Management Console using vSphere

Once you have downloaded PCoIP Management Console, deploy it as an Open Virtual Appliance (OVA) using vSphere Client. The following instructions apply to deployments in IPv4 networks. Installations into pure IPv6 networks require an additional firewall configuration. See New Installation of Management Console OVA format in IPv6.

To install PCoIP Management Console using vSphere Client:

- Download the latest PCoIP Management Console OVA file to a location accessible from your vSphere Client.
- 2. Log in to your vSphere Client.
- 3. If you have more than one ESXi host, select the desired ESXi node; otherwise, there is no need to select a node.
- 4. From the vSphere client's File menu, select **Deploy OVF Template**.
- 5. In the *Source* window, click **Browse**, select the PCoIP Management Console's OVA file, click **Open** and **Next**.
- 6. In the OVF Template Details window, view the information and click Next.
- 7. In the *Name and Location* window, enter the name for your PCoIP Management Console and click **Next**.
- 8. In the *Host/Cluster* window, select the ESXi host on which you want to deploy the PCoIP Management Console and click **Next**.
- 9. In the Disk Format window, select a thick or thin provision option and click Next.
- 10. In the End User License Agreement window, read the EULA information, click Accept and then Next.
- 11. In the Storage window, select the local disk or SAN where you wish to deploy the PCoIP Management Console and click Next.
- 12. In the *Network Mapping* window, select the network or VLAN where you wish to deploy the PCoIP Management Console and click **Next**.
- 13. In the Ready to Complete window, view your settings and click Finish.

- 14. Make a note of the IP address of your PCoIP Management Console's virtual machine (VM) to log in to your PCoIP Management Console from a browser.
- 15. To activate PCoIP Management Console Enterprise, see Managing Licenses Online.

NEW INSTALLATION OF MANAGEMENT CONSOLE OVA FORMAT IN IPV6

See <u>Using IPv6</u> for an overview of IPv6 with Management Console.

TO DEPLOY MANAGEMENT CONSOLE OVA IN AN IPV6 ENVIRONMENT PERFORM THE FOLLOWING STEPS:

- 1. Deploy Management Console OVA in an IPv6 environment with the guidance from steps 1-16.
- Configure the firewall for IPv6.
 Installations into IPv6 networks require you make firewall configurations for IPv6. See <u>OVA New Installations</u>: To configure firewalld in IPv6 environment.
- Confirm your IP address.
 DHCPv6 networks that are SLAAC enabled will dispaly two addresses which can be used to access Management Console.

ip a

4. Access Management Console via an IPv6 address.

Generate and Create a Management Console AMI

This topic provides step-by-step instructions for creating the MC AMI.

There are two ways to generate the MC AMI:

- · Install the Management Console after the VMDK import
- Install the Management Console during VMDK generation

Install the Management Console after the VMDK Import

In this approach, there are detailed steps to first create a VMDK file with Rocky Linux installed, upload it to an S3 bucket, import it as an AMI, and then launch an EC2 instance. After launching the instance, install and configure the Management Console (MC) on the EC2 instance.

Step 1: Generate VMDK for Rocky Linux 8

- 1. Download and install the VirtualBox from VirtualBox.org.
- 2. Create a New Virtual Machine:
 - a. Open the VirtualBox, and then click New.
 - b. Provide name for the VM (e.g., RockyLinux810).
 - c. Select Linux as the Type and Red Hat 8.x (64-bit) as the Version.
 - d. Click Next.
- 3. Allocate Resources:
 - a. Allocate resources (e.g., Memory: 12288 MB, CPU: 4).
 - b. Click Next.
- 4. Create a Virtual Hard Disk:
 - a. Select Create a virtual hard disk now.
 - b. Choose VMDK (Virtual Machine Disk) as the file type.

- c. Set the disk size (e.g., 62 GB).
- d. Click Finish.
- ${\it 5. Download the Rocky Linux ISO from Official Rocky Linux page.}\\$

reference: Rocky Linux 8.10 ISO.


- 6. Mount the ISO File:
 - a. Select the VM and click Settings.
 - b. Go to the **Storage** tab.
 - c. Click on the empty CD/DVD drive.
 - d. Select Choose a disk file.
 - e. Browse to the downloaded Rocky Linux ISO file and select it.
 - f. Click OK.
- 7. Start the VM and Install Rocky Linux:
 - a. Select the VM and click Start. The VM will boot from the ISO file.
 - b. Follow the installation prompts to install the **Rocky Linux**.
 - c. Choose your language, keyboard layout, and other preferences.
 - d. During the installation process, you will be prompted to create a user.
 - i. Enter the following details:
 - Full Name: Enter the full name for the administrative account (Example: admin)
 - Username: Provide a username for logging into the Management Console (Example: admin)
 - Password: Choose a secure password to protect the administrative account
 - Confirm Password: Re-enter the chosen password to confirm
 - ii. Select the Make this user an administrator checkbox, and then click Next.
 - e. Choose your destination for installation (a virtual hard disk of size 20 GB).
 - f. Click Begin Installation.
 - g. Click Reboot system

8. Log in to Rocky Linux:

- a. Log in with your created user account credentials.
- b. Verify that Rocky Linux is installed successfully.

9. Prepare VMDK for Export:

- a. Shut down the VM.
- b. Select the VM and click File → Export Appliance
- c. Select the Rocky Linux VM and change the file extension from .ova to .ovf



- d. Choose the destination for the exported files.
- e. Locate the VMDK file in the specified file location.

Creating and Using the Rocky Linux VMDK

Generating the VMDK is a one-time task (<u>Step 1: Generate VMDK for Rocky Linux 8</u>). After creation, upload the VMDK to Amazon S3 and import it as a base Rocky Linux AMI. You can then use this base AMI to install different MC versions. A new VMDK is only required if you change the operating system version—for example, when migrating from Rocky Linux 8 to Rocky Linux 9.

Step 2: Upload the VMDK to S3

- 1. Open the AWS Management Console, and navigate to the S3 service.
- 2. Create a new bucket (or use an existing one) to store the VMDK file.
- 3. Upload the VMDK file to the S3 bucket. (Uploading may take 5-10 minutes.)

Step 3: Import VMDK to Create a Base AMI

- 1. Open the AWS Management Console, and navigate to the **EC2 Image builder** service.
- 2. In the left-hand menu, select Images → Import Image.
- 3. Click the **Import Image** button.
- 4. Provide name, version and select the Base Image operating system as Red Enterprise Linux 8.
- 5. Browse the VMDK file in s3 or enter the s3 VMDK URL.
- 6. Attach the existing IAM role or create a new one which has access to import the VMDK.
- 7. Start the import process and Import the Rocky Linux VMDK. (Import process will take about 5-10 mintues.)

Step 4: Launch EC2 Instance from Base AMI

- 1. After the import is complete, locate the newly created AMI in the **AMIs** section.
- 2. Select the **AMI**, and then click **Launch Instance**.
- 3. Configure the instance details:
 - Instance Type: t3.xlarge
 - Security Group: ensure appropriate rules (e.g., allow SSH, HTTP, HTTPS). Refer to <u>System</u> Configuration
 - Key Pair: select or create a key pair for SSH access.
- 4. Launch the instance. (It will take about 2-5 mintues.)

Step 5: Install MC RPM and Configure Instance

- 1. Connect to the EC2 Instance:
 - a. Open the AWS Management Console.
 - b. Navigate to the **EC2** service.
 - c. Select the running instance and click **Connect**.
 - d. Use an SSH client to connect to the instance.
- 2. Install MC RPM:
 - a. Upload the MC RPM package **24.05** or **latest** and required dependencies to the instance by using **WinSCP** or **SFTP**.
 - b. Connect to the instance via SSH.
 - c. Run following command

sudo dnf update

- d. Install the MC RPM package. Refer to MC Installation Using RPM.
- 3. Execute firewall commands required for Management Console. Refer to Moving Between IPv4 and IPv6.
- 4. After Installation, verify if MC is up and running in the IP address provided by the instance.

Step 6: Create a New AMI from the Configured Instance

- 1. In the EC2 Management Console, select the running instance.
- 2. Click Actions \rightarrow Image and templates \rightarrow Create image.
- 3. Provide the name and details to create the image. This will create a new AMI with MC installed. (This process will take 5 minutes).
 - Note: Copy AMI to Other Regions and Make Public

Complete steps $\underline{7}$ and $\underline{8}$ only if you need to copy the AMI to other regions and make it public.

Step 7: Copy AMI to Multiple Regions:

- 1. In the EC2 Management Console, navigate to the AMIs section.
- 2. Select the newly created AMI.
- 3. Click Actions → Copy AMI.
- 4. Choose the target region and start the copying process.
- 5. Repeat this process for each desired AWS region.

Step 8: Make AMIs Public:

- 1. In the EC2 Management Console, navigate to the AMIs section.
- 2. Select each AMI (in each region) that you want to make public.
- 3. Click Actions → Modify Image Permissions.
- 4. Set the image to public.

Note: If you encounter any issues in AMI generation

If you encounter any issues in AMI generation with Amazon S3 access and Amazon EC2 instance launch, verify that the required permissions are correctly configured.

Install the Management Console during VMDK generation

This approach installs the MC on Rocky Linux during VMDK creation. After you create the VMDK, upload it to an S3 bucket and import it as an AMI. Use this AMI to launch an EC2 instance with the MC already installed and configured.

Step 1: Generate VMDK for Rocky Linux and Install MC

- 1. Download and install the VirtualBox from VirtualBox.org.
- 2. Create a New Virtual Machine:
 - a. Open VirtualBox and click New.

- b. Name the VM (e.g., RockyLinux810).
- c. Select Linux as the Type and Red Hat 8.x (64-bit) as the Version.
- d. Click Next.
- 3. Allocate Resources:
 - a. Allocate resources (e.g., Memory: 12288 MB, CPU: 4)
 - b. Click Next.
- 4. Create a Virtual Hard Disk:
 - a. Select Create a virtual hard disk now.
 - b. Choose VMDK as the file type.
 - c. Set the disk size (e.g., 62 GB).
 - d. Click Next.
- 5. Download the Rocky Linux ISO from the official page: Rocky Linux 8.10 ISO.
- 6. Mount the ISO File:
 - a. Select the VM and click Settings.
 - b. Go to the Storage tab.
 - c. Click on the empty CD/DVD drive.
 - d. Select Choose a disk file.
 - e. Browse to the downloaded Rocky Linux ISO file and select it.
 - f. Click **OK**.
- 7. Start the VM and Install Rocky Linux:
 - a. Select the VM and click Start. The VM will boot from the ISO file.
 - b. Follow the installation prompts to install Rocky Linux.
 - c. Choose your language, keyboard layout, and other preferences.
 - d. During the installation process, you will be prompted to create a user.
 - i. Enter the following details:
 - Username: Provide a username for logging into the Management Console. (Example: admin)

- Password: Choose a secure password to protect the administrative account
- · Confirm Password: Re-enter the chosen password to confirm
- e. Select the Make this user an administrator checkbox, and then click Next.
- f. Choose your installation destination (a virtual hard disk of size 20 GB).
- g. Click **Begin Installation**.
- h. Click Reboot system.

8. Install MC in Rocky Linux:

- a. After you install Rocky Linux, sign in with the user account you created.
- b. If you aren't already connected to the internet, connect to the internet.
- c. Upload the MC RPM package **above 24.05** and required dependencies to the VM using WinSCP or SFTP.
- d. Connect to the VM by using SSH or the VirtualBox console.
- e. Run the following command:

sudo dnf update

- f. Install the MC RPM above 24.05 package. Refer to MC Installation Using RPM.
- g. Configure firewall rules required for the MC. Refer to Moving Between IPv4 and IPv6.
- 9. Prepare VMDK for Export:
 - a. Shut down the VM.
 - b. Select the VM and click **File** → **Export Appliance**.
 - c. Select the Rocky Linux VM and change the file extension from .ova to .ovf.
 - d. Choose the destination for the exported files.
 - e. Locate the VMDK file in the specified file location.

Step 2: Upload VMDK to S3

- 1. Open the AWS Management Console, and navigate to the S3 service.
- 2. Create a new bucket (or use an existing one) to store the VMDK file.

3. Upload the VMDK file to the S3 bucket. (This process takes about 5-10 minutes.)

Step 3: Import VMDK to Create a Base AMI

- 1. Open the AWS Management Console.
- 2. Navigate to the EC2 Image builder service.
- 3. In the left-hand menu, select **Images** \rightarrow **Import Image**.
- 4. Click the **Import Image** button.
- 5. Provide the necessary details for the import, such as the source URL (S3 bucket link) and the format (VMDK).
- 6. Attach the existing IAM role or create a new one which has access to import the VMDK.
- 7. Start the import process for the Rocky Linux VMDK. (This process takes about 5–10 minutes.)

Step 4: Launch EC2 Instance from Base AMI

- 1. After the import is complete, locate the newly created AMI in the AMIs section.
- 2. Select the AMI and click Launch Instance.
- 3. Configure the instance details:
 - Instance Type: t3.xlarge
 - Security Group: Ensure appropriate rules (e.g., allow SSH, HTTP, HTTPS). Reference: <u>System Configuration</u>.
 - Key Pair: Select or create a key pair for SSH access.
- 4. Launch the instance. (This process takes about 2-5 minutes.)

Step 5: Verify MC Installation on EC2 Instance

- 1. Connect to the EC2 Instance:
 - a. Open the AWS Management Console.
 - b. Navigate to the EC2 service.
 - c. Select the running instance and click Connect.

- d. Use an SSH client to connect to the instance.
- 2. Verify MC Installation:
 - a. Verify that the Management Console is running.
 - b. Execute firewall commands required for Management Console. Refer to Moving Between IPv4 and IPv6.
 - c. Verify that the Management Console is running by using the IP address provided by the instance.

Note: Copy AMI to Other Regions and Make Public

If you need to copy the AMI to different regions and make it public, refer to step 7 and 8.

Related Information

Securing PCoIP Management Console User Passwords

<u>Default Rocky Linux Configuration for PCoIP Management Console</u>

Setting up Security

Managing Licenses Online

PCoIP Management Console Remote Endpoint Management (Enterprise)

Management Console as an RPM

The Management Console RPM allows administrators an opportunity to manage and control Linux packages in a way that complies to their individual corporate IT policies. The <code>teradicimc<mc_version>.rpm</code> package, when connected to the internet, will automatically update any required dependencies not available on your Linux VM so you can be operational quickly. The RPM is provided as a file for download. A public RPM repository will be available for seamless installs in a future release.

By introducing this RPM package into your network, you accept that there are risks involved in deploying the system, and you acknowledge that you have reviewed the default PCoIP Management Console and OS configuration and have performed any other changes to make the security level appropriate for your deployment.

Update your software to the current release

From time to time, updates may be made available from support, or the OS developers. While we recommend staying current on releases, it is also recommended that you test updates on a test system prior to upgrading your production system or back up a snapshot of the PCoIP Management Console before running the update.

b Linux Proficiency

It is expected that administrators of Linux operating systems are proficient at using the Linux OS and have an account with **sudo** access. Different Linux distributions may require different procedures. We use the Linux OS distribution for instructional information.

Dedicated Host

It is recommended that the Management Console host be dedicated for Management Console use only.

Minimum Requirements Validation

The Management Console RPM package will check for the minimum hardware resource requirements (CPU, disk, ram) and fail if it is not met. To disable the minimum requirement check, enter the following command:

```
sudo MC NO CHECK=1 rpm -Uvh teradicimc-<mc version>.rpm
```

Disabling the minimum requirements check is not recommended! Lowering minimums may reduce Management Console performance, particularly in large deployments.

Management Console RPM Installation and Removal

Management Console is provided with everything needed in order to get Management Console to work except the firewall exceptions. After installation, make sure that you have configured your firewall and that it complies to your corporate security policies. If you don't have a security policy, you can review the <u>firewall reference</u> that will allow you to get an understanding of what firewall requirements Management Console needs to be operational. Once the firewall exceptions are made, you can upgrade or remove the Management Console as required.

Directions for upgrades are described in <u>Upgrading Management Console Using RPM</u>.

Installation using RPM

These instructions apply to the **first time installation** of Management Console on a host Linux machine that contains the RPM and any required packages for this release. The administrator installing the RPM should have sudo privileges.

- 1. Download the <u>available RPM</u> file for this release from the <u>support site</u> and ensure they are located on the Management Console Linux VM.
 - You can use a third party tool such as WinSCP to copy and move files into the RHEL/Rocky Linux host operating system.
- 2. Install the RPM package using the following commands for your Linux distribution.

Download the appropriate rpm file for RHEL and Rocky Linux

To install on RHEL 8 or Rocky Linux 8, download the *teradicimc-<mc_version>.el8.x86_64.rpm* file.

To install on RHEL 9 or Rocky Linux 9, download the *teradicimc-<mc_version>.el9.x86_64.rpm* file.

a. Rocky Linux 8 and 9 users, follow these steps:

- i. sudo dnf -y module disable postgresql && sudo dnf -y module enable
 postgresql:15
- ii. sudo dnf install teradicimc-<mc_version>.rpm from the directory where the rpm file is located.

b. RHEL 8 users, follow these steps:

- i. sudo subscription-manager repos --enable rhel-8-for-x86_64-baseos-rpms -enable rhel-8-for-x86_64-appstream-rpms
- ii. sudo dnf install https://dl.fedoraproject.org/pub/epel/epel-releaselatest-8.noarch.rpm
- iii. sudo dnf -y module disable postgresql && sudo dnf -y module enable postgresql:15
- iv. sudo dnf install teradicimc-<mc_version>.rpm from the directory where the rpm
 file is located.

c. RHEL 9 users, follow these steps:

- i. sudo subscription-manager repos --enable rhel-9-for-x86_64-baseos-rpms -enable rhel-9-for-x86_64-appstream-rpms
- ii. sudo dnf install https://dl.fedoraproject.org/pub/epel/epel-releaselatest-9.noarch.rpm
- iii. sudo dnf -y module disable postgresql && sudo dnf -y module enable
 postgresql:15
- iv. sudo dnf install teradicimc-<mc_version>.rpm from the directory where the rpm file is located.

PCoIP Management Console Remove Management Console


- 3. Configure your firewall.
 - IPv4

See the firewall reference on how to configure Management Console firewall for use in an IPv4 environment perform the following steps:

· IPv6

See the firewall reference on how to configure Management Console firewall for use in an IPv6 environment perform the following steps:

- 4. If applicable, enable your HSTS policy. See HTTP Strict Transport Security.
- 5. If installing Management Console Enterprise, license your installation.
 - See Managing Licenses Online.
 - If applicable see <u>Managing Licenses Offline</u>.



Remove Management Console

To remove Management Console, you will have two choices, remove Management Console or remove Management Console with all its dependencies.

PCoIP Management Console Remove Management Console

A

Ignore warning message

Please ignore the following warning message as it does not have any impact on the Management Console removal process.

warning: file remove failed: No such file or directory.

REMOVE ONLY MANAGEMENT CONSOLE

To remove Management Console only run the following command:

```
sudo dnf remove teradicimo
```

REMOVE MANAGEMENT CONSOLE WITH ALL DEPENDENCIES

To remove Management Console and any package that was required by Management Console, run the following command:

```
sudo dnf autoremove teradicimo
```

REMOVE POSTGRESQL

To remove PostgreSQL, run the following command:

```
psql -U <username>
drop database <mc_database_name>;
\q
sudo dnf remove postgresql\*
```

Moving to a New Version of Management Console

If you are upgrading from an older version of PCoIP Management Console, you may have additional steps or considerations to review. Review the relevant topics particular to your upgrade path.

- Upgrading using OVA
- Upgrading using RPM
- Migrating from Management Console 1
- Moving Between IPv4 and IPv6
- Migrating to firewalld

Running Different PCoIP Management Console Versions in Parallel

During the migration process to a new PCoIP Management Console, you will need to run both PCoIP Management Console 1 (which has reached End of Support as of April, 2020) and the new PCoIP Management Console in parallel. You may also need to operate two versions of the PCoIP Management Console if you have endpoints that cannot be updated to firmware version 20.01 or higher.

Note: Test a small number of endpoints first before upgrading all the endpoints

Test a small number of endpoints before upgrading all the endpoints in your system. Place them in a test group in a segregated network. If you are using automatic discovery, this may require modifications to your DHCP options or DNS SRV records.

An endpoint can only be managed by one PCoIP Management Console at a time. If you are using DHCP options discovery and you plan to keep some of your endpoints managed by PCoIP Management Console 1, you can configure your DHCP server with the PCoIP Endpoint MC Address option on a scope-by-scope basis. See <u>Configuring Endpoints using Auto Discovery</u> for details.

Note: Ensure different versions of PCoIP Management Console have different IP addresses

If you are running PCoIP Management Console 1 in parallel with a newer PCoIP Management Console, ensure the two versions of the PCoIP Management Console have different IP addresses.

The table shown next lists interoperability issues when running a newer release of PCoIP Management Console in parallel with PCoIP Management Console 1 which has reached End of Support as of April, 2020.

Current versions of PCoIP Management Console and PCoIP Management Console 1 Interoperability

Category	PCoIP Management Console (2.x to Current Version)	PCoIP Management Console 1 (1.10.8) End of Support
Endpoint firmware	PCoIP endpoints must run firmware 20.01 or higher. PCoIP Management Console cannot discover and manage endpoints running previous versions of the firmware.	PCoIP Endpoints must run a 4.x firmware version. PCoIP Management Console 1 cannot discover and manage devices running firmware 20.01 or higher.
DHCP/DNS discovery	Current versions of PCoIP Management Console use a different format for DHCP options and DNS SRV records from PCoIP Management Console 1.	For information on DHCP and DNS discovery for PCoIP Management Console 1, see the PCoIP Management Console 1.x User Manual.
Management	PCoIP endpoints are managed by at most one PCoIP Management Console.	PCoIP Zero Clients can be managed by more than one PCoIP Management Console 1 simultaneously.
Database	Cannot import PCoIP Management Console 1 database.	Importing a database from a current version of PCoIP Management Console is not supported
Profiles	You can import PCoIP Management Console 1.10.x profiles.	Importing profiles from a current version of PCoIP Management Console is not supported
Communication	Does not communicate with PCoIP Management Console 1.	Does not communicate with current versions of PCoIP Management Console.

PCoIP Management Console Administrators' Guide

Administrators' Guide

PCoIP Management Console Administrators' Guide

A

RPM upgrades may require new certificates uploaded to your endpoints

If you are upgrading to Management Console 25.06 from version 23.06 or earlier, and if you are not using custom certificates, you must upload the new Management Console certificate to your endpoints. For the new Management Console certificate SHA-256 & SHA-512 values, see the release notes.

For instructions on how to upload your certificate see <u>Updating PCoIP Management Console</u> <u>Certificates after Endpoint Discovery</u>

Prior to upgrading Management Console you can:

- Clear the management state on all your endpoints **before** the upgrade and rediscover them after the upgrade.
- Ensure that the new certificate is uploaded to your endpoints **before** you upgrade to Management Console 25.06.

Welcome to the PCoIP Management Console Administrators' Guide.

The PCoIP Management Console is an Enterprise level management software appliance that allows ease of management of PCoIP endpoints through a single interface. With Management Console Enterprise, administrators can quickly and easily provision new devices, peer PCoIP Zero Clients with Remote Workstation Cards, report on inventory, review metrics, configure settings, and update firmware from a single console.

PCoIP Management Console Getting Started

Getting Started

Log In to the PCoIP Management Console Web User Interface

This section assumes that the PCoIP Management Console is configured to connect to your network. If you used DHCP to assign the IP address, then you will be able to continue in this section. If you require static IP addresses, see Changing the Default Network Configuration for instructions prior to continuing.

Before accessing the PCoIP Management Console web user interface (UI) from your browser for the first time, ensure that the following are in place:

- Your license has been activated for PCoIP Management Console Enterprise. See <u>Activating</u> Licenses.
- You know the IP address of your PCoIP Management Console virtual machine. To locate the address:
 - · Using vSphere Client, log in to your vCenter server.
 - In the Inventory list, select VMs and Templates.
 - Select your PCoIP Management Console virtual machine and then click the **Summary** tab.
 - Note the IP address in the General pane.

Using the Web Interface for the First Time

The Management Console's Web User Interface (Web UI) contains information that can be useful when troubleshooting issues. These references are identified in the following web user interface login screen example.





WebUI Area	Description
1	Identifies if you are using FREE or licensed ENTERPRISE mode of PCoIP Management Console
2	Identifies the release number of your Management Console
3	Informational message advising on how to upgrade to ENTERPRISE if new features are required
4	Links to find further information. • Help: redirects you to the current product page of Management Console
	• License Agreement: Displays the license agreement for your installed Management Console
	Support: Redirects you to the support site
	• teradici.com: Links to our web page where you can quickly find further information such as white papers and the latest information on new products


Note: The Web UI admin account for PCoIP Management Console is different "from the virtual machine admin account

The default **admin** account that you use when first logging in to the PCoIP Management Console web UI is *not* the same **admin** account you use for logging in to the PCoIP Management Console virtual machine console.

To log in to the PCoIP Management Console web interface:

1. In your browser's address bar, enter the IP address of the PCoIP Management Console virtual machine. See <u>Installing PCoIP Management Console using vSphere</u>.

- 2. At the PCoIP Management Console login screen, enter the web interface credentials.
 - USERNAME admin
 - PASSWORD password



Login Screen


Note: Changing default settings

In order to change the PCoIP Management Console's default settings and run various scripts, you must connect to the PCoIP Management Console's virtual machine console and log in. See <u>Accessing the PCoIP Management Console Virtual Machine Console</u>

1. Click **SIGN IN**. If login is successful, the PCoIP Management Console dashboard displays in your browser window.


PCoIP Management Console Enterprise

The next example shows the PCoIP Management Console Enterprise dashboard. The banner will indicate PCoIP Management Console Free if you are running in free mode.



PCoIP Management Console Web UI User Account Lockout

The PCoIP Management Console inhibits automated system attacks on its web UI. If a user login fails 6 times within a 30-minute period, that user account will be locked out for 30 minutes. If this occurs, the login screen will display the message shown next.




User Account Lockout Screen

Understanding the PCoIP Management Console Dashboard

The **DASHBOARD** page gives you an overview of the PCoIP Management Console's current configuration and health, as well as the status and activity of your PCoIP deployment. You can also use the dashboard to keep track of upcoming schedules and to view their details.

An example of the PCoIP Management Console Enterprise dashboard is shown. The table that follows describes the various sections in the dashboard layout and contains links to more information about the dashboard components.





PCoIP Management Console Dashboard

PCoIP Management Console Dashboard Description

Area	Dashboard	Description
1	Welcome message LOGOUT	Displays the PCoIP Management Console user account for the logged in user. Lets you log out from your PCoIP Management Console session.
2	DASHBOARD	Navigates to the DASHBOARD page. The DASHBOARD link occurs at the top of all PCoIP Management Console pages.
	ENDPOINTS	Navigates to the ENDPOINTS page. From this page you can structure endpoints into groups, apply profiles, discover endpoints manually, view endpoint details, search, and filter endpoints in the endpoint tables. The ENDPOINTS link occurs at the top of all PCoIP Management Console
	PROFILE	

Area	Dashboard	Description
	SCHEDULE (Enterprise)	Navigates to the SCHEDULE page which includes the schedule HISTORY tab. From the SCHEDULE page you can create, view, edit, delete, enable and disable schedules to update groups of endpoints in the future and access the PCoIP Management Console's schedule history tab. The SCHEDULE link occurs at the top of all PCoIP Management Console pages.
	AUTO CONFIGURATION (Enterprise)	Navigates to the AUTO CONFIGURATION page. From this page you can configure, edit, and delete rules to automatically assign endpoints to a specific group when they are first discovered or whenever they move to or from a group. The AUTO CONFIGURATION link occurs on at the top of all PCoIP Management Console pages.
	ENDPOINT CERTIFICATES (Enterprise)	Allows administrators to configure rules that request certificates for endpoints.
	SETTINGS	Navigates to the SETTINGS page. From this page you can manage PCoIP Management Console users, change the time zone for your PCoIP Management Console web interface, configure a persistent naming convention for automatically naming endpoints, upload firmware and certificates to the PCoIP Management Console, manage PCoIP Management Console databases, view license information, view PCoIP Management Console version information, and configure the PCoIP Management Console log level. The SETTINGS link occurs at the top of all PCoIP Management Console pages.
3	License expiry notification banner	Displays the number of days remaining until the PCoIP Management Console Enterprise's license expires. If you disable this message, it will not appear again for 30 days when viewing the PCoIP Management Console Enterprise using that browser. You will see it again if you access the PCoIP Management Console Enterprise using a different browser that does not have the notification disabled.
4	MANAGEMENT CONSOLE STATUS	Shows the PCoIP Management Console's status and contains information about how the PCoIP Management Console is configured: • Health: The PCoIP Management Console health displays as 'good' unless the disk is more than 80% full and/or the PCoIP Management Console daemon is halted. • Disk Capacity: Shows the percentage of disk space used.

Area	Dashboard	Description
		 DNS SRV Record: Displays the PCoIP Management Console's FQDN that is configured in the DNS SRV record. If no record exists, this field is left blank. Auto Config: Indicates whether auto configuration is enabled or disabled. Scheduling: Indicates whether schedules are enabled or disabled. Time Zone: Indicates the time zone setting for the user's PCoIP Management Console web interface. By default, the time zone is set to the PCoIP Management Console virtual machine's time zone, which is always in Coordinated Universal Time (UTC). If desired, you can set your web interface time to reflect your local time zone. MC Version: Displays the current PCoIP Management Console release version.
	DEPLOYMENT CONSOLE STATUS	Displays status information about the managed endpoints in your system, such as the number that are online and offline, and the number that are grouped and ungrouped. This section also indicates important information about profiles that failed to apply.
	CURRENT ACTIVITY	Displays the number of endpoint updates in progress, pending, scheduled, and the number of endpoints waiting to restart or requiring a manual reboot.
	UPCOMING SCHEDULES	Displays information about upcoming schedules, including the date and time they will apply.
	CERTIFICATES (This dashboard feature is limited to SCEP generated certificates)	Identifies the number of endpoints with SCEP generated certificates: • Expired certificates • Certificates expiring today • Certificates that are less than 30 days from expiring • No certificates • Valid certificates
	VIEW SCHEDULES	Lets you open the SCHEDULE page to view details for a schedule.
5	Footnote Information	The following links occur at the bottom of every PCoIP Management Console page:

Area	Dashboard	Description
		 Help: Opens the PCoIP Management Console support
		page where you can find information about the PCoIP
		Management Console.
		 License Agreement: Opens the End User License
		Agreement (EULA) in your browser window.
		 Support: Opens the Teradici Support page in your
		browser window.
		 teradici.com: Opens the Teradici web page in your
		browser window.
		 Release: Identifies the PCoIP Management Console
		release version.

Managing Licenses Online

PCoIP Management Console Enterprise is enabled through subscription licensing provided on a per managed device basis for terms of one and three years. Licenses can be added together to achieve the total number of necessary managed devices.

Licenses come by email after you order them and contain one activation code for each license SKU ordered. Activation codes (also known as entitlement IDs) have an alphanumeric format of 0123-4567-89AB-CDEF.

The following is an example of the email content for 3x100 license SKUs:

✓ Note: License keys shown next are examples

The license keys shown next do not contain real activation codes.

Description: Teradici PCoIP® Management Console Enterprise – 1 year. Includes support and maintenance.

No. of Devices: 10 Devices

Quantity: 3

Valid Until: 12/31/2016

Activation Code: 0123-456Z-89AB-CDEF

Contact your reseller to obtain your license key for PCoIP Management Console Enterprise or go to https://connect.teradici.com/mc-trial to request a free PCoIP Management Console Enterprise trial license. For more information on license options and packaging, see https://anyware.hp.com/products-and-solutions/pcoip-products/management-console or one of Teradici's resellers.

License Requirements and Restrictions

The following requirements and restrictions apply for PCoIP Management Console:

Caution: Return all licenses before migrating

If your PCoIP Management Console appliance will be moved to another server or replaced with an upgrade, you must return all the PCoIP Management Console licenses before the migration and then re-activate the licenses after the migration.

- When a license expires, PCoIP Management Console will operate in Free mode. Enterprise mode features will stop working Licenses are installed per PCoIP Management Console appliance.
- If no licenses are installed, the PCoIP Management Console will operate in Free mode.
- Internet access to https://teradici.flexnetoperations.com/ on port 443 is required for the PCoIP Management Console to activate the license against the license server. The PCoIP Management Console may also require the ability to contact this server from time to time to keep the license activated.
- Licenses can be returned multiple times. If the system prevents activation after returning a license, contact support at Support Center.
- You can have multiple licenses active on PCoIP Management Console, however each license can only be active on one PCoIP Management Console.
- Licenses are activated one license at a time.

Expiry Notifications

The Management Console interface displays a notification when licenses are about to expire, when they have expired, when you are approaching your licensed device count limit, and when you have reached the limit.

Support and Maintenance

Use the activation code you received to request Support and Maintenance.

For more information on support and maintenance, see the Support Programs.



Info: License Scripts

If managing licenses through the command line, please see License Scripts

Activating Licenses


Before you can activate your license, you will need your activation key. If you are activating from behind a proxy, you will also need the IP address, port number, username, and password to authenticate to your proxy server. If you wish to use the virtual machine console to manage your licenses, see <u>Using your Virtual Machine Console to Administer Licenses when Connected to the Internet</u>

Using the UI to activate your PCoIP Management Console Enterprise license:

- 1. Navigate to SETTINGS > LICENSE page.
- 2. Select the **NEW LICENSE** button.
- 3. Enter your License Key and select the **ACTIVATE LICENSE** button.

Using the UI to activate your PCoIP Management Console Enterprise license from behind a proxy server:

Activating your license from behind a proxy server requires you configure the additional parameters that appear after activating the **Connect through a proxy** option. The additional parameters are Proxy Address, Port, Username, and Password of the proxy server.



Activate New License Dialog

Viewing Installed Licenses

Once your license is activated, its information is stored on the PCoIP Management Console virtual machine.

To view installed licenses via the PCoIP Management Console user interface:

Navigate to SETTINGS > LICENSE.

The following information will be displayed:

- Fulfillment ID: XXXXXXXX: An ID assigned to a license after it is activated. This ID is required if you deactivate the license. The fulfillment ID will be different each time you reactivate a license after it has been deactivated.
- Entitlement ID: XXXX-XXXX-XXXX: The license key you received via email that you use to activate your license.
- Expiration date: DD-MMM-YYYY: The day, month, and year your license expires.



LICENSE Page

Deactivating Licenses

It is important to deactivate a license when you no longer need it, for example, when you decommission a virtual machine. This frees up the license and makes it available for a different PCoIP Management Console Enterprise deployment.

Note: Deactivating license reverts PCoIP Management Console to PCoIP Management Console Free

PCoIP Management Console will run in Free mode when all its licenses are deactivated.

▲ Warning: Internet Access Required

When deactivating a license, an internet connection to the licensing server is required unless the offline license activation steps are used.

Deactivating Your PCoIP Management Console License

Using your UI to deactivate PCoIP Management Console Enterprise license:

- 1. Navigate to SETTINGS > LICENSE page.
- 2. Highlight the licenses you want deactivated and select the **DEACTIVATE** button.

Deactivating your PCoIP Management Console Enterprise license from behind a proxy server:

Deactivating your license from behind a proxy server requires you configure the additional proxy server parameters that appear after activating the Connect through a proxy option. The additional parameters are Proxy Address, Port, Username, and Password.

Using your UI to deactivate PCoIP Management Console Enterprise license behind a proxy server:

- 1. Navigate to SETTINGS > LICENSE page.
- 2. Highlight the licenses you want deactivated and select the **DEACTIVATE** button.
- 3. Select the **Connect through a proxy** radio button and fill out the proxy fields.
- 4. Select the **DEACTIVATE** button in the *DEACTIVATE LICENSE* dialog.

Managing Licenses Offline

License Scripts

HP provides shell scripts that let you activate, view information about, and deactivate PCoIP Management Console Enterprise licenses. All scripts are located in the PCoIP Management Console virtual machine console's /opt/teradici/licensing directory and require you to connect to your PCoIP Management Console virtual machine console. See Logging in to the PCoIP Management Console OVA Virtual Machine Console.

Activating Your PCoIP Management Console License from a Location Without Internet Access

To activate your PCoIP Management Console Enterprise license when the PCoIP Management Console is located on a site without Internet access (sometimes referred to as a dark site), you will need to create a ticket for Offline License Activation. A <u>support site account</u> will be required to create this ticket. The ticket must include your license activation code that was provided by email when you requested a trial license or when your Enterprise license was purchased. Once the ticket is created, you will be provided with an offline activation .asr file allowing you to produce an offline activation short code to return to support. Support will in turn provide you with a response text file which you will use to activate PCoIP Management Console Enterprise. Activating and deactivating licenses from a site without Internet access must be done using the virtual machine console.

REQUESTING OFFLINE ACTIVATION

Go to the <u>support site</u>, sign in and create a ticket for Offline License Activation. Include your PCoIP Management Console Enterprise license activation code that was provided by email when your trial license was requested or when your Enterprise license was purchased.

PRODUCING AN OFFLINE ACTIVATION SHORT CODE

The ticket will first be updated by support with an ASR file which you have to upload to your PCoIP Management Console. Once you have the ASR file, perform the following steps from your PCoIP Management Console virtual machine console.

1. Enable SSH if using PCoIP Management Console in OVA format. See: <u>Temporarily Enabling SSH</u>
Access

2. Connect a Secure Copy Protocol (SCP) client such as Putty or WinSCP to the PCoIP Management Console virtual machine using the PCoIP Management Console virtual machine administrative credentials.

- 3. Upload the ASR file provided in your ticket to the administrative home directory (/home/admin/).
- 4. Connect a Secure Shell (SSH) client to to the PCoIP Management Console virtual machine using the PCoIP Management Console virtual machine administrative credentials.
- 5. Change directories to the licensing directory.

```
[admin@localhost ~]$ cd /opt/teradici/licensing/
```

6. Set the LD_LIBRARY_PATH variable.

```
[admin@localhost licensing]$ export LD_LIBRARY_PATH=.
```

7. Process offline_activation.asr with appactutil.

```
[admin@localhost licensing]$ ./appactutil -shortcode ~/
offline_activation.asr
```

Activation short code output example:

Activation short code:

```
216360-082292-891921-316997-475492-227533-740186-228152
```

8. Copy your Activation short code into a text file and enter it into your ticket. Wait for the response code text file to be returned from support.

COMPLETING THE OFFLINE ACTIVATION

Once the support ticket has been updated with a response code text file, you can then follow these steps to activate your PCoIP Management Console Enterprise with the response code file.

- From the PCoIP Management Console virtual machine console enable SSH. See: <u>Temporarily</u> <u>Enabling SSH Access</u>
- 2. Connect a Secure Copy Protocol (SCP) client such as Putty or WinSCP to the PCoIP Management Console virtual machine using the PCoIP Management Console virtual machine administrative credentials.

3. Upload the response text file provided in your ticket to the administrative home directory (/home/admin).

4. Change directories to the licensing directory.

```
[admin@localhost ~]$ cd /opt/teradici/licensing/
```

5. Set the LD_LIBRARY_PATH variable.

```
[admin@localhost licensing]$ export LD LIBRARY PATH=/opt/teradici/licensing
```

6. Process response.txt with appactutil.

```
[admin@localhost licensing]$ ./appactutil -process ~/response.txt
```

```
Reading response from /home/admin/response.txt
SUCCESSFULLY PROCESSED RESPONSE
ProductID MC, FulfillmentID FID-CUSTNAME-2016-1
```

Viewing Installed Licenses

To view your installed licenses:

- 1. Enable SSH. See: <u>Temporarily Enabling SSH Access</u>
- 2. Connect a Secure Shell (SSH) client to the PCoIP Management Console virtual machine using the PCoIP Management Console virtual machine administrative credentials.
- 3. Change directories to the licensing directory.

```
[admin@localhost ~]$ cd /opt/teradici/licensing/
```

4. Set the *LD_LIBRARY_PATH* variable

[admin@localhost licensing] \$ export LD_LIBRARY_PATH=/opt/teradici/licensing

5. View the installed licenses and note the Fullfillment ID of the license to return.

[admin@localhost licensing]\$./appactutil -view

```
Trust Flags: FULLY TRUSTED
Fulfillment Type: SHORTCODE
Status: ENABLED
Fulfillment ID: FID-OFFLINE-12345678-1
Entitlement ID: ENTL-OFFLINE-12345678-2-1
Product ID: MC
Suite ID: NONE
Expiration date: 30-may-2017
Feature line(s):
INCREMENT MC_nDevices TERADICI 2.00000 30-may-2017 1 \
VENDOR_STRING="nDev=500, FNO=90, SN=19137747" ISSUER=Teradici \
ISSUED=13-mar-2017 NOTICE="Teradici - Dev Ops" TS_OK \
SIGN="00D0 A25F 78FB A9C4 7093 EB1A 2744 8500 DF9B 8201 9CFE \
F024 08A5 67DE CD45"
```

Deactivating Your PCoIP Management Console Enterprise License from a Location Without Internet Access

To deactivate your PCoIP Management Console Enterprise license when the PCoIP Management Console is located in a site without Internet access:

- 1. Enable SSH. See: Temporarily Enabling SSH Access
- 2. Connect a Secure Copy Protocol (SCP) client such as Putty or WinSCP to the PCoIP Management Console virtual machine using the PCoIP Management Console virtual machine administrative credentials.
- 3. Upload the ASR file provided in your ticket to the administrative home directory.
- 4. Connect a Secure Shell (SSH) client to the PCoIP Management Console virtual machine using the PCoIP Management Console virtual machine administrative credentials.
- 5. Change directories to the licensing directory.

```
[admin@localhost ~]$ cd /opt/teradici/licensing/
```

6. Set the LD_LIBRARY_PATH variable

```
[admin@localhost licensing] $ export LD_LIBRARY_PATH=/opt/teradici/licensing
```

7. View the installed licenses and note the Fullfillment ID of the license to return.

```
[admin@localhost licensing]$ ./appactutil -view
```

```
Trust Flags: FULLY TRUSTED
Fulfillment Type: SHORTCODE
Status: ENABLED
Fulfillment ID: FID-OFFLINE-12345678-1
Entitlement ID: ENTL-OFFLINE-12345678-2-1
Product ID: MC
Suite ID: NONE
Expiration date: 30-may-2017
Feature line(s):
INCREMENT MC_nDevices TERADICI 2.00000 30-may-2017 1 \
VENDOR_STRING="nDev=500, FNO=90, SN=19137747" ISSUER=Teradici \
ISSUED=13-mar-2017 NOTICE="Teradici - Dev Ops" TS_OK \
SIGN="00D0 A25F 78FB A9C4 7093 EB1A 2744 8500 DF9B 8201 9CFE \
F024 08A5 67DE CD45"
```

8. Generate the return request code by using appactutil. The ASR file referenced must be the one used to activate the license. The <u>-return</u> parameter is the Fulfillment ID noted in the previous step.

```
[admin@localhost licensing]$ ./appactutil -shortcode ~/ offline_activation.asr -return FID-OFFLINE-12345678-1
```

```
Return short code: 163698-563854-292262-189561-853089-634323-881517-668156
```

- 9. Send the return short code returned in step 8 as a text file to HP.
- 10. Support will return a response file where you must finish the deactivation by following the Completing the Offline Activation
 - Note: Finding fulfillment ID

To find your fulfillment ID, see <u>Viewing Installed Licenses</u>.

Uploading Endpoint Firmware to the PCoIP Management Console

Endpoint firmware files must first be uploaded to the PCoIP Management Console before you can create profiles or perform firmware updates.

Note: Prior to importing a PCoIP Management Console 1 profile

For PCoIP Zero Clients and Remote Workstation Cards, PCoIP Management Console must have at least one firmware image uploaded to it before you can import a PCoIP Management Console 1 profile. Migrated profiles will be assigned the latest firmware version that is present on PCoIP Management Console.

To upload endpoint firmware files to PCoIP Management Console:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Click **SOFTWARE** in the left pane.
- 3. Click Add Software/Firmware.
- 4. Click Select file.
- 5. Select the desired combined firmware file (.pcoip), and then click **Open* and **Upload** to upload the file to the PCoIP Management Console.

PCoIP Management Console Setting up Security

Setting up Security

Caution: Ensure system operates at a security level that matches your organization's requirements

As an administrative user, you must ensure your system operates at a security level that matches the requirements of your organization.

Update your software to the current release

From time to time, updates may be made available from support, or the OS developers. While we recommend staying current on releases, it is also recommended that you test updates on a test system prior to upgrading your production system or back up a snapshot of the PCoIP Management Console before running the update.

The OS admin user must use the sudo command when performing actions that require elevated privileges.

Note: Non-root Linux passwords must be at least ten characters long

Non-root Linux passwords must be at least ten characters long and contain one each of upper case, lower case, decimal, and special characters. When changing a non-root Linux password, the new password must be at least four characters different from the previous password.

The following table contains some further recommendations for securing your PCoIP Management Console over and above the default Rocky Linux security configuration undertaken by Teradici.

PCoIP Management Console Setting up Security

PCoIP Management Console Security Recommendations


Recommendations	Description
Network security	Configure your corporate firewall as follows: Block inbound traffic from unsecured networks to the PCoIP Management Console on all ports (for example, block traffic from the Internet). Block outbound traffic from the PCoIP Management Console to unsecured
	networks on all ports except for ports 80 and 443. Port 80 must be open for system updates and port 443 for system updates and licensing.
Operating system security	 Change the default passwords for the virtual machine admin user, root user, and web UI admin user immediately after installing the PCoIP Management Console. See <u>Accessing the PCoIP Management Console</u>
	Virtual Machine Console.
	• Ensure the Rocky Linux firewall only allows port access to the ports
	that are required for the PCoIP Management Console to run. See
	<u>Default firewall port settings are as follows.</u>
	Update Rocky Linux third-party packages on a regular basis using the
	sudo dnf update "package" command. Note: Prior to updating your production system
	To ensure that a library update does not cause problems, HP
	recommends that you perform updates on a test system (or that you
	take a snapshot of the PCoIP Management Console) before updating
	your production system. See <u>Backing Up PCoIP Management Console</u> <u>Database</u> .
	 Remove external NTP server references. See <u>NTP Configuration</u> <u>Considerations</u>
PCoIP Management Console web UI security	 Create a new PCoIP Management Console web UI administrative user and disable the default admin account and provide the desired role. (PCoIP Management Console Enterprise only).
	Note: Re-enabling admin account
	If you have disabled the admin account and plan to revert the PCoIP
	Management Console Enterprise to PCoIP Management Console Free,
	this account must be re-enabled before you can log in again to the
	PCoIP Management Console web UI. Alternatively, you can run a script from the PCoIP Management Console virtual machine console to re-
	enable the default admin account.

PCoIP Management Console Setting up Security

Recommendations	Description	
	 Replace the PCoIP Management Console certificate with your own 	
	custom certificate and upload it to all endpoints. See Managing PCoIP	
	Management Console Certificates.	
	Check the HP support site for the <u>latest PCoIP Management Console</u>	
	<u>release</u> .	
Enable HTTP Strict	HTTP Strict Transport Security (HSTS) is a policy that helps protect web server	
Transport Security	appliances against particular types of attacks against the communication between the	
(HSTS)	web browser and the web server.	
	See HTTP Strict Transport Security for details on how to enable HSTS.	
	Important: Requirements	
	HTTP Strict Transport Security (HSTS) requires:	
	 PCoIP Management Console have a proper trusted certificate installed 	
	 The chain or root certificate installed in the browser used to connect to 	
	the PCoIP Management Console	

Active Directory Authentication

PCoIP Management Console Active Directory (AD) authentication uses Lightweight Directory Access Protocol (LDAP) or Secure Lightweight Directory Access Protocol (LDAPS) with Active Directory servers for user authentication. LDAPS is recommended to give you a more secure environment, through the use of an Active Directory Certificate, which should be available before activating the Active Directory configuration.



Caution: LDAP or LDAPS

LDAPS is the secure version of LDAP and is recommended for production environments and requires installation of the Active Directory Certificate.

Active Directory Users

All Active Directory users have a default time zone of UTC which can be modified by a Management Console System Administrator after the user has logged in the first time.

Important Notes

This release of AD in PCoIP Management Console has important limitations which need to be considered before using this feature in your deployment.

- The MC's AD authentication only works for the same domain as the Domain Controller you have configured in the Management Console's SETTINGS > AUTHENTICATION > ACTIVE DIRECTORY **CONFIGURATION** tab
- Only supports on-premises Active Directory
- Only supports one active domain at a time

- Only supports UPN/AD and local user login
- Only supports uploading one AD certificate to the certificate store

Upload the Root Certificate

Upload the Root Certificate from the CA that issued the Domain Controller's certificate

- Configurations for parent groups do not transfer to child groups. Ensure the child group is configured as required.
- Does not support domain trust relationships
- A user must be member of at least one group created in the Active Directory Server that exists in the Management Console Active Directory Groups configuration.
- The Management Console Root DN field must include the users Active Directory Servers parent or child container's distinguished name (i.e. OU=Users,OU=Accounting,DC=domain,DC=local)



Installing an Active Directory Certificate

LDAPS requires a Base64 encoded certificate in .pem or .cer format to be uploaded to the certificate store. The LDAPS certificate should be downloaded from the same Active Directory that will be used for authentication. This can be done before or after enabling Active Directory.

To install your Active Directory Certificate:

- 1. Browse to **SETTINGS > SECURITY** and select the *ADD CERTIFICATES* tab.
- 2. Select the **UPLOAD CERTIFICATE** button.
- 3. Use the **SELECT CERTIFICATE** button and browse to where your Active Directory Certificate is located, highlight it and select the **Open** button.
- 4. Select the **UPLOAD** button and then **OK** in the Active Directory Certificate Details dialog.

 Access the PCoIP Management Console virtual machine console, (see <u>Accessing the PCoIP</u> <u>Management Console Virtual Machine Console</u>) and run the import script located in /opt/teradici/ scripts directory.

To run the script ensure you include the full path to the script and that you type the name of the correct AD uploaded certificate.


sudo /opt/teradici/scripts/import_ldaps_certificate.sh /opt/teradici/console/
certs/adcerts/< certificate_name >

b Tip: Dialog Information

After selecting the certificate the dialog contains additional information that is useful for managing your certificate from the virtual machine console.

Viewing your Active Directory Certificate

You can view the Active Directory Certificate by viewing the ACTIVE DIRECTORY CERTIFICATES tab located on the SECURITY settings page.



Active Directory Certificates tab

Removing your Active Directory Certificate

Removing your Active Directory Certificate requires you to login to the PCoIP Management Console virtual machine console, see <u>Accessing the PCoIP Management Console Virtual Machine Console</u> to run the removal script located in the **/opt/teradici/scripts** directory.

Once logged in to the virtual machine console, browse to the **opt/teradici/scripts** directory and **enter** ./remove ldaps certificate.sh.

Creating and Enabling Active Directory Configuration

The optional **Root DN** field, allows you to limit where the Management Console search begins in Active Directory. The entries must be in the correct format and order. For example the format would be **OU=Users,OU=Accounting,DC=domain,DC=local** or **DC=domain,DC=local** or similar.

To create and enable an Active Directory configuration:

- 1. Log in to PCoIP Management Console
- 2. Browse to **SETTINGS > AUTHENTICATION** and select the *ACTIVE DIRECTORY CONFIGURATION* tab.
- 3. Select the **NEW** button.
- 4. Select your preferred protocol **LDAP** or **LDAPS**.
- 5. Enter the **Host Name / IP Address** of your Active Directory Server and any specific port that you want to use.
- 6. Enter the **Domain Name** that the Active Directory Server manages.
- 7. Enter the **Root DN** (optional).
 - The Root DN or root distinguished name will tell Management Console which container in AD to start searching for approved Management Console users instead of searching the full list of domain users. Perform a group query (e.g. OU=Users,OU=Accounting,DC=domain,DC=local). Error messages for incorrect query strings will be presented that help guide the user using this method. Valid attributes are **DC**, **CN**, **OU**, **O**, **STREET**, **L**, **ST**, **C**, **UID**.
- 8. Save your configuration.
- Return to the ACTIVE DIRECTORY CONFIGURATION tab and click Enable to enable the connection.
 The PCoIP Management Console will reboot.
- 10. Login to Management Console with your Active Directory UPN and domain password.

Tip: If PCoIP Management Console does not restart

If your PCoIP Management Console does not restart using the PCoIP Management Console GUI, you can issue the following command from the PCoIP Management Console virtual machine console:

sudo service mcconsole restart

Adding Active Directory Groups

Adding Active Directory groups require that you have already enabled and configured Active Directory on the PCoIP Management Console. When adding Active Directory groups to PCoIP Management Console, ensure the added group has the identical name as the group in Active Directory and the Managing Users have been assigned to the group for PCoIP Management Console use. You can use just the group name or the group UPN name in this field.

To add or edit an active directory group:

- 1. Browse to **SETTINGS > AUTHENTICATION** and select the *ACTIVE DIRECTORY GROUPS* tab.
- 2. Select the ADD button.
- 3. Enter the required information.
 - · Group: Enter the group name.

Multiple Groups

- The Active Directory Group cannot be nested under any other group.
- If the name of the user is in multiple groups, the user in the first matching group is used.
- If a user is removed from that Active Directory group, then the next listed group will be used.
- Domain: Select the domain from the drop down where the Active Directory group resides.
- Role: This will be the PCoIP Management Console role given to the user for use when logging into the PCoIP Management Console. User roles can be changed at any time from the *Authentication* page. See <u>Managing Users</u> for further information on Users and User Roles.
- 4. Select the SAVE button.



Added AD Group


Identity Provider (IDP) Integration with Management Console (Enterprise)

Management Console allows for secure network Single Sign-on (SSO) with Multi-factor Authentication (MFA). It also allows for integration with your Active Directory servers and your Identity Providers (IDP) using the Security Assertion Markup Language 2.0 (SAML). With the benefit of SSO, users will be able to securely sign into Management Console without having to remember a separate Management Console password. These instructions are to help with configuration of single sign-on with a third party Identity Provider (IDP) which will allow for the authentication of management console users.

The Service Provider (SP) referenced in this instruction topic is the Management Console while the Identity Provider (IDP) used for reference is Okta and PingFederate. When you configure the IDP, you are using SAML2.0 to allow the IDP to pass the authorization credentials to Management Console or any other service provider.

You can enable IDP configuration via the IDP CONFIGURATION tab on the AUTHENTICATION page.

The basic IDP flow for Management Console is shown in this flow image.




Requirements

Management Console Enterprise License

- IPv4 network (IDP, SSO and MFA for IPv6 currently not supported)
- Account with an IDP Service Provider (Okta and PingFederate IDPs will be used for reference)
 - · IDP Metadata XML file
- Matching time configuration

The date and time configurations on Management Console and your IDP must match for the successful authentication of the Management Console using an IDP user. This includes the same date, time, and time zone.

 IDP must be enabled on Management Console. (SETTINGS > AUTHENTICATION > IDP CONFIGURATION > ON)



SSO Behaviors

Single Sign-on configurations for web based applications are browser specific, and do not support cross browser authentication. When you maintain an active browser session to an application that has been authenticated by an IDP, you will auto-login to applications authenticated by that IDP as long as the session is active.

IDP configured with SSO for Management Console and other applications (e.g. Office 365, Atlassian, ServiceNow)

When you are logged into another application and access the Management Console with the same browser, you will auto-login to Management Console without being prompted for IDP login credentials. Similarly, when you are logged into Management Console and access another application with the same browser, you will auto-login to the application without being prompted for IDP login credentials.

- Browser session time-outs do not affect Management Console user time-out settings. You have to sign out of Management Console to close your Management Console session. This applies to both IDP and direct Management Console sign ins.
- If your browser times out, re-launching your browser and accessing the Management Console will not prompt you for login credentials.

IDP Behaviors

- A continuous session for an IDP user is independent of the Management Console session time out.
- For all IDP users, the session will end by explicitly logging out of Management Console.
- If an IDP user session expires, the IDP user's session in Management Console will not close until they log out of the existing session from Management Console. This is due to the IDP not sending a closed session notification.
- If an IDP user session expires and the user then logs out of Management Console, than if the user logs in again with the SIGNIN WITH IDP button, the user will be redirected to the IDP login page.
- First time sign in to Management Console using an IDP user will automatically create a Management Console user with the default Administrator role.

Administrator default role

An IDP created user in Management Console will not have access to the SETTINGS page nor will they be able to change the default Management Console settings.

Administrators should consider changing the default IDP user role to System Administrator to provide access to SETTINGS and have the session timeout disabled.

Logging Out

- Logging out of a Management Console session only terminates the local Management Console session and does not affect the IDP session, nor sessions at other SPs where the IDP user may have been logged in using SSO.
- Logging out of a Management Console session using the dashboard LOGOUT link will close the user session and redirect the user to the Management Console login page.
- Using the **Sign In With IDP** button after logging out from the same browser will redirect the user to the Management Console dashboard page without redirecting to the IDP login page, as the IDP session is still active.
- All Management Console sessions in all browsers will close when a user logs out from any Management Console IDP connected session.
- Logging out of an IDP session will redirect the user to the IDP login page when using the **Sign In**With IDP button.

Roles and Permissions

- The default IDP role is Administrator and can be changed by any user with the System Administrator role.
- · Management Console created/edited user roles do not affect the IDP.
- IDP created/edited user roles do not affect Management Console

Management Console IDP Configuration

Prior to configuring the IDP for Management Console, you will need an IDP service that you can manage. Complete the referenced Okta or PingFederate configuration prior to performing the next steps. Okta Reference | PingFederate Install Reference & PingFederate Configuration Reference

1. Download the IDP metadata XML file from your IDP and upload this to Management Console. (See Okta reference here)

XML metadata file validation

To confirm the IDP metadata.xml file is valid, ensure the following:

- The Metadata XML file, Attributes, and Tags are not empty
- The file contains starting and ending tags
- · The contained signing certificate is valid
- The file does not contain a { RoleDescriptor } tag

2. Enter the Assertion Consumer Service URL.

The Assertion Consumer Service URL should be the same as the single sign-on URL in the IDP configuration and it must be entered in following format https://{ MC_FQDN/MC_IP_ADDRESS }/ saml/SSO.


3. Enter the SP Entity ID.

This ID will be any unique string specified in the IDP configuration to identify the Management Console application as a service provider connection.

4. Update the **Encryption Certificate** on Management Console.

By default, a self-signed certificate is available in Management Console which you can update at any time. You can use any of the following certificates when updating your Management Console certificate:

- The default Management Console Certificate:** Select the Revert Self-Signed Certificate button to have all the proper configurations using the default Management Console certificate applied. The Management Console will reset and be offline for a short period of time.
- CA Signed Certificate: Select the Update Certificate button and then individually upload the Encryption Certificate, Encryption Private Key, and the Encryption Chain.
- **Self-Signed Certificate**: Select the **Update Certificate** button and then individually upload the Encryption Certificate, Encryption Private Key, and the Encryption Chain.



- 5. Download the Encryption Certificate used in step 4 which will be required in your IDP configuration.
- 6. Use the Save Configuration button to save the IDP SAML configuration.
 This will cause the Management Console to restart and present the additional SIGN IN WITH IDP option on the Management Console sign in page.
- 7. Download the Service Provider(SP)/Management Console metadata XML file by using the **Download SP Metadata** button. This button becomes active once the SAML configuration is enabled after performing step 6. See OKta-Obtaining IDP Metadata File
- 8. Sign in to the Management Console using the **SIGN IN WITH IDP** button.

PCoIP Management Console Securing User Passwords

Securing User Passwords

Securing PCoIP Management Console User Passwords

This section provides an overview of how to change your PCoIP Management Console default passwords.

Accessing the PCoIP Management Console Virtual Machine Console

In order to change the PCoIP Management Console's default settings and run various scripts, you must connect to the PCoIP Management Console's virtual machine console and log in. The SSH server on the Rocky Linux operating system virtual machine is disabled on the OVA release of PCoIP Management Console since access to the virtual machine console can be made using VMware vSphere Client. However, if your security requirements permit SSH access, you can temporarily or permanently enable SSH for the PCoIP Management Console virtual machine **admin** user. This section provides instructions for both methods.

Info: PCoIP Management Console AMI virtual machine console

When using PCoIP Management Console AMI format, SSH on the Rocky Linux operating system virtual machine is enabled by default to provide console access via an SSH Client.

PCoIP Management Console AMI users should start at Logging in from an SSH Client

Logging in to the PCoIP Management Console OVA Virtual Machine Console

To log in to virtual machine console from vSphere Client:

- 1. Launch VMware vSphere Client.
- 2. Enter the IP address or FQDN for your vCenter Server along with your user name (**DOMAIN\user name**) and password.
- 3. Select Inventory > VMs and Templates.
- 4. Expand the inventory tree and locate your PCoIP Management Console virtual machine.
- 5. Right-click on the virtual machine and select **Open Console**.
- 6. Log in to the console:

user name: admin

password: **ManagementConsole2015** (default) or the password you have assigned to the **admin** user.

Note: Releasing the cursor once connected

Once you are connected to the console through the VMware vSphere client, you can release the cursor at any time by pressing Ctrl + Alt (Windows) or Fn + Control + Option (Mac).

7. When you have finished using the console, type logout to log out.

Enabling/Disabling SSH Access

By default, SSH access is disabled when the PCoIP Management Console OVA release is first installed. If your security requirements permit SSH access and you wish to log in to the PCoIP Management Console virtual machine console this way, you can run commands to enable SSH temporarily or permanently.

Note: Only admin user can access SSH on AMI and OVA distributions

The PCoIP Management Console is configured to only enable SSH access for the admin user when the SSH server is enabled. The PCoIP Management Console (OVA or AMI) always restricts SSH access for the root user.

TEMPORARILY ENABLING SSH ACCESS

To run the SSH server and enable SSH access for the admin user until the next reboot:

- 1. Log in as admin to the PCoIP Management Console OVA virtual machine console from your vSphere Client. See Logging in to the PCoIP Management Console OVA Virtual Machine Console.
- 2. Run the following command at the command line:

```
sudo /sbin/service sshd start
```

TEMPORARILY DISABLING SSH ACCESS

To stop the SSH server and disable SSH access for the admin user until the next reboot:

- 1. Log in as **admin** to the PCoIP Management Console virtual machine console from your vSphere Client. See <u>Logging in to the PCoIP Management Console OVA Virtual Machine Console</u>.
- 2. Run the following command at the command line:

```
sudo /sbin/service sshd stop
```

Note: Permanent SSH configuration

A permanent SSH configuration will automatically start the SSH service on reboot.

PERMANENTLY ENABLING SSH ACCESS

To permanently enable SSH on next reboot:

- 1. Log in as admin to the PCoIP Management Console OVA virtual machine console from your vSphere Client. See Logging in to the PCoIP Management Console OVA Virtual Machine Console.
- 2. Run the following command at the command line:

```
sudo chkconfig sshd on
```

3. If SSH is disabled, Run the following command at the command line to start SSH immediately:

sudo service sshd start

PERMANENTLY DISABLING SSH ACCESS

Caution: Disabling SSH access on PCoIP Management Console AMI release not recommended

Disabling SSH access on PCoIP Management Console AMI releases is not recommended as it will prevent you from gaining vm console access which may be required to make changes such as security updates and password changes.

To permanently disable SSH for the admin user after the next reboot:

- 1. Log in as admin to the PCoIP Management Console OVA virtual machine console from your vSphere Client. See Logging in to the PCoIP Management Console OVA Virtual Machine Console).
- 2. Run the following command at the command line:

```
sudo chkconfig sshd off
```

3. Disable the service by running the following command at the command line:

sudo service sshd stop

LOGGING IN FROM AN SSH CLIENT

To log in to virtual machine console from SSH Client once SSH is enabled:

1. Launch your preferred SSH client.

2. Enter the following information:

- Host name: Enter the FQDN or IP address for your PCoIP Management Console virtual machine.
- Port: 22
- · Connection type: SSH
- 3. Click Open.
- 4. Log in to the PCoIP Management Console virtual machine console:
- 5. user name: admin
- 6. **password:** ManagementConsole2015 (default) or the password you have assigned to the admin user. See <u>Changing the PCoIP Management Console Virtual Machine Default User Password.</u>
- 7. When you are finished using the console, type exit to log out and exit the application.
- 8. If desired, disable SSH. See Enabling/Disabling SSH Access.

CHANGING THE PCOIP MANAGEMENT CONSOLE VIRTUAL MACHINE DEFAULT USER PASSWORD

The PCoIP Management Console's default password when it is first installed is ManagementConsole2015. To secure the PCoIP Management Console, it is critical to change this password immediately after installation.

To change the virtual machine default user password:

- 1. Log in to your PCoIP Management Console virtual machine console as admin using the default password, ManagementConsole2015.
- 2. Type passwd at the command prompt.
- 3. When prompted, enter the default password and then your new password twice:

```
passwd
Changing password for admin user.
New password:
Retype new password:<br/>br>passwd:<br/>vassword updated successfully.
```

4. Follow your company's policy for storing and sharing passwords.

Changing the PCoIP Management Console Web Interface Default Password

Disable default admin user

For security reasons, you must disable the default admin user and create a different administrative user with a new name and password (Management Console Enterprise only). See <u>Managing</u> Users.

Important: Set time zone

You should select your time zone at this point. If you do not set the desired time zone, you may run schedules at an undesirable time.

The PCoIP Management Console web user account has the following default user name and password when it is first deployed which must be changed immediately after first login:

- User name: admin
- · Default password: password
- Default Role: System Administrator

If further changes to the admin account password are required, perform the following steps:**To** change the admin account password:

- 1. Click **SETTINGS** and then **AUTHENTICATION** to display the *MANAGEMENT CONSOLE USERS* window.
- 2. In the USERNAME column, select admin and then click EDIT.
- 3. In the *Current Password* field enter the current password.
- 4. In the New Password field, enter the new password.
- 5. In the Confirm Password field, enter the password again.
- 6. Click SAVE.

Re-enabling the PCoIP Management Console's Web UI Admin User Account

The PCoIP Management Console virtual machine contains a script that lets you re-enable the PCoIP Management Console web UI **admin** account from the PCoIP Management Console virtual machine console command line. This is useful if you disable the **admin** account from PCoIP Management Console Enterprise and subsequently transition to PCoIP Management Console Free before reenabling the account from the PCoIP Management Console web UI. In this case, you can run this script to re-enable the **admin** user and enable administrative access to the PCoIP Management Console Free web UI.

To re-enable the admin account:

- 1. Select one of the following choices depending on whether you are using the OVA or AMI version of PCoIP Management Console.
 - Open the PCoIP Management Console console from vSphere Client. See <u>Logging in to the PCoIP Management Console OVA Virtual Machine Console</u>.
 - SSH into the PCoIP Management Console AMI console.
- 2. Log in using the PCoIP Management Console console admin user name and password.
- 3. Change to the scripts directory:

```
cd /opt/teradici/scripts
```

4. Type the following command to run the script:

```
./enable admin.sh
```

Reverting the PCoIP Management Console's Web UI Admin User Password

The PCoIP Management Console virtual machine contains a script that lets you revert the password for the PCoIP Management Console's web interface **admin** user to **password** (the default) from the PCoIP Management Console command line. This is useful if administrators lose their PCoIP Management Console web interface passwords and need a way to get logged in again.

To revert the admin account password to its default value:

- 1. Open the PCoIP Management Console console from vSphere Client. See Logging in to the PCoIP Management Console OVA Virtual Machine Console.
- 2. Log in using the PCoIP Management Console console admin user name and password.
- 3. Change to the scripts directory:

```
cd /opt/teradici/scripts
```

4. Type the following command to run the script:

```
./reset admin password.sh BCRYPT New Password
```

Password Hashes

There are two hash arguments when resetting the admin password. BCRYPT is the recommended hash argument to use for passwords over SHA512

Changing the PCoIP Management Console Virtual Machine Default 'Root' Password

For security reasons, the **root** user is not used for PCoIP Management Console administration. This user account has a large, randomly-generated password that is not published. To secure the PCoIP Management Console, it is critical to change this password immediately after installation.

Virtual Machine Password

On first boot, the PCoIP Management Console generates a random password. Though the password is randomly generated, it is still recommended that you change this password. Consult with your security team to ensure your new password conforms with your local security policy.

To change the virtual machine default root password:

- 1. Log in to your PCoIP Management Console virtual machine console as admin.
- 2. Type the following command at the prompt:

```
sudo passwd root
```

3. When prompted, enter the new password twice:

```
Changing password for root user.

New password:

Retype new password:

passwd: all authentication tokens updated successfully.
```

PCoIP Management Console Moving to a Newer Version

Moving to a Newer Version

Migrating PCoIP Management Console to a Newer Release Using OVA

Note: DNS Records

Ensure your PCoIP Management Console has a correctly configured A record and PTR record on your DNS server. It is important to maintain the IP address and DNS hostname of your currently deployed PCoIP Management Console when migrating to a newer release. This enables a seamless transition to the new PCoIP Management Console and eliminates unnecessary PCoIP endpoint configuration as each endpoint is configured to report to the previous PCoIP Management Console IP address.

Tip: Disable Auto-Config and Scheduling

Consider turning off Auto-Config and Scheduling prior to doing a database backup. Performing this step ensures both features will be off when you restore the database preventing unexpected schedules from running and preventing new devices from suddenly appearing in the PCoIP Management Consoleduring the migration process. After confirming a successful database restore consider re-enabling Auto-Config and Scheduling.

These instructions explain how to migrate PCoIP Management Console 2.x or later to a more current PCoIP Management Console release.

At the end of this section you will find instructions that will allow the new Management Console OVA format to work in an IPv6 environment.

To migrate PCoIP Management Console to a newer release:

- 1. Connect to your PCoIP Management Console virtual machine console that you wish to migrate from and log in using the admin account and password. See <u>Accessing the PCoIP Management</u> Console Virtual Machine Console.
 - If migrating from PCoIP Management Console 2.x go to step 2.
 - If migrating from PCoIP Management Console 3.x, 19.x or higher go to step 3.
- 2. PCoIP Management Console 2 users. Perform the following steps to record the IP address, netmask, and default gateway:
 - a. Type sudo system-config-network to launch the network configuration tool.
 - b. From the main menu, select **Device configuration**.
 - c. In the next screen, select eth0 (eth0) vmxnet3.
 - d. Make a note of PCoIP Management Console 2's static IP address, netmask, default gateway, and DNS server. If no IP information is displayed, it is because the PCoIP Management Console 2 is configured to use DHCP which is not recommended. See <u>Assigning a Static IP</u> Address.
 - e. Select Ok.
 - f. In the next screen, select **Cancel**.
 - g. In the next screen, select Quit.

Recommendation

Support does not recommend changing the PCoIP Management Console DNS configuration.

- 3. PCoIP Management Console 3 and higher users. Perform the following steps to record the IP address, netmask, and default gateway:
 - a. Type sudo nmtui to launch NetworkManager TUI.
 - b. From the main menu, select Edit a connection.
 - c. In the next screen, select **eth0**, and press [Enter].
 - d. Make a note of PCoIP Management Console 3's static IP address, netmask, default gateway DNS servers, and domains (if configured). If no IP information is displayed, it is because the

PCoIP Management Console is configured to use DHCP which is not recommended. See Assigning a Static IP Address.

- e. Select < **OK** > or < **Cancel** > and press Enter
- f. Select < Back > to return to the main screen.

Recommendation

Support does not recommend changing the PCoIP Management Console hostname using this tool.

- g. In the next screen, select Quit.
- 4. Manage your PCoIP Management Console certificate:

▲ Management Console default certificate expiry date

The default Management Console certificate used in versions 23.06 or older expired on October 15, 2023.

If you are managing endpoints using the default Management Console certificate from Management Console 23.06 or older, you will no longer be able to manage new endpoints. Existing endpoints will be lost if they lose communication to Management Console (i.e. network or power loss). You will need to upload a valid certificate to your existing endpoints and Management Console.

Management Console 23.08 and newer has an <u>updated default certificate</u>.

• To use the **updated 23.08+ default Management Console certificate**, first you will need to update your endpoint profiles to include the new default Management Console certificate and push the profile out to every endpoint, including any ungrouped endpoints, before deploying the new console. If necessary, use each individual endpoint's AWI to upload the new default Management Console certificate to the endpoint. See <u>Managing Profiles</u>.

b Important: Update endpoint profile's new certificate before deploying the upgrade

Ensure that you roll out the new certificate to the endpoints prior to deploying the new PCoIP Management Console; that is, update your profile certificates using the original console. Otherwise, you will lose the management of the endpoint.

- If you plan to use your custom PCoIP Management Console certificate after upgrading, our support team recommends that you copy it to a safe location where you can retrieve it to use with the new PCoIP Management Console. See <u>Managing PCoIP Management Console</u> Certificates.
- If you plan to use a **new custom PCoIP Management Console certificate** after upgrading, first you will need to update your endpoint profiles to include the new PCoIP Management Console certificate (or its issuer) and push the profile out to every endpoint, including any ungrouped endpoints, before deploying the new console. If necessary, use each individual endpoint's AWI to upload the new PCoIP Management Console certificate (or its issuer) to the endpoint. See Managing PCoIP Management Console Certificates.
- 5. Back up and download the current PCoIP Management Console database archive file to an external location before beginning the upgrade:
 - a. Log in to the PCoIP Management Console web interface.
 - b. From **SETTINGS > DATABASE**, select **BACK UP**.
 - c. Enter a description for the backup and click BACK UP.
 - d. When the backup completes, select the file in the database table, click **DOWNLOAD**, and then save the archive file. You will need to retrieve this file later.
 - Important: Database upgrades when migrating from PCoIP Management Console 2.4 or older

Upgrades when migrating from PCoIP Management Console 2.4 or older can generate large databases that can cause issues during upgrades. See knowledge-base-article-1029 for workarounds.

- 6. If you are using PCoIP Management Console Enterprise, record the following licensing information by <u>viewing installed licenses for online</u> installations or <u>viewing installed licenses for offline</u> installations.
 - Fulfillment ID
 - Entitlement ID (activation code)
- 7. If you are using PCoIP Management Console Enterprise, deactivate the PCoIP Management Console Enterprise license from the **SETTINGS > LICENSE** page.
- 8. Shut down the PCoIP Management Console virtual appliance.

- 9. Follow <u>Installing PCoIP Management Console using vSphere</u> to deploy the new PCoIP Management Console release.
- 10. Connect to your PCoIP Management Console virtual machine console. See <u>Logging in to the PCoIP Management Console OVA Virtual Machine Console</u>.
- 11. Log in as admin using the default password (ManagementConsole2015) and change the admin user password. See <u>Accessing the PCoIP Management Console Virtual Machine Console</u>.
- 12. Use the same network settings as the previous PCoIP Management Console release.
 - Note: Reserve IP address against the new virtual machine if using DHCP reservation

If you are using DHCP reservation, reserve the IP address against the new PCoIP Management Console virtual machine. Otherwise, see Assigning a Static IP Address for instructions.

- **Migration between IPv4 and IPv6**: If your migration includes changing IPv4 and IPv6 networks, review <u>using IPv6</u> and <u>moving between IPv4 and IPv6</u>
- 13. Restart the PCoIP Management Console and ensure it has the correct addressing information.
- 14. If you are using PCoIP Management Console Enterprise, activate its license from the SETTINGS > LICENSE page.
- 15. Log in to the PCoIP Management Console web interface using the following default user account:
 - User name: admin
 - Password: password
- 16. If you are using a custom PCoIP Management Console certificate (either the custom certificate from the previous PCoIP Management Console release or a new custom certificate), upload the certificate to the new PCoIP Management Console. For more information creating and uploading your own certificate, see Managing PCoIP Management Console Certificates.
 - Note: Skip this step if using the default signed certificate

If you are using the default self-signed PCoIP Management Console certificate, skip this step.

17. Upload the database archive file you saved in step 5, and then restore the database. See <u>Managing PCoIP Management Console Databases</u>.

This step reverts user accounts and passwords to previous PCoIP Management Console release

This step replaces all users on the system with the user accounts and passwords that existed on the previous PCoIP Management Console. If you changed the default web UI password for the admin account, it will not be the standard default password. If necessary, you can revert the admin account password to its default value and then reset the password. To revert the password, see Reverting the PCoIP Management Console Web Interface Default Password.

- 18. Log in again using your standard user account.
- 19. Check the Management Console Health field on the **DASHBOARD** page to ensure the PCoIP Management Console status is **GOOD**. See <u>Understanding the PCoIP Management Console Dashboard</u>.
- 20. From the ENDPOINTS page, click **REFRESH** to see endpoints begin contacting the new PCoIP Management Console. You can also verify groups, profiles, schedules, and auto configuration rules at this time. See <u>Managing Endpoints</u>.

Migrating Management Console OVA format to IPv6

To migrate Management Console OVA format to IPv6, you must configure your network interface to IPv6 and then configure your firewall rules to remove IPv4 rules and allow IPv6 rules for Management Console communication. The firewall rules referenced below refer to firewalld.

- 1. Perform the steps above. After performing the steps above, change the Management Console network configuration to IPv6 by performing the steps in <u>Moving between IPv4 and IPv6</u>
- 2. Access Management Console Web UI via IPv6 address.

5 Time Settings

Ensure your Management Console time settings are correct by using the sudo hwclock --debug
command. If there are issues, check your host computer time and date settings, BIOS and VM hardware settings.

PCoIP Management Console Upgrading using RPM

Upgrading using RPM

Upgrading Management Console Using RPM

Update your software to the current release

From time to time, updates may be made available from support, or the OS developers. While we recommend staying current on releases, it is also recommended that you test updates on a test system prior to upgrading your production system or back up a snapshot of the PCoIP Management Console before running the update.

Backup Your Database

Always ensure you have a working backup of your Management Console data when performing a Management Console removal, upgrade, or installation. Considerations should include:

- * having a current snapshot of your virtual machine
- * having a complete backup or clone of your Linux PC
- * having a current backup of your Management Console database.

There are two different scenarios that require slightly different steps when upgrading Management Console using the RPM. One scenario has Management Console deployed on a site that has access to the Internet and the other scenario is having Management Console deployed on a dark site where there is no internet access.

Prior to performing a RPM upgrade, the default certificate should be uploaded to all endpoints either through a profile or directly from an endpoint AWI.

Note: Users of RHEL 7 and CentOS 7

If you are using MC in RHEL 7 or CentOS 7, we recommend to use RHEL 8, RHEL 9, Rocky Linux 8, or Rocky Linux 9 and do a fresh installation then upload the Database backup.

PCoIP Management Console Upgrading using RPM

Download the appropriate rpm for RHEL and Rocky Linux

To install on RHEL 8 or Rocky Linux 8, download the teradicimc-<mc_version>.el8.x86_64.rpm file. To install on RHEL 9 or Rocky Linux 9, download the teradicimc-<mc_version>.el9.x86_64.rpm file.

UPGRADING MANAGEMENT CONSOLE WITH INTERNET ACCESS

RPM upgrades may require new certificates uploaded to your endpoints

If you are upgrading to Management Console 25.06 from version 23.06 or earlier, and if you are not using custom certificates, you must upload the new Management Console certificate to your endpoints. For the new Management Console certificate SHA-256 & SHA-512 values, see the release notes.

For instructions on how to upload your certificate see <u>Updating PCoIP Management Console</u> Certificates after Endpoint Discovery

Prior to upgrading Management Console you can:

- Clear the management state on all your endpoints **before** the upgrade and rediscover them after the upgrade.
- Ensure that the new certificate is uploaded to your endpoints before you upgrade to Management Console 25.06.

PCoIP Management Console Upgrading using RPM

b Important: Upgrading on RHEL in an IPV6 environment

If you are upgrading the Management Console in **RHEL 8 or 9** with IPV6, you must disable the local repository before starting the upgrade and then re-enable it after the upgrade is complete. Run the following commands:

Before upgrading, disable local repos:

```
subscription-manager config --rhsm.manage_repos=0
```

• After upgrading is complete, re-enable local repos:

```
subscription-manager config --rhsm.manage repos=1
```

- Upload the Management Console default self-signed certificate to all endpoints either through a
 profile or directly from an endpoint AWI if you are using the Management Console default
 certificate.
 - a. Login to your existing Management Console, create a profile with the provided default certificate <u>cert.pem</u> file uploaded in the Certificate Store.
 - b. Apply the profile to all the endpoints discovered in Management Console. Once the profile is applied successfully, the endpoint will have the new default certificate uploaded.
- 2. Download the <u>available RPM</u> and ensure that they are located in the <logged in user directory> on the Management Console Linux VM.

You can use a third party tool such as WinSCP to copy and move files into the RHEL/Rocky Linux host operating system.

PCoIP Management Console Upgrading using RPM

△ Caution: RHEL IPv6 User or Upgrading from MC 24.03 or Previous Versions to 25.06

If you are a RHEL 8 or 9 IPv6 user or upgrading from MC 24.03 or previous versions to MC 25.06, follow the below step before proceeding with the next step:

Download the RHEL dependency file for this release from the support site and run below command from the directory where the dependency file is located.

RHEL 8:

```
sudo sh ./teradicimc <mc version> mc dependency rhel8.tar.gz
```

RHEL 9:

```
sudo sh ./teradicimc_<mc_version>_mc_dependency_rhel9.tar.gz
```

3. Upgrade the Management Console from the directory where the rpm file is located.

```
sudo dnf install teradicimc-<mc version>.rpm
```

Note: Applying Profiles

If a profile was created in Management Console 23.12.1 or earlier with the **Enable Audio** property set to Disabled and FW 23.12.x version, and you intend to apply this profile in Management Console 23.12.2 or later, ensure that **Enable Analog Audio Input** is disabled before applying this profile.

UPGRADING MANAGEMENT CONSOLE WITHOUT INTERNET ACCESS (DARK SITE)

- 1. Upload the Management Console default self-signed certificate to all endpoints either through a profile or directly from an endpoint AWI if you are using the Management Console default certificate
 - a. Login to your existing Management Console, create a profile with the provided default certificate cert.pem file uploaded in the Certificate Store.
 - b. Apply the profile to all the endpoints discovered in Management Console. Once the profile is applied successfully, the endpoint will have the new default certificate uploaded.

Upgrading using RPM **PCoIP Management Console**

2. Download the <u>available RPM</u> and MC RPM dependencies from the <u>support site</u> and ensure they are located in the <logged in user directory> on the Management Console Linux VM.

You can use a third party tool such as WinSCP to copy and move files into the RHEL/Rocky Linux host operating system.

▲ Caution: Upgrading from MC 24.10 or previous versions to 25.06

If you are upgrading from MC 24.10 or previous versions to MC 25.06, follow step 3 below before proceeding with the upgrade.

- 3. Upgrade the MC Dependencies using the dependency.tar.gz.
 - RHEL 8:

```
sudo sh ./teradicimc <mc version> mc dependency rhel8.tar.gz --
disablerepo=*
```

• Rocky Linux 8:

```
sudo sh ./teradicimc <mc version> mc dependency rocky8.tar.gz --
disablerepo=*
```

• RHEL 9:

```
sudo sh ./teradicimc <mc version> mc dependency rhel9.tar.gz --
disablerepo=*
```

• Rocky Linux 9:

```
sudo sh ./teradicimc_<mc_version>_mc_dependency_rocky9.tar.gz --
disablerepo=*
```

4. Upgrade the Management Console from the directory where the rpm file is located

```
sudo dnf install teradicimc-<mc version>.rpm --disablerepo=*
```

Moving Between IPv4 and IPv6

Management Console supports only pure IPv4 or IPv6 networks and not hybrid or stacked networks.

Upgrading and migrating at the same time

If a user wants to upgrade and migrate (Ipv6 to Ipv4 and vice versa) at the same time e.g. user want to upgrade from 20.04 IPv4 to 20.07 IPv6, we suggest they first complete upgrade (20.04 IPv4 to 20.07 IPv4 upgrade) and then following the IPv4 to IPv6 migration guideline

These steps must be performed in order for Management Console to operate successfully in a pure IPv4 or pure IPv6 environment.

Deleted Data

Be sure to backup your database in case you have to revert your change. When changing networks, Management Console will permanently delete unrelated data. See <u>deleted data</u> for more information on what is deleted.

To configure firewalld for an existing Management Console deployment that has been changed from IPv4 to IPv6 or vice versa

- 1. Login to the Management Console host operating system console.
- 2. Stop the mcconsole service.

sudo systemctl stop mcconsole

3. Stop the mcdaemon service.

sudo systemctl stop mcdaemon

4. To Enable or Disable IPv6 environment, you must modify the **teradici.ipv6.conf** file by executing either of the following commands.

• To disable IPv6 configuration in an IPv4 environment

```
sudo su
echo -e
"net.ipv6.conf.all.disable_ipv6=1\nnet.ipv6.conf.default.disable_ipv6=1"
> /usr/lib/sysctl.d/teradici_ipv6.conf
exit
```

• To enable IPv6 configuration in an IPv6 environment

```
sudo su
echo -e
"net.ipv6.conf.all.disable_ipv6=0\nnet.ipv6.conf.default.disable_ipv6=0"
> /usr/lib/sysctl.d/teradici_ipv6.conf
exit
```

- 5. Change the NIC IP address to IPv4 or IPv6.
- 6. Reboot your computer.

```
sudo init 6
```

- 7. Configure your Management Console firewall for the appropriate network.
 - Configuration rules from 20.04 or later to 20.07.1
 - Moving from IPv4 to IPv6: Follow the same steps as shown at <u>Firewall changes required</u> after an RPM <u>Upgrade from Management Console 20.04 to Management Console 20.07</u> in IPv6 Environment
 - Moving from IPv6 to IPv4: Follow the same steps as shown at <u>Firewall changes required</u> after an RPM <u>Upgrade from Management Console 20.04 to Management Console 20.07</u> in IPv6 Environment
 - Configuration rules from 20.01 or older to 20.07.1
 - Moving from IPv4 to IPv6: Follow the same steps as shown at <u>Updating firewall</u> configuration after upgrading from Management Console 19.05 through to 20.01 to <u>Management Console 20.07 with IPv6</u>

 Moving from IPv4 to IPv4: Follow the same steps as shown at <u>Firewall changes after a</u> RPM Upgrade from Management Console 20.01 or older using IPv4

8. Run the scripts to delete unrelated data to maintain a pure IPv4 or IPv6 network.

```
cd /opt/teradici/database
sudo python3.9 mc_env_db.py
```

9. Start the mcconsole service.

```
sudo systemctl start mcconsole
```

10. Start the mcdaemon service.

sudo systemctl start mcdaemon

Existing IPv6 rule removal

If your Management Console happens to have previous Management Console IPv6 rules configured, remove them now by performing the following steps.

Note: If rule is not enabled it shows a warning NOT_ENABLED

1. Close port 443:

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 port port=443 protocol=tcp accept'
```

2. Close port 22:

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 port port=22 protocol=tcp accept'
```

3. Close port 5172:

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 port port=5172 protocol=tcp accept'
```

4. Close port 80:

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 port port=80 protocol=tcp accept'
```

5. Remove port forwarding of 8443 to 443:

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 forward-port to-port=8443 protocol=tcp port=443'
```

6. Remove port forwarding of 8080 to 80:

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 forward-port to-port=8080 protocol=tcp port=80'
```

To configure firewalld rules for an existing Management Console moving from an IPv6 to an IPv4 network perform the following steps:

- 1. Login to the Management Console host operating system console.
- 2. Enable required IPv4 ports.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-
port={22,443,80,5172}/tcp
```

3. Redirect IPv4 port 443 to port 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-forward-
port=port=443:proto=tcp:toport=8443
```

4. Redirect IPv4 Port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-forward-
port=port=80:proto=tcp:toport=8080
```

- 5. Remove IPv6 rules.
 - Remove port forwarding to 8443 and 8080

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-forward-
port=port=443:proto=tcp:toport=8443
```

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-forward-
port=port=80:proto=tcp:toport=8080
```

Close port 443

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 port port=443 protocol=tcp accept'
```

· Close port 22

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 port port=22 protocol=tcp accept'
```

Close port 5172

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 port port=5172 protocol=tcp accept'
```

· Close port 80

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 port port=80 protocol=tcp accept'
```

6. Remove redirect of IPv4 port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 forward-port to-port=8443 protocol=tcp port=443'
```

7. Remove redirect IPv6 Port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-rich-
rule='rule family=ipv6 forward-port to-port=8080 protocol=tcp port=80'
```

8. Reload the firewall.

```
sudo firewall-cmd --reload
```

- 9. Confirm the rules are applied.
 - a. Check the firewalld status is active.

```
sudo systemctl status firewalld
```

```
[autorunner@gcp892b829c82864a9aa9b870e795e74383 ~]$ sudo systemctl status firewalld

• firewalld.service - firewalld - dynamic firewall daemon
Loaded: loaded (/usr/lib/systemd/system/firewalld.service; enabled; vendor preset: enabled)
Active: active (running) since Fri 2020-02-14 10:24:12 UTC; 34min ago
Docs: man:firewalld(1)
Main PID: 730 (firewalld)
CGroup: /system.slice/firewalld.service
L730 /usr/bin/python2 -Es /usr/sbin/firewalld --nofork --nopid
```

b. Verify all rules are added in firewalld or not, all rules should be applied.

```
sudo firewall-cmd --list-all
```

```
[admin@localhost ~]$ sudo firewall-cmd --list-all
public (active)
 target: default
  icmp-block-inversion: no
 interfaces: eth0
  sources:
  services: dhcpv6-client ssh
 ports: 80/tcp 22/tcp 443/tcp 5172/tcp
 protocols:
 masquerade: no
 forward-ports: port=443:proto=tcp:toport=8443:toaddr=
      port=80:proto=tcp:toport=8080:toaddr=
  source-ports:
 icmp-blocks:
 rich rules:
admin@localhost ~]$
```

To configure firewalld rules for an existing Management Console moving from an IPv4 to an IPv6 network perform the following steps:

- 1. Login to the Management Console host operating system console.
- 2. Remove IPv4 rules.
 - · Close IPv4 ports

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-
port={22,443,80,5172}/tcp
```

Remove IPv4 port forwarding to 8443 and 8080

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-forward-
port=port=443:proto=tcp:toport=8443
```

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-forward-
port=port=80:proto=tcp:toport=8080
```

3. Enable required IPv6 ports.

Open port 443

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=443 protocol=tcp accept'
```

• Open port 22

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=22 protocol=tcp accept'
```

Open port 5172

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=5172 protocol=tcp accept'
```

• Open port 80

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=80 protocol=tcp accept'
```

4. Redirect IPv6 port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8443 protocol=tcp port=443'
```

5. Redirect IPv6 Port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8080 protocol=tcp port=80'
```

6. Reload the firewall.

```
sudo firewall-cmd --reload
```

7. Confirm the rules are applied.

a. Check the firewalld status is active.

sudo systemctl status firewalld

b. Verify all rules are added in firewalld or not, all rules should be applied.

```
sudo firewall-cmd --list-all
```

```
Distributer # 12 mg/o firewall-cmd --list-all
public (active)

interfaces: employs with the selection of interfaces of interface
```

Migrating from PCoIP Management Console 1

Follow the steps outlined here to migrate your PCoIP Management Console 1 to PCoIP Management Console version 2 or later.

PCoIP Management Console properties

Not all properties from PCoIP Management Console 1 have been migrated to the current release of PCoIP Management Console. For further details, see PCoIP Management Console 1 Profile **Properties Renamed or Not Migrated**

Step 1: Install and configure this version of PCoIP Management Console

Management Console formats

These instructions are for configurations using the OVA format of this release of Management Console. Different formats (AMI, RPM) will require similar steps.

To install and configure the current OVA version of PCoIP Management Console:

- 1. To install PCoIP Management Console using vSphere Client
- 2. To log in to virtual machine console from vSphere Client
- 3. Changing the PCoIP Management Console Virtual Machine Default User Password
- 4. Changing the Default Network Configuration
- 5. Managing Licenses Online (optional).
- 6. If you are using an autodiscovery method, update your DHCP or DNS server with the new PCoIP Management Console information:
 - <u>Configuring DHCP Options</u> (for DHCP discovery)
 - Adding the DNS SRV Record (for DNS discovery)
 - Adding a DNS TXT Record (for DNS discovery)
- 7. <u>Using the Web Interface for the First Time</u>.

- 8. Changing the PCoIP Management Console Web Interface Default Password.
 - HP recommends that you disable the web UI **admin** user and create a new PCoIP Management Console administrative user.
- 9. From the PCoIP Management Console web UI, upload the desired 20.01 or later firmware file for your endpoints.
 - At least one 20.01 or later firmware image must be uploaded before a profile can be created.

Step 2: Import profiles, create groups, and assign profiles to the groups

PCoIP Management Console provides a profile import script that enables you to import your PCoIP Management Console 1 profiles into newer releases of PCoIP Management Console.

Importing process creates tab for endpoints

The profile import process will create a tab for Tera2 Dual and Quad PCoIP Zero Clients and Remote Workstation Cards. If you are only migrating one type of endpoint (quad or dual), it is recommended that you delete the tab for the other type to avoid accidentally configuring the wrong profile type. For example, if you are only migrating dual PCoIP Zero Clients and you set properties in the **QUAD** tab, the profile will not be applied.

Migrated Profile Naming Rules

Migrated profiles are named according to the following rules:

- If there is no profile in the new PCoIP Management Console with the PCoIP Management Console 1 profile name, then the migrated profile is called the same name as was used in PCoIP Management Console 1.
- If there is a profile in the new PCoIP Management Console with the PCoIP Management Console 1 profile, then the migrated profile is called the PCoIP Management Console 1 name with **imported** appended to it. If that name is already taken, then the script appends #, where # is an integer that starts counting up from one until it finds a name that is not taken.

Example

If the new PCoIP Management Console does not have a 'My Profile' profile, importing this profile four times from PCoIP Management Console 1 would result in the following PCoIP Management Console profile names.

Migrated Profile Naming Example

# of Times Migrated	PCoIP Management Console 1 Profile Name	PCoIP Management Console Profile Name
1	My Profile	My Profile
2	My Profile	My Profile_imported
3	My Profile	My Profile_imported 1
4	My Profile	My Profile_imported 2

Sort the DESCRIPTION column to show the last created profile

If you are unsure what name the migrated profile is called, sort the profile table's DESCRIPTION column by the last created description. The most recently created profile will be at the top. See <u>Displaying Profile Information</u>.

Before You Import Your Profiles

Before beginning, ensure the following prerequisites are in place:

- For PCoIP Zero Clients and Remote Workstation Cards, ensure you have uploaded the firmware version used in your profiles, otherwise migrated profiles will be assigned the latest firmware version that exists in PCoIP Management Console.
- The import script requires the following firmware conditions be met, or the migration script will abort and provide an error message.

Firmware applied in PCoIP Management Console 1 profile being migrated	Firmware required to be preloaded to PCoIP Management Console 3 or later for migration script to run successfully	
No firmware applied to MC1 profile	Client and Remote Workstation Card	
Client only	Client	
Remote Workstation Card only	Remote Workstation Card	
Client and Remote Workstation Card	Client and Remote Workstation Card	

- You know your PCoIP Management Console 1 user password (that is, the password for the *teradici* administrative user) if it was changed. The default password is **4400Dominion**.
- You know the PCoIP Management Console 1 profile name(s).

PCoIP Management Console 1

Profile names are case and white space sensitive.

- Both PCoIP Management Console 1 virtual appliance and the new PCoIP Management Console virtual appliance reside on the same network.
- PCoIP Management Console virtual appliance is able to open an SSH tunnel to the PCoIP Management Console 1 virtual appliance over port 22.

To test if the virtual appliance is able to open an SSH tunnel:

- a. From your PCoIP Management Console VM console, type **ssh teradici@< PCoIP Management Console 1 IP address or domain name >**.
- b. Enter your PCoIP Management Console 1 VM password.
- c. Type exit to close the session and return to your PCoIP Management Console.
- On PCoIP Management Console 1.x, you perform the following steps:
 - a. With root privileges, modify /etc/postgresql/9.1/main/postgresql.conf by replacing the line

```
listen addresses = 'localhost' with listen addresses = '*'.
```

6 Commented lines

Note that any code preceded by the # symbol is a comment. The functioning line of code in this step is located at the bottom of the file.

- b. With root privileges, modify /etc/postgresql/9.1/main/pg_hba.conf by appending a new line host all all 0.0.0.0/0 md5 and saving the file.
- c. Reboot MC1 and make sure the changes were saved.
- On PCoIP Management Console 3.x or newer releases, you perform the following step:
 - 1.Run the command sudo iptables -I INPUT 1 -p tcp -m state --state NEW --dport 5432 -j ACCEPT

Import Individual Profiles

To import profiles to PCoIP Management Console release 2 or later, run the migration script shown next for each profile that you want to import:

- 1. Log in to your new PCoIP Management Console VM console. See <u>Logging in to the VM Console on page 1</u>.
- 2. Change to the **migration_script** directory:

```
cd /opt/teradici/database/legacy/migration script
```

- 3. Run the script (one or more times) to migrate one profile at a time using one of the following commands:
 - If you have not changed the PCoIP Management Console 1 user password:

```
./migrate mc1 profile.sh -a <MC 1 address> -p <"profile name">
```

• If you have changed the PCoIP Management Console 1 user password:

```
./migrate_mc1_profile.sh -a <MC 1 address> -p <"profile name"> -l <MC 1 user password>
```

where <"profile name"> is the exact PCoIP Management Console 1 profile name enclosed in double quotes (for example, "My Profile").

Profile Names in PCoIP Management Console 1

Profile names are case and white space sensitive.

- 4. Load (or reload) the newPCoIP Management Console *PROFILE* page to see the migrated profiles. See Managing Profiles.
- 5. Select each profile and click **EDIT** to check that the profile settings are correct. For example, if your PCoIP Management Console 1 profile contained a certificate file, this file should also be present in your new PCoIP Management Console profile.

Note: OSD logo is never imported

The OSD logo is never imported. While you are in edit mode, you can manually add this logo to your PCoIP Management Console profile or modify the profile as desired. For details about other profile properties that are not migrated or that have been renamed by the profile import process, see PCOIP Management Console 1 Profile Properties Renamed or Not Migrated.

- 6. From the PCoIP Management Console 1 web UI, make a note of the groups that contain the endpoints you want to migrate and then create the groups from the new **ENDPOINTS** page on the new PCoIP Management Console using the same group names.
- 7. Associate the correct profile with each group in turn.

Troubleshooting the Profile Import Script

The profile import script is case and white space sensitive because PCoIP Management Console 1 profile names are case and white space sensitive. If the script is unable to find your 1.10.x profile, try copying the exact profile name from PCoIP Management Console 1.

To copy the exact profile name from PCoIP Management Console 1:

- 1. In the PCoIP Management Console 1 PROFILES page, click the profile's Edit link.
- 2. In the Edit Profile dialog, select the entire content of the Name field and copy it.
- 3. When you run the script, paste this name enclosed in double quotes as the < profile name > in the migration script instructions.

Step 3: Migrate each group of PCoIP Management Console 1 endpoints to this version of PCoIP Management Console

If you have a large deployment, support recommends that you migrate your endpoints on a group-by-group basis, checking that the endpoints in each group have successfully migrated to the new PCoIP Management Console, before proceeding with the next group.

To migrate each group of endpoints:

- 1. Create and enable an auto configuration rule.
- 2. From PCoIP Management Console 1, upgrade PCoIP endpoints to firmware 20.01 or higher.
- 3. If you are not using DHCP options or DNS service record discovery, perform a manual discovery from the new PCoIP Management Console to discover the endpoints.
- 4. Refresh the new PCoIP Management Console **ENDPOINTS** page and check that the endpoints have been discovered and placed in the correct group with the correct associated profile.

PCoIP Management Console Managing Firmware

Managing Firmware

Managing PCoIP Zero Client and Remote Workstation Card Firmware

<u>Upgrading Endpoints to Firmware 5.0 or Later</u> and <u>Downgrading to Older Firmware</u> provide an overview of how to upgrade or downgrade your version of the PCoIP Zero Client or Remote Workstation Card firmware.

Deployments containing endpoint groups with different versions of firmware should consider upgrading all endpoints to the (same) latest version of firmware for ease of management and upgradeability.

Firmware in migrated profiles

Migrating from Management Console 1

When using profiles from PCoIP Management Console 1 that were migrated to newer versions of PCoIP Management Console, ensure <u>firmware requirements are met</u>. You must upload at least one image of the firmware you wish to upgrade to. Migrated profiles will be assigned the latest firmware version that is present on PCoIP Management Console.

Recommendations for firmware use in Management Console

- First upgrade to Management Console 20.01 or newer and secondly deploy firmware 20.01 or newer.
- After upgrading your Management Console you will be able to manage any endpoints with older firmware.
- If you have a large deployment with multiple endpoint groups, we recommend scheduling firmware upgrades one group at a time.

Upgrading Endpoints to Firmware 5.0 or Later

PCoIP Management Console cannot upgrade endpoints running firmware versions prior to 5.0. Instead, you can perform this step remotely for a group of endpoints using PCoIP Management Console 1 or you can update the firmware for individual endpoints locally using each endpoint's AWI.

Firmware 20.01

If you use PCoIP Management Console to deploy firmware 20.01 or newer, it is strongly recommended that you first upgrade to Management Console 20.01 or newer and secondly deploy firmware 20.01 or newer.

Important: Test the upgrade with a small group of test endpoints

Before upgrading all your endpoints, first test the procedure with a small group of test endpoints to ensure that they can be discovered and managed by PCoIP Management Console.

A Caution: Remote Workstation Cards

Remote Workstation Cards cannot be powered down, power reset, or reset to default by the PCoIP Management Console as the Remote Workstation Card requires the host computer to be restarted due to the Remote Workstation Card obtaining its power from the host computer motherboard. An alternate method of restarting the host computer is required to restart the host computer.

Upgrading Firmware Using PCoIP Management Console 1

To update the firmware for a group of endpoints using PCoIP Management Console 1:

- 1. Ensure that the endpoints you wish to update are placed in their own group. Depending on your site configuration, this may require modifications to your DHCP options or DNS SRV records, or it may require disabling persistent auto-configuration or placing the endpoints into a segregated network with a new PCoIP Management Console 1.
- 2. From the PCoIP Management Console 1 or later home page, click **Update Firmware**.

- 3. Click the **Import Firmware** link to transfer the firmware 20.01 or higher release file from your host machine to the PCoIP Management Console 1 virtual machine.
- 4. Click **Browse**, locate the combined firmware file, and then click **Open**. This file will have a .pcoip extension.
- 5. Click **Import Now** to transfer the firmware 20.01 or higher release file from your host machine to the PCoIP Management Console 1 virtual machine.
- 6. Click the **Update Devices** link.
- 7. In the Select Devices to Update section, you can further define the endpoints you wish to upgrade by 3 different groupings.
 - Device Family: lists the processor family used by the endpoint Tera2.
 - **Version Number:** represents the currently applied firmware on the endpoints you want to update (for example, **20.07**).
 - **Group:** lists any groups you have previously configured for endpoint management.

• Tip: Upgrade firmware one group at a time

HP recommends upgrading firmware one group at a time. Groups that are not migrated and will have to be recreated manually in the new PCoIP Management Console.

- 8. Click View Devices to Update.
- 9. Select the endpoints you wish to update, choose the desired endpoint restart and schedule options, and then click **Schedule Update**.
- 10. If desired, click **View Status** to watch the update status of the endpoints.

Note: Update endpoint firmware by applying a profile

You can also update endpoint firmware by applying a profile that contains an associated firmware file. For information about managing endpoints with PCoIP Management Console 1, see the <u>PCoIP Management Console 1.x User Manual</u>.

After the endpoints reboot, they are no longer online in PCoIP Management Console 1. If you configure the endpoints to include the address for the newer PCoIP Management Console, or update

your DHCP options appropriately, then the endpoints are present in the new PCoIP Management Console in a few minutes.

Upgrading Firmware Using the Endpoint's AWI

To update the firmware for an individual endpoint using the AWI:

- 1. Enter the endpoint's IP address in your browser's address bar and then log in to its AWI.
- 2. Select the **Upload > Firmware** menu.
- 3. From the *Firmware Upload* page, browse to the folder containing the firmware file. This file will have an .all extension.
- 4. Double-click the '.all' firmware file and then click **Upload*.
- 5. Click **OK** to confirm that you want to proceed with the upload. The operation may take a few minutes. When completed, the AWI page displays two buttons—**Reset** and **Continue**.
- 6. Click Reset.
- 7. Click OK.

Downgrading Endpoints to an Older Firmware

From PCoIP Management Console, you can apply a profile to a group of endpoints running firmware 20.01 or higher to remotely downgrade firmware to an older version. Alternatively, you can downgrade the firmware on an individual endpoint using the endpoint's AWI.

Important: Perform a firmware upload twice when downgrading firmware to 4.8.x on a Tera2 PCoIP Zero Client

For PCoIP Zero Clients, you will need to perform a firmware upload twice. This is because the current firmware installed in the endpoint also contains a recovery image that exists in a different location in flash memory from the firmware image. When you upload a new firmware file to the endpoint, the recovery image is left untouched to guarantee that if the firmware upload fails, a bootable image to boot from still exists. It is therefore necessary to perform another full upload to ensure that the recovery image is completely removed. When using PCoIP Management Console to perform a downgrade to an older firmware, the second firmware upload will need to be completed using PCoIP Management Console 1. Alternatively, you can upload the firmware twice from the PCoIP Zero Client AWI. For more details about recovery mode, please see PCoIP Zero Client Firmware Administrators Guide. This does not apply to Remote Workstation Cards.

Downgrading Endpoint Firmware Using a PCoIP Management Console Profile

Before you begin, be sure you assign the firmware for the endpoints you wish to downgrade to a group. See <u>Organizing Endpoints into Groups</u> to find out more.

DOWNLOADING THE FIRMWARE

All access subscribers can obtain the latest firmware by navigating to the <u>Uploading the Firmware to</u> <u>the PCoIP Management Console</u>

To upload the firmware to the PCoIP Management Console:

1. Download the older firmware file for PCoIP Zero Clients, and if required the older firmware file for Remote Workstation Cards, and extract the package contents.

- 2. From PCoIP Management Console, click **SETTINGS > SOFTWARE** to display the *SOFTWARE MANAGEMENT* window.
- 3. Click Add Software/Firmware.
- 4. Click **Select file**, select the combined firmware .pcoip file that you extracted previously, and then click **Open** and **Upload** to upload the file to the PCoIP Management Console.

ASSOCIATING A PROFILE WITH A GROUP

To associate a profile with a group:

- 1. In the PCoIP Management Console top menu, click PROFILE and then NEW PROFILE.
- 2. Enter a name and description for the older firmware profile.
- 3. Click the + tab, select the appropriate profile option and click **ADD**.

 Options are:
 - TERA2: CLIENT [DUAL] (latest firmware)
 - TERA2: CLIENT [QUAD] (latest firmware)
 - TERA2: HOST [DUAL] (latest firmware)
 - TERA2: HOST [QUAD] (latest firmware)
- 4. In the SOFTWARE section, select the firmware file from the Firmware Version drop-down list, and then click **SAVE**.
- 5. From the ENDPOINTS page, select the group containing the endpoint(s) you want to downgrade.
- 6. Click **PROFILE** and then select **CHANGE**.
- 7. In the drop-down list, select the profile you just created, and then click **OK**.
- 8. Select the I understand message and click OK again.

APPLYING THE PROFILE IMMEDIATELY

You can apply the profile immediately to either a group of endpoints or an individual endpoint.

To apply the group or individual profile immediately:

- 1. In the PCoIP Management Console top menu, click **ENDPOINTS** and select the desired group or endpoint.
- 2. Click **PROFILE** and then select **APPLY**.
- 3. Enable the I understand message and then click APPLY.
- 4. From the *DASHBOARD*, check **Endpoint Updates in Progress** in the *CURRENT ACTIVITY* section for information about the update.

Note: Synchronize firmware image after applying profile

After the profile applies, the selected PCoIP Zero Clients will automatically restart and upload the latest firmware image. The Remote Workstation Cards will need to be restarted manually before it uploads the latest firmware image. After the restart, the endpoints will either no longer appear in the ENDPOINTS table or they may appear as offline. The PCoIP Management Console will not be able to manage them. To synchronize the recovery image (applicable to PCoIP Zero Clients only) in flash memory, perform the update again from PCoIP Management Console 1 using the UPDATE > Update Devices > Update Firmware feature. For details, see the PCoIP Management Console 1.x User Manual.

Creating a Schedule to Apply the Profile (Enterprise)

You can also create a schedule to apply the profile at a specific date and time.

To create a schedule to apply the profile:

- 1. In the PCoIP Management Console top menu, click SCHEDULE.
- 2. Ensure that the All Schedules setting is toggled to **ON**.
- 3. Select **NEW SCHEDULE**.
- 4. Configure the parameters as follows:
 - Type: Select Apply Profile.
 - · Name: Enter a name for the schedule.
 - Description: Enter a description for the schedule.
 - Enabled: Toggle to ON.

- **Groups:** Click **ADD**, select the group containing the endpoints you want to downgrade, and then click **ADD**.
- Start Time: Click the time zone widget and select the desired date, then click the clock widget below the calendar and select the desired time.

Note: Change the default time zone

By default, the PCoIP Management Console time zone is Coordinated Universal Time (UTC). If you are in a different time zone, you can display the PCoIP Management Console web interface in your own time zone to facilitate creating schedules. See <u>Config_local_time.md</u>.

- Ensure that Run Once is selected.
- 5. Click **SAVE** at the top of the page.
- 6. From the *DASHBOARD*, check **UPCOMING SCHEDULES** to see schedule information. When the schedule runs, you can view its progress by checking **Endpoint Updates in Progress** in the *CURRENT ACTIVITY* section.

PCoIP Management Console Discovering Endpoints

Discovering Endpoints

Discovery Process Overview

Before endpoints can be managed by the PCoIP Management Console, they must first be discovered. Once discovered, the PCoIP Management Console will label the device as either a local or remote endpoint.

During the discovery process, the PCoIP Management Console determines whether a device is local or remote by comparing the IP address of the communicating endpoint with the IP address that the endpoint is configured with. If the two addresses are the same, the PCoIP Management Console labels the endpoint as a local endpoint. If the two IP addresses are different, such as in networks utilizing NAT devices, the PCoIP Management Console labels the endpoint as a remote endpoint. The PCoIP Management Console also labels an endpoint as local if the endpoint reports its IP address in the configured Local IP Address Ranges field found on the **SETTINGS > REMOTE > REMOTE**CONFIGURATION page. Endpoints identified as remote endpoints require a reverse proxy and additional configurations which are further described in Remote Endpoint Management (Enterprise)

This topic provides an overview of the main steps of the PCoIP endpoint discovery process.


Important: Replace the default self-signed certificate with your own before configuring a discovery method and adding endpoints

We strongly recommend that you replace the PCoIP Management Console self-signed certificate with your own PCoIP Management Console certificates before configuring a discovery method and before adding endpoints to the PCoIP Management Console. See Management Console Certificates for details.

The following diagram illustrates how endpoints discover a PCoIP Management Console.

Note: PCoIP Management Console serves as both Endpoint Bootstrap Manager and Endpoint Manager

The PCoIP Management Console serves as both the Endpoint Bootstrap Manager and the Endpoint Manager. It is possible that other endpoint managers of the PCoIP Management Console may separate these roles.



An illustration of PCoIP endpoint discovery process

Endpoint Discovery Process

The steps outlined in the preceding illustration are explained next.

Note: Endpoint Bootstrap Manager and Endpoint Manager information

The Endpoint Bootstrap Manager/Endpoint Manager information with which an endpoint must be provisioned before it can be discovered depends on the endpoint's discovery method and security level. You can configure both these options from the endpoint's AWI **Configuration > Management** page. Please see PCOIP Zero Client Firmware Administrators' Guide for details. See also Configuring an Endpoint Manager Manually from an Endpoint for instructions on how to manually configure an Endpoint Manager from its AWI Management page.

Stage 1: Provisioning Endpoints

There are three ways in which you can provision endpoints with endpoint bootstrap manager or endpoint manager information for automatic and manual discovery — DHCP vendor-specific options, DNS service and text records, Uniform Resource Identifier (URI).

The first stage provisions endpoints with the information they need either to connect to the Endpoint Bootstrap Manager for bootstrapping, or to connect directly to the Endpoint Manager. Depending on the endpoint's configured discovery method, you can manually enter the information or it can be provisioned automatically.

DISCOVERY METHODS

For automatic discovery, endpoints are populated with the IP address or FQDN of the PCoIP Management Console to which they should connect via DHCP vendor-specific options or DNS service and text records. Optionally, endpoints can also be configured with the PCoIP Management Console certificate's fingerprint (that is, its digital signature) by the DHCP or DNS server. If the PCoIP Management Console certificate fingerprint is provided in the DHCP or DNS record, the endpoint (in low security mode) will verify the PCoIP Management Console certificate by only matching the fingerprint. This is intended for use cases where the PCoIP Management Console trusted root CA certificate (the PCoIP Management Console chain certificate) is not uploaded to the endpoint, or if the PCoIP Management Console certificate does not meet the verification requirement. If a fingerprint is not provisioned, an endpoint without a trusted PCoIP Management Console certificate will fail to connect. Automatic discovery is used for low and medium security environments.

For manual discovery, you manually configure each endpoint with the uniform resource identifier (URI) of the Endpoint Bootstrap Manager (for low and medium security environments), or with the URI of the actual Endpoint Manager (for high security environments).

ENDPOINT CERTIFICATE REQUIREMENTS

Depending on an endpoint's configured security level, you may also need to provision endpoints with an PCoIP Management Console certificate.

Endpoints configured for medium or high security must have a trusted certificate in their certificate store before they can connect to an PCoIP Management Console. For some endpoints, certificates may be pre-loaded by the vendor as a factory default. Otherwise, you can manually upload certificates using an endpoint's AWI.

Endpoints that are configured for low security do not need a PCoIP Management Console certificate in their trusted certificate stores if either of the following is true:

- They are using DHCP discovery or DNS discovery and the DHCP or DNS server has provisioned them with the PCoIP Management Console certificate's fingerprint.
- They are discovered using the PCoIP Management Console's manual discovery method. See <u>Discovering Endpoints Manually from PCoIP Management Console</u>.

The following table summarizes the certificate requirement for endpoints based on their discovery method and configured security level.

Certificate Requirements for Endpoints

Discovery Method	Low Security	Medium Security	High Security
DHCP/DNS discovery without Endpoint Bootstrap Manager fingerprint provisioned	Certificate required	Certificate required	N/A
DHCP/DNS discovery with Endpoint Bootstrap Manager fingerprint provisioned	Certificate *not*required	Certificate required	N/A
Discovery initiated by an endpoint configured for a high security environment	N/A	N/A	Certificate required
Manual discovery initiated by the PCoIP Management Console	Certificate not required	N/A	N/A

Information about endpoint security levels is summarized next.

Low Security

When low security is in use, endpoints can be discovered manually from the PCoIP Management Console. See <u>Discovering Endpoints Manually from PCoIP Management Console</u>.

Endpoints can use DHCP or DNS autodiscovery. If the Endpoint Bootstrap Manager fingerprint is also provisioned by the DHCP or DNS server, endpoints do not require a certificate.

Medium Security

When medium security is in use, endpoints cannot be discovered manually from the PCoIP Management Console.

Endpoints will not use the certificate fingerprint retrieved from the DHCP or DNS server to trust the PCoIP Management Console. A PCoIP Management Console certificate or its issuer public key certificate must be pre-loaded in the endpoint.

High Security

When high security is in use, endpoints cannot be discovered manually from the PCoIP Management Console and cannot use DHCP or DNS autodiscovery.

The Endpoint Manager's address must be manually entered into the endpoint.

A PCoIP Management Console public key certificate or its issuer public key certificate must be preloaded in the endpoint.

Stage 2: Entering the Bootstrap Phase

Endpoints that have been provisioned with Endpoint Bootstrap Manager information enter a bootstrap phase where they evaluate the Endpoint Bootstrap Manager's certificate fingerprint to determine whether the Endpoint Bootstrap Manager can be trusted. If the certificate fingerprint match succeeds, the endpoints proceed to the next step.

Note: High security endpoints configured with Endpoint Manager information bypass the bootstrap process

Endpoints in high security environments that are already configured with Endpoint Manager connection information bypass the Endpoint Bootstrap Manager bootstrap process and attempt to connect to the Endpoint Manager right away.

Stage 3: Receiving Endpoint Manager Information

Next, the Endpoint Bootstrap Manager provides the IP address and certificate fingerprint of the Endpoint Manager to which the endpoint should connect. The endpoint then disconnects from the Endpoint Bootstrap Manager and attempts to establish a connection with the Endpoint Manager.

Stage 4: Entering the Managed Phase

If Endpoint Manager certificate verification succeeds and the endpoint is able to establish a successful connection with the Endpoint Manager, the Endpoint Manager connection information is saved to the endpoint's permanent storage, and the endpoint enters the managed phase.

Configuring a Discovery Method

Note: Confirm your endpoint's discovery method


Review the administrators' guide for your endpoint to confirm the discovery method it supports.

The following topics contain information about how to configure an endpoint discovery method:

- <u>Configuring Endpoints using Auto Discovery</u>: Explains how to configure your DHCP server to provision endpoints with Endpoint Bootstrap Manager information.
- <u>Configuring DNS SRV Record Discovery</u>: Explains how to configure your DNS server to provision endpoints with Endpoint Bootstrap Manager information.
- <u>Configuring an Endpoint Manager Manually from an Endpoint</u>: Explains how to manually configure an Endpoint Manager for an endpoint in a high security environment.
- <u>Discovering Endpoints Manually from PCoIP Management Console</u>: Explains how to manually initiate discovery from the PCoIP Management Console. Endpoints must be configured for low security if you use this method.

Configuring DHCP for Endpoints that use Auto Discovery

This section explains how to configure your DHCP server to provision endpoints with Endpoint Bootstrap Manager information.



DHCP Discovery Process

When DHCP vendor class option discovery is used, endpoints receive a DHCP option value that contains information about the PCoIP Management Console (that is, the Endpoint Bootstrap Manager/Endpoint Manager) to which they should connect. If an endpoint has already obtained a DHCP lease before the server is configured with PCoIP Management Console DHCP options, it will be updated with this information when it renews the lease or acquires a new one. An endpoint will renew its lease after a reboot or when it detects that the network has returned after going down (for example, if someone reconnects the endpoint's network cable after unplugging one end of it).

✓ Note: Endpoints also poll DHCP server for option values

Endpoints also poll the DHCP server for option values at an interval equal to half the DHCP lease time.

You can configure your DHCP server with vendor class options to provide the following information:

• The PCoIP Management Console's IP address or FQDN.

• The PCoIP Management Console's certificate fingerprint (digital signature). This fingerprint is required if you have not installed the PCoIP Management Console's trusted root CA certificate (the PCoIP Management Console chain certificate) in the endpoint's certificate store and you want to use automatic discovery. DHCP options discovery will not succeed if you do not provide a digital signature and do not configure endpoints with a certificate that enables them to trust the PCoIP Management Console. If provided, this fingerprint is only used when the endpoint's security level is set to **Low Security Environment** and certificate verification has failed. It is ignored when the security level is set to **Medium Security Environment** or **High Security Environment**.

Note: Provide PCoIP Management Console information using either DHCP options or DNS records

The endpoint only picks up the fingerprint in a DHCP option if the PCoIP Management Console address is also specified in a DHCP option. For example, if the PCoIP Management Console address is specified as a DNS SRV record but the fingerprint is provided as a DHCP option, the endpoint will not retrieve the fingerprint information in the DHCP server. You should configure PCoIP Management Console information using either DHCP options or DNS records, but not both.

This discovery method requires you to have a DHCP server in your network that meets the following requirements:

- The DHCP server must support both DHCP option 60 (vendor class identifier) and option 43 (vendor-specific information). Option 60 is sent from the endpoint to the DHCP server. It contains a text string that uniquely identifies the endpoint type. Option 43 is created by the user. The steps provided in the sections that follow show how to create a DHCP option 43 called **PCoIP Endpoint** along with two sub-options under it— **EBM URI (sub-option 10)** and **EBM X.509 SHA-256** fingerprint (sub-option 11).
- The PCoIP endpoints must have DHCP enabled so they can send a request to the DHCP server and receive the address of the PCoIP Management Console in response. This is their default setting.

Before You Begin

These instructions explain how to create a **PCoIP Endpoint** vendor class and how to create two DHCP options (sub-options 10 and 11) that provide PCoIP Management Console information to the PCoIP Endpoint.

Note: Skip adding vendor class if you have previously configured PCoIP Endpoint vendor class

If you have used DHCP vendor class option discovery with a previous 1.x release of the PCoIP Management Console and have already configured your DHCP server with the PCoIP Endpoint vendor class, you can skip the following section entitled Adding the PCoIP Endpoint Vendor Class.

Before beginning, you should have the following information handy:

- The PCoIP Management Console's IP address or FQDN. In the following example, this address is configured in a DHCP sub-option called **EBM URI**.
- The PCoIP Management Console certificate SHA-256 fingerprint. In the following example, this hash value is configured in an optional DHCP sub-option called **EBM X.509 SHA-256 fingerprint**.

To locate the PCoIP Management Console's fingerprint:

- 1. Use Mozilla Firefox to log in to the PCoIP Management Console web interface.
- 2. Click the padlock icon in the browser's address bar.
- 3. Click More Information.
- 4. Click View Certificate.
- 5. In the **Fingerprints** section, copy and paste the SHA-256 fingerprint into a text editor.

✓ Note: Examples shown use Windows Server 2012 R2

The instructions provided may change slightly depending on your specific server version.

Adding the PCoIP Endpoint Vendor Class

To add the PCoIP DHCP vendor class to your DHCP server:

- 1. Log in to your Windows Server and select **DHCP**.
- 2. Right-click on your DHCP server in the **SERVERS** pane and select **DHCP Manager**.
- 3. Expand your server in the tree, right-click on IPv4, and then select Define Vendor Classes.
- 4. Click Add to add a new DHCP Vendor Class.

- 5. Enter **PCoIP Endpoint** in the *Display* name field.
- 6. Enter **PCoIP Endpoint** in the ASCII column as the Vendor ID.
- 7. Click **OK** to save and close the dialog.


Configuring DHCP Options

To add two PCoIP Management Console DHCP options and apply them to a scope:

- 1. Right-click on **IPv4** in the tree and select **Set Predefined Options**.
- 2. Select PCoIP Endpoint as the Option class and click Add.
- 3. In the *Option Type* dialog, enter the name **EBM URI**, data type **String**, code **10**, and description **Endpoint Bootstrap Manager URI**, then click **OK**.
- 4. Click **OK** to save and close the dialog.
- 5. For the PCoIP Management Console's SHA-256 certificate fingerprint, repeat steps 1 and 2 to add another option.
- 6. In the *Option Type* dialog, enter the name **EBM X.509 SHA-256 fingerprint**, data type **String**, code **11**, and description **EBM X.509 SHA-256 fingerprint**, then click **OK**.
- 7. Expand the tree for the DHCP scope to which you want to apply the options.
- 8. Right-click **Scope Options** and select **Configure Options**.
- 9. Click the Advanced tab and select the PCoIP Endpoint vendor class.
- 10. Enable the check box for **010 EBM URI** and then enter a valid Management Console URI in the **Data** entry field, and click **Apply**.
 - This URI requires a secured WebSocket prefix (for example, wss://:[port number]. The PCoIP Management Console's listening port is 5172. Entering this port number is optional. If you do not include it, port 5172 will be used by default.
- 11. Choose the checkbox for **011 EBM X.509 SHA-256 fingerprint** and paste the PCoIP Management Console certificate SHA-256 fingerprint you obtained previously into the *String value* field.
- 12. Click **OK** to save and close the dialog.

Configuring DNS for Endpoints that use Autodiscovery

This section explains how to configure your DNS server to provision endpoints with Endpoint Bootstrap Manager information, as part of the endpoint autodiscovery process.



DNS Discovery Process

Endpoints poll the DNS server for information about the PCoIP Management Console (that is, the Endpoint Bootstrap Manager/Endpoint Manager) to which they should connect only if the DHCP server does not have a DHCP option containing the PCoIP Management Console's IP address or FQDN.

If an endpoint has already retrieved a DNS record before the DNS server is configured with PCoIP Management Console information, it does not poll the DNS server again until the record's Time-To-Live expires (or the endpoint is rebooted). If the DHCP server does provide an option for the PCoIP Management Console address but the endpoint fails to connect for any reason (for example, because of a certificate verification failure or the PCoIP Management Console address is not reachable), DNS record lookup will not occur.

Note: Do not configure DHCP options when you are using DNS record discovery

Do not configure DHCP options if you want to use DNS record discovery. Endpoints always prefer the PCoIP Management Console address or fingerprint that is specified in the DHCP options over that specified in the DNS record. If you provide the PCoIP Management Console address both as DHCP option and also as the DNS record, the endpoint will only use the PCoIP Management Console address found in the DHCP option.

DNS service record discovery requires you to have a DNS server in your network that is configured with the following DNS records:

- An address record (A record): Specifies the FQDN and IP address of the PCoIP Management Console. This record may be automatically created by the DHCP server.
- A service location record (SRV record): Associates information such as the PCoIP Management Console's TCP/IP service and the port the PCoIP Management Console listens on with the PCoIP Management Console's domain and host name. The PCoIP Management Console's TCP/IP service is called _pcoip-bootstrap, as shown in Adding the DNS SRV Record.
- A DNS TXT record: Contains the PCoIP Management Console certificate SHA-256 fingerprint is also required if you have not installed the PCoIP Management Console's trusted root CA certificate (the PCoIP Management Console chain certificate) in the endpoint's certificate store and you want to use automatic discovery. The record's name must be the host name of the PCoIP Management Console offering the service. In the following example, this record is called pcoip-mc38719. The domain is appended automatically.

Note: Endpoint only picks up DNS TXT fingerprint if the PCoIP Management Console address is specified in a DNS SRV record

The endpoint only picks up the fingerprint from the DNS TXT record if the PCoIP Management Console address is specified in a DNS SRV record. For example, if the PCoIP Management Console address is specified as a DHCP option but the fingerprint is provided as a DNS TXT record, the endpoint will not retrieve the fingerprint information in the DNS server. Configure your PCoIP Management Console information using either DHCP options or DNS records, but not both.

Before You Begin

Before configuring your DNS SRV record discovery, you'll need the following information:

- The PCoIP Management Console's FQDN
- The PCoIP Management Console's certificate fingerprint (that is, the certificate's digital signature).
 If provided, this fingerprint is only used when the endpoint's security level is set to Low Security
 Environment and certificate verification has failed. It is ignored when the security level is set to
 Medium Security Environment or High Security Environment.

To locate the PCoIP Management Console's fingerprint:

- 1. Use Mozilla Firefox to log in to the PCoIP Management Console web interface.
- 2. Click the padlock icon in the browser's address bar.
- 3. Click More Information.
- 4. Click View Certificate.
- 5. In the **Fingerprints** section, copy and paste the SHA-256 fingerprint into a text editor.


Note: Examples shown use Windows Server 2012 R2

The instructions provided may change slightly depending on your specific server version.


Adding the DNS SRV Record

To add the PCoIP Management Console DNS SRV record to DNS server:

- 1. Log in to your Windows Server and select **DNS**.
- 2. Right-click on your DNS server in the *SERVERS* pane and select **DNS Manager** from the context menu.
- 3. In *Forward Lookup Zones*, right-click on your domain and select **Other New Records** from the context menu.




4. In the Resource Record Type dialog, select **Service Location (SRV)** from the list and click **Create Record**.



5. Fill in the entries as shown in the following example. Set Service to **_pcoip-bootstrap**, Protocol to **_tcp**, and *Port number* to **5172**, the PCoIP Management Console's default listening port. For *Host offering this service*, enter the PCoIP Management Console's FQDN.

Note: FQDN must be entered in place of IP address

The PCoIP Management Console's FQDN must be entered because the DNS specification does not enable an IP address in SRV records.



6. Click OK.


7. If you are not adding an optional DNS TXT record (see next) and have finished configuring your DNS server, power cycle your endpoints or put them online to enable them to make the connection to the PCoIP Management Console. You must also upload the PCoIP Management Console's root CA certificate to the endpoint's certificate store.

Adding a DNS TXT Record

If your endpoints do not have the PCoIP Management Console's root CA certificate installed in their certificate store, you must configure your DNS server with a DNS TXT record containing the PCoIP Management Console certificate SHA-256 fingerprint.

To add a DNS TXT record:

- 1. In *Forward Lookup Zones*, right-click on your domain and select **Other New Records** from the context menu.
- 2. In the Resource Record Type dialog, select **Text (TXT)** from the list and click **Create Record*.
- 3. Fill in the entries as follows:
 - In the *Record name* field, enter the host name of the PCoIP Management Console offering the service (this example uses *pcoip-mc38719*). The FQDN field will be automatically populated for you, and matches the FQDN of the PCoIP Management Console.
 - In the *Text* field, type pcoip-bootstrap-cert= and then paste the PCoIP Management Console certificate SHA-256 fingerprint you obtained previously immediately after this prefix, as shown in the following example.



- 4. Click OK.
- 5. When you have finished configuring your DNS server, power cycle your endpoints or put them online to enable them to make the connection to the PCoIP Management Console.

Note: Automatically name and group endpoints

You can configure the PCoIP Management Console to automatically name endpoints and place them in a specific group when they are discovered. See <u>Auto Naming Endpoints</u> and <u>Auto Configuring Endpoints</u> (Enterprise) for details.

See <u>Troubleshooting DNS</u> to verify that your DNS server is configured correctly for the PCoIP Management Console.

Discovering Endpoints Manually from PCoIP Management Console

The **ENDPOINTS** page contains an **ENDPOINT DISCOVERY** feature that lets you discover endpoints that are not pre-configured with PCoIP Management Console information. Endpoints must be configured for low security before they can be discovered using this method.

Important: If your endpoints are behind a NAT or proxy

Manual discovery of an endpoint will not work if the endpoint is behind a NAT or proxy.

MANAGEMENT profile properties, **Security Level** and **Discovery Mode** have been added to allow the PCoIP Management Console the ability to apply specific management security level and management server discovery methods. This enables highly secured environments to pre-stage endpoints in a secured environment with their future management settings, prior to delivery to their final location.

Note: Endpoint discovery options

The PCoIP Management Console also supports the DHCP vendor-specific option method, DNS service record method, and manual endpoint configuration for endpoint discovery.

You can discover endpoints from the PCoIP Management Console by scanning for their IP addresses. This discovery method is used in low security environments for endpoints that are not pre-configured with PCoIP Management Console connection information or certificates. It enables an improved out-of-box experience by removing the need for administrators to manually configure an endpoint with a PCoIP Management Console address and upload a PCoIP Management Console certificate to the endpoint. With this method, the endpoint retrieves the required trust information from the PCoIP Management Console during the discovery process.

In order for discovery to succeed, the following conditions must apply:


- The endpoint is powered on and connected to the network that is not behind a proxy or NAT.
- The endpoint is not connected to an Endpoint Manager and has an **Idle** management status (that is, is not engaged in any kind of PCoIP Management Console activity).
- The endpoint is configured for a Low Security Environment from its AWI Management page.

Configuring the Endpoint for Low Security Environment

Your endpoints may already be configured for low security by default. These steps are only necessary for endpoints with a different security configuration. It is important to complete them in the following order.

To configure the endpoint for Low Security Environment:

- 1. Enter the PCoIP Zero Client's IP address in your browser's address bar, then log in to its AWI.
- 2. From the Configuration menu, select **Management**.
- 3. Change the Security Level to Low Security Environment.



- 4. If the endpoint is not in the Idle state, click Clear Management State and then Continue.
- 5. Click **Apply** and then **Continue**.

Discovering Endpoints from the PCoIP Management Console

To discover endpoints manually:

- 1. From the PCoIP Management Console's ENDPOINT page, click **ENDPOINT DISCOVERY**.
- 2. Enter the endpoint's IP address in the **FROM IP** boxes. If you want to discover a range of endpoints, enter the last IP address in the **TO IP** boxes; otherwise, leave these boxes empty.

Note: IP address range is limited to Class C ranges only

The IP address range is limited to Class C ranges or smaller (for example, 10.0.0.1 to 10.0.0.255). It cannot support a range larger than a class C such as 10.0.0.1 to 10.0.255.255.

3. Click outside a box, and then click **DISCOVER**.



- 4. Click **DONE** when it appears next to ENDPOINT DISCOVERY to end the discovery process.
- 5. To see the newly discovered endpoints, click **REFRESH** in the endpoint table (**GROUPED** or **UNGROUPED**, depending on your auto configuration settings).



✓ Note: Automatically name and group endpoints

You can configure the PCoIP Management Console to automatically name endpoints and place them in a specific group when they are discovered. See <u>Auto Naming Endpoints</u> and <u>Auto Configuring Endpoints (Enterprise)</u> for details.

PCoIP Management Console Managing Endpoints

Managing Endpoints

Managing Endpoints

This section contains the following topics:

- <u>Understanding the PCoIP Management Console Dashboard</u>: Describes the information you can view from the PCoIP Management Console **DASHBOARD** page.
- <u>Changing the Web Interface Time Zone</u>: Explains how to change the PCoIP Management Console web interface time zone. By default, the web interface uses the PCoIP Management Console's Coordinated Universal Time (UTC). For convenience when you create schedules, you can update your user account to display the web interface in your own local time zone.
- The actions you can perform from the ENDPOINTS page are listed in the following table: Lists all the actions you can perform from the ENDPOINTS page and provides links to instructions for each one.
- <u>Displaying Endpoint Properties</u>: Shows how to select the endpoint properties you wish to include in a *GROUPED* or *UNGROUPED* endpoint table.
- <u>Using the ENDPOINT DETAILS Page</u>: Lists all the actions you can perform from the **ENDPOINT DETAILS** page and provides instructions for each one.
- Performing Power Management: Explains how to power down and reset endpoints remotely.
- Renaming Endpoints: Explains how to rename an endpoint from the ENDPOINTS page.
- Deleting Endpoints: This topic explains how to delete endpoints.
- <u>Discovering Endpoints Manually</u>: Provides information about how to use the PCoIP Management Console's manual endpoint discovery feature.
- <u>Searching an Endpoint Table</u>: Explains how to use a text search to locate endpoints in a *GROUPED* or *UNGROUPED* endpoint table.
- <u>Filtering the Endpoint List</u>: Explains how to use PCoIP Management Console filters to refine the endpoints that display in a *GROUPED* or *UNGROUPED* endpoint table.
- Requesting Endpoint Certificates Using SCEP (Enterprise): Available in PCoIP Management Console
 Enterprise. Explains how to simplify the retrieval and installation of digital certificates by enabling
 devices to obtain certificates automatically from a SCEP server.

PCoIP Management Console Managing Profiles

Managing Profiles

The PCoIP Management Console lets you create profiles that contain a list of the settings you want to apply to one or more groups of endpoints. After creating a profile, you can apply it immediately to a group, or you can create a schedule to apply it to the group at a specific time in the future.

Displaying Profile Information

The **PROFILE** page contains a table showing all the profiles that are currently configured. You can create a new profile from this page, or you can select a profile from the table to edit, duplicate, or delete it.

PCoIP Management Console Managing Profiles

Click the gear icon



to the right of

the table to change the information you want to display in the table columns. Your customized settings are saved in your browser and will be used for any user who subsequently logs in from that browser.

PCoIP Management Console Managing Profiles



PROFILE Page

Creating a Profile

When you configure a profile, you specify only the settings you want to configure in the endpoint. For example, you can create a profile that only updates endpoint firmware without changing any of the endpoint's other settings. Unless a particular setting is explicitly configured in a profile by enabling its **Set In Profile** check box, it will have no effect when the endpoints are updated.

Some settings will cause the endpoint to restart. These settings are identified by a white triangular



icon . If configured, a **Reset Notification Timeout** overlay will warn users of a pending restart. This warning can be configured to appear up to 5 minutes prior to the restart, and can be configured in the POWER section of the profile.

• Firmware in profile is the same as on the endpoint

The Management Console will only apply the firmware in a profile to the endpoint, if the firmware version is different from the firmware identified from the last polling communication between the Management Console and endpoint.

The settings that are available are based on the endpoint type and the firmware version the target endpoints are currently using or will use when the profile is applied. For this reason, the relevant

firmware file must already be uploaded to the PCoIP Management Console from the **SETTINGS > SOFTWARE** page before you can create a profile.

For the PCoIP Zero Client and Remote Workstation Card, you can configure profiles for dual and quad endpoint types. The dual PCoIP Zero Client supports two monitors. The quad PCoIP Zero Client supports four monitors. You need to create a separate profile for each endpoint type.

To create a profile:

- 1. From the PCoIP Management Console's top menu, click **PROFILE**.
- 2. Click **NEW PROFILE**.
- 3. Enter a unique profile name in the *Name* column and a description for the profile in the *Description* column.
- 4. Click the + tab and select one of the following profile types and then click **ADD**:
 - TERA2: CLIENT [DUAL]: For endpoints that support two monitors.
 - TERA2: CLIENT [QUAD]: For endpoints that support four monitors.
 - TERA2: HOST [DUAL]: For endpoints that support two monitors.
 - TERA2: HOST [QUAD]: For endpoints that support four monitors.
- 5. For each setting you want to configure:
 - a. Enable the Set In Profile check box.
 - b. Perform the required configuration.

Note: Navigating between profile settings To navigate between profile settings, you can either use the scroll bar or select a setting category in the left pane. Any setting followed by the restart icon indicates that the endpoint requires a restart after being changed. 🚯 DASHBOARD | 🔀 ENDPOINTS | 🚆 PROFILE | 🐹 SCHEDULE | 🗲 AUTO CONFIGURATION | 🖫 ENDPOINT CERTIFICATES | 🌣 SETTINGS SAVE APPLY CANCEL DELETE DUPLICATE Created: Last Modified: SETTINGS OVERVIEW TERAZ CLIENT [DUAL] + O indicates that the property requires a device restart after being changed SOFTWARE SOFTWARE NETWORK Firmware Version O: ② 6.3.0 DISCOVERY NETWORK Basic Advanced MANAGEMENT Set in Profile ■ SECURITY IPv4 o: Keep Device Setting SESSION IPv6 o: ② Keep Device Setting LOGGING DISCOVERY (I) POWER Set in Profile PERIPHERAL SLP Discovery O: Keep Device Setting DNS SRV Discovery O: Keep Device Setting DNS SRV Discovery Delay O: Keep Device Setting

- 6. Click SAVE.
- 7. Click **PROFILE** in the navigation link at the top to return to the main page.

Associating a Profile with a Group

Before you can apply a profile, you must associate it with a group. Profiles can also be associated with multiple groups.

To associate a profile with a group:

- 1. From the **ENDPOINTS** page, select the desired group.
- 2. Click PROFILE and then CHANGE.
- 3. In the Change Profile dialog, select the profile from the drop-down list and click OK.
- 4. Enable the I understand message and click OK.

Note: Child groups will inherit their parent group's profile

Child groups with no assigned profile inherit their parent group's profile. This rule is recursive. For example, if top-level group A has a profile and both its child B and B's child C do not, then B and C both use the profile assigned to A.

Changing a Profile Association

To change a profile that is assigned to a group:

- 1. From the **ENDPOINTS** page, select the desired group.
- 2. Click PROFILE and then CHANGE.
- 3. In the Change Profile dialog, select a different profile from the drop-down list and click OK.
- 4. Enable the I understand message and click OK.

Applying a Profile


You can apply profiles so they update endpoint settings right away (or after any currently running scheduled actions have completed), or you can create a schedule to apply the settings in the future.

You can apply a profile to one or more groups or endpoints from the **ENDPOINTS** page or you can apply a profile to an endpoint from its **ENDPOINT DETAILS** page.

Applying a Profile Immediately

To force the profile to apply right away or after any currently running scheduled actions have completed:

1. From the **ENDPOINTS** page, select one or more groups (or one or more endpoints).



2. Click PROFILE and then APPLY.

3. Enable the I understand message and then click APPLY.

Applying a Profile in the Future (Enterprise)

You can also create a schedule to run at a later time in the future with PCoIP Management Console Enterprise. For details, see <u>Creating a Schedule</u>.

Duplicating a Profile

The PCoIP Management Console provides an easy way to duplicate a profile when you want to copy all the profile's settings except for its group association.

To duplicate a profile:

- 1. Select the profile in the PROFILE list.
- 2. Click **DUPLICATE**.
- 3. Enter a unique name for the profile and click **DUPLICATE**.
- 4. Follow the instructions in Applying a Profile to associate the profile with the desired group and choose how to apply it.

Editing a Profile

To edit a profile:

- 1. Select the profile in the PROFILE list.
- 2. Click EDIT.
- 3. If desired, change the Name and/or Description entries.

4. To see the group(s) to which this profile is assigned, click the small group tab



that

appears to the right.

- 5. To edit profile settings, choose one of the following:
 - To remove all of the settings click the on the profile tab and then click REMOVE. You can then click the + tab and configure a new profile.
 - To change one or more settings, click the profile tab and make your changes, as explained in <u>Creating a Profile</u>.
- 6. Click SAVE.
- 7. Click **PROFILE** in the navigation link at the top to return to the main **PROFILE** page.
- 8. Follow the instructions in Applying a Profile to choose how to apply the updated profile.

Importing or Exporting a Profile

Management Console allows the saving and reusing of profile configurations through the import and export feature accessed via the IMPORT and EXPORT buttons. This feature has the following characteristics:

- Only one profile can be imported or exported at a time.
- Profile files are saved with a **.profile** extension and have the date and time appended to the file name.

Example: { Profile name }-Date(YYYYMMDD)-Time(HHMMSS).milliseconds.profile

• The appended information is not displayed as part of the profile name on the PROFILE page

Profile files

Profile files are identified by the **.profile** extension. Support recommends not changing the file name of a profile file. Instead, when a profile name needs to be changed, preform this task by editing the profile name seen on the *PROFILE* page of the Management Console

- Displayed dialog windows provides messages to warn administrators of possible firmware issues prior to applying the profile
- Profiles must contain a configuration to be imported or exported

To ensure all configured settings are correctly applied to your endpoints, Management Console must be uploaded with the same version of host or client firmware. However, Management Console will compensate for missing firmware versions by including warning messages before applying the profile. Warnings include advising endpoints will move to a newer firmware, unsupported settings will be ignored when moving to an older firmware, duplicate profiles are present. These messages allow administrator's to take corrective actions prior to applying a profile if required.

To import a profile:

- 1. Click the **Import** button.
- 2. Click **SELECT FILE** and browse to the location of the profile file you wish to import
- 3. Click Import.

To export a profile:

- 1. Select the **EXPORT** button.
- 2. Save your profile to a location of your choice.

Deleting a Profile

To delete a profile:

- 1. If the profile is assigned to one or more groups, first remove the association for each group as follows:
 - a. From the ENDPOINTS page, select the group to which the profile is assigned.
 - b. Click PROFILE and then CHANGE.
 - c. In the Change Profile dialog, select No Profile from the drop-down list and click OK.
 - d. Enable the I understand message and click OK.
- 2. From the PROFILE page, select the profile you wish to delete.
- 3. Click **DELETE**.
- 4. Enable the I confirm message and click DELETE.


Viewing Profile Details

To view profile details:


- 1. From the ENDPOINTS page, select a group to which a profile is assigned.
- 2. Click PROFILE and then DETAILS.

Persistent Configuration


 A toggle button with the name of Persistent Configuration available under the Profile page. It is disabled by default.



Persistent configuration in Profile can be accessible in Enterprise mode, whereas in free mode, a
notification will be shown.



• A pop-over confirm message will be displayed, as shown below, when the **Persistent Configuration** toggle button is disabled.



• A Global turn on or off persistent configuration is available under the following path: Settings > AUTHENTICATION > ROLES AND PERMISSION > ADD/EDIT > PROFILE > PROFILE TAB. It can set to either Enable, Disable, or Hide.


SET PERMISSIONS

	ENDPOINTS:
•	PROFILE : Show • Detail Permissions
	New profile :
	Edit profile :
	Duplicate profile :
	Delete profile :
	Import profile :
	Export profile :
	Global turn on or off persistent configuration :

Organizing Endpoints into Groups

The **ENDPOINTS** page enables you to organize managed endpoints into a hierarchy of parent groups and child groups. Each group can then be associated with a profile so that its endpoints can be updated with the same settings all at once.

When endpoints are first discovered, they appear in the **UNGROUPED** table if you have not created auto configuration rules to automatically group them as part of the discovery process. The following example shows a list of ungrouped endpoints.




The ENDPOINTS page – UNGROUPED

After creating parent groups and child groups, you can create auto configuration rules to automatically move endpoints into a group when they are first discovered. Alternatively, you can manually move endpoints into groups.

After an endpoint is moved to a group, either manually or automatically, it then appears in the **GROUPED** table on the **ENDPOINTS** page. If you have created an auto naming rule to name endpoints when they are first discovered or when they are moved between ungrouped and grouped categories, this rule is also applied at this time.

The **GROUPED** and **UNGROUPED** tabs have a endpoint count indicator showing how many endpoints are in that state.

The following example shows a structure with endpoints in two different groups.




The ENDPOINTS page - GROUPED

Creating Groups

To create groups:

- 1. From the PCoIP Management Console's top menu, click ENDPOINTS.
- 2. Click STRUCTURE and then NEW GROUP.
- 3. Select **^TOP** to create a group at the top level or select the parent group under which you want to create a child group.
- 4. Enter a unique name for the group (from within its group hierarchy) and click CREATE GROUP.



Moving Endpoints into Groups

You can move an endpoint either from its **ENDPOINT DETAILS** page or from the **ENDPOINTS** page.

To move endpoints into groups:

1. From the **ENDPOINTS** page, click either the **GROUPED** or **UNGROUPED** tab.

2. Select one or more endpoints in the table.

Use Shift +Click to select contiguous elements and Ctrl +Click to select non-contiguous elements.

- 3. Click STRUCTURE and then MOVE.
- 4. Select the desired parent group or child group, and then click MOVE TO GROUP.
 If you have configured an endpoint naming convention that applies when you move endpoints to or from a group, the endpoints may also be renamed during this procedure.

Moving Groups

To move groups:

- 1. From the **ENDPOINTS** page, click the **GROUPED** tab.
- 2. Select a group in the table.
- 3. Click STRUCTURE and then MOVE.
- 4. Select the desired parent group or child group, and then click MOVE TO GROUP.
 If you have configured an endpoint naming convention that applies when you move endpoints to or from a group, the endpoints may also be renamed during this procedure.

Renaming a Group

To rename a group:

- 1. From the **ENDPOINTS** page, click the **GROUPED** tab.
- 2. Select the group you want to rename.
- 3. Click STRUCTURE and then RENAME.
- 4. Enter a unique name (from within its group hierarchy) and click **RENAME GROUP**.

Removing a Group

Note: Child groups will be removed and any endpoint will become ungrouped

If you remove a parent group that contains child groups or endpoints, the child groups will also be removed and any endpoints will become ungrouped.

To remove a group:

- 1. From the **ENDPOINTS** page, click the **GROUPED** tab.
- 2. Select the group you want to remove.
- 3. Click STRUCTURE and then REMOVE GROUP.
- 4. Enable the I understand message and click REMOVE GROUP.

Auto Configuring Endpoints (Enterprise)

The PCoIP Management Console Enterprise lets you create rules to apply profiles and automatically move endpoints into a specific group when they are first discovered. After discovery, you can find the endpoints in the **GROUPED table diagram** on the **ENDPOINTS** page. Profiles that are applied to a group used in auto configuration will be applied to all endpoints that are in the group, not just the newly discovered endpoints. If you are using PCoIP Management Console Free, you will be able to edit existing configurations.

Displaying Auto Configuration Rules

The **AUTO CONFIGURATION** page contains a table showing all the auto configuration rules that are currently configured. You can create a new rule from this page, or you can select a rule from the table to edit or delete it. The **ON/OFF** switch at the top of the page lets you globally enable or disable all rules at once.

Click the gear icon



to the right of

the table to change the information you want to display in the table columns. Your customized settings are saved in your browser and will be used for any user who subsequently logs in from that browser.

Switching auto configuration rules on and off

The AUTO CONFIGURATION page has a global auto configuration ON/OFF switch that is located above the table. Auto configuration rules become active when this switch is set to ON. However, the rules are only applied to endpoints when the devices are first discovered. If the global auto configuration setting is switched on after discovery, your rules will have no effect. For this reason, it is important to set up your rules before enabling discovery of the endpoints to which the rules would apply.



AUTO CONFIGURATION page and switch button

Creating an Auto Configuration Rule



Click the? button beside each field for help with any of the settings.

The LAST UPDATED column displays the last time the Auto Cofiguration rule has been updated.

To create an auto configuration rule:

- 1. From the PCoIP Management Console's top menu, click AUTO CONFIGURATION.
- 2. Click **NEW RULE** and configure the rule as follows:
 - Rule Criteria: Select the criteria your auto configuration rule is based on:
 - **IP ADDRESS:** Click **ADD**, enter the IP address range of the endpoints you want to place in the group, and then click **OK**. The address range can encompass an entire class A network.

Example Name field displays endpoint name format


The Example Name field at the bottom of the page displays the endpoint name format based on your global naming convention. See <u>Creating a Global Endpoint Naming Convention</u>.

- PASSWORD: Enter the endpoints password. Endpoints with matching passwords will be auto configured
- GENERIC TAG: Enter the endpoints Generic Tag. Endpoints with a matching Generic Tag label will be auto configured
- Group: Click in this field, select the desired pre-configured group, and then click OK.

Stop profile from being applied

Profiles are applied when auto configuration is on. Use this option to move endpoints into groups while not applying a profile to that group.

- Rule Values: Enter the specific values required by the Rule Criteria.
- Request Certificate: Select to automatically retrieve a Simple Certificate Enrollment Protocol (SCEP) digital certificate from a SCEP server.
- Move to Group Only (Enterprise): Groups the discovered endpoints and not apply a profile or firmware to them. This permits endpoints to be discovered at any time, and allows a profile application to be scheduled through the Management Console Schedule for a time that would be more convenient for a user.



3. Click SAVE.

* Creating overlapping or conflicting rules is not allowed

The PCoIP Management Console will prevent you from creating overlapping or conflicting rules. You will be required to resolve any problems before the rule can be created.

 Click AUTO CONFIGURATION in the navigation link at the top to return to the main AUTO CONFIGURATION page. 5. If you want the rule to apply right away, make sure the global auto configuration setting is switched



to ON.

Viewing or Editing an Auto Configuration Rule

To view or edit an auto configuration rule:

- 1. Select the rule in the AUTO CONFIGURATION list.
- 2. Click **EDIT** to view or edit the rule.
- 3. Make desired changes.
- 4. Click SAVE.
- 5. Click **AUTO CONFIGURATION** in the navigation link at the top to return to the main page.

Deleting an Auto Configuration Rule

To delete an auto configuration rule:

- 1. Select the rule in the AUTO CONFIGURATION list.
- 2. Click **DELETE**.
- 3. Click **DELETE** again at the confirmation message.

PCoIP Management Console Auto Naming Endpoints

Auto Naming Endpoints

The **ENDPOINT NAMING** page lets you construct a naming format for endpoints by selecting endpoint attributes to include in the name and entering a custom prefix and postfix to the name if desired. For example, you can create a name that begins with your prefix text, followed by the endpoint's PCoIP Management Console parent group or child group name, followed by the endpoint's MAC address or endpoint label, and ends with your postfix text.

The names created from these settings are visible from the **ENDPOINTS** and **ENDPOINT DETAILS** pages. They are only used with the PCoIP Management Console and are not available from the endpoint's AWI or OSD.

Each time you change a setting as you configure the naming convention, the **Example Name** field at the bottom of the page updates to show the format you have created. When you have finished constructing the name, you then choose when the name should be applied.

You can configure auto naming by clicking **SETTINGS** from the PCoIP Management Console's top menu and then clicking the **NAMING** menu in the left pane.

Creating a Global Endpoint Naming Convention

Note: Help with settings


Click the ? button beside each field for help with any of the settings.

To create a global endpoint naming convention:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. In the left pane, click NAMING.
- 3. Configure the endpoint name format as follows:
 - **Endpoint Name:** Select whether to incorporate the endpoint's current unique ID (that is, its MAC address) or its endpoint label (for example, pcoip-portal-) into the endpoint name.
 - **Prefix:** Enter any text you wish to prepend to the name.
 - **Group Naming:** Select whether to add the endpoint's group name and/or immediate child group name after the prefix.

PCoIP Management Console Auto Naming Endpoints

- Postfix: Enter any text you wish to append to the name.
- 4. In the *Rename Endpoints when* field, select whether to apply the name when the endpoint is first discovered, or any time it is moved between groups or between a grouped and ungrouped category.



5. Click SAVE.

Requesting Endpoint Certificates Using SCEP (Enterprise)

Simple Certificate Enrollment Protocol (SCEP) lets you simplify the retrieval and installation of digital certificates by enabling devices to obtain certificates automatically from a SCEP server. Management Console supports SCEP requests for different certificates on client and host endpoints.

Administrators of Management Console Enterprise can reference SCEP issued certificate information from the dashboard and may now see certificate status of NOT APPLICABLE or NOT REQUESTED from the ENDPOINTS page when the certificate status column is displayed.

SCEP requested certificate information can be viewed from the Dashboard, ENDPOINTS, and ENDPOINT CERTIFICATES pages.



This topic covers creating, viewing, editing and deleting a certificate rule, and how to initiate a certificate request using SCEP.

▲ Upgrading to firmware 21.07

For deployments using SCEP issued certificates, Management Console must be upgraded to version 21.07 or newer prior to upgrading firmware 21.07.

CONDITIONS FOR CERTIFICATE REQUESTS USING SCEP

The following conditions apply when performing a certificate request using SCEP:

- See Obtaining Certificates Using SCEP for complete information on SCEP behaviors.
- SCEP certificate renewal requests occur sequentially in 1 hour intervals when the renewal setting
 has been reached. The first request must successfully complete before renewal of the next
 certificate is initiated. If unsuccessful, the renewal request for the first certificate is attempted
 again. Administrators should periodically review the validity period of the SCEP certificates to
 ensure that renewals were successful and the certificates do not expire.

- The PCoIP endpoint must have NTP properly configured.
- The renewal period must be less than the validity period of the certificate.
- A certificate usage can be used once in a rule per group
- A group can only be associated with one certificate rule
- Management Console will display information for one certificate on the ENDPOINT DETAILS page.
 You can review all certificates for an endpoint by reviewing the rules created on the ENDPOINTS
 CERTIFICATE page that apply to your endpoint's group.
- Remote Workstation Cards must be running firmware 21.07 or newer
- Zero Clients running firmware prior to 21.07:
 - Request 802.1x usage certificates only. Rules including Administrative Web Interface usage certificates will not initiate the AWI certificate request but will initiate an included 802.1X certificate request.
 - The Request Certificate button will not activate if the rule is only for AWI certificate usage and will display **NOT APPLICABLE** in the ENDPOINT page certificate status column.
- Endpoints running firmware 21.07 or newer:
 - Users can request all certificate usages available for that version of firmware
 - Initially the status will show NOT REQUESTED on the ENDPOINTS page
 - Users will have the information of only one certificate on the ENDPOINT DETAILS and ENDPOINTS pages after completion of the request even if multiple certificates are requested.

Certificate status for SCEP certificate request times


The certificate status will update after the SCEP requests complete which usually takes between 5 to 20 minutes.

SCEP Requested Certificate Usages

Certificate requests using SCEP are available for the following certificate uses:

• **802.1X**: Allows you to use SCEP to request a custom certificate to authenticate PCoIP endpoints in your 802.1x configuration.

- Administrators Web Interface (AWI): Allows you to use SCEP to request a custom certificate to access the Administrative Web Interface (AWI).
- Peer-to-peer Max Compatibility: Allows you to use SCEP to automatically request a custom
 certificate that allows secure negotiation using any of the common cipher suites to offer flexibility
 for your network security requirements.
- Peer-to-peer Suite B: Used in environments requiring Suite B cryptography. Allows you to use SCEP to automatically request a custom certificate offering the greatest security for negotiating session connections with a PCoIP endpoint.
- Syslog TCP/TLS: Certificates used to ensure a secure connection to your Syslog server.
 Select the Syslog Connection Type according to your security policies. If using Syslog TCP/TLS secure connections to your Syslog server, enable the Syslog Enable Metadata setting to tag every syslog entry with the PCoIP Device Name and Generic Tag. Add the client certificate for TCP with TLS syslog connections that require Mutual Authentication (Server and Client). See Syslog Connections that require Mutual Authentication (Server and Client). See Syslog Connections in the Uploading Certificates topic of the Zero Client Administrators' Guide.



Tip: Organize endpoints into groups

Before you create an endpoint certificate, organize your endpoints into groups. See <u>Organizing Endpoints into Groups</u>.

SCEP Feature Support Matrix

SCEP Issued Certificate Improvements	Management Console Version	Zero Client Firmware	Remote Workstation Card Firmware
802.1X certificate usage	All Versions	All Versions	21.07+
AWI Interface certificate usage	21.07+	21.07+	21.07+
Peer-to-peer Max Compatibility certificate usage	22.04+	22.01+	22.01+
Peer-to-peer Suite B certificate usage	22.04+	22.01+	22.01+
Automatic Renewal Period feature addition	22.04+	22.01+	22.01+
Syslog TCP/TLS certificate usage	22.07+	22.07+	22.07+

TO CREATE AN ENDPOINT CERTIFICATE RULE

- 1. Click **ENDPOINT CERTIFICATES** to display the *CERTIFICATE MANAGEMENT* window.
- 2. Click **NEW CERTIFICATE RULE**.
- 3. In the **Groups** field, click **ADD** to add a group that was set up on the **ENDPOINTS** page. If required, you can remove a group by highlighting it and clicking **REMOVE**.
- 4. From the **Request 1** tab, select the **Certificate Usage**.
- 5. In the **Server URI**, field, type the Uniform Resource Identifier (URI) of the SCEP server that is configured to issue certificates for the group.
- 6. In the **Server Password** field, type the password for the SCEP server.
- 7. In the **CA Identifier** field, type the certification authority issuer identifier if your SCEP server requires it (the CA Identifier is supported for devices running firmware 5.4 or later). A CA Identifier is any string that is understood by the SCEP server (for example, a domain name).
- 8. Enter the **Auto Renewal** period in days. The default value is 0 (disabled).


9. Click + icon beside the Request 1 tab to add a different certificate usage request per rule.

10. Click SAVE.

You can add an additional SCEP request by selecting the plus tab. When all the different certificate usages are configured, the plus tab no longer appears.

TO VIEW AN ENDPOINT CERTIFICATE RULE

- 1. Click **ENDPOINT CERTIFICATES** to display the **CERTIFICATE MANAGEMENT** window.
- 2. Highlight the certificate rule you would like to edit or review rule details and click the View button.



From the view rule window, you can use the **Next** or **Prev** (previous) buttons to browse your rules while looking at the details of each rule. In deployments with many rules, you can jump to a rule using one of the drop down menus that display the first group of the groups used in each rule.



TO EDIT AN ENDPOINT CERTIFICATE RULE

- 1. Click **ENDPOINT CERTIFICATES** to display the *CERTIFICATE MANAGEMENT* window.
- 2. Highlight the certificate rule you would like to edit.

- 3. Click **EDIT** to revise an endpoint certificate rule.
- 4. Click Save after you are finished making your edits.

TO DELETE AN ENDPOINT CERTIFICATE RULE


- 1. Click **ENDPOINT CERTIFICATES** to display the *CERTIFICATE MANAGEMENT* window.
- 2. Highlight a certificate rule that you want to delete.
- 3. Click **DELETE**.
- 4. Confirm your deletion by clicking **DELETE** in the DELETE CERTIFICATE RULE dialog box.

Deleting SCEP certificate rules

You can also delete a SCEP certificate rule using the DELETE button while editing or creating a rule.

INITIATING A CERTIFICATE REQUEST

Prior to requesting a certificate, a certificate rule for your endpoint must exist. If your endpoint is not part of a group the rule is applied to, the request certificate button will be deactivated.



You can use Management Console to request certificates for endpoints in 4 ways.

Using the ENDPOINTS page

a. From the dashboard click ENDPOINTS.

b. Highlight your endpoint or group of endpoints, and click **ENDPOINTS > REQUEST CERTIFICATES**.

Using the Endpoints details page

- a. From the dashboard click ENDPOINTS.
- b. Highlight your endpoint and click **ENDPOINTS > DETAILS**.
- c. Click ENDPOINTS > REQUEST CERTIFICATES.

· Create a schedule

- a. From the dashboard click SCHEDULE.
- b. Select **NEW SCHEDULE**.
- c. Select the **Request Certificate** type and all other schedule requirements for your schedule.
- d. Click Save. The request will initiate at the set scheduled time.

See Managing Schedules for further details creating schedules.

· Create an auto configuration rule

- a. From the dashboard click AUTO CONFIGURATION.
- b. Click **NEW RULE**.
- c. Ensure the **Request Certificate** checkbox is selected and configure all other values required for your auto configuration.
- d. Click Save.

See Auto Configuring Endpoints for further details creating auto configuration rules.

Managing Schedules (Enterprise)

The PCoIP Management Console Enterprise lets you create schedules that are configured to run either once, at a certain date and time, or repeatedly, over a specified time frame and at a specified frequency. You can create schedules to apply a profile to one or more groups of endpoints, to power down one or more groups of endpoints, or to perform a power reset on one or more groups of endpoints.

Displaying Schedule Information

All configured schedules are displayed on the PCoIP Management Console's **SCHEDULES** page. You can view information about schedules that have previously run by clicking the **HISTORY** tab. Any configured schedules that have yet to run are also displayed on the PCoIP Management Console dashboard in its **UPCOMING SCHEDULES** area.

SCHEDULES Page

The schedules page contains a table showing all the schedules that are currently configured for the PCoIP Management Console. You can create a new schedule from this page, or you can select a schedule from the table to view, edit, or delete.

ENABLING AND DISABLING SCHEDULE TYPES

Schedule types can be enabled or disabled via the switches at the top of this page:

· The All Schedules switch



enables or

disables all schedules at once, including persistent configuration schedules.

- On: All enabled schedules will run.
- Off: Disables and stops *all* schedules, including any Persistent Configuration schedules. Schedules that are currently running will be terminated.

CUSTOMIZING THE SCHEDULES PAGE

Click the gear icon



to the right of

the table to change the information you want to display in the table columns. Your customized settings are saved in your browser and will be used for any user who subsequently logs in from that browser.




SCHEDULES Page

PERSISTENT CONFIGURATION SCHEDULE TYPES

Persistent Configuration Schedules enforce a defined configuration profile on managed endpoints. Each time a persistent configuration schedule runs, its endpoints will be checked for compliance; if an endpoint's profile has been modified and does not match the expected configuration, the Management Console will re-apply the configured profile.

• To create a new Persistent Configuration schedule, open the schedule page and click New, then select the Persistent Configuration schedule type.



HISTORY Page

The **HISTORY** page provides a list of schedules that have previously run, along with pertinent information about each one. All scheduled and manual activities will appear in the schedule history (for example, profile applications, power downs and resets).

Note: Unscheduled events do not appear in schedule history

Events that are not scheduled, for example, profile updates driven by auto-configuration, do not appear in the schedule history.

Click the gear icon



to the right of

the table to change the information you want to display in the table columns. Your customized

settings are saved in your browser and will be used for any user who subsequently logs in from that browser.



HISTORY Page

Creating a Schedule

Note: Help with settings

Click the? button beside each field for help with any of the settings.


To create a schedule:

- 1. From the PCoIP Management Console's top menu, click SCHEDULE.
- 2. Click NEW SCHEDULE.
- 3. Configure the settings as follows:
 - Type: Select the type of schedule.

Caution: Using the Skip reboot when applying profile on endpoints check box

This option allows you to push the profile but skip rebooting the endpoint. However, for new firmware to take affect, or for some settings to be applied, your endpoint must be rebooted.

- Name: Enter a unique name for the schedule.
- **Description:** Enter a description for the schedule.
- **Enabled:** Toggle the status to **ON**.
- Groups: Click ADD, select one or more groups, and then click ADD again. The schedule will operate on all the endpoints in any group you select. Use Shift +Click to select contiguous elements and Ctrl +Click to select non-contiguous elements.
- · Scheduled Time Zone: Select the time zone for the start and end times when you want the schedule to run.
- For ease of management, set the time zone to the same time zone where the endpoint(s) are located. The schedules table will show the schedule in the timezone that was selected and in the Management Console users timezone.
- Start Time: Click the time zone widget and select the desired date, then click the clock widget below the calendar and select the desired time.
- Recurrence: Select whether the schedule will run once or if it will recur over a period of time. If it is recurring, you must also select end date and time and frequency information.



- 4. Click SAVE.
- 5. Click **SCHEDULE** in the navigation link at the top to return to the main page.

Viewing Schedule Details

To view schedule details:

- 1. From the table on the SCHEDULES page, select the schedule you wish to view.
- 2. Click VIEW.
- 3. If desired, you choose to view the previous or next schedule in the list, or you can click **EDIT** to edit the schedule.
- 4. Click **SCHEDULE** in the navigation link at the top to return to the main page.

Editing a Schedule

To edit a schedule:

- 1. From the table on the SCHEDULES page, select the schedule you wish to edit.
- 2. Click EDIT.
- 3. Change the schedule's settings as desired.
- 4. Click SAVE.
- 5. Click **SCHEDULE** in the navigation link at the top to return to the main page.

Deleting a Schedule

To delete a schedule:

- 1. From the table on the SCHEDULES page, select the schedule you wish to delete.
- 2. Click **DELETE**.
- 3. At the message prompt, click **DELETE**.

Hidden Endpoint Settings

Assigning Friendly Name to the Broker Address Cache List


The **Friendly Name** feature is supported on **Zero Client devices** starting with **firmware version 25.06**. You can now assign a friendly name to the Broker Cache address.

Starting with MC 25.06, you can also edit and remove entries in the Broker Addresses Cache List from the MC Profile page.

FRIENDLY NAME SUPPORTED SESSION CONNECTION TYPES

The friendly name is supported for the following connection types starting with **Firmware version 25.06**:

- Auto Detect
- PCoIP Connection Manager
- PCoIP Connection Manager + Auto-Logon
- View Connection Server
- View Connection Server + Auto-Logon





A maximum of 25 friendly names are supported at any given time. This applies to friendly names created through both the Management Console profile and the Administrative Web Interface (AWI).

Creating a New Profile for Friendly Name

To **create a new profile** for friendly name, follow these steps:

- 1. Click PROFILE, and then select NEW PROFILE.
- 2. Go to Session > Advanced.
- 3. Choose the **Session Connection** type.
- 4. Scroll to the Broker Address Cache List setting, and select it.
- 5. Add the broker address cache and friendly name in the appropriate fields.
- 6. To add entries individually, use the ADD button for each entry.
 - a. The Broker address cache must meet the below requirements:
 - Value must not be empty
 - Value must match the correct broker address pattern .com">https://syour-domain>.com or :<port>"https://sip_address>:https://sip_address>:https://sip_address>:https://sip_address>:https://sip_address>:https://sip_address>:https://sip_address>:https://sip_address]>https://sip_address>:https://

```
eg: https://example.com or https://172.168.1.1:80
```

- Duplicate broker address values are not allowed.
- b. The Friendly names must meet the below requirements:
 - Friendly name must not contain more than 32 characters.
 - · Duplicate friendly names values are not allowed.
 - · Friendly name can be empty.
- 7. After you add the broker address cache and assign a friendly name, the **EDIT** button appears. You can then modify both the broker address cache and the friendly name.
- 8. Use the **REMOVE** button to remove an individual entry.
- 9. Save the profile.
- 10. Apply the profile to the Zero Client group.

Editing a Profile

To edit an existing profile:

- 1. Select the profile you want to edit.
- 2. Click EDIT.
- 3. View, edit, or remove the broker address cache and the friendly name.



Hidden OSD Menus and Settings

The PCoIP Zero Client can be further secured by hiding certain OSD menu options and by enabling certain options via the Management Console. These configurations can not be done from the PCoIP Zero Client OSD or AWI. An administrator can choose to hide OSD menu items, or activate features like Local Administrative Password.


The profile settings that hide menus are found under the profile SECURITY section. Select and enable one or all of the following options.

Hidden OSD Menu Entries

- Options/Configuration
- Options/Diagnostics
- Options/Information
- Options/User Settings
- Options/Password
- Hide the Options menu
- Options
- All Menus

Hidden PCoIP Zero Client OSD User Setting Tab Entries:

- Options > User Settings > Certificate
- Options > User Settings > Mouse
- Options > User Settings > Keyboard
- Options > User Settings > Image
- Options > User Settings > Display Topology
- Options > User Settings > Touch Screen
- Options > User Settings > Tablet
- Options > User Settings > Region
- Options > User Settings > User Interface




These are other profile settings that are not found on your PCoIP Zero Client or Remote Workstation Card and sometimes not available by default:

Enable Password Protection for OSD and AWI (occasionally not available as OEM default)


SECURITY						
Set In Profile						
	Local Administrative Password: ②	Keep Device Setting				
	Force Password Change on Next Login: ②	Keep Device Setting				
•	Enable Password Protection for OSD and AWI O:	Enable 🕶				
	Password Protect User Settings for OSD ©: ②	Keep Device Setting				
	Administrative Web Interface O: ②	Keep Device Setting				
	Hotkey Parameter Reset: ②	Keep Device Setting				
	Hide Parameter Reset Hotkey Sequence: ②	Keep Device Setting				
	802.1X Security: ②	Keep Device Setting				
	802.1X Authentication Identity: ②	Keep Device Setting				
	802.1X Legacy Support ©: 🔞	Keep Device Setting				
	Management Console Interface ©: ②	Keep Device Setting				
	Hidden OSD Menu Entries O: ②	Keep Device Setting				
	Hidden OSD User Setting tab Entries ©:	Keep Device Setting				

Session Disconnect Hotkey (CTRL + ALT + F12) (not available when Session Connection Type is Auto Detect in AWI/OSD)



SNMP Trap Settings

These settings allow you to enable traps and enter the address of the network management system to send traps to. This setting will also require the authentication fields set on the endpoint. See the PCoIP Zero Client Administrators 'Guide SNMP Overview for further information on SNMP authentication.



Keyboard Scan Code Filters


This setting allows you to create rules that prevent the PCoIP endpoint user from using certain keys or key combinations on their keyboard. Each filter consists of the following options.

- Scan Codes: Each key that is pressed produces a scan code that represents the key stroke in the form of hexadecimal value with a value range between 04 to FF.
- **Keyboard Layout**: You can select the keyboard layout associated with the supported languages available for keyboards connected to PCoIP Zero Clients
- Lock State: Represents the state of the NUM Lock, Caps Lock, Scroll Lock, and KANA Lock keys. States available are Any/All, Unlocked and Locked.
- Modifier State: Represents the state of the left and right CTRL, SHIFT, ALT, and GUI (i.e. Windows) keys. The available states are Any/All, Pressed and Depressed. Each key can be further identified by either the left, right or both. For example, LCTRL represents the left CTRL key, while RCTRL represents the right CTRL key and if your rule includes both left and right CTRL keys, you would use BCTRL.

Keyboard property values will be displayed in text on the profile page, and in hexadecimal on the endpoint details page.

Keyboard						
Set In Profile						
•	Keyboard Scan Code Filter: 🔞		Scan Codes			
		4	(Hexadecimal ran	ge between 4	and FF)	
			Keyboad Layout	Any Keyboar	d supported	~
			Lock State			
			Any/All			
		•	Lock options			
			NUM LOCK •	Any/All	Locked	Unlocked
			CAP LOCK •	Any/All	Locked	Unlocked
			SCROLL LOCK •	Any/All	Locked	Unlocked
			KANA LOCK •	Any/All	Locked	Unlocked
			Modifier State			
		0	Any/All			
		•	Modifier options CTRL			
			Any/All			
			LCTRL			
			RCTRL			
			BCTRL			
			SHIFT			
			Any/All			
			LSHIFT			
			RSHIFT			
			BSHIFT			
			ALT			
			Any/All			
			LALT			
			RALT			
			BALT			
			GUI			
			Any/All			
			LGUI			
			RGUI			
			BGUI			

Examples of using Keyboard Scan Code Filters with PrtScn To block a screenshot of the whole screen using PrtScr while allowing a screenshot of the Active Window using Alt + PrtScn . • Scan Code: 46 • Lock State: Any/All • Modifier Option: ALT: BALT - Depressed Keyboard Set In Profile 0 Keyboard Scan Code Filter: 🔞 Scan Codes (Hexadecimal range between 4 and FF) Keyboad Layout Any Keyboard supported Lock State Any/All Lock options Modifier State Any/All Modifier options CTRL Any/All LCTRL RCTRL BCTRL Any/All LSHIFT RSHIFT BSHIFT Any/All LALT RALT BALT Any/All Pressed Depressed Any/All LGUI RGUI BGUI



Disable PrtScn for all cases.

This means the filter will filter out any messages whenever PrtScn is pressed, regardless if other keys are pressed.

• Scan Code: 46

• Lock State: Any/All

• Modifier Option: Any/All

Disable PrtScn only when NumLk is in the off state.

This means the filter filters out any messages whenever PrtScn is pressed and NumLk is depressed (not locked).

• Scan Code: 46

• Lock State: NUM LOCK - Depressed

• Modifier Option: Any/All

Disable Ctrl + Alt + PrtScn only.

This means the filter filters out any messages whenever PrtScn is pressed in conjunction with either the left or right Ctrl and Alt keys.

• Scan Code: 46

• Lock State: Any/All

 \bullet Modifier Option: <code>BCTRL - Pressed</code> and <code>BALT - Pressed</code>

Disable Ctrl + PrtScn while allowing the use of Ctrl + Alt + PrtScn and Ctrl + Gui + PrtScn.


• Scan Code: 46

• Lock State: Any/All

• Modifier Option: BCTRL - Pressed and BALT - Depressed and BGUI - Depressed

Entering AWS Registration Codes via Broker Address Cache List

If you have an allotment of AWS WorkSpaces that are available for a Zero Client user to use, you can add up to 50 of them to a Zero Client running firmware 21.10.0 or newer via a Management Console profile. These added Workspaces will not be editable via the Zero Client OSD or AWI and will be displayed as a list from the OSD Connect drop-down menu when the Zero Client Connection Server Cache Mode is set to **Read Only**. The added workspaces will be **editable** by creating a new profile or editing an existing one with **MC 25.06 onwards**.



To apply a bulk additions of Amazon WorkSpaces from Management Console you must enter the Amazon WorkSpace Registration Codes via a profile's **Session > Broker Address Cache List** setting. This can be done individually or in bulk using a comma separated (CSV) file.


Broker Cache List

- Pushing a profile with Broker Address Cache entries will overwrite the current Zero Client Broker Address Cache list.
- Amazon Workspaces Connection type will allow you to bulk upload up to 50 Registration Codes to the Broker Server cache list from a CSV file.
- Autodetect, PCoIP Connection Manager and View Connection Server sessions have separate server caches that do not have a bulk loading option and have a upper limit of 25 entries.

The CSV file must meet the following requirements to upload successfully:

- must not be empty
- · must be a CSV file format
- · must not have a header row
- the first column must contain the WorkSpaces Registration Code
- · must not have an empty first column entry
- · must not have more than 50 entries
 - If there are existing cached entries, the number of csv entries plus the existing cached entries must not exceed 50
- must not contain duplicate entries
- · must not contain commas

If the file only contains entries in the first column, then the column entries will be used as both AWS WorkSpaces Registration Code and AWS WorkSpaces Registration Name.



To add an Amazon WorkSpace for selection on a Zero Client perform the following steps.

- 1. Enter Amazon WorkSpaces Registration Codes to a CSV file with the Registration Code in the first column and the Registration Name in the second column.
- 2. Save the file to a location that can be access by the Management Console.
- 3. Navigate to an existing or new profile SESSION section and select the **Advanced** radio button.
- 4. Set the Session Connection Type to Amazon WorkSpaces.

Setting a dedicated Amazon WorkSpaces

An AWS WorkSpaces Registration Code and AWS WorkSpaces Registration Name can be entered if you have a dedicated WorkSpace.

5. Browse down to the Broker Address Cache List setting and click its Set In Profile button.

- 6. Use the appropriate button to add a new entry.
 - To bulk load up to 50 entries, use the **UPLOAD** button and add your saved CSV file.
 - To add entries individually, use the ADD NEW or ADD button for each entry.
- 7. Save the profile.
- 8. Apply the profile to the Zero Client group.

To remove Amazon WorkSpaces broker cache entries perform the following steps.

- 1. Edit an existing profile and browse to the **SESSION > Broker Address Cache List** section and use the **REMOVE** button to remove individual entries or use the **REMOVE ALL** button to remove all the profile entries.
- 2. Save the profile.
- 3. Apply the profile to the Zero Client group.



Enabling Audio and its Properties

Audio settings can be enabled from the Management Console by configuring the appropriate properties in the **ZERO CLIENT** and **HARD HOST** profiles. Audio properties differ slightly between the Zero Client and Hard Host profiles.

The parent property, **Enable Audio**, must be enabled to enable or disable its child properties. All child properties must be disabled before **Enable Audio** can be disabled. This property can be configured through the **Enable Audio** setting in both Client and Host profiles.

The following are the child properties of **Enable Audio** for **Zero Client** and **Hard Host**.

Enable Audio dependent properties for Zero Client:

- Enable Local USB Audio Driver
- Enable Dual Audio Output
- Enable Opus Audio Codec
- Enable Analog Audio Input


Enable Audio dependent properties for Hard Host:

• Enable Audio Line In

To enable audio input features, follow these steps:

- 1. Do one of the following steps:
 - To create a new profile, click PROFILE > NEW PROFILE.
 - To edit an existing profile, select a profile, and then click **EDIT**.
- 2. Click Session.
- 3. Setting Audio Input Properties:
 - a. Setting Audio Input Properties for Clients (Dual/Quad):
 - Ensure that Enable Audio is set to Enabled before enabling/disabling Enable Local USB Audio Driver, Enable Opus Audio Codec and Enable Analog Audio Input.
 - Ensure that both Enable Audio and Enable Local USB Audio Driver are set to Enabled before enabling/disabling Enable Dual Audio Output.

- b. Setting Audio Input Properties for Hard Host (Dual/Quad):
 - Ensure that Enable Audio is set to Enabled before enabling/disabling Enable Audio Line In.



4. Save your changes.

Session Audio Input properties can be viewed in the endpoint details page.

Note: Applying Profiles Created in Earlier Versions


- If a profile is created in version **earlier than 23.12.2** for Zero Clients running **firmware 23.12.x** and with **Enable Audio** disabled, while applying this profile in version 23.12.2 and later, ensure that **Enable Analog Audio Input** is disabled.
- If a profile was created using an **MC version earlier than 25.06** with **Enable Audio** disabled, but any of the following child properties were enabled:
 - Enable Local USB Audio Driver
 - Enable Dual Audio Output
 - · Enable Opus Audio Codec
 - Enable Audio Line In

When applying the same profile in MC 25.06 or later versions, ensure that these properties are manually disabled.

Remote Endpoint Management (Enterprise)

Remote Endpoint Management (Enterprise) Overview

Remote endpoint management allows PCoIP administrators to maintain central management of endpoints when they are no longer on-premises. Remote management is avialable with the Enterprise version of Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore it must be licensed with a trial or enterprise license. See Management Console therefore



Reverse Proxy Overview

PCoIP Management Console determines if an endpoint is behind a reverse proxy by inspecting the websocket upgrade header for the presence of X-Forwarded-For, X-Real-IP or Forwarded information.

An endpoint is treated as a remote endpoint when it is:

- explicitly connecting to the external interface of the PCoIP Management Console
- determined to be behind a reverse proxy
- behind a NAT and has a different internal IP address from its external IP address.

To complete a remote management deployment, requires the configuration of the management console, remote proxy, endpoint and if desired an auto-provisioning DNS SRV record which is recommended.

Each configuration can be found in the following topics:

Configuring PCoIP Management Console Remote Management

Reverse Proxy Configuration

Configuring DNS for Reverse Proxy

Connecting to a Remote Endpoint

Reverse Proxy Configuration

For remote administration of PCoIP endpoints to work, the reverse proxy must be accessible by the remote devices and by the PCoIP Management Console. Typically a reverse proxy will be installed in the DMZ of the network.

For remote administration of PCoIP endpoints, the reverse proxy must meet the following requirements.

- It must be able to proxy the WebSocket protocol. The WebSocket protocol is used for communication between the endpoint and the Management Console.
 Encrypted websocket connections have a wss:// preceeding the FQDN.
- It must be configured with a publicly accessible address.
 This same address is entered in the PCoIP Management Console External Address field on the REMOTE CONFIGURATION page, in SETTINGS > REMOTE.
- It must have communication port TCP 5172 open in both directions.
- It must have a certificate with its private key added to its configuration.
 The reverse proxy must have a certificate with its private key added to its configuration. Use the SHA256 fingerprint from the reverse proxy certificate in the PCoIP Management Console External Certificate Fingerprint field on the REMOTE CONFIGURATION page, in SETTINGS > REMOTE.

HP has provided a <u>sample configuration using nginx for a reverse proxy</u>, and is provided as-is, with no warranty. This sample configuration resides on a nginx proxy server.

Configuring PCoIP Management Console Remote Management

Remote Endpoint Management works by requiring a reverse proxy in the DMZ of the network and is configured by accessing the *REMOTE CONFIGURATION* page located by browsing PCoIP Management Console **SETTINGS > REMOTE**. Here you will find four configurable settings.

- Internal Address: Here you enter the internally published FQDN or IP address of the PCoIP Management Console. This is how "local" devices access the PCoIP Management Console.
- External Address: This address will lead to the reverse proxy. In this field you will enter the externally published FQDN or IP address of the reverse proxy. This is how "remote" devices will access the reverse proxy.
- External Certificate Fingerprint: Enter the Reverse Proxy Server's certificate SHA-256 fingerprint. Endpoints may require the fingerprint of the certificate used for external access.
- Local IP Address Ranges: Here you enter the IPv4 address ranges used within the corporate network. This will enable the PCoIP Management Console to identify local devices as opposed to remote devices.

Once your remote devices have checked in with the PCoIP Management Console, you can view the *ENDPOINTS* page, and see that the *IPv4 ADDRESS* column will show the IP address of the endpoint as seen by the PCoIP Management Console. In the case of a remote endpoint, this will be the public IP address.

The *INTERNAL IPv4* column will show the address assigned to the endpoint itself. In the case of a remote endpoint this will be the address assigned by the NAT or DHCP server of the remote endpoint.

The *CONNECTED BY* column will display either REMOTE or LOCAL based on where in the network the endpoint is in relation to the PCoIP Management Console.

Configuring DNS SRV Record Discovery for Reverse Proxy

This section explains how to configure a public facing DNS SRV and a DNS TXT record for your reverse proxy to provision endpoints with Endpoint Bootstrap Manager information, as part of the endpoint discovery process.

Endpoints polls the public facing DNS server for information about the reverse proxy (that is, the Endpoint Bootstrap Manager/Endpoint Manager) to which they should connect.

DNS service record discovery requires you to have a public facing DNS server in your network that is configured with the following DNS records:

- An address record (A record): Specifies the FQDN and IP address of the reverse proxy.
- A service location record (SRV record): Associates information such as the reverse proxy's TCP/IP service and the port the reverse proxy listens on with the reverse proxy's domain and host name.
 The reverse proxy's TCP/IP service is called _pcoip-bootstrap, as shown in Adding the DNS SRV Record.
 The remote PCoIP Zero Client will look for this external facing DNS record.
- A DNS TXT record: Contains the reverse proxy certificate SHA-256 fingerprint. The record's name must be the host name of the reverse proxy offering the service. In the following example, this record is called **proxy**. The domain is appended automatically.

DNS Text fingerprint

Remote Endpoints only pick up the DNS TXT fingerprint if the reverse proxy address is specified in a DNS SRV record

BEFORE YOU BEGIN


Before configuring your DNS SRV record discovery, you'll need the following information:

- The reverse proxy's FQDN
- The reverse proxy's certificate fingerprint (that is, the certificate's digital signature). If provided, this fingerprint is only used when the endpoint's security level is set to **Low Security Environment** and certificate verification has failed. It is ignored when the security level is set to **Medium Security Environment** or **High Security Environment**.

ADDING THE DNS SRV RECORD


To add the public facing reverse proxy DNS SRV record to DNS server:

- 1. Log in to your Windows Server and select DNS.
- 2. Right-click on your DNS server in the *SERVERS* pane and select **DNS Manager** from the context menu.
- 3. In *Forward Lookup Zones*, right-click on your domain and select **Other New Records** from the context menu.




Public Facing Forward Lookup Zone

4. In the Resource Record Type dialog, select **Service Location (SRV)** from the list and click **Create Record**.




New Resource Record Type for SRV

5. Fill in the entries as shown in the following example. Set Service to **_pcoip-bootstrap**, Protocol to **_tcp**, and *Port number* to **5172**, the reverse proxy's listening port. For *Host offering this service*, enter the reverse proxy's FQDN.



The reverse proxy's FQDN must be entered because the DNS specification does not enable an IP address in SRV records.



New Resource Record Dialog

6. Click OK.


ADDING A DNS TXT RECORD

If your endpoints do not have the reverse proxy's root CA certificate installed in their certificate store, you must configure your DNS server with a DNS TXT record containing the reverse proxy certificate SHA-256 fingerprint.

To add a public facing DNS TXT record:

- 1. In *Forward Lookup Zones*, right-click on your domain and select **Other New Records** from the context menu.
- 2. In the Resource Record Type dialog, select Text (TXT) from the list and click Create Record.
- 3. Fill in the entries as follows:
 - In the *Record name* field, enter the host name of the reverse proxy offering the service (this example uses proxy). The FQDN field will be automatically populated for you and should match the FQDN of the reverse proxy.

• In the *Text* field, type pcoip-bootstrap-cert= and then paste the reverse proxy certificate SHA-256 fingerprint you obtained previously immediately after this prefix, as shown in the following example.



New Text Record

- 4. Click OK.
- 5. When you have finished configuring your DNS server, power cycle your endpoints or put them online to enable them to make the connection to the reverse proxy.

See <u>Troubleshooting DNS</u> to verify that your DNS server is configured correctly for the reverse proxy.

Connecting to a Remote Endpoint

The remote endpoint must be configured with the external address of the reverse proxy. Depending on the configuration of the PCoIP Zero Client this can be done by either configuring and uploading the required certificates onto the PCoIP Zero Client via the AWI, or by creating an external DNS entry for the Reverse Proxy server via the PCoIP Zero Client OSD.

CONNECTING MANAGEMENT CONSOLE TO A REMOTE ENDPOINT FROM THE ENDPOINT OSD

This is the recommended method which requires the OSD be accessible and the end user knows the password, and that there is a properly configured corporate public facing DNS server that will provide the address and the SHA256 certificate fingerprint of the reverse proxy to the endpoint. (Configuring DNS for Reverse Proxy)

- 1. From your PCoIP Zero Client OSD, navigate to **Options > Configuration > Network**.
- 2. Unlock your PCoIP Zero Client and un-check **Enable DHCP** (do not modify any other information)
- 3. In the **Domain Name** field enter the domain name of the domain you created the DNS entry in.
- 4. Select **OK**, you will be prompted to reset the PCoIP Zero Client, select **Reset** to restart your PCoIP Zero Client.

The PCoIP Zero Client will restart and it will reach out to the specified domain name based on your recently configured DNS SRV and DNS TXT records which will reach your configured reverse proxy server. The reverse proxy server will pass the connection to the PCoIP Management Console. The PCoIP Zero Client will now show up in your Ungrouped devices tab after a short period of time. This can be verified by viewing the management page from the OSD screen by navigating to **Options > Configuration > Management**.

CONNECTING MANAGEMENT CONSOLE TO A REMOTE ENDPOINT FROM THE ENDPOINT AWI

This method is done from the endpoint and requires the AWI be enabled, accessible, and the user knows the AWI password.

1. Install the certificate of the reverse proxy into the endpoint via the AWI *Certificate Upload* page by browsing to **Upload > Certificate**.

Reverse Proxy Certificate

Typically this is the trusted root certificate for the reverse proxy.

- 2. Browse to **Configuration > Management** and set the **Manager Discovery Mode** to *Manual*.
- 3. Enter the address of the reverse proxy in the **Endpoint Bootstrap Manager URI** field. (i.e. wss://mc.company.local:5172)
- 4. Click **Apply** to save your changes and **Continue** to see the management connection status.

PCoIP Management Console Using the Endpoints Page

Using the Endpoints Page

Endpoints Page Overview

The actions you can perform from the **ENDPOINTS** page are listed in the following table.

ENDPOINTS Page Features

Menu	Action
EXPAND ALL ↔	 Toggles to display the following: Expand top-level and parent groups to display all child level groups and endpoints. Collapse the group hierarchy and display only top-level groups.
PROFILE *	 Displays on the GROUPED table and provides the following menus: DETAILS: View details about a profile assigned to a group. See Viewing Profile Details. CHANGE: Change the profile assigned to a group. See Changing a Profile Association. APPLY: Apply a profile to a group. See Applying a Profile.
STRUCTURE *	 Provides the following menus: MOVE: Move endpoints or groups to a group. See Moving Endpoints into Groups. RENAME: Rename a group or endpoint. See Renaming a Group. NEW GROUP: Create a new group. Creating Groups REMOVE GROUP: Remove a group. Removing a Group.
ENDPOINTS *	 Provides the following menus: DETAILS: View details about an endpoint. See <u>Using the ENDPOINT DETAILS Page</u>. POWER DOWN: Power down one or more endpoints. See <u>Powering Down PCoIP Zero Clients</u>. POWER RESET: Reset (reboot) one or more endpoints. See <u>Resetting PCoIP Zero Clients</u>.

PCoIP Management Console Endpoints Page Overview

Menu	Action
	• RESET TO DEFAULT: Reset endpoint properties to their
	default values. See Resetting Endpoint Properties to Their
	<u>Defaults</u> .
	An endpoint reboot may be needed If the endpoint properties have not been reset to their default values, then
	an endpoint properties have not been reset to their derault values, their an endpoint reboot will be required.
	• DELETE: Remove one or more endpoints from the PCoIP
	Management Console. See <u>Deleting Endpoints.</u>
	Lets you manually discover endpoints by their IP address. See
ENDPOINT DISCOVERY	Discovering Endpoints Manually from PCoIP Management Console.
	Lets you search for one or more endpoints in the endpoint table. See
SEARCH	Searching an Endpoint Table.
SLARCIT	
	Lets you create and manage filters to display only specified endpoints.
FILTER 💠 💆	See <u>Filtering the Endpoint List</u> .

Refreshes the endpoint table with the current configuration.


✓ Click REFRESH after completing a manual discovery

The endpoint table does not refresh automatically. Click REFRESH after completing a manual discovery and any time you do not see an endpoint that you expect to be there.

PCoIP Management Console Displaying Endpoint Properties

Displaying Endpoint Properties

The **ENDPOINTS** page, displayed next, contains GROUPED and UNGROUPED tables for displaying the endpoints in your system that are managed by the PCoIP Management Console.



View of the ENDPOINTS page

PCoIP Management Console Displaying Endpoint Properties

Selecting Endpoint Properties to Display

Click the gear icon



to the right of

the table to change the information you want to display in the table columns. Your customized settings are saved in your browser and will be used for any user who subsequently logs in from that browser.

Properties are ordered in the sequence you select them. You can rearrange a column by manually dragging the column heading to the desired position. You can also sort endpoints in ascending or descending order based on column contents by clicking on the column heading. Endpoints that occur in groups are sorted within their group.

You can choose to display the following properties:

Endpoint Properties

Property	Information	Grouped	Ungrouped	MC Enterprise Only
ATTACHED USB DEVICES	Displays information from attached USB Devices. Possible values:			
	 Model: Displays the model name of the USB device. 			
	 Vendor ID (VID): Displays the USB devices vendor identifying number provided to the vendor by the <u>USB</u> implementers forum. 			
	 Product ID (PID): Displays the product identifying number provided by the vendor or maker of the USB device. 			
AUTO CONFIGURATION STATUS	Displays an endpoint's auto configuration status. Possible values:			
	• NO PROFILE			
	• NOT STARTED			
	· AUTOCONFIG DISABLED			
	 FAILED DHCP OPTION GROUP NOT FOUND 			
	• FAILED DHCP OPTION RULE NOT FOUND			
	• FAILED DHCP OPTION BEHAVIOR NONE			
	 FAILED DHCP OPTION MATCHING DISABLED 			
	• FAILED IP RANGE CHECK			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
	• FAILED UNKNOWN ERROR			
	• ADDED TO DHCP OPTION GROUP			
	• ADDED TO GROUP			
	• PENDING PROFILE APPLICATION			
	 FAILED PROFILE APPLICATION IN PROGRESS 			
	• FAILED PROFILE APPLICATION			
	• COMPLETED			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
APPLY PROFILE	Displays the status of endpoint's profile update. Possible values:			
	NO PROFILE NOT STARTED			
	• IN PROGRESS			
	• COMPLETED			
	• FAILED			
	• PENDING REBOOT			
	• FAILED OFFLINE			
	• FAILED PENDING REBOOT TIMEOUT			
	• SKIPPED NO REBOOT			
	• SKIPPED			
	Some common reasons			
	for the 'skipped' status			
	is if the endpoint is			
	already configured with			
	the profile settings or if			
	its group does not have			
	an assigned profile.			
CERTIFICATE EXPIRY DATE	Displays the date the SCEP certificate will expire and become not valid. Possible values:			
	• CERTIFICATE EXPIRY DATE			
CERTIFICATE NAME	Displays the SCEP certificate subject name. Possible values:			
	• CERTIFICATE NAME			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
CERTIFICATE RULE	Displays the SCEP certificate rule assigned to a group. This rule defines the SCEP SERVER address and password that an Endpoint can use to request a SCEP certificate. You can create a certificate rule from the ENDPOINT CERTIFICATE tab. Possible values: • RULE NAME			
CERTIFICATE START DATE	Displays the date the SCEP certificate becomes valid. Possible values: • DATE			
CERTIFICATE STATUS (PCoIP Zero Client only)	Displays the status of the SCEP certificate. Possible values: Active About To Expire Expiring Today Expired Not Requested Not Applicable			
CLEAR MANAGEMENT STATE	Indicates if devices now have all management settings cleared and set back to a default state.			
CONNECTED BY	Identifies where in the deployment the PCoIP endpoint is placed. Possible Values: • NO PROFILE			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
	• Local			
	• Remote			
DENIED	Indicates whether or not the PCoIP Management Console has enough licenses to manage all the discovered endpoints. Possible values:			
	 NO PROFILE True: The endpoint is denied (that is, it cannot be managed) because a license is not available for it. False (displays as a blank in the column): The endpoint is not denied and can be managed. 			
DEVICE DESCRIPTION	Displays the PCoIP Device Description text located on the endpoints AWI Label page. Possible values: • any text string			
PCOIP DEVICE NAME	The MAC Address value will be set to the PCoIP Device Name field after a profile with this setting configured is successfully applied. The Device Name has a maximum length of 63 characters. • If the PCoIP device name in a profile is "true" and the PCoIP device name on the endpoint is the endpoint's MAC address, then the profile			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
	compliance will show as COMPLIANT			
	If the PCoIP device name in the profile is "true", and the PCoIP device name on the endpoint is not the endpoint's MAC address, then the profile compliance will show as NON COMPLIANT			
	• If the PCoIP device name in the profile is "false", and the PCoIP device name on the endpoint is either the MAC address or non MAC address, then the profile compliance will show as COMPLIANT			
	Possible values:			
	• any text string			
DEVICE STATUS	Indicates whether or not an endpoint is connected to the PCoIP Management Console and if it is in a PCoIP session with another PCoIP software or hardware endpoint. DEVICE STATUS is a combination of the previous ONLINE and IN SESSION properties.			
	Possible values:			
	NO PROFILEOfflineOut of Session (online)In Session (online)			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
	• In Recovery (online)			
DISPLAY TYPE	Displays the maximum number of monitors an endpoint supports. Possible values for a PCoIP Zero Client and Remote Workstation Card: • NO PROFILE • Dual: The endpoint supports up to two monitors. • Quad: The endpoint supports up to four monitors.			
ENDPOINT DESCRIPTION	Displays information about the endpoint family and endpoint type.			
ENDPOINT HEALTH	Displays the status of an endpoint's health state. Possible Values: • Unknown: The Management Console cannot determine, or is in the process of determining the status of endpoint. • Normal: The endpoint is operational and working as expected. • Recovery: This is a warning or notification to the user that the endpoint is in recovery mode and currently unable to connect to a session.			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
ENDPOINT	Displays the endpoint's PCoIP			
PLATFORM	family. In this release, only			
	endpoints that support the			
	Tera2 platform can be managed by the PCoIP			
	Management Console.			
	Possible values:			
	• NO PROFILE			
	• TERA2			
ENDPOINT TYPE	Displays the endpoint type.			
	Possible values:			
	• NO PROFILE			
	• Client			
	• Host			
FIRMWARE BUILD	Lists the firmware build			
ID	number in use on the PCoIP			
	endpoint.			
	Possible values:			
	• NO PROFILE			
	• FIRMWARE BUILD ID			
FIRMWARE POWER RESET	Displays the status of an endpoint's power reset after updating its firmware. Possible values:			
	• NO PROFILE			
	• NOT STARTED			
	• IN PROGRESS			
	• COMPLETED			
	• FAILED			
	• SKIPPED			
	• FAILED PENDING			
	REBOOT TIMEOUT			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
	• SKIPPED NO REBOOT			
	• PENDING REBOOT			
	• SKIPPED			
	One common reason for the			
	'skipped' status is if a firmware update failed for the endpoint.			
	In this case, the power reset			
	would not occur either.			
FIRMWARE	Displays the status of an			
UPLOAD	endpoint's firmware upload.			
	Possible values:			
	• NO PROFILE			
	• NOT STARTED			
	• IN PROGRESS			
	• COMPLETED			
	• FAILED			
	• FAILED OFFLINE			
	• PENDING REBOOT			
	TIMEOUT			
	• SKIPPED			
	One common reason for the			
	'skipped' status is if the			
	endpoint is already running the specified firmware version.			
FQDN	Displays an endpoint's fully-			
	qualified domain name.			
	Possible values:			
	• NO PROFILE			
	• FQDN			
GENERIC TAG	Displays the Generic Tag text			
	located on the endpoints AWI			
	Label page.			

Possible values: • any text string Displays an endpoint's polling status.			
Displays an endpoint's polling status.			
status.			
Possible values:			
• NO PROFILE			
• NOT STARTED			
• IN PROGRESS			
• COMPLETED			
• FAILED			
• FAILED OFFLINE			
Only the information of the network that Management Console is configured to operate in (IPv4 or IPv6) will be visible			
Possible values:			
• NO PROFILE			
• IP Address			
Displays an endpoint's IPv4/ IPv6 address			
Only the information of the network that Management Console is configured to operate in (IPv4 or IPv6) will be visible. Displays an endpoint's IPv4/IPv6 address for the network the endpoint is part of. For remote endpoints, this will be their internal			
	• IN PROGRESS • COMPLETED • FAILED • FAILED OFFLINE Only the information of the network that Management Console is configured to operate in (IPv4 or IPv6) will be visible Possible values: • NO PROFILE • IP Address Displays an endpoint's IPv4/ IPv6 address Only the information of the network that Management Console is configured to operate in (IPv4 or IPv6) will be visible. Displays an endpoint's IPv4/IPv6 address for the network the endpoint is part of. For remote endpoints, this	• IN PROGRESS • COMPLETED • FAILED • FAILED OFFLINE Only the information of the network that Management Console is configured to operate in (IPv4 or IPv6) will be visible Possible values: • NO PROFILE • IP Address Displays an endpoint's IPv4/ IPv6 address Only the information of the network that Management Console is configured to operate in (IPv4 or IPv6) will be visible. Displays an endpoint's IPv4/IPv6 address for the network the endpoint is part of. For remote endpoints, this will be their internal	IN PROGRESS COMPLETED FAILED FAILED FAILED OFFLINE Only the information of the network that Management Console is configured to operate in (IPv4 or IPv6) will be visible Possible values: NO PROFILE IP Address Displays an endpoint's IPv4/ IPv6 address Only the information of the network that Management Console is configured to operate in (IPv4 or IPv6) will be visible. Displays an endpoint's IPv4/IPv6 address for the network the endpoint is part of. For remote endpoints, this will be their internal

Property	Information	Grouped	Ungrouped	MC Enterprise Only
	Possible values:			
	• NO PROFILE			
	• IPv4 or IPv6 ADDRESS			
LAST POLLED	Displays the last date and time			
	that the PCoIP Management			
	Console polled an endpoint for its status and configuration			
	information. The PCoIP			
	Management Console's polling			
	interval is 60 minutes.			
	Possible values:			
	• NO PROFILE			
MAC ADDRESS	Displays an endpoint's MAC			
	address.			
	Possible values:			
	• NO PROFILE			
OSD LOGO	Displays the status of an			
	endpoint's OSD logo bitmap			
	file update to the endpoint's On Screen Display (OSD).			
	Possible values:			
	• NO PROFILE			
	• NOT STARTED			
	• IN PROGRESS			
	• COMPLETED			
	• FAILED			
	• SKIPPED			
	One common reason for the			
	'skipped' status is if the			
	endpoint already has the OSD logo configured.			

Property	Information	Grouped	Ungrouped	MC Enterprise Only
PEER	If a peer is configured for an endpoint, it's IP address is shown in the column. Possible values:			
	• NO PROFILE • PEER IP ADDRESS			
PROFILE	Appears next to a group to display the profile assigned to it. Possible values: • NO PROFILE • PROFILE NAME			
PROFILE COMPLIANCE	Indicates whether or not an endpoint's current known configuration differs from the PCoIP Management Console profile assigned to the endpoint's group. Possible values:			
	 NO PROFILE COMPLIANT: the endpoint matches the profile NON-COMPLIANT: the endpoint does not match the profile UNKNOWN: the MC cannot determine, or is in the process of determining if the endpoint matches the profile NO PROFILE: there is no 			
	profile to compare the endpoint to			

RESET reset star profile pr power re firmware Possib NO NO IN I CO FAI FAI REE	PROFILE OT STARTED PROGRESS OMPLETED		
• NO • IN I • CO • FAI • FAI REI	PROGRESS MPLETED ILED ILED PENDING BOOT TIMEOUT		
• IN I • CO • FAI • FAI REI	PROGRESS MPLETED ILED ILED PENDING BOOT TIMEOUT		
• IN I • CO • FAI • FAI REI	PROGRESS MPLETED ILED ILED PENDING BOOT TIMEOUT		
• CO • FAI • FAI REI	MPLETED ILED ILED PENDING BOOT TIMEOUT		
• FAI • FAI REI	ILED ILED PENDING BOOT TIMEOUT		
• FAI	ILED PENDING BOOT TIMEOUT		
REI	BOOT TIMEOUT		
• SK!	III I ED NO NEDOOT		
	NDING REBOOT		
	IPPED		
Orti			
'SKIPPED update fa the endp	nmon reason for the D' status is if a profile ailed or skipped for point. In this case, the		
power re	eset would not occur.		
	he table to display the		
DEFAULT default c COLUMNS Possib			
COLUMNS POSSID	le values:		
• NO) PROFILE		
serial num Manager endpoint number of into the I Possib	oints provide there Imbers to the PCoIP Iment Console Its table. The serial Its can also be exported Inventory Report. Ille values:		
• SEF	RIAL NUMBER		

Property	Information	Grouped	Ungrouped	MC Enterprise Only
SOFTWARE VERSION	Firmware file name used in the PCoIP firmware build minus the build number. Possible values: • NO PROFILE			
UNIQUE ID	Displays an endpoint's MAC address delimited with hyphens instead of colons. This field can be incorporated into the automatic naming convention for endpoints. Possible values: • NO PROFILE • ENDPOINT MAC ADDRESS			

Using the ENDPOINT DETAILS Page

The **ENDPOINT DETAILS** page displays complete configuration and status information for the selected endpoint.


It contains menu options that enable you to perform the following actions:

- Open the endpoint's profile in edit mode
- · Apply the profile to the endpoint right away
- Move the endpoint to a group
- · Rename the endpoint
- Power down the endpoint
- Power reset (reboot) the endpoint
- Resetting Endpoint Properties to Factory Defaults
- · Clear the management state of the endpoint
- Requesting an Endpoint Certificate
- Peering Endpoints (ENTERPRISE)
- Access the endpoint's web interface
- Refresh

1 Info: No data from the endpoint

In cases such as restoring a database, the PCoIP Management Console must first poll the online endpoint before it can display the endpoint details information.

PCoIP Management Console Using the ENDPOINT DETAILS Page



Displaying Endpoint Details

To display endpoint details:

- 1. From the PCoIP Management Console's top menu, click **ENDPOINTS**.
- 2. In either the GROUPED or UNGROUPED table, select the desired endpoint.
- 3. Click ENDPOINTS and then DETAILS.

Opening an Endpoint's Profile

To open an endpoint profile:

- 1. From the ENDPOINT DETAILS page, click PROFILE.
- 2. Click **DETAILS** to open the endpoint's profile in edit mode.

Applying a Profile to an Endpoint

You can update an endpoint by applying a profile from the ENDPOINTS page or the ENDPOINT DETAILS page. This applies the profile right away or after any currently running scheduled actions for this endpoint have completed.

To apply a profile to an endpoint:

- 1. From the *ENDPOINTS* page, select the endpoint.
- 2. Click PROFILE > APPLY.

Moving an Endpoint

You can move an endpoint to a group either from the ENDPOINTS page or the ENDPOINT DETAILS page.

To move an endpoint:

- 1. From the ENDPOINT DETAILS page, click STRUCTURE and then MOVE.
- 2. Select the desired parent group or child group, and then click **MOVE TO GROUP**.

Renaming an Endpoint

You can rename an endpoint either from the ENDPOINTS page or the ENDPOINT DETAILS page.

To rename an endpoint:

- 1. From the ENDPOINT DETAILS page, click STRUCTURE and then RENAME.
- 2. Enter a unique name for the endpoint (from within its group hierarchy) and click **RENAME** ENDPOINT.

Note: Auto naming endpoints

If you have configured a global naming convention for endpoints that applies when they move to or from a group, this overrides any manually configured endpoint name. If you then move the endpoint into or out of a group, the automatic naming rule will apply. See Auto Naming Endpoints.

Powering Down an Endpoint



Caution: Remote Workstation Cards

Remote Workstation Cards cannot be powered down, power reset, or reset to default by the PCoIP Management Console as the Remote Workstation Card requires the host computer to be restarted due to the Remote Workstation Card obtaining its power from the host computer motherboard. An alternate method of restarting the host computer is required to restart the host computer.

Powering Down a PCoIP Zero Client

The **POWER DOWN** option causes a PCoIP Zero Client to power down right away, or after any currently running scheduled actions for this endpoint have completed. You can power down a PCoIP Zero Client either from the ENDPOINTS page or the ENDPOINT DETAILS page.

To power down an endpoint:

- 1. From the ENDPOINT DETAILS page, click ENDPOINTS and then POWER DOWN.
- 2. Click **OK** at the message prompt.

Power Resetting an Endpoint



A Caution: Remote Workstation Cards

Remote Workstation Cards cannot be powered down, power reset, or reset to default by the PCoIP Management Console as the Remote Workstation Card requires the host computer to be restarted due to the Remote Workstation Card obtaining its power from the host computer motherboard. An alternate method of restarting the host computer is required to restart the host computer.

The **POWER RESET** option causes a PCoIP Zero Client to reset (reboot) right away, or after any currently running scheduled actions have completed. You can reset a PCoIP Zero Client either from the ENDPOINTS page or the ENDPOINT DETAILS page.

To reset an endpoint:

- 1. From the ENDPOINT DETAILS page, click ENDPOINTS and then POWER RESET.
- 2. Click **OK** at the message prompt.

Resetting Endpoint Properties to Factory Defaults

The **RESET TO DEFAULT** option causes an endpoint to reset to its default factory configuration right away, or after any currently running scheduled actions have completed. You can reset an endpoint to its default factory configuration either from the ENDPOINTS page or the ENDPOINT DETAILS page.

PCoIP Management Console Using the ENDPOINT DETAILS Page

A Caution: Remote Workstation Cards

Remote Workstation Cards cannot be powered down, power reset, or reset to default by the PCoIP Management Console as the Remote Workstation Card requires the host computer to be restarted due to the Remote Workstation Card obtaining its power from the host computer motherboard. An alternate method of restarting the host computer is required to restart the host computer.

To reset endpoint properties to their defaults:

- 1. From the ENDPOINT DETAILS page, click ENDPOINTS and then RESET TO DEFAULT.
- 2. Click **OK** at the message prompt.
- 3. If the endpoint does not reboot after the reset to default command completes, reboot the endpoint either manually or from the PCoIP Management Console using the **POWER RESET** command.

Clearing the Management State of the Endpoint

The PCoIP Management Console allows you to place the endpoint in an unmanaged state allowing the endpoint to be managed by another PCoIP Management Console or a compatible management tool of your choice.

To clear the management state of an endpoint:

1. From the ENDPOINT DETAILS page, click ENDPOINTS and then CLEAR MANAGEMENT STATE.

Requesting an Endpoint Certificate

The REQUEST CERTIFICATE option is an active option when your endpoint is in a group defined in your SCEP rule. The rule can contain one or more certificate usage types or requests. When you request a certificate for an endpoint, the Management Console initiates a request for a certificate using the certificate rules that apply to the endpoint.

To request a SCEP certificate:

- 1. Ensure your SCEP rules are configured. See Requesting Endpoint Certificates Using SCEP (Enterprise).
- 2. From the ENDPOINT DETAILS page, highlight your endpoint or the group of endpoints for this request and click ENDPOINTS and then REQUEST CERTIFICATE.

Peering Endpoints (ENTERPRISE)

PCoIP Management Console allows the option of peering a specific PCoIP Zero Client with a predetermined Remote Workstation Card. This is done using the PEER and UNPEER options found on the Endpoint DETAILS page. UNPEER is enabled when a host endpoint is selected prior to reaching the DETAILS page.

To peer a client and a host endpoint:

- 1. From the *ENDPOINT* page, highlight the endpoint you want to peer with.
- 2. From the ENDPOINT DETAILS page, click PEER.
- 3. Click **OK** at the message prompt.

Caution: UNPEER behavior on endpoints

When unpeered, the host card will accept connections from any peer and the PCoIP Zero Client will continue to have the host IP configured until a session configuration change is made to that PCoIP Zero Client.

To unpeer a client and a host endpoint:

- 1. From the ENDPOINT DETAILS page of a Remote Workstation Card, click ENDPOINTS and then UNPEER.
- 2. Click **OK** at the message prompt.



Info: Unpeer option

You can only unpeer a client from a Remote Workstation Card. The UNPEER option is disabled on the PCoIP Zero Client ENDPOINT DETAILS page.

Deleting an Endpoint

You cannot delete an endpoint from the ENDPOINTS DETAILS page but you can from the ENDPOINTS page. See Deleting Endpoints.

PCoIP Management Console

Using the ENDPOINT DETAILS Page

Accessing an Endpoint's AWI

From the *ENDPOINT DETAILS* page click **WEB INTERFACE** to open the endpoint's AWI in a browser to configure the endpoint directly.

0

Info: Network Access

If you do not have network access to the AWI, then the link won't work.

For information about the AWI, please see <u>PCoIP Zero Client Firmware Administrators' Guide</u> or the Remote Workstation Card Firmware Administrators' Guide.

Refreshing an Endpoint

Click **Refresh** will display the correct information for anything listed on that page for that particular endpoint. This may take several minutes to complete.

PCoIP Management Console Performing Power Management

Performing Power Management

The **ENDPOINTS** page provides menu options to let you power down and reset PCoIP Zero Clients from the PCoIP Management Console. These actions are performed on one or more individual PCoIP Zero Clients and occur as soon as you apply them from the **ENDPOINTS** menu, or after any currently running scheduled actions for this PCoIP Zero Client have completed. Alternatively, you can create a schedule to power down or reset one or more groups of PCoIP Zero Clients in the future. See Creating a Schedule.

Caution: Remote Workstation Cards

Remote Workstation Cards cannot be powered down, power reset, or reset to default by the PCoIP Management Console as the Remote Workstation Card requires the host computer to be restarted due to the Remote Workstation Card obtaining its power from the host computer motherboard. An alternate method of restarting the host computer is required to restart the host computer.


Powering Down PCoIP Zero Clients

The **POWER DOWN** option causes an PCoIP Zero Client to power down right away, or after any currently running scheduled actions have completed. You can power down PCoIP Zero Clients either from its **ENDPOINT DETAILS** page or from the **ENDPOINTS** page.

To power down PCoIP Zero Clients:

- 1. From the PCoIP Management Console's top menu, click ENDPOINTS.
- 2. In either the GROUPED or UNGROUPED table, select one or more PCoIP Zero Clients that you wish to power down.
 - a. From the PCoIP Management Console's top menu, click **ENDPOINTS**.
 - b. In either the GROUPED or UNGROUPED table, select one or more PCoIP Zero Clients that you wish to reset.

PCoIP Management Console Powering Down PCoIP Zero Clients




- c. Click ENDPOINTS and then POWER RESET.
- d. Click **OK** at the message prompt.
- 3. Click ENDPOINTS and then POWER RESET.
- 4. Click **OK** at the message prompt.

Resetting PCoIP Zero Clients

The **POWER RESET** option causes PCoIP Zero Clients to reboot right away, or after any currently running scheduled actions for this PCoIP Zero Clients have completed. You can reset an endpoint either from its **ENDPOINT DETAILS** page or from the **ENDPOINTS** page.

To reset endpoints:

- 1. From the PCoIP Management Console's top menu, click **ENDPOINTS**.
- 2. In either the *GROUPED* or *UNGROUPED* table, select one or more PCoIP Zero Clients that you wish to reset.



- 1. Click ENDPOINTS and then POWER RESET.
- 2. Click **OK** at the message prompt.

PCoIP Management Console Powering Down PCoIP Zero Clients

Resetting Endpoint Properties to Their Defaults

Note: Resetting an endpoint clears the management state and disables the AWI


See <u>Configuring DNS for Endpoints that use Autodiscovery</u> or <u>Configuring DHCP for Endpoints that use Auto Discovery</u>

- Management State: Resetting an endpoint to factory defaults will clear the management state
 of the endpoint. The bootstrap and endpoint discovery will need to be done automatically or
 manually. If the endpoint has autodiscovery enabled, it will check back into the Management
 Console. If the endpoint has not been configured for autodiscovery, you will have to have
 physical access to the endpoint to use the OSD or configure management access.
- AWI: Resetting a Zero Client to factory defaults will disable the Administrative Web Interface. The Remote Workstation Card AWI is not disabled by default. You can gain access to the AWI again if you are on site and can access the OSD, or if autodiscovery is enabled where you can re-apply a profile that enables the AWI.

The **RESET TO DEFAULT** option causes an endpoint to reset to its default configuration right away, or after any currently running scheduled actions for this endpoint have completed. You can reset an endpoint to its default configuration either from its **ENDPOINT DETAILS** page or from the **ENDPOINTS** page. Performing a **RESET TO DEFAULT** on a Remote Workstation Card requires someone onsite to power cycle the host computer.

To reset endpoint properties to their defaults:

- 1. From the PCoIP Management Console's top menu, click the **ENDPOINTS** link.
- 2. In either the GROUPED or UNGROUPED table, select one or more endpoints that you wish to reset.



3. Click RESET TO DEFAULT then OK.

PCoIP Management Console Renaming Endpoints

Renaming Endpoints

You can rename an endpoint either from its ENDPOINT DETAILS page or the ENDPOINT page.

To rename endpoints:

- 1. From the PCoIP Management Console's top menu, click ENDPOINTS.
- 2. In either the GROUPED or UNGROUPED table, select the endpoint that you wish to rename.
- 3. Click STRUCTURE and then RENAME.
- 4. Enter a unique name for the endpoint (from within its group hierarchy) and click **RENAME ENDPOINT**.

Note: Auto naming endpoints

If you have configured a global naming convention for endpoints that applies when they move to or from a group, this overrides any manually configured endpoint name. If you then move the endpoint into or out of a group, the automatic naming rule will apply. See <u>Auto Naming Endpoints</u>.

PCoIP Management Console Deleting Endpoints

Deleting Endpoints

You can delete an endpoint when you no longer wish it to be managed by the PCoIP Management Console. This also removes it from its *GROUPED* or *UNGROUPED* endpoints table.

If auto-discovery is used (DHCP option-based or DNS SRV records) and the endpoint is still connected to the network, it will attempt to initiate a new connection to the PCoIP Management Console and re-register with it.

✓ Note: Deleting endpoint does not clear its management state

Once an endpoint is managed by a PCoIP Management Console, deleting an endpoint from the PCoIP Management Console does not clear the management state of the endpoint itself. If you wish to connect the endpoint to another PCoIP Management Console, then you must clear the management state of that endpoint from the endpoint's AWI. If you do not clear the management state of the endpoint, and it is still has network connectivity to the PCoIP Management Console, then it will reconnect and re-register itself with the PCoIP Management Console.

To delete endpoints:

- 1. From the PCoIP Management Console's top menu, click **ENDPOINTS**.
- 2. In either the GROUPED or UNGROUPED table, select one or more endpoints that you wish to delete.
 - Tip: Press Shift +Click to select contiguous elements

 Use Shift +Click to select contiguous elements and Ctrl +Click to select non-contiguous elements.
- 3. Click ENDPOINTS and then CLEAR MANAGEMENT STATE.
- Click ENDPOINTS and then DELETE.
- 5. Click I AM SURE at the message prompt.

PCoIP Management Console Searching an Endpoint Table

Searching an Endpoint Table

The **ENDPOINTS** page contains a search function that lets you locate endpoints in either the *GROUPED* or *UNGROUPED* endpoint table by searching on any text that appears in the displayed columns.

To perform a search:


- 1. Enter the desired search text in the search text box.
- 2. Press Enter or click **SEARCH**.

To clear a search, click the **x** in the search text box.

PCoIP Management Console Filtering the Endpoint List

Filtering the Endpoint List

The *ENDPOINTS* page contains a filter function that lets you select from a list of predefined filters to refine the endpoints that display in a *GROUPED* or *UNGROUPED* endpoints table. For example, you can display only endpoints with profile mismatches or endpoints that have failed to power down or reset. You can also create your own filter criteria and save your filters into the list. New filters may be added as improvements are developed.



Endpoint predefined filters

Selecting a Predefined Filter

To select a predefined filter:

- 1. From the PCoIP Management Console's top menu, click **ENDPOINTS**.
- 2. Select either the GROUPED or UNGROUPED tab.
- 3. Click the arrow to the side of the **FILTER** button.
- 4. Select a predefined filter from the drop-down list. Your active filter will display as a new dark gray filter icon next to the **FILTER** button, as shown next.

PCoIP Management Console Filtering the Endpoint List



5. To return to the unfiltered endpoint list, click the x on the filter icon, or select **CLEAR FILTER** from the *FILTER* drop-down list.

Adding a Filter

To add a filter:

- 1. From the PCoIP Management Console's top menu, click **ENDPOINTS**.
- 2. Select either the GROUPED or UNGROUPED tab.
- 3. Click the FILTER button.
- 4. In the ADD FILTER dialog, use the drop-down menus to select your filter criteria. When you are finished, click the filter icon to the right.
- 5. You can repeat this step to add additional criteria to the filter, for example, **Power DOWN is Failed** and **Online Status is Online**. Multiple criteria in a filter are logically ANDed, not ORed.
- 6. Click OK.
- 7. To save your filter, select **SAVE ACTIVE FILTER** from the *FILTER* drop-down list on the main *ENDPOINTS* page.
- 8. Enter a unique name for the filter in the **SAVE ACTIVE FILTER** dialog, and click **SAVE**. When you click the **FILTER** button, your filter will now appear in the **Predefined Filters** list.

Managing Saved Filters

To manage saved filters:

- 1. From the PCoIP Management Console's top menu, click **ENDPOINTS**.
- 2. Select either the GROUPED or UNGROUPED tab.
- 3. Click the arrow to the side of the FILTER button and select MANAGE SAVED FILTERS.
- 4. Select a saved filter in the drop-down list and choose one of the following:
 - · Click **NEW** to add a new filter.

PCoIP Management Console Filtering the Endpoint List

- \bullet Click $\mbox{\bf EDIT}$ to change the filter criteria.
- Click **DELETE** to delete the saved filter.

PCoIP Management Console Exporting an Endpoint List

Exporting an Endpoint List

You can generate a comma-delimited file listing all endpoints, or all endpoints and columns, visible in the *ENDPOINTS* table. PCoIP Management Console administrators can use this file to import inventory information on their deployment into third-party inventory management systems.

Note: Exporting endpoints available on PCoIP Management Console Enterprise

This feature is available for the PCoIP Management Console Enterprise only.

To generate a list of endpoints visible in an endpoints table:

- 1. From the PCoIP Management Console's top menu, click **ENDPOINTS**.
- 2. Select either the GROUPED or UNGROUPED tab.
- 3. Click ENDPOINTS and then select EXPORT ALL or EXPORT CURRENTLY VIEWED.
- 4. Follow the prompts to open or save the file.

Note: Change the file type to .csv

If the exported file has no file type, change the file type to .csv to open it in Microsoft Excel as a comma-delimited file.

PCoIP Management Console Managing the Console

Managing the Console

Creating and Managing User Roles

Management Console allows the creation and management of user roles. Roles are created with a set of permissions that allow the administrator to configure which Management Console pages are accessible as well as what options within each page that are enabled. Each role can be finely tuned to a set of permissions that limit the access users have to configurable options within Management Console.

Default roles for users are applied to users depending on where the user is created.

- Management Console created users obtain the System Administrator role.
- IDP created users obtain the Administrator role by default. Management Console System Administrators can subsequently change this users role.
- Active Directory users can have roles assigned to them from roles assigned to there AD Groups.

Unlicensed Management Console

The DELETE and EDIT buttons are deactivated on unlicensed versions of Management Console.

The **SET PERMISSIONS** allow each Management Console page to be made available for use by the role. Permissions of **Show** and **Hide** can be set for each page. Once the SET PERMISSION is selected, the **Detail Permissions** become viewable and represent the configurable options within each Management Console page. Detailed permissions can be set to **Enable**, **Disable** or **Hide**.

When managing a new role, take the time to plan your administrative structure for PCoIP endpoints. If your organization requires changes to existing roles, you can easily do this by using the **EDIT** button and changing the permissions of each role. If role permissions are changed while a user of the role is logged in, the permissions take affect right away and will be seen when the user refreshes the Management Console page.

6 Active Directory Groups

- You can identify Active Directory Groups associated with a user by viewing the AD GROUP column in the ROLES AND PERMISSIONS tab on the Management Console AUTHENTICATION page.
- When an Active Directory user belongs to multiple Active Directory groups, the USER ROLE will take from the first group listed by Active Directory Server.
- When a new role has been applied to an Active Directory group or user, the changes will be reflected in all relative fields only after logged in users log out and back in again.

Creating a User Role

To create a user role, perform the following steps:

- 1. From the SETTINGS > AUTHENTICATION page, click the **ROLES AND PERMISSIONS** tab.
- 2. Click ADD.
- 3. Enter the **Role Name** (no spaces allowed) and then select the set of permissions specific to that role.
- 4. Click SAVE.

The newly created role will now be available to assign to any Management Console user.

Deleting Roles

Roles cannot be deleted if a user is associated with that role. You can only delete multiple roles at once if all the selected roles for deletion do not have a user associated with it.

Resetting User Roles

Administrators can reset user roles using the provided script in the scripts folder located at /opt/teradici/scripts. This may be required when a role is limiting users to a Management Console feature. Running of the script will provide full Management Console access back to the specific user role. Allow a few minutes for Management Console to reboot.

To reset a user role to provide full access

1. SSH to the Management Console.

2. Browse to /opt/teradici/scripts and type the command:

sh reset user role.sh { userName }

Available role permissions

SET PERMISSION	Detailed Permissions
(Show or Hide)	(Show, Hide, Enable, Disable or Hide)
ENDPOINTS	Permissions with Show or Hide • Grouped
	• Ungrouped
	Permissions with Enable, Disable or Hide
	Profile (Group only)
	• Details
	• Change
	• Apply
	• Sructure
	• Move
	• Rename
	 New Group (Grouped only)
	• Remove Group (Grouped only)
	• Endpoints
	• Details
	• Power Down
	 Power reset
	• Reset to default
	· Clear management state
	• Export all
	27,501.411

PCoIP Management Console Creating and Managing User Roles

SET PERMISSION (Show or Hide)	Detailed Permissions (Show, Hide, Enable, Disable or Hide)
	 Export currently viewed
	• Delete
	• Get all settings
	 Request Certificate (Grouped only)
	• Endpoints Discovery
PROFILE	Permissions with Enable, Disable or Hide • New profile
	• Edit profile
	Duplicate profile
	Delete profile
	• Import File
	• Export File
	Global turn on or off Persistent Configuration
SCHEDULE	Permissions with Show or Hide • Schedule tab
	• History tab
	Permissions with Enable, Disable or Hide
	New schedule
	• Edit schedule
	View schedule
	Delete schedule
ENDPOINT CERTIFICATES	Permissions with Enable, Disable or Hide • New certificate rule
	View certificate rule
	• Edit certificate rule
	Delete certificate rule
	Global turn on or off certificate rule
AUTO CONFIGURATION	Permissions with Enable, Disable or Hide
	New autoconfig rule
	Edit autoconfig rule
	Delete autoconfig rule

PCoIP Management Console Creating and Managing User Roles

SET PERMISSION (Show or Hide)	Detailed Permissions (Show, Hide, Enable, Disable or Hide)
	Global turn on or off autoconfig
SETTINGS	N/A

Managing Users

PCoIP Management Console Enterprise supports multiple concurrent administrative users. There are two default user roles that have different administrative capabilities—System Administrator and Administrator. Additionally, Management Console allows you to create new user roles with your own set of permissions. Roles can be applied to individual users that are created locally on the PCoIP Management Console, created by an integrated Identity Provider, or by the Active Directory group that an AD authenticated user is part of. A user with the **System Administrator** role can perform any function on the Management Console, while a user with the **Administrator** role can access everything except the SETTINGS pages. Roles that have been specially created will have their own set of permissions depending on what the administrator has chosen when making the role. For more informations on roles, see Managing User Roles.

Management Console Free - Roles

PCoIP Management Console Free supports one administrative user with the System Administrator role.

Users with any role can edit their own profile by clicking on their username at the top right of the Management Console screen.

System Administrators can manage PCoIP Management Console Enterprise user accounts by clicking **SETTINGS** from the top menu and then clicking the **AUTHENTICATION > USERS** tab.

The following tasks are performed from a user account with the System Administrator role.

Displaying User Information


The PCoIP Management Console Enterprise AUTHENTICATION page contains a table showing all the users that are currently configured to use PCoIP Management Console. This page is viewable by any System Administrator. PCoIP Management Console Enterprise allows you to create, edit, enable or disable one or more user accounts, assign different user roles, and view user logs to see user activity. You can also refine the list of users in the table by clicking **ENABLED USERS** to display only users with enabled accounts, or **ALL USERS** to display all user accounts. With the introduction of IDP support, you can view which of your users are maintained by an IDP and which are local to Management Console. Local users are recognized as DB users and IDP users are recognized as IDP.

Click the gear icon




to the right of

the table to change the information you want to display in the table columns. Your customized settings are saved in your browser and will be used for any user who subsequently logs in from that browser.



PCoIP Management Console Enterprise AUTHENTICATION Page

PCoIP Management Console Free supports only one administrative user. Enabling and disabling this user is not supported in PCoIP Management Console Free.



PCoIP Management Console Free AUTHENTICATION Page



User and Role names cannot contain white spaces. Spaces given in starting and ending of role name will be trimmed automatically while whitespaces between words will not be accepted.

Creating a New User Account in PCoIP Management Console Enterprise

Before creating a new user, make sure you have planned your administrative environment first. This may require that you have created specific roles for your users. See <u>Managing User Roles</u> for information on role permissions.

To create a new user account in PCoIP Management Console Enterprise:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Ensure the **USERS** tab is active.
- 3. Click NEW USER.
- 4. Configure the parameters as follows:
 - Role: Select Administrator (limited), System Administrator (full access), (access is limited to the configured options selected when creating the role)
 - Username: Enter a unique name for the user. Ensure the username does not exceed 80 characters. It can include dots (.), hyphens (-), and underscores (_), but it must contain at least one alphanumeric character. The @ symbol is allowed only for IDP and AD users.


• First Name: Enter the user's first name. Ensure the first name does not exceed 80 characters. It can include dots (.), hyphens (-), underscores (_), and the at symbol (@), but it must contain at least one alphanumeric character.

- Last Name: Enter the user's last name. Ensure the last name does not exceed 80 characters. It can include dots (.), hyphens (-), underscores (_), and the at symbol (@), but it must contain at least one alphanumeric character.
- Password: Enter a password for the user. It must not exceed 80 characters.
- Confirm Password: Enter the password again. It must not exceed 80 characters.
- **Time Zone:** Select the user's local time zone from the drop-down list. Time zones in this list are presented in IANA format.

▲ Active Directory Users

All Active Directory users have a default timezone of UTC which can be modified by a Management Console System Administrator after the user has logged in the first time.

Account Enabled: Select to enable the account.



5. Click SAVE.

Enabled vs. not enabled for new users

If a new user is not enabled and the MANAGEMENT CONSOLE USERS page is set to show enabled users only, this user will not be visible in the table until the page is changed to show all users.

Editing a User Account

To edit a user account:

Username Behavior After Upgrade

In versions of MC earlier than 25.06, if a database user was created with special characters in the username, the username remains unchanged and non-editable after upgrading to version 25.06.

- 1. From the table on the MANAGEMENT CONSOLE USERS page, select the user account you wish to edit.
- 2. Click EDIT.
- 3. Change the user's settings as needed, making sure the changes comply with the configured validation rules.
 - First Name: Enter the user's first name. Ensure the first name does not exceed 80 characters. It can include dots (.), hyphens (-), underscores (_), and the at symbol (@), but it must contain at least one alphanumeric character.
 - Last Name: Enter the user's last name. Ensure the last name does not exceed 80 characters. It can include dots (.), hyphens (-), underscores (_), and the at symbol (@), but it must contain at least one alphanumeric character.
 - Password: Enter a password for the user. It must not exceed 80 characters.
 - Confirm Password: Enter the password again. It must not exceed 80 characters.
- 4. Click SAVE.

Enabled vs. not enabled for existing users

If an edited user is not enabled and the MANAGEMENT CONSOLE USERS page is set to show enabled users only, this user will not be visible in the table until the page is changed to show all users.

Enabling or Disabling User Accounts in PCoIP Management Console Enterprise


To enable or disable user accounts in PCoIP Management Console Enterprise:

- 1. From the table on the MANAGEMENT CONSOLE USERS page, select one or more users.
- 2. Use Shift +Click to select contiguous elements and Ctrl +Click to select non-contiguous elements.
- 3. Click **ENABLE** to enable the accounts or **DISABLE** to disable the accounts.

Viewing User Logs

To view user logs:

1. In the MANAGEMENT CONSOLE USERS page, click **VIEW LOG** to see the date and type of action for each user, as shown next:



- 2. Scroll to the bottom of the list to see the most recent actions.
- 3. Click **OK** to close the user log.

Managing PCoIP Management Console Logs

The PCoIP Management Console **VERSION** page displays the version of the PCoIP Management Console that you are currently running, and also lets you select the level of diagnostic logging for the PCoIP Management Console. You can access this page by clicking **SETTINGS** from the PCoIP Management Console's top menu and then clicking the **VERSION** menu in the left pane.

Release version can be viewed on dashboard

The PCoIP Management Console release version is also displayed on the dashboard.

Locating the PCoIP Management Console's Log Files

All PCoIP Management Console logs are located in the PCoIP Management Console's virtual machine in its /opt/teradici/log directory. You can access these files by logging in to your PCoIP Management Console virtual machine console using vSphere Client. Log files are included in database archives.

The PCoIP Management Console's log directory contains the following files:

- console.log: Logs information about the PCoIP Management Console's front-end console. In this release, its level is set to Info and cannot be changed.
- daemon.log: Logs information about the PCoIP Management Console's back-end daemon. You can set a diagnostic log level for the PCoIP Management Console 2's daemon process.
- daemon-startup.log: Logs information about when the PCoIP Management Console's daemon starts up or stops.
- daemon.log.< date >.gz: Contains a gzip archive file for any daemon.log file that has reached 100 MB. These files are zipped to save space on the virtual machine.

Log File Size and Rotation

Both console and daemon logs are limited to 200 files—two uncompressed (up to 100 MB each) and 98 compressed (approximately 5 MB each). These files are rotated as needed.

Both console and daemon logs are limited to a set of 200 files. Out of this set, there are two uncompressed files that can grow to 100 MB each while the other 98 files are compressed and reach a size of approximately 5 MB each. These files are rotated as needed.

Linux system logs are rotated using default Rocky Linux settings. The PCoIP Management Console does not configure Linux system logs.

Setting the PCoIP Management Console's Diagnostic Log Level

The PCoIP Management Console has five log levels that you can set. Troubleshooting an issue requires capturing all the details of an event in both the daemon and console logs. This is why setting the level for either daemon or the console adjusts both logs to the same level. By default the logging level is set to **INFO**.

The logging level can be set from the Management Console **SETTINGS > VERSION** page. Simply select the level of logging from the drop down field under MANAGEMENT CONSOLE DIAGNOSTIC LOGGING.

The five log levels are:

- **ERROR:** Only logs error messages. Error messages are logged events that occurred that were not supposed to have occurred.
- **WARN:** Only logs warning messages. Warning messages are logged events that may cause an issue in the future.
- INFO: Logs informational messages and events at a coarse-grained level.
- **DEBUG:** Logs deeper information that is useful for a debug application to troubleshoot.
- **TRACE**: Logs finer-grained informational messages and events. Trace should only be used under the direction of support for debugging issues.

Obtaining Management Console Logs

To obtain logs you first need to ensure SSH is enabled to allow access to the Management Console VM from applications like WinSCP or FileZilla. These applications can be downloaded from the Internet.

1. To enable SSH go to the VMware console screen for the Management Console VM, log in and type the following command:

sudo service sshd start

This will temporarily enable SSH access until the next reboot of the Management Console or you can stop the service by typing the following command:

sudo service sshd stop

6 Alternative method to access Management Console's VM console

See Accessing the PCoIP Management Console Virtual Machine Console

- 2. Next log into the Management Console VM using a utility such as WinSCP or FileZilla.
- Change directories to /opt/teradici/log.Normally you will be at the /home/admin folder.
- 4. Download both the **console.log** and the **daemon.log** files to be used for your investigation.

Management Console support

The console.log and the daemon.log files are required for Management Console investigations.

Creating and Managing PCoIP Management Console Certificates

This section contains information on how to manage your PCoIP Management Console certificates, including custom certificate requirements, creation, upload, update, and general management of certificates

b Important: Generate your own custom certificate and configuring endpoint discovery

The PCoIP Management Console is shipped with a default self-signed certificate. We strongly recommend that you generate your own certificates signed by a recognized certificate authority (CA), and then update both your PCoIP Management Console and your endpoints with the certificates before configuring a discovery method or adding endpoints to your PCoIP Management Console.

The following requirements and procedures will help guide you with creating a self-signed certificate for use with Management Console in a secure environment.

CUSTOM CERTIFICATE REQUIREMENTS

The certificate loaded onto the PCoIP Management Console for use as the PCoIP Management Console web interface certificate and for endpoint management must meet the following requirements:

- It must be a X.509 certificate in PEM format.
- Three PEM files are needed to install the certificate into the PCoIP Management Console:
 - The first file contains only the PCoIP Management Console public certificate. This is generally referred to as the leaf or server certificate.
 - The second file contains only the PCoIP Management Console certificate's private key. This is the private key that was generated when you made the certificate request.
 - The third file contains the PCoIP Management Console certificate's issuing chain, this chain will contain the first certificate and the root certificate and in some cases an intermediate certificate will be required (intermediate CAs, if applicable, and root CA).

Order of Issuing Chain

The certificate must have an entire verifiable chain. Any certificate used to sign the leaf certificate must be present in the chain.

Generally it will be the order of the certificates in the chain will be:

- a. Leaf/Server
- b. Intermediate
- c. Root Ca
- The certificate must be valid, meaning that the current time is after the 'not valid before' time and before the 'not valid after' time.
- Certificate RSA keys.
 - Management Console supports RSA keys or signing algorithm. (ECDSA is not currently supported)
 - Management Console also supports MD5 signatures.
 - The certificate's RSA key must be 1024 bit or greater. The recommended length is 2048 bits.
 - If the PCoIP Management Console certificate contains an Enhanced Key Usage extension, it must include the Server Authentication usage. It is also acceptable for the certificate to not include an Enhanced Key Usage extension.

Creating and Preparing Your Own Custom Certificate for PCoIP Management Console

This section demonstrates how to create your own certificate using OpenSSL and your own CA server. The following steps use the PCoIP Management Console VM and a Microsoft CA server but it can be done from any VM with OpenSSL and a CA server of your choice.

Examples use Teradici's PCoIP Management Console name

All the following examples use Teradici's PCoIP Management Console name. Replace any name with your own.


STEP 1 - ENSURE YOUR PCOIP MANAGEMENT CONSOLE DOES NOT HAVE ANY CUSTOM CERTIFICATES INSTALLED

To make sure you don't have custom certificates installed:

- 1. Log into the PCoIP Management Console web interface.
- Go to SETTINGS > SECURITY > CERTIFICATES and ensure the default certificate is installed by confirming:
 - Security Certificate section Subject and Issued By are populated with localhost. (see #1)
 - Security Chain section is empty. (see #2)

Custom Certificates

The Security Certificate and Security Chain fields of custom certificates will be populated by data that does not include localhost and will not have empty values.



STEP 2 - CONNECT AND ENABLE SSH TO CREATE YOUR CERTIFICATE SIGNING REQUEST VIA THE PCOIP MANAGEMENT CONSOLE VIRTUAL MACHINE

You will need to enable SSH prior to creating your certificate. See <u>Accessing the PCoIP Management</u> Console Virtual Machine Console.

Run OpenSSL on a 'Trusted' computer

OpenSSL can be run on any 'Trusted' computer.

To create your Certificate Signing Request:

- 1. SSH into the PCoIP Management Console VM using your preferred SSH client. The example shown next uses PuTTY.
- 2. Run the OpenSSL command:

```
openssl req -out CSR.csr -new -newkey rsa:3072 -nodes -keyout mccertprivateKey.pem
```

3. You will get the following response and be asked a series of questions, as shown next:

Modify each entry with your own detailed information. Descriptions are shown next:

Country Name: Your country

State of Province Name: Your state or province

· Locality Name: Your city

Organization Name: Your company

· Organizational Unit Name: Your department

 Common Name: Your PCoIP Management Console Name (for example, hostname of PCoIP Management Console such as se-pcoip-mc-200) • Email Address: you@yourcompany.com

• A challenge password: Your password

· An optional company name: Optional

- 4. Press Enter
- 5. Two files will be generated in the admin folder: mccertprivateKey.pem and CSR.csr.
- 6. Using a file management tool of your choice, copy the two files off of your PCoIP Management Console to a desktop of your choice.


STEP 3 - SUBMIT YOUR CERTIFICATE SIGNING REQUEST (CSR)

Caution: Certificates with Private Key


Do not send certificates containing your private key to the CA. A certificate with private key should not be sent outside your organization. The private key provides access to your secured resources and should remain under tight control.

To submit your certificate signing request (CSR) (this example is using a Microsoft CA server):

- 1. From your CA Server, enable Certification Authority Web Enrollment if it is not enabled. Follow the steps below to enable it.
 - a. In the dashboard, select Manage, then click Add Roles and Features.




b. Select the Server Roles section and enable the Certification Authority Web Enrollment.



2. Access the CA server by entering the following URL into a web browser http://<Host IP address>/ certsrv.





- 3. Select Request a Certificate.
- 4. Select Advanced Certificate Request.

• For Internet Explorer user


If you are using Internet Explorer, select submit a certificate request by using a **base-64-encoded CMC** or **PKCS #10** file, or submit a renewal request by using a **base-64-encoded PKCS #7** file.

5. From the VM/PC you saved your CSR.csr files, open the **CSR.csr** file in a text editor and copy the contents of the csr request into Base-64-encoded certificate request (CMC or PKCS #10 or PKCS #7) field on your Certificate Authority (CA) server.

Using text editor to copy the Certificate Signing Request

If CSR.csr does not open in your text editor, you can rename **CSR.csr** to **CSR.csr.txt** to open it in Notepad and copy the content.


- 6. For Certificate Template, select Web Server.
- 7. Do not add anything in the attributes box.
- 8. Click Submit.




STEP 4 - DOWNLOAD AND PREPARE THE CERTIFICATE

To download and prepare the certificate:


1. You can now download the created certificate from the CA server in Base 64 format. However, do not download the certificate chain as it is still in the wrong format. The certificate will show up as **certnew.cer**.



- 2. Rename certnew.cer to certnew.pem.
- 3. Get a copy of the CA certificate from the certificate server in Base64. The CA will return a certificate that will be used as part of the chain.
 - a. From the CA server home page click the **Download a CA certificate** link.



b. Select Base64 and then click the **Download CA Certificate** link.



- c. Save the file as CA.cer.
- d. Rename the file to CA.pem.
- 4. Create a new certificate called **chain.pem** by combining the contents of **certnew.pem** with **CA.pem** using a text editor. (Occasionally the CA certificate may contain intermediate certificates which may need to be added to the chain)

To combine the certificates:

- a. Rename both certificate extensions to .txt.
- b. Using a text editor like Notepad, create a new file called **chain.txt** by combining the CA.txt content under the certnew.txt content.
- c. Rename chain.txt to chain.pem.
 - Note: All certificates must be in PEM format

All PCoIP Management Console certificates must be issued in PEM format.

- 5. Now, you will have three certificates:
 - · certnew.pem: The certificate returned from the CA
 - mccertprivateKey.pem: The certificate from the OpenSSL command executed in Step 2 above.
 - · chain.pem: The combination of certnew.pem and CA.pem

Uploading Your Own PCoIP Management Console Certificates

This section explains how to upload your own certificates to the PCoIP Management Console and to endpoints that require a PCoIP Management Console certificate before discovery. If you wish to avoid browser certificate warnings when you access the PCoIP Management Console's web interface, you can also install the PCoIP Management Console certificate in your browser.

Important: Use the following sequence if you are installing certificates before adding endpoints

If you are installing your own PCoIP Management Console certificates before you have added endpoints to the PCoIP Management Console, please follow the instructions in the order shown. If you need to update your PCoIP Management Console certificates for any reason after the PCoIP Management Console has already discovered your endpoints, the order of this procedure is slightly different. See Updating PCoIP Management Console Certificates after Endpoint Discovery for details.

The PCoIP Management Console requires the following certificates:

Note: All certificates must be in PEM format

All PCoIP Management Console certificates must be issued in PEM format.

- PCoIP Management Console server's certificate (*.pem): Contains the public key. The PCoIP Management Console's public key certificate fingerprint is also used for DHCP/DNS endpoint discovery. (e.g. certnew.pem in this topic's example)
- PCoIP Management Console server's private certificate (*.pem): Contains the private key. (e.g. mccertprivateKey.pem in this topic's example)
- PCoIP Management Console chain certificate (*.pem): Contains the leaf/server certificate, any intermediate certificates, and the trusted root CA certificate used to issue PCoIP Management Console server certificates. (e.g. chain.pem in this topic's example)


STEP 1 - UPLOAD CUSTOM CERTIFICATE TO THE PCOIP MANAGEMENT CONSOLE VM

Note: Uploading Certificates causes the application to restart


Uploading a certificate signs out all PCoIP Management Console users and causes the PCoIP Management Console application to restart. Users will not be able to access the PCoIP Management Console for one to two minutes.

To upload your certificates to the PCoIP Management Console VM:


- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- Click SECURITY in the left pane and select the CERTIFICATES tab in the SECURITY pane to the right.
- 3. Click UPDATE.
- Click SELECT CERTIFICATE, select the PCoIP Management Console's public certificate file (eg. certnew.pem), and then click NEXT.




5. Click **SELECT KEY**, select the PCoIP Management Console's private certificate file (eg. **mccertprivateKey.pem**), and then click **NEXT**.



Click SELECT CHAIN, select the PCoIP Management Console's chain certificate file (eg. chain.pem), and then click NEXT.



- 7. Click Apply.
- 8. Read the warning message and then click APPLY.
- When the update process completes, click LOGIN to log in to the PCoIP Management Console again.



STEP 2 - UPDATE YOUR DHCP/DNS SERVER WITH THE PCOIP MANAGEMENT CONSOLE SERVER'S PUBLIC CERTIFICATE FINGERPRINT

If your DHCP or DNS server is configured to provision endpoints with the PCoIP Management Console's public certificate fingerprint, this information must be updated next. You can update your server with your PCoIP Management Console certificate fingerprint as follows:

• **DHCP server**: Edit the **EBM X.509 SHA-256 fingerprint** option for the PCoIP Endpoint option class. For details, see <u>Configuring DHCP Options</u>.

• **DNS server**: Edit the **EBM-SHA-256-fingerprint** DNS text record. For details, see <u>Adding a DNS TXT</u> Record.

STEP 3 - UPLOAD PCOIP MANAGEMENT CONSOLE CERTIFICATE TO YOUR ENDPOINTS

If your endpoints are configured with a discovery method and security level that require them to have a PCoIP Management Console certificate in their trusted certificate store before they can connect to the PCoIP Management Console, you can either upload the PCoIP Management Console certificate for a group of endpoints using a PCoIP Management Console profile, or you can upload the PCoIP Management Console certificate locally using each endpoint's AWI. Depending on your security requirements, you can upload either a PCoIP Management Console issuer certificate (that is, the root CA certificate (or intermediate certificate) that was used to issue a PCoIP Management Console server's public key certificate.

To upload the PCoIP Management Console certificate for a group of endpoints using PCoIP Management Console:

1. Ensure that all ungrouped endpoints are moved from the ungrouped category into a group.

Possible modifications due to your deployment

Depending on your site configuration, this may require modifications to your DHCP options or DNS SRV records, or it may require disabling persistent auto-configuration or placing the endpoints into a segregated network with a new PCoIP Management Console.

- 2. Ensure that every group (or at least one parent group) is associated with a profile.
- 3. Update all existing profiles to push the new certificate to endpoints. For each profile:
 - a. From the PCoIP Management Console's top menu click PROFILE.
 - b. Click the **NEW PROFILE** button.
 - c. Enter a name and description for the profile in their respective fields.
 - d. Click the + tab beside the **SETTINGS OVERVIEW** tab and then select the appropriate type of profile (e.g. TERA2: CLIENT [DUAL], TERA2 HOST [QUAD]) that applies to your endpoints and click **ADD**.
 - e. In the SOFTWARE section, ensure the correct **Firmware Version** is selected for your endpoints.
 - f. Click **SECURITY** in the left navigation pane, scroll down to **Certificate Store**, and select **Set in Profile**.

- g. Click **Add New**, browse to your PCoIP Management Console public key certificate, highlight it and click **Open**. (This certificate must have a .pem extension)
- h. Click Upload.
- Ensure the correct usage type is selected for any specialized certificates such as 802.1x and Syslog.

6 Certificate Usage type Limitation

Only one specialized usage type can be selected in one profile. Any subsequent certificate selected for the same usage type will cause the previous certificate to change usage type to **No Usage**.

802.1x and Syslog options are disabled when you upload certificates without a private key

- j. Click **SAVE** at the top of the page.
- k. Apply the profile immediately or create a schedule to update your group(s) with the profile.

Installing the PCoIP Management Console Certificate in Your Browser

If you wish to avoid browser certificate warnings when you access the PCoIP Management Console's web interface, you can install a PCoIP Management Console certificate in your browser. You can use either a PCoIP Management Console issuer certificate or the PCoIP Management Console server's public key certificate. For more information, see How do I get the fix the unsecure browser warning when accessing the Management Console 2.x and 3.x web interface? (1406)

Reverting to the Default Self-signed PCoIP Management Console Certificate

Note: Reverting the default certificate disables all users and causes application to restart

Reverting the PCoIP Management Console to its self-signed certificate disables all PCoIP Management Console users and causes the PCoIP Management Console application to restart. Users will not be able to access the PCoIP Management Console for one to two minutes.

To revert to the default PCoIP Management Console certificate:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Click **SECURITY** in the left pane.
- 3. Click REVERT SELF-SIGNED CERTIFICATE.
- 4. Read the warning message and then click APPLY.



5. When the update process completes, click **LOGIN** to log in to the PCoIP Management Console again.

Updating PCoIP Management Console Certificates after Endpoint Discovery

The steps provided next are for updating your PCoIP Management Console certificates if your certificate expires, or if you need to update your PCoIP Management Console certificate for any other reason.

Note: Update endpoints with new certificate before updating the PCoIP Management Console certificates

It is important to update endpoints with their new PCoIP Management Console certificate before you update the PCoIP Management Console's certificates. Otherwise, your endpoints will not be able to trust the PCoIP Management Console, and your profile update will fail when you attempt to apply it.

STEP 1 - UPDATE ENDPOINTS WITH THE NEW PCOIP MANAGEMENT CONSOLE CERTIFICATE

Note: All certificates must be in PEM format

All PCoIP Management Console certificates must be issued in PEM format.

To upload the PCoIP Management Console certificate for a group of endpoints using PCoIP Management Console:

1. Ensure that all ungrouped endpoints are moved from the ungrouped category into a group.

Possible modifications due to your deployment

Depending on your site configuration, this may require modifications to your DHCP options or DNS SRV records, or it may require disabling persistent auto-configuration or placing the endpoints into a segregated network with a new PCoIP Management Console.

2. Ensure that every group (or at least one parent group) is associated with a profile.

- 3. Update all existing profiles to push the new certificate to endpoints. For each profile:
 - a. From the PCoIP Management Console's top menu click **PROFILE**.
 - b. Click the **NEW PROFILE** button.
 - c. Enter a name and description for the profile in their respective fields.
 - d. Click the + tab beside the **SETTINGS OVERVIEW** tab and then select the appropriate type of profile (e.g. TERA2: CLIENT [DUAL], TERA2 HOST [QUAD]) that applies to your endpoints and click **ADD**.
 - e. In the SOFTWARE section, ensure the correct **Firmware Version** is selected for your endpoints.
 - f. Click **SECURITY** in the left navigation pane, scroll down to **Certificate Store**, and select **Set in Profile**.
 - g. Click **Add New**, browse to your PCoIP Management Console public key certificate, highlight it and click **Open**. (This certificate must have a .pem extension)
 - h. Click Upload.
 - i. Ensure the correct usage type is selected for any specialized certificates such as 802.1x and Syslog.

Certificate Usage type Limitation

Only one specialized usage type can be selected in one profile. Any subsequent certificate selected for the same usage type will cause the previous certificate to change usage type to **No Usage**.

802.1x and Syslog options are disabled when you upload certificates without a private key

- j. Click **SAVE** at the top of the page.
- k. Apply the profile immediately or create a schedule to update your group(s) with the profile.

Tip: Using the Tera2 Endpoint AWI

If a Tera2 endpoint's AWI is enabled, you can directly access it via the Management Console **ENDPOINT DETAILS** page and selecting the **WEB INTERFACE** button. This will allow you to directly manage a single Tera2 endpoint if required.

From the Management Console homepage:

- 1. Select **ENDPOINTS**.
- 2. Find your endpoint in the **GROUPED** or **UNGROUPED** tab and highlight it.
- 3. Select ENDPOINTS > DETAILS.
- 4. Select the WEB INTERFACE button.

For more information about using the endpoint AWI after selecting the WEB INTERFACE button see Remote Workstation Card Firmware Administrators' Guide or PCoIP Zero Client Firmware Administrators' Guide.


STEP 2 - UPLOAD CUSTOM CERTIFICATE TO THE PCOIP MANAGEMENT CONSOLE VM

✓ Note: Uploading Certificates causes the application to restart


Uploading a certificate signs out all PCoIP Management Console users and causes the PCoIP Management Console application to restart. Users will not be able to access the PCoIP Management Console for one to two minutes.

To upload your certificates to the PCoIP Management Console VM:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Click **SECURITY** in the left pane and select the **CERTIFICATES** tab in the **SECURITY** pane to the right.
- 3. Click **UPDATE**.
- Click SELECT CERTIFICATE, select the PCoIP Management Console's public certificate file (eg. certnew.pem), and then click NEXT.



5. Click **SELECT KEY**, select the PCoIP Management Console's private certificate file (eg. **mccertprivateKey.pem**), and then click **NEXT**.




Click SELECT CHAIN, select the PCoIP Management Console's chain certificate file (eg. chain.pem), and then click NEXT.



7. Click Apply.

- 8. Read the warning message and then click APPLY.
- When the update process completes, click LOGIN to log in to the PCoIP Management Console again.



STEP 3 - UPDATE YOUR DHCP OR DNS SERVER

If your DHCP or DNS server is configured to provision endpoints with the PCoIP Management Console's public key certificate fingerprint, this information must be updated next. You can update your server with your PCoIP Management Console certificate fingerprint as follows:

• **DHCP server:** Edit the **EBM X.509 SHA-256 fingerprint** option for the PCoIP Endpoint option class. For details, see <u>Configuring DHCP Options</u>.

• DNS server: Edit the EBM-SHA-256-fingerprint DNS text record. For details, see Adding a <u>DNS TXT</u> Record.

Uploading the PCoIP Management Console Certificate to an Endpoint

If your endpoints are configured with a discovery method and security level that require them to have a PCoIP Management Console certificate in their trusted certificate store before they can connect to the PCoIP Management Console, you can either upload the PCoIP Management Console certificate to a group of endpoints using a PCoIP Management Console profile, or you can upload the PCoIP Management Console certificate locally using each endpoint's AWI. Depending on your security requirements, you can upload either a PCoIP Management Console issuer certificate (that is, the root CA certificate (or intermediate certificate) that was used to issue a PCoIP Management Console server's public key certificate.

For information on PCoIP Management Console certificates, see <u>Managing PCoIP Management</u> Console Certificates.

Uploading PCoIP Management Console Certificates to Endpoints

Note: All certificates must be in PEM format

All PCoIP Management Console certificates must be issued in PEM format.

To upload the PCoIP Management Console certificate for a group of endpoints using PCoIP Management Console:

1. Ensure that all ungrouped endpoints are moved from the ungrouped category into a group.

Possible modifications due to your deployment

Depending on your site configuration, this may require modifications to your DHCP options or DNS SRV records, or it may require disabling persistent auto-configuration or placing the endpoints into a segregated network with a new PCoIP Management Console.

- 2. Ensure that every group (or at least one parent group) is associated with a profile.
- 3. Update all existing profiles to push the new certificate to endpoints. For each profile:
 - a. From the PCoIP Management Console's top menu click **PROFILE**.
 - b. Click the **NEW PROFILE** button.

- c. Enter a name and description for the profile in their respective fields.
- d. Click the + tab beside the **SETTINGS OVERVIEW** tab and then select the appropriate type of profile (e.g. TERA2: CLIENT [DUAL], TERA2 HOST [QUAD]) that applies to your endpoints and click **ADD**.
- e. In the SOFTWARE section, ensure the correct **Firmware Version** is selected for your endpoints.
- f. Click **SECURITY** in the left navigation pane, scroll down to **Certificate Store**, and select **Set in Profile**.
- g. Click **Add New**, browse to your PCoIP Management Console public key certificate, highlight it and click **Open**. (This certificate must have a .pem extension)
- h. Click **Upload**.
- i. Ensure the correct usage type is selected for any specialized certificates such as 802.1x and Syslog.

Certificate Usage type Limitation

Only one specialized usage type can be selected in one profile. Any subsequent certificate selected for the same usage type will cause the previous certificate to change usage type to **No Usage**.

802.1x and Syslog options are disabled when you upload certificates without a private key

- j. Click **SAVE** at the top of the page.
- k. Apply the profile immediately or create a schedule to update your group(s) with the profile.

Tip: Using the Tera2 Endpoint AWI

If a Tera2 endpoint's AWI is enabled, you can directly access it via the Management Console **ENDPOINT DETAILS** page and selecting the **WEB INTERFACE** button. This will allow you to directly manage a single Tera2 endpoint if required.

From the Management Console homepage:

- 1. Select **ENDPOINTS**.
- 2. Find your endpoint in the **GROUPED** or **UNGROUPED** tab and highlight it.
- 3. Select ENDPOINTS > DETAILS.
- 4. Select the **WEB INTERFACE** button.

For more information about using the endpoint AWI after selecting the WEB INTERFACE button see Remote Workstation Card Firmware Administrators' Guide or PCoIP Zero Client Firmware Administrators' Guide.

Configuring the Console Settings

Configuring PCoIP Management Console Session Timeout (Enterprise)

PCoIP Management Console Enterprise allows administrators to set a session timeout for the Web UI of 10, 30, 60, or 120 minutes as well as disabling the session time out by using Never which is not recommended. This setting is located on the security page (**SETTINGS > SECURITY**). Once a period of inactivity reaches the set time, the administrator will be logged out of PCoIP Management Console Enterprise.

Configuring PCoIP Management Console web UI Time Zone

b Important: PCoIP Management Console operates in Coordinated Universal Time (UTC)

The PCoIP Management Console virtual machine operates in Coordinated Universal Time (UTC) and *must not* be changed.

If you are in a different time zone, you can change the PCoIP Management Console's web interface to display your local time to make it more convenient to create schedules and view time-related information. The PCoIP Management Console will perform the conversion and run the schedule using your time.

To configure your local time zone:

- 1. Log in to the PCoIP Management Console web interface.
- 2. Click **SETTINGS** and then **AUTHENTICATION** to display the *MANAGEMENT CONSOLE USERS* window.
- 3. In the USERNAME column, select your user account and then click EDIT.
- 4. In the *Time Zone* field, select your local time zone from the drop-down list.
- 5. Click SAVE.

Default Rocky Linux Configuration for PCoIP Management Console

After installation, the Rocky Linux operating system on which your PCoIP Management Console virtual appliance runs has the following default configuration. For further recommendations on how to improve security for your PCoIP Management Console, see <u>Setting Up Security</u>.

Default PCoIP Management Console Rocky Linux Configuration

Configuration	Description
Installed packages	The following applications have been installed on the Rocky Linux operating system for PCoIP Management Console: • Text editor (from the Rocky Linux repo)
	• man
	• Python 3.9
	 Java Platform: OpenJDK-17 configured with weak ciphers and hashes disabled
	• PostgreSQL-server =15.x
	• PostgreSQL-contrib =15.x
	• openssl
	• epel-release
	Important: Dependencies
	Installed packages may have included other additional dependencies.

Configuration	Description		
PCoIP	Note: Root user is not used for PCoIP Management Console administration		
Management	For security reasons, the root user is not used for PCoIP Management Console		
Console users	administration. This user account has a large, randomly-generated password that is not		
	published. It is critical to change this password immediately after installing your PCoIP		
	Management Console.		
	The following PCoIP Management Console virtual machine users are		
	created by default:		
	• admin: Default administrative user; has sudo privileges; default password is		
	ManagementConsole2015.		
	Note: To secure your PCoIP Management Console, it is critical to change this password immediately after installing the PCoIP Management Console.		
	• mcconsole: No login shell; can use restricted sudo to manage PCoIP Management		
	Console web UI components; has no password.		
	• mcdaemon: No login shell; has no password.		
	• postgres: Has login shell due to PostgreSQL limitations; has no password.		
Security	Security-Enhanced Linux (SELinux) is enabled with a default configuration.		
	The PCoIP Management Console SSH server is disabled by default. You can use vSphere		
	Client to access the PCoIP Management Console's virtual machine console.		
	Note: SSH access for the admin user		
	Although the PCoIP Management Console permits you to re-enable the		
	SSH server (temporarily or permanently), for security reasons it only allows		
	SSH access for the admin user while the SSH server is enabled.		
	Default firewall port settings are as follows:		
	 Port 22: Allow incoming SSH connections on TCP port 22. 		
	• Ports 80, 443, 8080 and 8443: Allow incoming web UI connection on TCP ports 80, 443,		
	8080, and 8443. The firewall redirects port 80 to port 8080 and port 443 to port 8443.		
	The web UI server listens for HTTP connections on port 8080 and HTTPS connections		
	on port 8443.		
	 Port 5172: Allow incoming PCoIP Management Protocol connections on TCP port 5172. 		
	Allow all outgoing traffic.		
Open file limit	The maximum number of open files for all OS processes is 65,535.		
IPv6	IPv6 is disabled.		
NTP By default, Rocky Linux 8.10 uses chrony as an NTP client. NTP traffic to outsi			
	be found by entering the chronyc sources -v command to provide a verbose listing		

Configuration	Description
	of NTP servers chrony is syncing too. Configuration changes can be made by editing the /etc/ chrony.conf file. See <u>Chrony Configuration</u> for further information.
PCoIP Management Console directories and scripts	The following scripts and files are included on the PCoIP Management Console virtual machine: /opt/teradici/scripts • enable_admin.sh: Enables the PCoIP Management Console's web UI admin user. This is useful if you disable the admin Web UI account from PCoIP Management Console Enterprise and subsequently transition to PCoIP Management Console Free without reenabling the account from the web UI. In this situation, you must run this script from the PCoIP Management Console's virtual machine console before the user can log in to the [PCoIP Management Console web UI.
	 reset_admin_password.sh: Reverts the password for the PCoIP Management Console's web interface admin user to its default value (password). This is useful if the password to the admin user web UI account becomes lost and the user needs a way to get logged in again.
	• remove_ldaps_certificate.sh: Removes the uploaded Active Directory Certificate
	 import_ldaps_certificate.sh: Imports and activates the uploaded Active Directory Certificate
	/opt/teradici/log Contains PCoIP Management console log files.

Default configuration of MC OVA

Note: Default configuration of MC OVA

The default storage controller for MC OVA is IDE. Switching to a different controller type may lead to compatibility issues within the MC OVA.

SI No.	MC OVA	Configurations
1	RAM	12288 MB
2	Processors	4
3	Video Memory	16 MB
4	Graphics controller	VBoxVGA
5	Storage	Controller: IDE

SI No.	MC OVA	Configurations
		Type: PIIX4
6	Network	Bridge Adapter
7	Audio	Default

Changing the Default Network Configuration

The PCoIP Management Console virtual machine requires Linux command knowledge or a network configuration tool such as NetworkManager-tui (textual user interface) to assign a static IP address or change the PCoIP Management Console's default network configuration. The following example shows how to make this type of change using NetworkManager-tui. If your host Linux computer does not have this tool, you can install it using the following command sudo dnf install
NetworkManager-tui. Do NOT modify the Hostname configuration with this tool. The Management Console host name should be set correctly in DNS.

Resetting the network interface for changes to take affect immediately

The command line method to restart the network no longer applies IP configuration changes. Using nmtui to activate and deactivate the network interface is the recommended way for your IP configuration changes to take affect immediately. This is user friendly and works seamlessly for AMI, RPM and OVA implementations of Management Console.

Tip: Ensure you have correct DNS A and DNS PTR records set

Before you run the Network Configuration Tool, be sure to set the correct DNS A record and DNS PTR record in your DNS server for the PCoIP Management Console. If the records are already set, ensure you use the same IP address associated with the DNS records.

Note: Give PCoIP Management Console a fixed IP address

We recommend that you give the PCoIP Management Console a fixed "static" IP address, either through a DHCP reservation or by Assigning a Static IP Address using the PCoIP Management Console's network configuration tool. If a PCoIP Management Console is configured using DHCP and the IP address of the PCoIP Management Console changes, the endpoints it manages will be unable to connect to it.

Launching the PCoIP Management Console Network Configuration Tool


To launch the network configuration tool:


- 1. Log in to the PCoIP Management Console virtual machine console. For instructions, see Accessing the PCoIP Management Console Virtual Machine Console.
- 2. Type the following command at the command line to launch the network configuration tool:

sudo nmtui



Network Manager Configuration Tool





Assigning a Static IP Address

To assign a static IP address using the PCoIP Management Console's network configuration tool:

1. Launch the PCoIP Management Console's network configuration tool.

sudo nmtui

- 2. Select Edit a connection.
- 3. Select your correct connection such as **wired connection 1** (for RPM installs it may be referred to as **eth0**) and press the Enter key.


Note: Shown next are example IP addresses

The IP addresses shown next are for example purposes only. Enter your own information.

b Important: Correctly identifying subnets

Addresses and subnets must be correctly defined otherwise the PCoIP Management Console will not operate. Subnets are defined through the slash notation used in the Addresses field. The example of /24 represents 255.255.255.0. Your network may use different subnet sizes.


- 4. To access configurable parameters, tab to and configure your IPv4/IPv6 parameters:
 - IPv4/IPv6 CONFIGURATION: Set to Manual for a static IP configuration. Be sure to enter your correct network details, see screen shot below.
 - Addresses: Enter the IP address you selected for your Management Console, ensuring you use the appropriate slash notation to define your subnet mask.
 - Gateway: Enter your default gateway IP address for the Management Console's network.
 - DNS servers: Enter the IP address of your DNS servers.
 - Search domains: Enter the domains used in your deployment in the format of mydomain.local.
 - Routing: Enter your networks routing requirements.




5. Set manual address:

- Tab to **IPv4 CONFIGURATION** and change Automatic to Disabled if setting a static IPv6 address.
- Tab to IPv6 CONFIGURATION and change Automatic to Ignore if setting a static IPv4 address.
- 6. Tab to { **OK** } and press Enter.
- 7. Tab to { Back } and press Enter to get to the main screen of the network configuration tool.
- 8. Reactivate your network so your changes take affect.
 - a. Tab and highlight **Activate a connection** and press Enter.


 This brings you to the next screen which will allow you to highlight the connection you made your changes to.



a. With the connection you made your changes to highlighted in above steps such as **wired connection 1** or **eth0**, ensure { **Deactivate** } is highlighted and press <code>Enter</code> to deactivate your connection.



a. Ensure { Activate } is highlighted and press Enter to activate your connection.



- 9. Tab to { Back } and press Enter to get to the main screen of the network configuration tool.
- 10. Highlight ${f Quit}$ and tab to ${f OK}$ to exit nmtui.

Configuring an Endpoint Manager Manually from an Endpoint

For environments that do not use automatic DHCP or DNS discovery, you can manually configure each PCoIP Zero Client with the IP address or FQDN of the PCoIP Management Console to which it should connect. The endpoint must also have a trusted PCoIP Management Console certificate in its certificate store in order for discovery to succeed. Typically, this method is used in medium and high security environments. If your endpoint does not have a pre-loaded certificate, you can use the alternative method of manual endpoint discovery initiated by the PCoIP Management Console. See Discovering Endpoints Manually from PCoIP Management Console.

This example shows how to configure a PCoIP Zero Client for discovery by a specific Endpoint Manager from the endpoint's AWI Management page. For information about configuring endpoints for automatic discovery from this page, please see the <u>PCoIP Zero Client Administrators' Guide</u>.

Note: PCoIP Management Console servers as both Endpoint Bootstrap Manager and Endpoint Manager

In the PCoIP Zero Client *Management* page, your PCoIP Management Console serves as both the Endpoint Bootstrap Manager and the Endpoint Manager. Use the PCoIP Management Console's IP address or FQDN when specifying either an Endpoint Bootstrap Manager or an Endpoint Manager URI.

To configure your endpoint with a specific Endpoint Manager:

Note: Complete the following steps in sequence

It is necessary to complete these steps in the sequence shown next.


- 1. Enter the PCoIP Zero Client's IP address in your browser's address bar, then log in to its AWI.
- 2. From the **Configuration** menu, select **Management**.
- 3. Select the desired security level:
 - Low Security Environment PCoIP Zero Client is discoverable by Endpoint Managers: This security level is intended for discovery that is initiated manually by a PCoIP Management

Console. It enables endpoints that are shipped with empty certificate stores to use trust information retrieved during the discovery process.

Note: Low Security Environment also works for endpoints configured for DHCP options or DNS SRV record discovery

You can also use this security level for endpoints that are configured for DHCP options discovery or DNS SRV record discovery when the DHCP or DNS server also provisions the endpoint with the Endpoint Bootstrap Manager certificate's fingerprint.

- Medium Security Environment Endpoint Bootstrap Manager must be trusted by installed certificate: When this security level is selected, the endpoint must have a trusted PCoIP Management Console certificate in its certificate store in order for discovery to succeed. The certificate can be provisioned either by the vendor when an endpoint is shipped or by uploading the PCoIP Management Console certificate to the endpoint. See <u>Uploading the PCoIP Management Console Certificate to an Endpoint</u>.
- High Security Environment Bootstrap phase disabled: With this security level, a user must manually enter an internal (and optionally an external) URI for the PCoIP Management Console from the endpoint's AWI Management page. The user must also upload a PCoIP Management Console certificate to the endpoint's trusted certificate store. Automatic provisioning and discovery methods cannot be used in a high security environment.
- 4. In the Manager Discovery Mode drop-down list, select Manual.
- 5. If the endpoint is not in the Idle state, click **Clear Management State** and then **Continue**.
- 6. Enter the URI for your PCoIP Management Console.



Note: URIs require a secure WebSocket prefix

URIs require a secured WebSocket prefix (for example, wss://< internal EM IP address|FQDN >: [port number]). The PCoIP Management Console's listening port is 5172. Entering this port number is optional. If you do not include it, port 5172 will be used by default.

7. Click **Apply** and then **Continue** once more.

If discovery succeeds, the endpoint's Management page will show the following information:



Note: Automatically name and group endpoints

You can configure the PCoIP Management Console to automatically name endpoints and place them in a specific group when they are discovered. See Auto Naming Endpoints and Auto Configuring Endpoints (Enterprise) for details.

Managing PCoIP Management Console Databases

The PCoIP Management Console maintains a database containing its configuration data, information about the PCoIP endpoints it has discovered, console and daemon log files. You can archive multiple snapshots of these PCoIP Management Console database settings and store them on your PCoIP Management Console virtual machine. You can also download a stored archive to a location external to your PCoIP Management Console virtual machine, for instance, the host PC you use to access the PCoIP Management Console web browser.

Management Console requires at minimum, 1.5 times the size of the database to successfully perform a database restore, backup or upload. This calculation happens automatically and if the requirement is not met, a warning banner is displayed advising the Management Console VM is running out of disk space.

b Database log file size

Database can become very large. If your backup is failing due limited disk space, you can try excluding the log files from the backup.

You can manage PCoIP Management Console database archives by clicking **SETTINGS** from the PCoIP Management Console's top menu, then clicking the **DATABASE** menu in the left pane.

Note: Applying Profiles Created in Versions Earlier than 23.12.2

If a profile is created in version earlier than 23.12.2 for Zero Clients running firmware 23.12.x and with **Enable Audio** disabled, while applying this profile in version 23.12.2, ensure that **Enable Analog Audio Input** is disabled.

Displaying Database Information

The *DATABASE MANAGEMENT* page enables you to back up, upload, download, restore, and delete PCoIP Management Console database archives.

Click the gear icon



to the right of

the table to change the information you want to display in the table columns. Your customized settings are saved in your browser and will be used for any user who subsequently logs in from that browser.




The DATABASE MANAGEMENT page

Backing Up PCoIP Management Console Database

To take a snapshot of your current PCoIP Management Console and store it in a database archive within the PCoIP Management Console virtual machine:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Click **DATABASE** in the left pane.
- 3. Click BACK UP.
- 4. Enter a description, check the EXCLUDE LOGS option if you want to exclude the log files, and click **BACK UP**. Log files can become large and take up additional disk space, so you may wish to check this option if disk space is a concern.



Backup Dialog

The database log files can be found in the Management Console VM /opt/teradici/backups/
<database_folder>/logs folder. For more information on database log files see Managing
Management Console Logs

The archive will appear in the database table when the backup has completed.

Uploading a Database Archive from an External Location

To upload a database archive from an external location:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Click **DATABASE** in the left pane.
- 3. Click UPLOAD.
- 4. Click **Select File**, locate the archive file (.archive) and then click **Open**.
- 5. Click **UPLOAD** to transfer the archive file to the PCoIP Management Console virtual machine. The archive file will appear in the database table when you are finished.

Downloading a Database Archive to an External Location

To download a database archive to an external location:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Click **DATABASE** in the left pane.
- 3. From the database table, select the archive file you wish to transfer to a location external to your PCoIP Management Console virtual machine.
- 4. Click **DOWNLOAD**.
- 5. Save the file to the desired location.

Typically, this is a directory on the host PC that is running the PCoIP Management Console web browser.

Restoring PCoIP Management Console Database



Caution: Take a snapshot of your current virtual machine database before restoring a database archive

Restoring a database archive will permanently delete all current data from the database. Please ensure you have taken a snapshot of your current PCoIP Management Console virtual machine database before proceeding.

To restore a database archive from the PCoIP Management Console virtual machine:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Click **DATABASE** in the left pane.
- 3. From the database table, select the archive file you wish to restore.
- 4. Click **RESTORE**.
- 5. Enable the message prompt and then click **RESTORE**.

Deleting PCoIP Management Console Database

To delete a database archive from the PCoIP Management Console virtual machine:

- 1. From the PCoIP Management Console's top menu, click **SETTINGS**.
- 2. Click **DATABASE** in the left pane.
- 3. From the database table, select the archive file you wish to delete.
- 4. Click **DELETE**.
- 5. Enable the message prompt and then click **DELETE**.

Expanding the PCoIP Management Console Virtual Machine Database and Disk Size

This section provides information on expanding your PCoIP Management Console Virtual Machine database size and the related disk sizing guidelines.

The basic PCoIP Management Console OVA will create a default configuration as follows:

· Virtual Machine Hardware Version: 14

· CPU: 4 vCPU

• Memory: 12 GB

• Provisioned Storage: 62 GB

A Caution: Modifying virtual machine settings should only be considered by qualified individuals

Only qualified individuals should modify any virtual machine settings. Support strongly recommends you perform a database backup of the PCoIP Management Console and download the archive file to a safe location. You should also take a snapshot of the virtual machine prior to modifying any settings.

PCoIP Management Console References

References

PCoIP Management Console 1 Profile Properties Renamed or Not Migrated

The following table lists PCoIP Management Console 1 profile properties that have been renamed PCoIP Management Console Enterprise or Free and are not migrated when you import a PCoIP Management Console 1 profile to a current release of PCoIP Management Console.

Reference to PCoIP Management Console refer to this release or later releases, unless otherwise specified.

Migrating and renaming notes

In the next table, when a PCoIP Management Console 1 property is not migrated, its Migration Notes column will have an explanation. If this column is blank, then the property only has a name change in the new PCoIP Management Console. Some properties that are currently not migrated may be included in future PCoIP Management Console releases.

PCoIP Management Console 1 Profile Information Renamed or Not Migrated

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
Network Configuration	SNMP NMS Address	Network	Trap NMS Address	Not migrated when PCoIP Management Console 1 property Network Configuration > Enable SNMP is not Set in Profile or is set to False
Network Configuration	Enable SNMP Cold Start Trap	Network	SNMP Cold Start Trap	Not migrated when PCoIP Management Console 1 property Network Configuration > Enable SNMP is not Set

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
				in Profile or is set to False.
Network Configuration	Enable SNMP V1 Traps	Network	SNMP V1 Traps	Not migrated when PCoIP Management Console 1 property Network Configuration > Enable SNMP is not Set in Profile or is set to False.
Network Configuration	Enable SNMP V2c Traps	Network	SNMP V2 Traps	Not migrated when PCoIP Management Console 1 property Network Configuration > Enable SNMP is not Set in Profile or is set to False.
Network Configuration	SNMP Community Name	Network	SNMP Community Name	Not migrated when PCoIP Management Console 1 property Network Configuration > Enable SNMP is not Set in Profile or is set to False.
Network Configuration	Static Fallback IP Address	Network	Static Fallback IPv4 Address	Not migrated when PCoIP Management Console 1 property Network Configuration> Enable SNMP is not Set in Profile or is set to False.
Network Configuration	Static Fallback Subnet Mask	Network	Static Fallback IPv4 Subnet Mask	Not migrated when PCoIP Management Console 1 property Network Configuration > Enable SNMP is not Set in Profile or is set to False.
Network Configuration	Static Fallback Gateway Address	Network	Static Fallback IPv4 Gateway	Not migrated when PCoIP Management Console 1 property Network Configuration >

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
				Enable SNMP is not Set in Profile or is set to False.
Network Configuration	Static Fallback Timeout	Network	Static Fallback IPv4 Timeout	Not migrated when PCoIP Management Console 1 property Network Configuration > Enable SNMP is not Set in Profile or is set to False.
Discovery Configuration	PCoIP Management Console DNS- Based Discovery Prefix			Never migrated. Not used in firmware 5.0.0 and later.
Session Configuration	PCoIP Connection Manager Server Address	Session > Session Type	Server URI	Not migrated when PCoIP Management Console 1 property Session Configuration > Session Connection Type is not Set in Profile or is not set to one of the following: PCoIP Connection Manager PCoIP Connection Manager + Auto- Logon
Session Configuration	Auto Detect Server URI	Session > Session Type	Server URI	Not migrated when PCoIP Management Console 1 property Session Configuration > Session Connection Type is not Set in Profile or is not set to Auto Detect.
Session Configuration	Auto-Logon Username	Session > Session Type	Logon Username	Not migrated when PCoIP Management Console 1 property Session Configuration >

Release 1	Release 1	Current Release	Current Release	Migration Notes
Category	Property Name	Category	Property Name	
				Session Connection Type is not Set in Profile or is not set to one of the following: View Connection Server + Auto- Logon PCoIP Connection Manager + Auto- Logon
Session	Auto-Logon	Session >	Logon	Not migrated when PCoIP Management Console 1 property Session Configuration > Session Connection Type is not Set in Profile or is not set to one of the following: • View Connection Server + Auto- Logon • PCoIP Connection Manager + Auto- Logon
Configuration	Password	Session Type	Password	
Session	Auto-Logon	Session >	Logon Domain	Not migrated when PCoIP Management Console 1 property Session Configuration > Session Connection Type is not Set in Profile or is not set to one of the following: • View Connection Server + Auto- Logon • PCoIP Connection Manager + Auto- Logon
Configuration	Domain	Session Type	Name	

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
Session Configuration	Enable View Connection Server SSL			Never migrated. Not used in firmware 4.x and later.
Session Configuration	Kiosk Mode Custom Username	Session > Session Type	Username	Not migrated when PCoIP Management Console 1 property Session Configuration > Session Connection Type is not Set in Profile or is not set to View Connection Server + Kiosk.
Session Configuration	Kiosk Mode Password	Session > Session Type	Password	Not migrated when PCoIP Management Console 1 property Session Configuration > Session Connection Type is not Set in Profile or is not set to View Connection Server + Kiosk.
Session Configuration	Organization ID			Never migrated. Currently not included in PCoIP Management Console.
Session Configuration	OneSign Direct to View Address			Never migrated. Currently not included in PCoIP Management Console.
Session Configuration	Disconnect Dialog Display Mode	Session > Session Type	Disconnect Message Filter	
Session Configuration	Enable Login Username Caching	Session > Session Type	Remember Username	
Session Configuration	Prefer GSC-IS Over PIV Endpoint	Session > Session Type	Prefer GSC-IS	

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
Session Configuration	Proximity Reader Beep Mode	Session > Session Type	Pre-Session Reader Beep	
Encryption Configuration	Enable Salsa20-256- Round12 Encryption			Never migrated. Applies to Tera1 endpoints only.
Encryption Configuration	Enable AES-128-GCM Encryption			Never migrated. Not configurable in FW 5.0.0 and later.
Encryption Configuration	Enable AES-256-GCM Encryption			Never migrated. Not configurable in FW 5.0.0 and later.
Encryption Configuration	Session Negotiation Security Level	Session > Session Type	Session Negotiation Cipher	
OSD Configuration	Hidden Menu Entries	Security	Hidden OSD Menu Entries	
Image Configuration	Low Bandwidth Text Codec Mode			Never migrated. Currently not included in PCoIP Management Console.
Image Configuration	Enable Client Image Settings			Never migrated. Remote Workstation Card property.
Display Configuration	Enable Monitor Emulation on Video Port 1-4			Never migrated. Remote Workstation Card property.
Display Configuration	Enable Host Hot-Plug Delay			Never migrated. Remote Workstation Card property.
Display Configuration	Enable Display Cloning	Session > Display Configuration	Clone Primary Display	
Display Configuration	Enable Accelerated			Never migrated. Remote Workstation Card property.

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
	Monitor Emulation			
Time Configuration	Enable DST	Other > Time	Daylight Saving Time	
Time Configuration	Time Zone Offset	Other > Time	Time Zone	Converted to IANA zoneinfo time zone. See Time Zone Definitions for PCoIP Management Console 1 or 2
Security Configuration	Password	Security	Local Administrative Password	
Security Configuration	Enable Password Protection	Security	Enable Password Protection for OSD and AWI	
Security Configuration	Enable 802.1X Support for Legacy Switches	Security	802.1X Legacy Support	
Audio Permissions	Enable Vista/ Windows 7 64- bit Mode			Never migrated. Remote Workstation Card property
Audio Permissions	Enable Audio Line In			Never migrated. Remote Workstation Card property
Audio Permissions	Dual Audio Output Mode		Dual Audio Output	Migrated in PCoIP Management Console 19.11.
Audio Permissions	Audio In Device Type	Session > Audio Input	Audio Device Type	
Audio Permissions	Audio In Preferred USB Vendor ID	Session > Audio Input	Preferred USB Vendor ID	
Audio Permissions	Audio In Preferred USB	Session >Audio Input	Preferred USB Device Product ID	

Release 1 Category	Release 1 Property Name Device Product	Current Release Category	Current Release Property Name	Migration Notes
Audio	ID Audio Out	Session > Audio	Audio Device	
Permissions	Device Type	Output	Туре	
Audio Permissions	Audio Out Preferred USB Vendor ID	Session > Audio Output	Preferred USB Vendor ID	
Audio Permissions	Audio Out Preferred USB Device Product ID	Session / Audio Output	Preferred USB Device Product ID	
Power Permissions	Client Power Button Function	Power	Remote Host Power Control	
Power Permissions	Wake-on-USB Mode	Power	Wake-on-USB	
Power Permissions	Wake-on-LAN Mode	Power	Wake-on-LAN	
Power Permissions	Power On After Power Loss ModeA	Power	Power On After Power Loss	
Power Permissions	Client Power Down Timeout Seconds	power	Auto Power-Off Timeout	
Power Permissions	Display Suspend Timeout Seconds	Power	Display Suspend Timeout	
Host Driver Configuration	Enable Host Driver			Never migrated. Remote Workstation Card property.
Event Log Control	Enable Diagnostic Log			Never migrated. Not used in firmware 5.0.0 and later.
Event Log Control	Event Log Filter Mode			Never migrated. Not used in firmware 5.0.0 and later.

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
Event Log Control	Syslog Facility Number	Logging	Syslog Facility	
Event Log Control	Enhanced Logging Mode Mask	Logging	Enhanced Logging Mode	Not migrated when PCoIP Management Console 1 is configured to Enhanced logging disabled.
Peripheral Configuration	Enable USB EHCI	Peripheral	EHCI	
Peripheral Configuration	Force Local Cursor Visible	Peripheral	Force Local Cursor Visibility	Migrated in MC 3.2
		Peripheral	Devices Forced to USB 1.1	Migrated in MC 3.2. This feature is available in firmware 5.0+
IPv6 Configuration	IPv6 Domain Name	Network	IPv6 Domain Name	Not migrated when PCoIP Management Console 1 property IPv6 Configuration > Enable IPv6 is not Set in Profile or is set to False
IPv6 Configuration	Enable DHCPv6	Network	DHCPv6	Not migrated when PCoIP Management Console 1 property IPv6 Configuration > Enable IPv6 is not Set in Profile or is set to False
IPv6 Configuration	Enable SLAAC	Network	SLAAC	Not migrated when PCoIP Management Console 1 property IPv6 Configuration > Enable IPv6 is not Set in Profile or is set to False
IPv6 Configuration	IPv6 Gateway Address	IPv6 Gateway Address Prefix Length	Network	IPv6 Gateway
IPv6 Configuration	IPv6 Primary DNS Address	IPv6 Primary DNS Address Prefix Length	Network	Primary IPv6 DNS

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
IPv6 Configuration	IPv6 Secondary DNS Address	IPv6 Secondary DNS Address Prefix Length	Network	Secondary IPv6 DNS
SCEP Configuration	SCEP Server URI			Never migrated. Currently not included in PCoIP Management Console
SCEP Configuration	Challenge Password			Never migrated. Currently not included in PCoIP Management Console
SCEP Configuration	Use Certificate for 802.1X			Never migrated. Currently not included in PCoIP Management Console
Display Configuration	Preferred Override Resolution on Port 1-4	Session > Display Configuration: Video Port 1-4	Preferred Resolution	Not migrated when PCoIP Management Console 1 property Preferred Resolution is set to Native
Display Topology Configuration (Dual and Quad)	Display Layout Alignment	Session > Display Configuration: Dual/Quad Display Topology	Display Layout Alignment	Not migrated when PCoIP Management Console 1 property Display Topology Configuration > Enable Configuration is not Set in Profile or is set to False
Display Topology Configuration (Dual and Quad)	Primary Port	Session > Display Configuration: Dual/Quad Display Topology	Primary Port	Not migrated when PCoIP Management Console 1 property Display Topology Configuration > Enable Configuration is not Set in Profile or is set to False
Display Topology Configuration	Position	Session > Display Configuration:	Position	Not migrated when PCoIP Management Console 1 property Display Topology

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
(Dual and Quad)		Dual/Quad Display Topology		Configuration > Enable Configuration is not Set in Profile or is set to False
Display Topology Configuration (Dual and Quad)	Rotation	Session > Display Configuration: Dual/Quad Display Topology	Rotation	Not migrated when PCoIP Management Console 1 property Display Topology Configuration > Enable Configuration is not Set in Profile or is set to False
Display Topology Configuration (Dual and Quad)	Resolution	Session > Display Configuration: Dual/Quad Display Topology	Resolution	Not migrated when PCoIP Management Console 1 property Display Topology Configuration > Enable Configuration is not Set in Profile or is set to False
Profile OSD Logo		Other > OSD	OSD Logo	Never migrated
Profile Firmware		Software		Firmware Version
Image Configuration	Low Bandwidth Text Codec Mode	Image	Enable Low Bandwidth Text Codec	Migrated value applicable only for DUAL Client device
Image Configuration	Enable Client Image Settings	Image	Use Client Image Settings	Migrated value applies to Host (DUAL and QUAD) device only
Display Configuration	Enable Monitor Emulation on Video Port 1-4	Session	Monitor Emulation: Video Port 1 Monitor Emulation: Video Port 2 Monitor Emulation: Video Port 3 Monitor	Migrated values apply to Host device only. Values of port 3 and 4 are ignored for DUAL type

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name Emulation: Video Port 4	Migration Notes
Display Configuration	Enable Host Hot-Plug Delay	Session Host Hot-Plug Delay	Migrated value applies to Host (DUAL and QUAD) device only	
Display Configuration	Enable Display Cloning	Session > Monitor Emulation	Clone Primary Display	Applies to Client DUAL devices only
Display Configuration	Enable Accelerated Monitor Emulation	Session > Monitor Emulation	Accelerated Monitor Emulation	Migrated value applies to Host (DUAL and QUAD) device only
Audio Permissions	Enable Vista/ Windows 7 64- bit Mode			Never migrated. Applied to Tera1 devices
Audio Permissions	Enable Audio Line In	Session > Audio		Audio Line In
Audio Permissions	Audio In Device Type	Session > Audio Input	Audio Device Type	Migrated value applies to Client (DUAL and QUAD) device only
Audio Permissions	Audio In Preferred USB Vendor ID	Session > Audio Input	Preferred USB Vendor ID	Migrated value applies to Client (DUAL and QUAD) device only
Audio Permissions	Audio In Preferred USB Device Product ID	Session > Audio Input	Preferred USB Device Product ID	Migrated value applies to Client (DUAL and QUAD) device only
Audio Permissions	Audio Out Device Type	Session > Audio Output	Audio Device Type	Migrated value applies to Client (DUAL and QUAD) device only
Audio Permissions	Audio Out Preferred USB Vendor ID	Session > Audio Output	Preferred USB Vendor ID	Migrated value applies to Client (DUAL and QUAD) device only
Audio Permissions	Audio Out Preferred USB	Session > Audio Output		

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
	Device Product ID		Preferred USB Device Product ID	Migrated value applies to Client (DUAL and QUAD) device only
Power Permissions	Client Power Button Function	Power	Remote Host Power Control	Migrated value applies to Client (DUAL and QUAD) device only Only the following values from MC1 are migrated, e rest are no longer supported in MC 3 The user can only invoke a hard power off The user cannot invoke any power
Power Permissions	Wake-on-LAN Mode	Power	Wake-on-LAN	Migrated value applies to Host (DUAL and QUAD) device only
Power Permissions	Power On After Power Loss Mode	Power	Power On After Power Loss	Migrated value applies to Client (DUAL and QUAD) device only
Power Permissions	Client Power Down Timeout Seconds	Power	Auto Power-Off Timeout	Migrated value applies to Client (DUAL and QUAD) device only
Power Permissions	Display Suspend Timeout Seconds	Power	Display Suspend Timeout	Migrated value applies to Client (DUAL and QUAD) device only
Host Driver Configuration	Enable Host Driver	Host Driver	Host Driver	Migrated value applies to Host (DUAL and QUAD) device only
Peripheral Configuration	Enable USB EHCI	Peripheral	EHCI	Migrated value applies to Client (DUAL and QUAD) device only

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
SCEP Configuration	SCEP Server URI			Never Migrated. Included under ENDPOINT CERTIFICATES IN mc 3.1
SCEP Configuration	Challenge Password			Never Migrated. Included under ENDPOINT CERTIFICATES IN mc 3.1
SCEP Configuration	Use Certificate for 802.1X			Never Migrated. Included under ENDPOINT CERTIFICATES IN mc 3.1
Display Topology Configuration (Dual and Quad)	Primary Port	"Session > Monitor emulation: Quad Display Session > Monitor Emulation Dual Display"	Position	"Not migrated when PCoIP Management Console 1 property Display Topology Configuration > Enable Configuration is not Set in Profile or is set to False. Migrated value applies to Client (DUAL and QUAD) device only
Display Topology Configuration (Dual and Quad)	Rotation	"Session > Monitor emulation: Quad Display Session > Monitor Emulation Dual Display"	Rotation	"Not migrated when PCoIP Management Console 1 property "Display Topology Configuration > Enable Configuration is not Set in Profile or is set to False. Migrated value applies to Client device only. Values for Port 3 and 4 ignored for DUAL display"
Display Topology Configuration (Dual and Quad)	Resolution	"Session > Monitor emulation: Quad Display Session > Monitor Emulation Dual Display"	Resolution	"Not migrated when PCoIP Management Console 1 property Display Topology Configuration > Enable Configuration is not Set in Profile or is set to False. Migrated value applies to

Release 1 Category	Release 1 Property Name	Current Release Category	Current Release Property Name	Migration Notes
				Client device only. Values for Port 3 and 4 ignored for DUAL display
Profile Firmware	Software			Never migrated. All migrated profiles are assigned to appropriate PCoIP Zero Client or Hard Host firmware

In addition to the previous table, the following table lists properties that are also not migrated when you import a PCoIP Management Console 1 profile, because they are not managed by the PCoIP Management Console newer releases.

PCoIP Zero Client Properties not Managed by the PCoIP Management Console

Firmware Property	Firmware Version	Description
Prefer IPv6 FQDN Resolution	4.8.0	Not managed by PCoIP Management Console 1.x or later releases of PCoIP Management Console
IPv6 Address Resolution	4.8.0	Not managed by PCoIP Management Console 1.x or later releases of PCoIP Management Console
OSD Region Tab Lockout	5.0.0	Never managed by PCoIP Management Console 1.x

Time Zone Definitions for PCoIP Management Console 1 or later releases

Reference to PCoIP Management Console refer to releases 2.0 or later, unless otherwise specified.

The PCoIP Management Console web interface uses Internet Assigned Numbers Authority (IANA) time zone definitions to let users configure the PCoIP Management Console web interface in their local time. The following table shows how the profile import script converts the PCoIP Management Console 1 time zones to PCoIP Management Console IANA time zones.

Note: Time zone selection/setting in PCoIP Management Console display offset as standard time

Time zone selection on Profile > Edit > OTHER and Settings > USERS > Edit pages show offsets with respect to 'Standard Time' only (not the 'Daylight Savings Time').

PCOIP MANAGEMENT CONSOLE 1 AND PCOIP MANAGEMENT CONSOLE TIME ZONE DEFINITIONS

PCoIP Management Console 1 Time Zone Definition	PCoIP Management Console Time Zone Definition
gmt_minus_1200_international_date_line_west	Asia/Anadyr
gmt_minus_1100_midway_island	Pacific/Midway
gmt_minus_1000_hawaii	Pacific/Honolulu
gmt_minus_0900_alaska	America/Anchorage
gmt_minus_0800_pacific_time	America/Vancouver
gmt_minus_0800_tijuana	America/Tijuana
gmt_minus_0700_arizona	America/Phoenix
gmt_minus_0700_chihuahua_new	America/Chihuahua
gmt_minus_0700_chihuahua_old	America/Chihuahua
gmt_minus_0700_mountain_time	America/Denver
gmt_minus_0600_central_america	America/Costa_Rica
gmt_minus_0600_central_time	America/Chicago

PCoIP Management Console 1 Time Zone Definition	PCoIP Management Console Time Zone Definition
gmt_minus_0600_guadalajara_new	America/Mexico_City
gmt_minus_0600_guadalajara_old	America/Mexico_City
gmt_minus_0600_saskatchewan	America/Regina
gmt_minus_0500_bogota	America/Bogota
gmt_minus_0500_eastern_time	America/New_York
gmt_minus_0500_indiana	America/Indiana/Indianapolis
gmt_minus_0430_caracas	America/Caracas
gmt_minus_0400_atlantic_time	Atlantic/Bermuda
gmt_minus_0400_la_paz	America/La_Paz
gmt_minus_0400_manaus	America/Manaus
gmt_minus_0400_santiago	America/Santiago
gmt_minus_0330_newfoundland	America/St_Johns
gmt_minus_0300_brasilia	America/Sao_Paulo
gmt_minus_0300_buenos_aires	America/Argentina/Buenos_Aires
gmt_minus_0300_greenland	America/Godthab
gmt_minus_0300_montevideo	America/Montevideo
gmt_minus_0200_mid_atlantic	Atlantic/South_Georgia
gmt_minus_0100_azores	Atlantic/Azores
gmt_minus_0100_cape_verde_is	Atlantic/Cape_Verde
gmt_plus_0000_casablanca	Africa/Casablanca
gmt_plus_0000_greenwich_mean_time	Europe/London
gmt_plus_0100_amsterdam	Europe/Amsterdam
gmt_plus_0100_belgrade	Europe/Belgrade
gmt_plus_0100_brussels	Europe/Brussels
gmt_plus_0100_sarajevo	Europe/Sarajevo
gmt_plus_0100_west_central_africa	Africa/Lagos
gmt_plus_0100_windhoek	Africa/Windhoek
gmt_plus_0200_amman	Asia/Amman

PCoIP Management Console 1 Time Zone Definition	PCoIP Management Console Time Zone Definition
gmt_plus_0200_athens	Europe/Athens
gmt_plus_0200_beirut	Asia/Beirut
gmt_plus_0200_cairo	Africa/Cairo
gmt_plus_0200_harare	Africa/Harare
gmt_plus_0200_helsinki	Europe/Helsinki
gmt_plus_0200_jerusalem	Asia/Jerusalem
gmt_plus_0200_minsk	Europe/Minsk
gmt_plus_0300_baghdad	Asia/Baghdad
gmt_plus_0300_kuwait	Asia/Kuwait
gmt_plus_0300_moscow	Europe/Moscow
gmt_plus_0300_nairobi	Africa/Nairobi
gmt_plus_0330_tehran	Asia/Tehran
gmt_plus_0400_abu_dhabi	Asia/Dubai
gmt_plus_0400_baku	Asia/Baku
gmt_plus_0400_caucasus_standard_time	Asia/Yerevan
gmt_plus_0400_yerevan	Asia/Yerevan
gmt_plus_0430_kabul	Asia/Kabul
gmt_plus_0500_ekaterinburg	Asia/Yekaterinburg
gmt_plus_0500_islamabad	Asia/Karachi
gmt_plus_0530_chennai	Asia/Kolkata
gmt_plus_0530_sri_jayawardenepura	Asia/Colombo
gmt_plus_0545_kathmandu	Asia/Kathmandu
gmt_plus_0600_almaty	Asia/Almaty
gmt_plus_0600_astana	Asia/Almaty
gmt_plus_0630_yangon	Asia/Rangoon
gmt_plus_0700_bangkok	Asia/Bangkok
gmt_plus_0700_krasnoyarsk	Asia/Krasnoyarsk
gmt_plus_0800_beijing	Asia/Hong_Kong

PCoIP Management Console 1 Time Zone Definition	PCoIP Management Console Time Zone Definition
gmt_plus_0800_irkutsk	Asia/Chita
gmt_plus_0800_kuala_lumpur	Asia/Kuala_Lumpur
gmt_plus_0800_perth	Australia/Perth
gmt_plus_0800_taipei	Asia/Taipei
gmt_plus_0900_osaka	Asia/Tokyo
gmt_plus_0900_seoul	Asia/Seoul
gmt_plus_0900_yakutsk	Asia/Yakutsk
gmt_plus_0930_adelaide	Australia/Adelaide
gmt_plus_0930_darwin	Australia/Darwin
gmt_plus_1000_brisbane	Australia/Brisbane
gmt_plus_1000_canberra	Australia/Sydney
gmt_plus_1000_guam	Pacific/Guam
gmt_plus_1000_hobart	Australia/Hobart
gmt_plus_1000_vladivostok	Asia/Vladivostok
gmt_plus_1100_magadan	Asia/Magadan
gmt_plus_1200_auckland	Pacific/Auckland
gmt_plus_1200_fiji	Pacific/Fiji
gmt_plus_1300_nukualofa	Pacific/Tongatapu

Expanding the PCoIP Management Console Disk Size

The following steps are required to expand the vdisk of the PCoIP Management Console.



Caution: Modifying virtual machine settings should only be done by qualified individuals

Modifying any virtual machine settings should only be done by qualified individuals. HP strongly recommends you do a database backup of the PCoIP Management Console and download the archive file to a safe location. You should also take a snapshot of the virtual machine prior to modifying any settings.

To expand your PCoIP Management Console disk size:

1. Check the current disk size from the command prompt:

```
df --total
```

This will display the space used by each volume in /dev/mapper/vg_main-lv_root.

- 2. Ensure you have allocated enough disk space.
- 3. From vSphere, select the virtual machine to be modified and power it down.
- 4. Determine the increased disk size.
- 5. Edit the virtual machine settings to increase the vDisk and the vRAM. To do this, run sudo fdisk /dev/sda and follow these steps in order:
 - a. You may get a Warning about DOS-compatible mode being deprecated. Type C to switch off DOS-compatible mode. Type **U** to change display units to sectors.
 - b. Press place to print the partition table to identify the number of partitions. By default, there are 2: sda1 and sda2.
 - c. Press N to create a new primary partition.
 - d. Press P for primary.
 - e. Press [3] for the partition number, depending on the output of the partition table print.
 - f. Press Enter two times.

- g. Press T to change the system's partition ID.
- h. Press (3) to select the newly creation partition.
- i. Type **8e** to change the Hex Code of the partition for Linux LVM.
- j. Press w to write the changes to the partition table.
- 6. Run sudo init 6 to restart the virtual machine.
- 7. When the virtual machine restarts, run the following commands in order:
 - a. sudo pvcreate /dev/sda3 (This should create the physical volume /dev/sda3).
 - b. sudo vgextend vg_main /dev/sda3 (This will extend the Volume Group VG_Main).
 - c. sudo vgdisplay (This will display information about the Volume Group. Make note of the Free PE / Size. The first number is the number of free extents and will be used in the following command).
 - d. sudo lvextend -1 511 /dev/mapper/vg_main-lv_root (You will get a message telling you the volume has been extended from 8.31GB to 15.97GB / 511 extents).
 - e. sudo resize2fs /dev/mapper/vg main-lv root (This will resize the partition).
 - f. sudo init 6 (this will restart the virtual machine).
- 8. Power the virtual machine back on.

Note: Extending logical volume in Linux

For information on how to extend logical volume in a virtual machine running RedHat, see https://kb.vmware.com/selfservice/microsites/search.do?
language=en_US&cmd=displayKC&externalId=1006371.

Using your Virtual Machine Console to Administer Licenses when Connected to the Internet

1 Info: Virtual machine console

The use of the vm console is required for license management on PCoIP Management Console releases 2.0 to 3.0. From MC 3.1 onwards, a UI is present for managing licenses when connected to the internet.

Activating Licenses

Using your virtual machine console to activate your PCoIP Management Console Enterprise license:

- Connect to your PCoIP Management Console virtual machine console and log in using the admin account and password. See <u>Logging in to the PCoIP Management Console OVA Virtual Machine</u> <u>Console</u>.
- 2. Run the following command:

/opt/teradici/licensing/mc activate lic.sh -k <entitlementID>

where entitlementID is the activation key you received via email. Example:

/opt/teradici/licensing/mc activate lic.sh -k 1234-5678-90AB-CDEF

Using your virtual machine console to activate your PCoIP Management Console Enterprise license from behind a proxy server:

PCoIP Management Console Viewing Installed Licenses

Info: Proxy parameter

Activating PCoIP Management Console Enterprise license when the PCoIP Management Console is located behind a proxy server requires appending the -p parameter that defines the proxy parameters.

- 1. Connect to your PCoIP Management Console virtual machine console and log in using the admin account and password.
- 2. Run the following command:

```
/opt/teradici/licensing/mc_activate_lic.sh -k <entitlementID> -p
[<user:password>@] proxyhost:port>
```

where:

<entitlementID. is the activation key you received via email.</pre>

[<user:password>] is optional. If >user is provided, password must also be provided.

proxyhost:port> is the IP address and port number of your proxy server.

Examples:

• If the proxy requires a user name and password:

```
/opt/teradici/licensing/mc_activate_lic.sh -k 1234-5678-90AB-CDEF -p
bob:bobpasswd@192.168.45.23:3128
```

If the proxy does not require a user name and password:

```
/opt/teradici/licensing/mc_activate_lic.sh -k 1234-5678-90AB-CDEF -p
192.168.45.23:3128
```

Viewing Installed Licenses

Once your license is activated, its information is stored on the PCoIP Management Console virtual machine.

You can view the installed licenses via the command prompt on the vm console.

View installed licenses via the command prompt:

- Connect to your PCoIP Management Console virtual machine console and log in using the admin account and password. See <u>Logging in to the PCoIP Management Console OVA Virtual Machine</u> Console.
- 2. Run the following command:

```
/opt/teradici/licensing/mc view lic.sh
```

The script will output the following information:

- Fulfillment ID: XXXXXXXX: An ID assigned to a license after it is activated. This ID is required if you deactivate the license. The fulfillment ID will be different each time you reactivate a license after it has been deactivated.
- Entitlement ID: XXXX-XXXX-XXXX: The license key you received via email that you use to activate your license.
- Expiration date: DD-MMM-YYYY: The day, month, and year your license expires.

Deactivating Licenses

It is important to deactivate a license when you no longer need it, for example, when you decommission a virtual machine. This frees up the license and makes it available for a different PCoIP Management Console Enterprise deployment.

Note: Deactivating license reverts PCoIP Management Console to PCoIP Management Console Free

PCoIP Management Console will run in Free mode when all its licenses are deactivated.

!!! warning "Warning: Internet Access Required" When deactivating a license, an internet connection to the licensing server is required unless the offline license activation steps are used.

Deactivating Your PCoIP Management Console License

Using your virtual machine console to deactivate PCoIP Management Console Enterprise license:

- 1. Connect to your PCoIP Management Console console and log in using the **admin** account and password.
- 2. Run the following command:

```
/opt/teradici/licensing/mc return lic.sh -f <fulfillment ID>
```

where <fulfillment ID> is the ID assigned to the license after it was activated.

Example:

/opt/teradici/licensing/mc return lic.sh -f 12345678

Note: Finding fulfillment ID

To find your fulfillment ID, see Viewing Installed Licenses.

To deactivate your PCoIP Management Console Enterprise license when the PCoIP Management Console is located behind a proxy server:

- 1. Connect to your PCoIP Management Console Enterprise virtual machine console and log in using the admin account and password. See <u>Logging in to the PCoIP Management Console OVA Virtual Machine Console</u>.
- 2. Run the following command:

```
/opt/teradici/licensing/mc_return_lic.sh -f <fulfillmentId> -p
[<user:password>@] proxyhost:port>
```

where:

<fulfillmentID> is the ID assigned to the license after it was activated.

[<user:password>] is optional. If user is provided, password must also be provided.

Example:

If the proxy requires a user name and password:

```
/opt/teradici/licensing/mc_return_lic.sh -f 12345678 -p
bob:bobpasswd@192.168.45.23:3128
```

• If the proxy does not require a user name and password:

/opt/teradici/licensing/mc_return_lic.sh -f 12345678 -p 192.168.45.23:3128

PCoIP Management Console HTTP Strict Transport Security

HTTP Strict Transport Security

HTTP Strict Transport Security (HSTS) is a policy that helps protect web server appliances against unwanted access. It allows only trusted connections with browsers using HTTPS. When HSTS is enabled, it informs a web browser that has previously visited a site to only use HTTPS connections. Web browsers that have never connected to the site may use HTTP for the initial connection. HSTS is an IETF standards track protocol and specified in RFC 6797.

Warning: Not all browsers will react the same way. Ensure you thoroughly test using all browsers you intend to use

Some web browsers may terminate the connection to the web server and prevent access to the PCoIP Management Console if the security of the connection cannot be verified. Therefor it is important to have a properly created and trusted certificate installed into the Management Console and the ability for the web browser to be able to verify the authenticity of that certificate.

HSTS can be enabled on the PCoIP Management Console by editing the mc-external-config.yml file. It also requires a proper certificate be loaded on the PCoIP Management Console. For more information on configuring HSTS and how it works please review RFC 6797.

The certificate requirements are determined by the browser you are using. See browser documentation for requirements. Requirements include the following and can change at anytime:

- SHA 256 is the minimum signature algorithm
- CA signed (can not be a self-signed certificate)
- Subject Alternative Name (Chrome requirement)

To enable HSTS and configure the timeout setting:

- 1. Accessing the PCoIP Management Console Virtual Machine Console
- 2. SSH to the PCoIP Management Console virtual machine console.
- 3. Log in as administrator and enter the command sudo su.
- 4. Change to the following directory: /opt/teradici/console/config/

PCoIP Management Console HTTP Strict Transport Security

- 5. Edit the mc-external-config.yml file to activate HSTS and set the time out by:
 - a. Uncommenting (remove # symbol) from the **jetty, port, hsts, enabledHSTS and stsMaxAge** from the following lines:

```
#jetty:
# port: 8080
# sendServerVersion: false
# hsts:
# enableHSTS: false
# stsMaxAge: 31536000
# traceEnabled: false
# optionsEnabled: false
```

b. Editing the **enableHSTS** value to true.

```
enableHSTS: true
```

c. Editing the **stsMaxAge** value to the desired time out in seconds.

```
stsMaxAge: 31536000
```

stsMaxAge

is configurable from the default of -1 to one year (31536000 seconds) and defines how long the web browser should cache the HSTS policy against the server.

Your edited lines should look like the following:

```
jetty:
    port: 8080
# sendServerVersion: false
    hsts:
        enableHSTS: true
        stsMaxAge: 31536000
# traceEnabled: false
# optionsEnabled: false
```

- 6. Save your edits to mc-external-config.yml.
- 7. Restart the Management Console console service.

```
sudo service mcconsole restart
```

PCoIP Management Console HTTP Strict Transport Security

• Tip: Is HSTS enabled?

To confirm if HSTS is enabled, run

curl -k -s -vv https://<PCoIP Management Console ip address>/login/auth | grep Strict

and look at any HTTP response from the server. If enabled, the header will display the max age.

Configure Crypto Policy to Disable CBC and sha1 hash

1. Run the following command to check the **crypto policy** which is currently in use in the Rocky Linux 8/RHEL 8 VM. If it's set to **DEFAULT** (By default, it's set to **DEFAULT**) or any **other policy**, copy it to the following location: /etc/crypto-policies/policies/modules/. Then follow the below steps to remove the **CBC ciphers**:

```
update-crypto-policies --show

sudo cp /usr/share/crypto-policies/policies/DEFAULT.pol /etc/crypto-
policies/policies/modules/DISABLE-CBC.pmod

sudo sed --in-place 's/CAMELLIA-256-CBC//' /etc/crypto-policies/policies/
modules/DISABLE-CBC.pmod

sudo sed --in-place 's/AES-256-CBC//' /etc/crypto-policies/policies/
modules/DISABLE-CBC.pmod

sudo sed --in-place 's/CAMELLIA-128-CBC//' /etc/crypto-policies/policies/
modules/DISABLE-CBC.pmod

sudo sed --in-place 's/AES-128-CBC//' /etc/crypto-policies/policies/
modules/DISABLE-CBC.pmod
```

- 2. To **disable sha1**, follow the below steps:
 - a. Run the below command:

```
sudo cp /usr/share/crypto-policies/policies/modules/NO-SHA1.pmod /etc/
crypto-policies/policies/modules/NO-SHA1.pmod
```

b. Set the DISABLE-CBC and NO-SHA1 policies and run the following command to restart the VM.

```
sudo update-crypto-policies --set DEFAULT:DISABLE-CBC:NO-SHA1
sudo init 6
```

c. After the VM is restarted, run the following command to check the updated cryptographic policies. sudo update-crypto-policies --show

Chrony NTP Configuration

By default, the Management Console RPM based on Rocky Linux uses chrony as the NTP client in which there are default references to public NTP servers. To configure chrony to not communicate with external time servers and adhere to your companies security policy, consider the following actions:

- 1. Refer to your Security policy to ensure your NTP configuration complies to set standards. Considerations should include:
 - Confirming if your companies DNS server provides an NTP sever or server pool.
 - · Remove public server pools from chrony.conf
 - · Add your own public server pool to chrony.conf
 - Disabling chrony
- 2. Review the current Management Console chrony configuration by entering the chronyc sources -v command from the Management Console/s console/ to provide a verbose listing of NTP servers chrony is syncing too.
- Consider using internal NTP servers authorized by your companies security policy by editing the / etc/chrony.conf file.

Example

We have provided the following example of viewing and editing an NTP configuration. In this example the default ntp servers are commented out and replaced by another NTP server.

1. Check the currently used NTP servers using chronyc sources -v.

```
[admin@localhost ~]$ chronyc sources -v
.-- Source mode '^' = server, '=' = peer, '#' = local clock.
/ .- Source state '*' = current best, '+' = combined, '-' = not combined,
            'x' = may be in error, '\sim' = too variable, '?' = unusable.
.- xxxx [ yyyy ] +/-
ZZZZ
     Reachability register (octal) -.
                                        | xxxx = adjusted
offset,
|| Log2(Polling interval) --. | yyyy = measured
offset,
                          \ | zzzz = estimated
error.
MS Name/IP address Stratum Poll Reach LastRx Last sample
______
^+ 66-49-211-122.cpe.distri> 3 9 377 107 +1481us[+1481us] +/-
95ms
^+ stirling.fsck.ca
                         2 10 377
                                      397 +1083us[+1083us] +/-
^+ 131.153.171.22
                       2 10 377
                                      323 -1233us[-1233us] +/-
46ms
^* ntp2.torix.ca
                   1 10 377
                                     560 +1036us[+1213us] +/-
29ms
[admin@localhost ~]$
```

2. Edit the **chrony.conf** file to change the referenced NTP servers using the sudo vi chrony.conf command. In this example, the public tick.usask.ca and internal 192.168.1.50 NTP servers are

added. The iburst option speeds up the first synchronization and the prefer option advises chrony which NTP server you want to use if available.

```
# Use public servers from the pool.ntp.org project.
# Please consider joining the pool (http://www.pool.ntp.org/join.html).
# pool 2.rocky.pool.ntp.org iburst
server tick.usask.ca iburst prefer
server 192.168.1.50 iburst
# Record the rate at which the system clock gains/losses time.
driftfile /var/lib/chrony/drift
# Allow the system clock to be stepped in the first three updates
# if its offset is larger than 1 second.
makestep 1.0 3
# Enable kernel synchronization of the real-time clock (RTC).
rtcsync
# Enable hardware timestamping on all interfaces that support it.
#hwtimestamp *
# Increase the minimum number of selectable sources required to adjust
# the system clock.
#minsources 2
# Allow NTP client access from local network.
#allow 192.168.0.0/16
# Serve time even if not synchronized to a time source.
#local stratum 10
# Specify file containing keys for NTP authentication.
keyfile /etc/chrony.keys
# Get TAI-UTC offset and leap seconds from the system tz database.
leapsectz right/UTC
# Specify directory for log files.
logdir /var/log/chrony
# Select which information is logged.
#log measurements statistics tracking
```

3. Restart chrony for the changes to take effect using the command sudo systematl restart chronyd.

4. Confirm the new configuration of the **chrony.conf** file.

```
[admin@localhost etc]$ chronyc sources -v
 .-- Source mode '^' = server, '=' = peer, '#' = local clock.
/ .- Source state '*' = current best, '+' = combined, '-' = not combined,
           'x' = may be in error, '~' = too variable, '?' = unusable.
.- xxxx [ yyyy ] +/-
ZZZZ
    Reachability register (octal) -. | xxxx = adjusted
offset.
| Log2(Polling interval) --. | yyyy = measured
offset,
                          \ |
| zzzz = estimated
error.
MS Name/IP address
                    Stratum Poll Reach LastRx Last sample
______
^* tick.usask.ca
                          1 6 17 41 +3545ns[ +33us] +/-
13ms
^- 192.168.1.50
                         3 6 17 40 +411us[ +411us] +/-
126ms
[admin@localhost ~]$
```

5. View status in real time using the command watch chronyc tracking

```
[admin@localhost etc]$ watch chronyc tracking
Every 2.0s: chronyc
tracking
localhost.localdomain: Wed Mar 6 11:52:27 2024
Reference ID : 80E99AF5 (tick.usask.ca)
               : 2
Stratum
Ref time (UTC) : Wed Mar 06 11:52:18 2024
System time : 0.000002575 seconds slow of NTP time
Last offset
              : +0.000002259 seconds
RMS offset
              : 0.000026505 seconds
Frequency
              : 25.173 ppm slow
Residual freq : +0.000 ppm
Skew
               : 0.168 ppm
Root delay : 0.025361167 seconds
Root dispersion: 0.000044461 seconds
Update interval : 64.6 seconds
Leap status : Normal
```

PCoIP Management Console Disabling the Chrony

Disabling the Chrony

If required, disable chrony by issuing the following commands:

- 1. sudo systemctl stop chronyd to stop the chronyd service
- 2. sudo systemctl disable chronyd to disable the chrony service.

Issue the systemctl status chronyd command to confirm chrony is disabled.

PCoIP Management Console SSH Security Considerations

SSH Security Considerations

The following SSH configuration considerations will help secure the Management Consoles underlying OS SSH package. Thorough knowledge of using Linux commands is assumed.

These considerations are based on the Rocky Linux wiki which contain additional configurations and can be found at https://docs.rockylinux.org/guides/security/ssh_public_private_keys/?h=ssh.

The following configurations are separated individually but you can make all these changes at once if you decide that all these configurations conform to your IT departments security policy.

Disable Root Login

1. Edit /etc/ssh/sshd_config

```
# Prevent root logins:
   PermitRootLogin no
```

2. Restart SSH

\$ sudo service sshd restart

Limit User Logins

1. Edit /etc/ssh/sshd_config

```
# Limit User Logins to the following
AllowUsers admin
```

2. Restart SSH

\$ sudo service sshd restart

PCoIP Management Console Disable SSH Protocol 1

Disable SSH Protocol 1

1. Edit /etc/ssh/sshd_config

```
# Protocol 2,1
Protocol 2
```

2. Restart SSH

```
$ sudo service sshd restart
```

Use Public/Private Keys for authentication and disable Password Authentication

1. Generate public and private certificate.

```
$ ssh-keygen -t rsa
```

- a. Either specify a file name or accept the default.
- b. If you want to be asked for a password everytime you connect, supply a passphrase.
- c. A private (id_rsa by default) and a public key (id_rsa.pub by default) will be created in the ~/.ssh directory.
- 2. In the Management Console, ssh as admin and copy the public key in the ~/.ssh folder. You may need to create the ~/.ssh folder.
- 3. Install the public key into the authorized_keys list:

```
$ cat id_rsa.pub >> ~/.ssh/authorized_keys
```

4. Set permissions on the .ssh directory and authorized_keys file

```
$ chmod 700 ~/.ssh
$ chmod 600 ~/.ssh/authorized_keys
```

- 5. Enable SSH public key authentication
 - a. Edit /etc/ssh/sshd_config

```
#Enable Public Key authentication
PubkeyAuthentication yes
```

b. Restart SSH

```
$ sudo service sshd restart
```

6. In the workstation where you will run the ssh client, copy the private key in the ~/.ssh folder. Set the permissions as follows:

```
$ chmod 700 ~/.ssh
$ chmod 600 ~/.ssh/id_rsa
```

7. Test the SSH connection using public/private keys by using SSH to connect to your VM from a different VM where you have copied your generated SSH key

```
$ ssh admin@your_mc_ip_or_fqdn -i ~/.ssh/id_rsa
```

- 8. Disable password authentication.
 - a. Edit /etc/ssh/sshd_config

```
# Disable password authentication forcing use of keys:
PasswordAuthentication no
```

b. Restart SSH

\$ sudo service sshd restart

Identity Provider(IDP) Integrations

Create Self-Signed Certificate

Management Console by default contains a self-signed certificate that can be used for SAML encryption. However, some organizations prefer to use their own self-signed certificates. In order to complete these steps, you may need to install a version of OpenSSL if you don't have one installed already.

If you want to update Management Console with a new self-signed certificate, perform the following steps:

STEP 1: GENERATE RSA PRIVATE KEY

To generate a RSA private key, at the command prompt, run the following command:

```
openssl command: openssl genrsa -out <key output path> <modulus bit length>
```

Example:

openssl genrsa -out samlkey.key 2048

```
D:\development\KEYSTOREGUIDE>openssl genrsa -out samlkey.key 2048
Generating RSA private key, 2048 bit long modulus
.....+++
....++
unable to write 'random state'
e is 65537 (0x10001)
D:\development\KEYSTOREGUIDE>
```

STEP 2: GENERATE CERTIFICATE REQUEST

Once a private key has been generated, you can create a certificate request which is needed to generate a self-signed certificate. The openssl command openssl req -new -key <key_path> -out <request output path> will be used to generate the certificate request.

Example:

PCoIP Management Console Create Self-Signed Certificate

openssl req -new -key samlkey.key -out samlcertrequest.csr

You will be prompted to enter the attributes such as country name, province, email address, etc.

```
D:\development\KEYSTOREGUIDE>openssl req -new -key samlkey.key -out
samlcertrequest.csr
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
Country Name (2 letter code) [AU]:IN
State or Province Name (full name) [Some-State]:AP
Locality Name (eq, city) []:HYD
Organization Name (eg, company) [Internet Widgits Pty Ltd]:PRIME
Organizational Unit Name (eg, section) []:SECA
Common Name (e.g. server FQDN or YOUR name) []:PRIME
Email Address []:abc@example.com
Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:password
An optional company name []:PRIME
D:\development\KEYSTOREGUIDE>
```

STEP 3: GENERATE CERTIFICATE

Once you have a private key and certificate request, you are ready to create a self-signed certificate.

```
openssl x509 -req -days <expiry_in_days> -in <cert_request_path> -signkey
<private key path> -out <cert output path>
```

Example:

```
openssl x509 -req -days 3650 -in samlcertrequest.csr -signkey samlkey.key -out samlcert.crt
```

PCoIP Management Console Create Self-Signed Certificate

Note: The above generated certificate(samlcert.crt) should be uploaded in IDP.

```
D:\development\KEYSTOREGUIDE>openssl x509 -req -days 3650 -in
samlcertrequest.csr -signkey samlkey.key -out samlcert.crt
Signature ok
subject=/C=IN/ST=AP/L=HYD/O=PRIME/OU=SECA/CN=PRIME/
emailAddress=abc@example.com
Getting Private key
unable to write 'random state'

D:\development\KEYSTOREGUIDE>
```

Okta Reference

This reference article describes an integration between Management Console and Okta's authentication software. The basic configuration principals should apply for most IDPs.

Okta Configuration

- 1. Register for an account at Okta.com.
- 2. Accept the multifactor authentication requirement.
- 3. Sign in to your account.
- 4. Create an application in Okta.
 - a. From the top left accordion button, select the Applications menu and click **Applications** >Create **App Integration**.
 - b. Select SAML2.0 sign on method then Next.
 - c. Enter a name and optional logo (i.e. Management Console Vancouver) and select Next.
 - d. Enter your SAML settings:
 - Single sign on URL: { MC IP Address }/login/saml2/sso/idp
 - · Use this for Recipient URL and Destination URL: selected
 - Allow this app to request other SSO UIRLs: deselected
 - Audience URI: { MC IP Address }/saml2/service-provider-metadata/idp
 - **Default Relay State**: leave default (empty)
 - Name ID Format: leave default value Unspecified
 - Application username: leave default value Okta username
 - Response: Signed (default)
 - · Update application username on: leave default value Create and update

SAML Settings	Edit
GENERAL	
Single Sign On URL	https://10.12.56.139/login/saml2/sso/idp
Recipient URL	https://10.12.56.139/login/saml2/sso/idp
Destination URL	https://10.12.56.139/login/saml2/sso/idp
Audience Restriction	https://10.12.56.139/saml2/service-provider-metadata/idp
Default Relay State	
Name ID Format	Unspecified
Response	Signed
Assertion Signature	Signed

Show Advanced Settings

The defaults can be used unless you would like to use encrypted assertions. Encryption secures the assertion between the sender and receiver. See the caution note on **Using encrypted assertions** for configuration information on using Assertion Encryption. As of publication of this article, the advanced default settings are:

Assertion Signature: Signed (default)

• Signature Algorithm: RSA-SHA256 (default)

• Digest Algorithm: SHA256 (default)


Assertion Encryption: Unencrypted (default)

Using encrypted assertions

Encrypted assertions require you to upload the encryption certificate to Okta and is obtained by downloading it from the Management Console IDP Configuration tab. You cannot upload an encryption certificate that is expired, however if the expiry date is reached after it is being used, encryption assertions will continue to work as the expiry date is not monitored after implementation.

Selecting Encrypted for the Assertion Encryption type displays additional settings which the defaults can be used. The additional settings are:

- Encryption Algorithm set to AES256-CBC
- Key Transport Algorithm set to RSA-OAEP



- Enable Single Logout: deselected (default)
- Assertion Inline Hook: None(disabled) (default)
- Authentication context class: PasswordProtectedTransport (default)
- · Honor Force Authentication: Yes (default)
- SAML Issuer ID: http://www.Okta.com/\${org.externalKey} (default)

Configuring FirstName and LastName

1. Enter the following two attribute statements in the Attribute Statements (optional) section:

Name: firstName

Name format: Unspecified Value: user.firstName

• Name: lastName

Name format: Unspecified


Value: user.lastName

2. Select Next.

3. Answer Okta's support question to be able to select **Finish** on the next screen. Continue with next step obtaining IDP metadata file.

Obtaining IDP Metadata File

1. From the Application settings Sign On tab, select the **Identity Provided metadata** link.



2. Right click on the newly opened page containing the XML metadata and save the page. This file is used in the Management Console IDP configuration.

Okta Multi-factor Authentication

In this reference article, we will change the default to Duo as the application authenticator performing MFA as an example for you to follow in the event you are already using a different authenticator. By default, Okta enables multi-factor authentication (MFA) using their authenticator application.

MFA can be achieved using a variety of different methods to improve security Management Console sign in security. This article provides Okta configurations for the following MFA authentication types:

- Email Authentication
- **DUO** Authentication
- SMS Authentication
- Smart Card Authentication

EMAIL AUTHENTICATION CONFIGURATION


- 1. From the **Security** tab, select **Multifactor**. You will be placed on the **Factor Types** setting tab.
- 2. Select Email Authentication and click the Edit link.
- 3. Select **Active** for Email Authentication and configure the *token lifetime* setting to comply with your corporate security policies.
- 4. Click Save.
- 5. Select the **Factor Enrollment** tab and select **Edit**.
- 6. Update **Assigned to groups** and select **Required** for Email Authentication and click **Update Policy**.
- 7. From the **Applications** window, select your appliance and then select the **Sign On** tab.
- 8. Select **Add Rule** under Sign On Policy.
- 9. Enter a rule name.
- 10. Under the actions section, check **Prompt for factor Multifactor settings** and select **Every sign on** and save. (You can configure other options to your corporate security policies)

SMS AUTHENTICATION CONFIGURATION

- 1. Navigate to the **Security > Multifactor > SMS Authentication**.
- 2. Select **Activate** from the SMS Authentication drop down option.
- Select the Factor Enrollment tab.
- 4. Select **Edit** and update Assigned to groups (use Everyone group for all users).
- 5. Change SMS Authentication to **Required** for Eligible Factors.
- 6. Add a sign on policy to Management Console.
 - a. Navigate to **Applications > Applications** and select your Management Console application.

- b. Select the Sign On tab.
- c. Click on Add Rule button in the Sign On Policy section.
- d. Enter a Rule Name.
- e. Under the *Actions* section, check **Prompt for factor Multifactor settings** and select **Every sign on** (Configure other options according to your corporate security policies).
- f. Ensure the drop down option for **When all the conditions above are met, sign on to this application is: Allowed**.
- g. Select **Save**.

When an IDP user, attempts to sign into Management Console the user will be presented with a notice from the SSO provider (in this example Okta) that MFA is required.



The next screen will allow the IDP user to enter a cell number that will receive a code via SMS. Once the cell number is entered, another screen will allow the IDP user to verify the SMS code and if successful, they will be logged into Management Console.

Smart Card Authentication

The reference instructions for smart card authentication can be found here.

DUO Authentication

For this example we are using DUO as the MFA application to approve the Single Sign on.

- 1. Sign up for a DUO account and log into your account.
- 2. Navigate to Applications > Protect an Application.
- 3. Locate Okta and select the Protect button.
- 4. Copy your **Integration key**, **Secret key**, and **API hostname** to use in your Okta configuration. Destroy your copied versions after you finish your configuration.

Okta Configuration

- 1. From the Okta dashboard navigate to **Security > Multifactor**.
- 2. Select **Duo Security** and click on the **Edit** link.
- 3. Enter the **Integration key**, **Secret key**, and **API hostname** appropriately and use the name format used to log in to Okta.
- 4. Activate Duo Security from the drop down option and select Save.
- 5. Navigate to **Security > Authentication** and select the **Sign On** tab.
- 6. Select **Default Policy**, and then select the **Add Rule** button.


You can either add a new rule for Duo Authentication to an existing Okta sign-on policy, or create a new policy for Duo and assign it to specific groups. In this example, we'll turn on Duo for all users in the **Default Policy**.


- a. Enter a descriptive rule name.
- b. Leave defaults and ensure **Prompt for Factor** is checked along with the **Every Time** option.
- c. Select Create Rule.

User Management


To assign users to the Management Console application in Okta perform the following steps.


1. Login to Okta and navigate to **Directory > People** and click the **Add person** button, fill in the fields and click **Save**.





2. Navigate to **Applications**, click the **Assign** button and click the Assign link beside the people you want to assign Management Console too.







Session Time Out

Set session timeout rules to groups in Okta.


- 1. Navigate to **Security > Authentication** and select the **Sign On** tab.
- 2. Click the Add New Okta Sign-on Policy button, enter a policy name and click Create Policy and Add Rule.



3. Enter a rule name, set the session expiry and select Create Rule.



4. Verify the configuration is active.



Smartcard Authentication with SSO


This article will provide you with basic details to configure a Domain Controller, add test users and integrate the users for smart card authentication using Okta as the IDP. This reference is based on using Windows Server 2019 Standard with Okta IDP for Single Sign-on.

After completing these steps you will be able to:


- Use Okta to login with Smart card authentication using an Active directory user certificate.
- Use Okta to login using the username and password of an Active directory user.

Windows Server Configuration


- 1. Open Server Manager from the Windows Server search field.
- 2. Select the **Active Directory Domains and Services** as a server role from the **Add Roles and Features Wizard** and click **Next** then **Install**.




3. Click the flag and select **Promote this Server to a DC** (Domain Control).



- 4. Select Add a new forest and create a domain name and click Next.
- 5. Create a password and select **Next** until the install button shows.




- 6. Select Install.
- 7. Restart the server and create some users and groups in Active Directory Users and Computers.
- 8. From the Domain Controller that was just created, login to Okta, navigate to **Settings > Downloads** and download the Okta AD Agent and install it.
- 9. Enter the AD Domain Name.
- 10. Create an Okta Service Account as recommended and enter the password.
- 11. Enter the Okta URL, once redirected to the Okta page, enter the Okta credentials and select **Allow** access.
- 12. From the Okta dashboard, navigate to **Directory > Directory Integrations**.
- 13. Select the AD Server name and configure it using the default settings. Once completed, the agent displays as active.



- 14. Click on the **Import** tab and Import now with full import.
- 15. After the import, highlight the users and select **Assign the users**.


 After assigning the users you can see the AD users in the *Assignments* tab.



16. Navigate to **Directory > People** and **Activate** the imported AD users.

After activating the AD users, try to login Okta with the AD credentials to verify a working configuration.


17. From the Domain Controller server, navigate to Server Manager > Manage > Add Roles and Features, select Active Directory Certificate Services and select Next.




- 18. Select Certificate Authority and Certificate Authority Web Enrollment and click Install.
- 19. (22) From the Server Manager header, click the flag icon and click **Promote this Server to a** certificate server.

While Configuring Certificate Authority select Enterprise and Root CA

20. In the search bar, type Certification Authority and select your local CA.




21. Right click Certificate Template and click Manage.




22. Right click **Enrollment Agent** and click **Duplicate Template**.


- 23. Right click **Duplicated Template** and click **Properties**.
- 24. From the General tab, select the Publish Certificate in Active Directory checkbox.




25. From the **Compatibility** tab and ensure **Windows Server 2003** is selected for *Certificate Authority* and *Certificate recipient* compatibility settings.




- 26. From the **Request Handling** tab, select **Signature** from the *Purpose* drop-down list and select the **Prompt the user during enrollment and require user input when the private key is used** radio button.
- 27. From the **Cryptography** tab, ensure the **Microsoft Base Smart Card Crypto Provider** checkbox is selected.




28. From the **Subject** tab, ensure the **Include e-mail name in subject name** and **E-mail name** checkboxes are cleared.




- 29. From the Security tab, ensure Full Control is selected for Authenticated Users and click OK.
- 30. Create a Group in Active Directory with one or two users and add them in the security tab with **Full Control** permissions and click OK.
- 31. From the **Certification Authority**, right click the **Certificate Template** folder and select **Manage**, then right click on **Smartcard User** and select **Duplicate Template**.
- 32. From the **General** tab of the Smartcard user properties dialog, set the *Validity* and *Renewal* periods and ensure **Publish certificate in Active Directory** is selected.




33. From the **Compatibility** tab, ensure **Windows Server 2003** is set for *Certificate Authority* and *Certificate recipient* compatibility options and that *Show resulting changes* is selected.




34. From the **Request Handling** tab, select **Signature and encryption** from the *Purpose* option drop-down list and select the **Enroll subject without requiring any user input** radio button.




35. From the **Cryptography** tab, ensure the **Microsoft Base Smart Card Crypto Provider** option is selected.



36. From the **Subject** tab, clear the **Include e-mail name in subject name** and **E-mail name** options.




- 37. From the **Security** tab, select **Read**, **Write** and **Enroll** permissions for Authenticated Users.
- 38. Create a Group for smart card users in Active Directory with one or two users and add them in the Security tab with **Read**, **Write** and **Enroll** permissions and click OK.
- 39. (41)From the **Certification Authority**, right click the **Certificate Templates** and click **New > Certificate Template to issue** and select the two duplicated templates—**Copy of Enrollment Agent**and **Copy of Smartcard User**. After adding the templates, they are visible in the Certificate
 Templates folder.




40. Find the Certificate Revocation List certificate (extension is .crl) in C:

\Windows\System32\certsrv\CertEnroll and create a customized link to this certificate using a format of **FQDN/Path/Certificate_Name**. The link must be reachable from both inside and outside of the server's network.



- 41. From the Certification Authority, right click on your **Domain Name** and click on **Properties**.
- 42. From the **Extensions** tab, select **CRL Distribution Point (CDP)** from the *Select extension* drop-down list, click Add to add the customized Certificate Revocation List certificate link, and ensure the following checkboxes are selected.
 - · Include in CRLs. Clients use this to find Delta CRL locations.
 - Include in the CDP extension of issued certificates.
 - Include in the IDP extension of issued CRLs


Confirm the path has been added.



43. Restart the Certificate Authority Server.


Download the Chain Certificate from the Certificate Authority Server

- 1. Use the URL of the Certificate Authority Server to download the certificate. The URL will have the format similar to http://{ server_IP_address }/certsrv/.
- 2. Click on the **Download CA certificate chain** link and download your certificate.




Okta Configuration

Login to Okta and navigate to Security > Identity Providers > Add Identity Providers > Add Smart
 Card and upload the certificate chain that was downloaded in the previous steps.




2. In the USER MATCHING section ensure **idpuser.subjectAltNameUpn** is entered in the *IDP Username* field and **Okta Username or Email** is selected in the *Match against* drop-down fields and click the Update Identity Provider button.




Workstation Configuration

- 1. Login to the workstation as { DOMAIN_NAME }\Administrator and join the domain.
- 2. Install smart card drivers and minidrivers. Such as the PIVKEY Administrators Kit https://pivkey.com/pkadmin.zip.
- 3. Run Microsoft Management Console (mmc.exe).
- 4. Click File > Add or Remove Snap-in, select Certificates and click Add.
- 5. Select the My User Account radio button and click Finish and then OK.
- 6. From the Console root expand Certificates Current User, right click Personal and select All Tasks> Request a New Certificate....




- 7. Click Next on the Before you Begin and Next on the Certificate Enrollment Policy dialogs.
- 8. Select the **Copy of Smartcard User** checkbox and then click **Enroll**.



9. Enter the smart card PIN to enroll the certificate to the smart card.

Login to Okta Using PIV Card

- 1. Browse to the Okta URL where the smartcard is configured.
- 2. Click on PIV Card button.



- 3. Select your user Certificate.
- 4. Click OK.
- 5. Enter your smart card PIN.

You are now logged into Okta using smart card authentication.

Browser Configuration for use with Smartcards

Chrome and Edge (version 88.0 or newer) browsers are not known to require additional configurations at the time this article was written. Firefox requires the following configuration to display the certificate popup dialog box.

Open a Firefox browser and enter **about:config** in the URL field and configure the following options. If the option does not exist, it can be added.

- security.cert_pinning.max_max_age_seconds: 30
- security.remember_cert_checkbox_default_setting: false
- network.ssl_tokens_cache_enabled: true
- security.osclientcerts.autoload: true

Return to the Okta configuration reference

PingFederate Installation Reference

- 1. Register for trial and download the PingFederate Windows Installer MSI from here. From the same site select the **Add-ons** tab and download Duo Security Integration Kit 3.0.
- 2. Request a license key from Pingldentity and download the key.
- 3. Download and install OpenJDK 11 and set the JAVA_HOME environment variable to the Java installation directory path, and add its bin directory to the PATH environment variable.
- 4. Install PingFederate using the downloaded MSI installer and select **Standalone** mode. The rest of the values during installation can be left default.
- 5. After installation the admin console can be accessed via https://>FQDN<:9999/pingfederate/app.
- 6. Access the admin console link in the browser and follow the onscreen instructions. Select **No**, **setup PingFederate Without PingOne** when prompted.
- 7. In the next window, browse to the downloaded license file and click Next.
- 8. Select Identity Provider and click Next.
- 9. Click Next.
- 10. Create an Administrator account.
- 11. Follow the instructions to install the Duo Security Integration Kit from https://docs.pingidentity.com/bundle/integrations/page/kzh1602706841985.html.

Before installing the integration kit

Before installing the integration kit, stop the pingfederate service from the **Services** window and start the service after the kit is deployed.

12. To integrate existing local active directory to PingFederate. Please follow the steps <u>at https://www.coreblox.com/blog/2015/02/add-ms-activedirectory-authentication-to-pingfederate.</u>


PingFederate Configuration for Management Console

Install PingFederate IDP on local system. See PingFederate install reference.

Limitations

- If we are accessing a PingFederate URL created with a hostname from a different domain, it has to be added to the **C:\Windows\System32\drivers\etc\hosts** file.
- MFA and SSO are not support with IPv6.
- PingFederate throws an unexpected system error when the entityID in SP connection is different from { MC_URL }/saml2/service-provider-metadata/idp. This behavior is also seen in PingOne (cloud).

This can be seen in the server.log messages located at { pf_server }\Program Files\Ping Identity\pingfederate-10.1.2\pingfederate\log\server.log.




The following configurations are required to create a **SPConnection** in PingFederate (Reference links can be found <u>here</u> and <u>here</u>)


- Create a Password Credential Validator
- Create an AD Adapter (For first factor authentication)
- Create a Smartcard Implementation with PingFederate
- Create a MFA Policy Contract

Create a Password Credential Validator


1. Navigate to **PingFederate > SYSTEM** and select **Password Credential Validators** (See reference here).



2. Click on **Create New Instance** to create a new password validator with desired name. This will be used in the AD adapter.




- 3. Select password credential validator type as **LDAP Username Password Credential Validator** and fill required fields to configure an AD Datastore.
 - a. Enter the **INSTANCE NAME**, **INSTANCE ID** and select *LDAP Username Password Credential Validator* for **TYPE** and click on **Next**.




Password Credential Validator Type

a. Configure the LDAP datastore information similarly to what is displayed in the next image.




Password Credential Validator Instance Configuration

a. From the Extended Contract tab, configure similarly to the next displayed image and SAVE.




Password Credential Validator Extended Contract

4. Summary of password credential validator.




Create an AD adapter (For first factor authentication)


1. Navigate to PingFederate > AUTHENTICATION and click the IDP Adapters shortcut.




2. Click on **Create New Instance** to create a new adapter with a unique name to configure AD. This will be used in the SPConnection configuration.




3. Select the adapter TYPE as **HTML Form IDP Adapter** and use the images showing the adapter mappings for your configuration.




PingFederate Type HTML Form IDP Adapter




PingFederate Adapter Authentication IDP




PingFederate Adapter Authentication IDP 2




PingFederate Adapter Authentication Extended Contract



PingFederate Adapter Authentication Attributes



PingFederate Adapter Authentication Contract Mapping



PingFederate Adapter Authentication Summary


Create a Smartcard Implementation with PingFederate

The following configurations are required to implement use of a smartcard system with PingFederate.


- Download CA certificate chain file from Active Directory Server
- Install the X.509 Certificate Adapter (Integration Kit) in PingFederate
- Port Number for X.509 Certificate Authentication Configuration
- X.509 Certificate Adapter Configuration
- System with USB Card Reader Configuration
- Browser Configuration for use with Smartcards

DOWNLOAD CA CERTIFICATE CHAIN FILE FROM ACTIVE DIRECTORY SERVER

- 1. In Windows Server configure the domain service with a Domain Name and Install certificate authority with web enrollment.
- 2. Download the CA certificate chain at http://{ActiveDirectory_IP or FQDN //certsrv/ and upload the certificate chain to the PingFederate server.
- 3. Click on the **Download a CA certificate, certificate chain, or CRL** link.



- 4. Click on **Download CA certificate chain** to download the certificate.
- 5. Login to the PingFederate admin console.



6. Click **Security > Trusted CA > Import** and select the downloaded chain certificate file.

Note: Make sure the web enrollment certificate features is installed in Active directory certificate services in Windows Server.

INSTALL THE X.509 CERTIFICATE ADAPTER (INTEGRATION KIT) IN PINGFEDERATE

This section describes how to install and configure the X.509 Certificate Adapter for smart card.


- From the system where PingFederate is installed, download the X.509 Certificate Integration Kit
 1.3.1 PingFederate add-on. You can find the X.509 Certificate Integration Kit 1.3.1 from the Addons tab at the PingFederate download site and search the Integration Kits section.
- 2. Unzip and install X.509 Certificate Integration Kit 1.3.1.
- 3. Copy the x509-certificate-adapter-1.1.jar file in the **dist** directory of the distribution ZIP file to the { pf-install }/pingfederate/server/default/deploy directory of your PingFederate server installation.

PORT NUMBER FOR X.509 CERTIFICATE AUTHENTICATION CONFIGURATION


- 1. In the { pf-install }/pingfederate/bin directory, edit the file **run.properties** and change the value of pf.secondary.https.port to a valid port number.(For this example we will configure it as 9032).
- 2. Press the Windows key, type **services** and press the Enter key and the Services dialog displays.
- 3. Right click the PingFederate service and restart it.

X.509 CERTIFICATE ADAPTER CONFIGURATION


1. From PingFederate AUTHENTICATION tab select the IDP Adapters shortcut.




2. Click on **Create New Instance** to create a new adapter with a descriptive name. This will be used in the smart card SPConnection.



3. Select type as **X509 Certificate IDP Adapter 1.3** and enter the Client Auth Port specified for the pf.secondary.https.port (see Configure port number for x509 certificate authentication) and for client hostname enter the fqdn of the PingFederate system.




PingFederate IDP Adapter Type Settings



PingFederate IDP Adapter Port Settings img/pingfederate-idp-adapter-attributes-setting.png) **PingFederate IDP Adapter Attributes Settings**

4. Review the smart card adapter summary.



PingFederate IDP Adapter Summary

Browser Configuration for use with Smartcards

Chrome and Edge (version 88.0 or newer) browsers are not known to require additional configurations at the time this article was written. Firefox requires the following configuration to display the certificate popup dialog box.

Open a Firefox browser and enter **about:config** in the URL field and configure the following options. If the option does not exist, it can be added.

- security.cert_pinning.max_max_age_seconds: 30
- security.remember_cert_checkbox_default_setting: false
- network.ssl_tokens_cache_enabled: true
- security.osclientcerts.autoload: true

SYSTEM WITH USB CARD READER CONFIGURATION

This configuration is required on the computer that has a USB Smart Card Reader attached.

- 1. Login to the workstation as{ DOMAIN_NAME }\Administrator and join the domain.
- 2. Install smart card drivers and minidrivers from the PIVKEY Administrators Kit https://pivkey.com/pkadmin.zip.
- 3. Insert a smart card into the smart card reader.
- 4. Run Microsoft Management Console (mmc.exe).

- 5. Click **File > Add or Remove Snap-in**, select **Certificates** and click **Add**.
- 6. Select the My User Account radio button and click Finish and then OK.
- 7. From the Console root expand **Certificates Current User**, right click **Personal** and select **All Tasks** > **Request a New Certificate...**.
- 8. Click Next on the Before you Begin and Next on the Certificate Enrollment Policy dialogs.
- 9. Select the **Copy of Smartcard User** checkbox and then click **Enroll**.
- 10. Enter the smart card PIN to enroll the certificate to the smart card. The Certificate is enrolled to the Smartcard.
- 11. Make sure the smart card services is up and running. (verify through mmc services)
- 12. Make sure that the smart card has the certificate issued by the local AD server certificate authority.
- 13. Browse to the Management Console login page using the FQDN of the application (i.e. https://mcapplication.domain.name) and click on **SIGN IN WITH IDP**.
 - You will be prompted to select the smart card certificate and once selected you will be prompted to enter the PIN.

Browser Configuration for use with Smartcards


Chrome and Edge (version 88.0 or newer) browsers are not known to require additional configurations at the time this article was written. Firefox requires the following configuration to display the certificate popup dialog box.

Open a Firefox browser and enter **about:config** in the URL field and configure the following options. If the option does not exist, it can be added.


- security.cert_pinning.max_max_age_seconds: 30
- security.remember_cert_checkbox_default_setting: false
- network.ssl_tokens_cache_enabled: true
- · security.osclientcerts.autoload: true

Create a MFA Policy Contract


1. Select the smart card adapter from **Authentication > IDP Adapters**




2. Ensure the **INCLUDE SUBJECT ALTERNATIVE NAME (SAN)** checkbox is selected to get the userPrincipalName in the IDP adapter and click **Save**.




3. Select the Extended Contract tab, use the Add button to enter userPrincipalName and click Save.




4. Click Create New Contract.




5. Add userPrincipalName by extending the contract in Contract Attributes and Save.




6. Review the Summary of the Authentication Policy Contract.




7. Select **Authentication > Policies** to add the created policy contract.



8. Review the policy and select the **Contract Mapping** link for the **mfa-contract** Policy Contract.



- AD adapter(AdAuth) is configured for first factor authentication.
- X509 adapter(SmartCardAuth) is configured for smart card as second factor authentication.
- The Policy Contract(**mfa-contract**) is configured to validate first factor username with smart card certificate username.
- 9. Select the Contract Fulfillment tab and map the attributes




10. Select the **Issuance Criteria** tab and add the following ONGL expression to validate the username of the first factor with the smart card certificate username. The ONGL expression will be changed based on AD configurations in the AD adapter.


```
#this.get("ad.HTMLFormAdapter.username").toString().trim().equalsIgnoreCase(#
[0])?true:false
```

You can test the ONGL expression by clicking the **Test** link and providing sample values. The test results will return true if the username is the same in both AD Adapter and Smartcard adapter and false if not.


After testing, ensure the ONGL entered expression is correct and click **Done**.



11. Select the **Summary** tab and review the Policy Contract Mapping.



12. Select the **Applications** tab and review Summary for **SP Connections**.



CREATING A SP CONNECTION

An SP Connection is comprised of the following configurations.

- SP Connection
- Configure Browser SSO
- Configure Assertion Creation
- Configure Protocol Settings
- Configure Credentials

SP Connection

- 1. Navigate to **APPLICATIONS** → **SP Connections**
- 2. Click Create Connection.
- 3. Select the DO NOT USE A TEMPLATE FOR THIS CONNECTION radio button and click Next.
- 4. Select the **Connection Type** tab and select the **BROWSER SSO PROFILES** check box and select **SAML2.0** as the Protocol.
- 5. Select the BROWSER SSO checkbox and click Next.
- Select the FILE radio button to upload SP metadata XML or select NONE to configure the required fields manually and click Next.
- 7. Enter /saml2/service-provider-metadata/idp for the PARTNER'S ENTITY ID (CONNECTION ID) field.


- 8. Enter a descriptive connection name.
- 9. Enter the Management Console's URL in the BASE URL field and click Next.


Configure Browser SSO

- 1. Click the **Configure Browser SSO** button.
- 2. From the SAML Profiles page, select the **IDP-INITIATED SSO** and **SP-INITIATED SSO** checkboxes and click **Next**. (Management Console does not support SLO)
- 3. Enter Assertion Lifetime values and click Next.

Configure Assertion Creation

- 1. Click the **Configure Assertion Creation** button on the Assertion Creation page.
- 2. Select the STANDARD: radio button and click Next and Next again.
- Click the Map New Adapter Instance button on the Authentication Source Mapping page and click Next.
- Select Create AD/Smartcard adapters from the ADAPTER INSTANCE drop-down list and click Next.
- 5. Select the **Manage Adapter Instances** button to create a new adapter and then **Next > Next > Next**.
- Select USE ONLY THE ADAPTER CONTRACT VALUES IN THE SAML ASSERTION and click on Next.
- 7. Select the username as **SAMLSUBJECT** and click on **Next** and **Next** again.






8. Click the **Map New Authentication Policy** button and select the created policy contract(mfacontract)




9. Click Next until the summary tab and click Save to save the New Authentication Policy.



10. Click Save to save the adapters and policy contract.



11. Click Next to review the authentication policy Summary page and click Done.




Configure Protocol Settings


1. Click the Configure Protocol Settings button.




2. Select **POST** from the Binding drop-down list and enter the SAML Endpoint URL /login/saml2/sso/idp copied from Management Console in the Endpoint URL field click **Add > Next**.



- 3. Select the POST/REDIRECT checkboxes on the Allowable SAML Bindings page and click Next.
- Click Next on the Signature Policy page, click Next again on the Encryption Policy page, then click Done on the protocol settings Summary page.



5. Click **Done** on the Browser SSO Summary page and click **Next** on the Browser SSO page.



Configure Credentials

1. Click the Configure Credentials button on the SP Connection Credentials page.



Select the certificate you want to use with Management Console from the SIGNING CERTIFICATE drop-down list and select INCLUDE THE CERTIFICATE IN THE SIGNATURE ELEMENT and click Next.




3. Click **Done** on the Credentials Digital Signature Summary page and then click **Next** on the Credentials page.







4. Toggle the SSO Application Endpoint slider button to **Active** on the *Activation & Summary* page, then scroll down and click **Save**.



5. From **APPLICATIONS > SP Connections**, select **Export Metadata** from the **Select Action** drop-down list for Management Console and upload it to Management Console.





 Upload the downloaded metadata XML file to Management Console > SETTTINGS > AUTHENTICATION > IDP CONFIGURATION tab.


LINK TO MC GUIDE REQUIRED HERE (Please check Identity Provider Metadata Upload functionality in Management Console section). IDP user can able to login to MC using PingFederate IDP.

- 7. Test IDP login. The login flow will be as follows:
 - a. Select the Management Console SIGN IN WITH IDP button.
 - b. You will be redirected to the PingFederate login page.
 - c. Enter your IDP user login credentials.
 - d. Select your smart card certificate.

- e. Enter your smart card PIN number.
- f. You are now logged into Management Console using your smart card issued credentials.

SSO POLICY CREATION

1. To support SSO in PingFederate, Navigate to **Authentications > Policies > Sessions** and in the OVERRIDES section, select **AD Adapter(AdAuth)** from the Authentication Source drop-down list and select the **Enable Sessions** checkbox and click **Save**.




FIRSTNAME AND LASTNAME CONFIGURATIONS


Configuration of firstName and lastName is optional. By default, Management Console saves usernames as firstname and lastname.

The following steps are required to map Management Console user credentials in PingFederate.


1. Map the Active Directory **givenName** as firstName, and **sn** as lastName of a user in the ADadapter, smart card adapter, and contract policy.




2. Review the summary and click Save.




3. Add the firstName and lastName in the Authentication Policy Contract and click Save.



4. Add the firstName and lastName in the SPConnection > IDP Adapter Mapping and click Save.




5. Add the firstName and lastName in the Authentication Policy Mapping and click Save.




UPLOAD ASSERTION ENCRYPTION CERTIFICATE IN PINGFEDERATE


1. In SP Connection details, navigate to the Protocol Settings section and click on Signature policy.




2. From the Browser SSO Protocol Settings Page, select the **Signature Policy** tab and select the **ALWAYS SIGN ASSERTION** and **SIGN RESPONSE AS REQUIRED** checkboxes and click on **Next**.




3. Select **THE ENTIRE ASSERTION** radio button on the *Encryption Policy* page and click **Next**.




4. Review the Protocol Settings Summary page and click Save.



5. In the Credentials section, click the Select XML Encryption Certificate link.



6. (Optional) Click on the Manage Certificates button if you want to upload a new certificate.




7. Click on the **Import** button.



8. Select the **Choose File** and select the encryption certificate and click on **Next**.


!!! tip "Encryption Certificate" The encryption certificate is downloaded from the **Management** Console > AUTHENTICATION > IDP CONFIGURATION tab.



9. On the Import Certificate summary page click on Save.




10. On the XML Encryption Certificate Management page click on Done.



11. On the Select XML Encryption Certificate tab of the *Credentials* page, select the **AES-256** and **RSA-OAEP** radio buttons, then select the uploaded certificate from the drop-down list and click **Next**.



12. Verify the details on the Summary page and click on Save.



PCoIP Management Console Firewall References

Firewall References

Configuring firewalld for New Installs of Management Console 20.04 or newer

As of release 20.04, Management Console was upgraded for use with firewalld. Current versions of Management Console do not configure any firewall settings, but instead leaves firewall configurations in control of the administrator. In earlier versions of Management Console, the installer would enable **iptables**, create and apply a new set of rules that would allow the Management Console to communicate properly. Therefore, firewall configurations were not required for releases 20.01 or older.

If you you are using a firewall with Management Console on your Linux system, you must follow the recommended instructions that show how to create the rules required for Management Console communications. You must also add additional rules required to meet the requirements of your corporate security policy.

The steps below are instructions for configuring firewalld, grouped by IPv4 and IPv6 environments.

To configure firewalld in IPv4 environment

IPv4 firewalld script

RPM New Installations: To configure firewalld in IPv6 environment

OVA New Installations: To configure firewalld in IPv6 environment

Firewalld default behaviors when enabled

- All inbound connections are tested against configured rules that have been applied
- · All outbound connections are allowed
- Rules to allow traffic are added to the default zone. All other traffic will be blocked.

Uninstalling RPM

Uninstalling the Management Console RPM does not completely remove the firewall rules.

New Installs in IPv4 Environment

To configure firewalld for Management Console communication in an IPv4 environment perform the following steps:

- 1. Login to the Management Console host operating system console.
- 2. Enable firewalld.

```
sudo systemctl enable firewalld --now
```

3. Get the default zone. If the default zone is trusted it will allow all packets. It is recommended that the default zone is set to public.

```
sudo firewall-cmd --get-default
```

If default zone is not public, execute the following commands to set the default zone to public.

```
sudo firewall-cmd --permanent --zone=trusted --remove-service=pcoip-agent
sudo firewall-cmd --set-default=public
sudo firewall-cmd --reload
```

4. Get the default zone and assign it to a variable.

```
def zone=$(firewall-cmd --get-default)
```

5. Set the log (all denied packets logged together).

```
sudo firewall-cmd --set-log-denied=all
```

6. Add an interface.

```
sudo firewall-cmd --zone=$(echo $def zone) --change-interface=$(ip addr
show | grep "state UP" | head -1 | awk -F': ' '{print $2}')
```

7. Enable required ports.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-
port={80,443,22,5172}/tcp
```

8. Allow pings.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-icmp-
block={echo-reply,echo-request} 2>/dev/null
```

9. Redirect port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-forward-
port=port=443:proto=tcp:toport=8443
```

10. Enable IP Masquerading.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-masquerade
```

11. Redirect Port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-forward-
port=port=80:proto=tcp:toport=8080
```

12. Drop incoming packets to 127/8 from other interfaces other than loopback interface.

```
sudo firewall-cmd --permanent --new-zone loopback 2>/dev/null
sudo firewall-cmd --permanent --zone=loopback --change-interface=lo 2>/dev/
null
sudo firewall-cmd --zone=loopback --permanent --set-target=ACCEPT
sudo firewall-cmd --zone=loopback --permanent --add-source=127.0.0.0/8
```

13. Reload the firewall.

```
sudo firewall-cmd --reload
```

14. Confirm the rules are applied.

a. Check the firewalld status is active.

```
sudo systemctl status firewalld
```

b. Verify all rules are added in firewalld or not, all rules should be applied.

```
[autorunner@gcp8ccbf5e557cd4a089155360bfe8c794b ~]$ sudo firewall-cmd --list-all
trusted (active)
  target: ACCEPT
  icmp-block-inversion: no
  interfaces: eth0
  sources:
    services: pcoip-agent
  ports: 80/tcp 443/tcp 22/tcp 5172/tcp
  protocols:
    masquerade: yes
  forward-ports: port=443:proto=tcp:toport=8443:toaddr=
        port=80:proto=tcp:toport=8080:toaddr=
    source-ports:
  icmp-blocks:
  rich rules:
[autorunner@gcp8ccbf5e557cd4a089155360bfe8c794b ~]$
```

Firewalld Script for New Installations of Management Console 20.04 or newer Using IPv4

HP has provided instructions to create a script that stops the iptables service, and enables firewalld with the required IPv4 rules for Management Console to work correctly.

The script file is created and executed using the following steps:

1. Copy the script content and save into firewalld.sh

```
sudo vi firewalld.sh
```

```
#!/bin/bash
val1=1
if [ $val1 -eq 1 ]; then
systemctl stop iptables || service iptables stop
systemctl enable firewalld --now
def zone=$(firewall-cmd --get-default)
if [ $def zone != "public" ] ; then
    firewall-cmd --permanent --zone=trusted --remove-service=pcoip-agent
    firewall-cmd --set-default=public
    firewall-cmd --reload
    def zone=$(firewall-cmd --get-default)
fi
firewall-cmd --set-log-denied=all
firewall-cmd --permanent --zone=$(echo $def zone) --change-interface=`ip
addr show | grep "state UP" | head -1 | awk -F': ' '{print $2}'`
firewall-cmd --zone=$(echo $def zone) --permanent --add-
port={22,443,80,5172}/tcp
firewall-cmd --zone=$(echo $def zone) --permanent --remove-icmp-
block={echo-reply,echo-request}
firewall-cmd --zone=$(echo $def zone) --permanent --add-forward-
port=port=443:proto=tcp:toport=8443
firewall-cmd --zone=$(echo $def zone) --permanent --add-forward-
port=port=80:proto=tcp:toport=8080
firewall-cmd --permanent --new-zone loopback
firewall-cmd --permanent --zone=loopback --change-interface=lo
firewall-cmd --zone=loopback --permanent --set-target=ACCEPT
firewall-cmd --zone=loopback --permanent --add-source=127.0.0.0/8
firewall-cmd --reload
fi 2> /dev/null
```

1. Provide permissions for the script to execute.

```
sudo chmod +x ./firewalld.sh
```

2. Run firewalld.sh:

```
sudo ./firewalld.sh
```

New Installs in IPv6 Environment¶

To configure firewalld for new RPM installation of Management Console allowing communication in an IPv6 environment perform the following steps:

1. Login to the Management Console host operating system console.

2. Enable firewalld.

```
sudo systemctl enable firewalld --now
```

3. Get the default zone. If the default zone is trusted it will allow all packets. It is recommended that the default zone is set to public.

```
sudo firewall-cmd --get-default
```

If default zone is not public, execute the following commands to set the default zone to public.

```
sudo firewall-cmd --permanent --zone=trusted --remove-service=pcoip-agent
sudo firewall-cmd --set-default=public
sudo firewall-cmd --reload
```

4. Get the default zone and assign it to a variable.

```
def_zone=$(firewall-cmd --get-default)
```

5. Set the log (all denied packets logged together).

```
sudo firewall-cmd --set-log-denied=all
```

6. Add an interface.

```
sudo firewall-cmd --permanent --zone=$(echo $def_zone) --change-
interface=`ip addr show | grep "state UP" | head -1 | awk -F': ' '{print
$2}'`
```

- 7. Enable required IPv6 ports.
 - Open port 443

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=443 protocol=tcp accept'
```

• Open port 22

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=22 protocol=tcp accept'
```

Open port 5172

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=5172 protocol=tcp accept'
```

• Open port 80

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=80 protocol=tcp accept'
```

8. Allow pings.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-icmp-
block={echo-reply,echo-request} 2>/dev/null
```

9. Redirect IPv6 port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8443 protocol=tcp port=443'
```

10. Redirect IPv6 Port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8080 protocol=tcp port=80'
```

11. Drop incoming packets to 127/8 from other interfaces other than loopback interface.

```
sudo firewall-cmd --permanent --new-zone loopback 2>/dev/null
sudo firewall-cmd --permanent --zone=loopback --change-interface=lo 2>/dev/
null
sudo firewall-cmd --zone=loopback --permanent --set-target=ACCEPT
sudo firewall-cmd --zone=loopback --permanent --add-source=127.0.0.0/8
```

12. Reload the firewall.

```
sudo firewall-cmd --reload
```

13. Confirm the rules are applied.

a. Check the firewalld status is active.

```
sudo systemctl status firewalld
```

b. Verify all rules are added in firewalld or not, all rules should be applied.

```
sudo firewall-cmd --list-all

[primeuser@localhost_=19 sudo firewall-cmd --list-all
public (active)

target: default
tampel-block-inversion: no
interfaces: emplosS wip20

DOUCES!

DOUCES!

DOUCES!

DOUCES!

DOUCES!

Sugo-blocks:

Ich rules:

Ich
```

To configure firewalld for new OVA installation of Management Console allowing communication in an IPv6 environment perform the following steps:

PCoIP Management Console OVA comes ready for an IPv4 deployment. When deploying into an IPv6 environment, the firewalld IPv4 rules must be replaced with IPv6 rules. Perform the following steps to ensure Management Console only has IPv6 rules enabled after deploying Management Console OVA in an IPv6 environment.

- 1. Login to the Management Console host operating system console.
- 2. Close IPv4 22, 443, 80, 5172 ports.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-
port={22,443,80,5172}/tcp
```

3. Remove IPv4 internal port forwarding from 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-forward-
port=port=443:proto=tcp:toport=8443
```

4. Remove IPv4 internal port forwarding from 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-forward-
port=port=80:proto=tcp:toport=8080
```

5. Open IPv6 port 443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=443 protocol=tcp accept'
```

6. Open IPv6 port 22.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=22 protocol=tcp accept'
```

7. Open IPv6 port 5172.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=5172 protocol=tcp accept'
```

8. Open IPv6 port 80

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=80 protocol=tcp accept'
```

9. Redirect IPv6 port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-r
```

10. Redirect IPv6 port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8080 protocol=tcp port=80'
```

11. Reload the firewall rules.

Reload firewall rules

12. Confirm the rules are applied.

a. Check the firewalld status is active.

sudo systemctl status firewalld

b. Verify all rules are added in firewalld or not, all rules should be applied.

```
sudo firewall-cmd --list-all
```

Configuring firewalld after a Management Console Upgrade

In Management Console releases 19.05 through 20.01, installation disabled **firewalld**, enabled **iptables** and created rules that allowed Management Console to work as expected. Starting with release 20.04, Management Console upgraded to firewalld, and leaves the firewall configuration in the hands of the local administrator.

If you are upgrading from Management Console release 19.05 through 20.01 to release 20.04 or newer using Management Console RPM, existing firewall configurations can be left intact or if moving to firewalld they will have to be re-applied to the upgraded version of Management Console.

If you decide to use firewalld, the following instructions provide the steps to remove the iptables configuration applied by Management Console and steps to add firewalld rules required by Management Console to operate properly. Additional rules required to comply to your corporate security policy must be added by the administrator.

Upgrade Scenarios discussed in this topic are:

Firewall changes after a RPM Upgrade from Management Console 20.01 or older using IPv4

Firewall changes for RPM Upgrades from Management Console 20.04 to Management Console 20.07 or newer in IPv4 Deployments

Firewalld IPv4 Script

<u>Firewall changes required after an Upgrade from Management Console 20.01 or older to Management Console 20.07 or newer in an IPv6 Deployment</u>

Firewalld Script for IPv6

<u>Firewall changes required after an RPM Upgrade from Management Console 20.04 to Management Console 20.07 or newer in IPv6 Deployment</u>

<u>Firewall changes required after updating a Management Console OVA IPv4 deployment to an IPv6</u>

<u>Deployment</u>

<u>Firewall changes required when changing an existing Management Console IPv4 deployment to an IPv6 Deployment</u>

Upgrades in IPv4 Environments

Firewall changes after a RPM Upgrade from Management Console 20.01 or older using IPv4

When upgrading from a Management Console 20.01 or older installation using RPM, consideration for all previous installation firewall rules must be considered. The following steps will remove previously installed Management Console iptables IPv4 rules and add firewalld IPv4 rules so Management Console can operate properly in an IPv4 environment.

- 1. Login to Management Console host operating system console.
- 2. Check iptables status(which should be active).

```
sudo systemctl status iptables
```

```
[admin@ip-10-12-56-215 ~]$ sudo systemctl status iptables
• iptables.service - IPv4 firewall with iptables
Loaded: loaded (/usr/lib/systemd/system/iptables.service; enabled; vendor preset: disabled)
Active: active (exited) since Fri 2020-02-14 11:46:49 UTC; 12min ago
Process: 889 ExecStart=/usr/libexec/iptables/iptables.init start (code=exited, status=0/SUCCESS)
Main PID: 889 (code=exited, status=0/SUCCESS)
CGroup: /system.slice/iptables.service
```

3. Check the applied iptables rules.

```
sudo iptables -L
```

```
Chain INPUT (policy ACCEPT)
            prot opt source
tcp -- anywhere
tcp -- anywhere
tcp -- anywhere
                                                     destination
                                                                                 state NEW tcp dpt:ssh
                                                                                 state NEW tcp dpt:pcsync-https
state NEW tcp dpt:5172
                                                     anywhere
 CEPT
CCEPI
                  -- anywhere
-- anywhere
                                                     anywhere
loopback/8
                                                                                 reject-with icmp-port-unreachable
                                                                                 state RELATED, ESTABLISHED
                                                                                 limit: avg 5/min burst 5 LOG level debug prefix "iptables denie
                                                     anywhere
Chain FORWARD (policy ACCEPT)
             prot opt source
all -- anywhere
                                                                                 reject-with icmp-port-unreachable
                                                     anywhere
Chain OUTPUT (policy ACCEPT)
             prot opt source
icmp -- anywhere
icmp -- anywhere
                                                     destination
                                                                                 icmp echo-reply
                                                     destination
```

4. Remove rule which enabled port 8080.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 8080 -j ACCEPT
```

5. Remove rule which enabled port 8443.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 8443 -j ACCEPT
```

6. Remove rule which enabled port 5172.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 5172 -j ACCEPT
```

7. Remove rule which allowed incoming and outgoing pings.

```
sudo iptables -D INPUT -p icmp --icmp-type echo-request -j ACCEPT sudo iptables -D OUTPUT -p icmp --icmp-type echo-reply -j ACCEPT sudo iptables -D OUTPUT -p icmp --icmp-type echo-request -j ACCEPT sudo iptables -D INPUT -p icmp --icmp-type echo-reply -j ACCEPT
```

8. Remove PREROUTING rule.

```
sudo iptables -t nat -D PREROUTING -i `ip addr show | grep "state UP" |
head -1 | awk -F': ' '{print $2}'` -p tcp --dport 443 -j REDIRECT --to-port
8443
```

9. Drop incoming packets to 127/8 from other interfaces other than loopback interface.

```
sudo iptables -D INPUT -i lo -j ACCEPT
sudo iptables -D INPUT -i lo -d 127.0.0.0/8 -j REJECT
```

10. Remove outbound traffic rule.

```
sudo iptables -D OUTPUT -j ACCEPT
```

11. Remove logging rule.

```
sudo iptables -D INPUT -m limit --limit 5/min -j LOG --log-prefix "iptables
denied: " --log-level 7
```

12. Remove rule which dropped packets not matching any other rule.

```
sudo iptables -D INPUT -j DROP
sudo iptables -D FORWARD -j REJECT
```

13. Save iptables service to save your changes (should show status OK).

```
sudo service iptables save
```

14. Restart iptables to apply your changes.

```
sudo systemctl restart iptables
```

15. Check iptables rules (should not contain rules which Management Console install previously added).

```
sudo iptables -L
```

```
[admin@ip-10-12-56-215 \sim]$ sudo iptables -L
Chain INPUT (policy ACCEPT)
          prot opt source
ACCEPT
           tcp -- anywhere all -- anywhere
                                                                      state NEW tcp dpt:ssh
                                              anywhere
                                                                      state RELATED, ESTABLISHED
                                              anywhere
ACCEPT
Chain FORWARD (policy ACCEPT)
                                              destination
Chain OUTPUT (policy ACCEPT)
         prot opt source
target prot opt source [admin@ip-10-12-56-215 ~]$
                                              destination
```

16. Mask iptables.

```
sudo systemctl mask iptables
```

17. Stop iptables service.

```
sudo systemctl stop iptables
```

18. Unmask firewalld, (should show removed symlink).

```
sudo systemctl unmask firewalld
```

```
[admin@ip- ~]$ sudo systemctl unmask firewalld
Removed symlink /etc/systemd/system/firewalld.service.
[admin@ip- ~]$
```

19. Enable firewalld.

```
sudo systemctl enable firewalld --now
```

20. Start firewalld.

```
sudo systemctl start firewalld
```

21. Check firewalld status (should be active).

```
sudo systemctl status firewalld
```

a. Get the default zone. If the default zone is trusted it will allow all packets. It is recommended that the default zone is set to public.

```
sudo firewall-cmd --get-default
```

If default zone is not public, execute the following commands to set the default zone to public.

```
i. sudo firewall-cmd --permanent --zone=trusted --remove-service=pcoip-agentii. sudo firewall-cmd --set-default=public
```

- iii. sudo firewall-cmd --reload
- 22. Get the default zone and assign it to a variable.

```
def_zone=$(firewall-cmd --get-default)
```

23. Set the log.(all denied packets logged together)

```
sudo firewall-cmd --set-log-denied=all
```

24. Add an interface.

```
sudo firewall-cmd --zone=$(echo $def_zone) --change-interface=$(ip addr
show | grep "state UP" | head -1 | awk -F': ' '{print $2}')
```

25. Enable required ports.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-
port={80,443,22,5172}/tcp
```

26. Allow pings.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-icmp-
block={echo-reply,echo-request} 2>/dev/null
```

27. Redirect port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-forward-
port=port=443:proto=tcp:toport=8443
```

28. Enable IP Masquerading.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-masquerade
```

29. Redirect Port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-forward-
port=port=80:proto=tcp:toport=8080
```

30. Drop incoming packets to 127/8 from other interfaces other than loopback interface.

```
sudo firewall-cmd --permanent --new-zone loopback 2>/dev/null
sudo firewall-cmd --permanent --zone=loopback --change-interface=lo 2>/dev/
null
sudo firewall-cmd --zone=loopback --permanent --set-target=ACCEPT
sudo firewall-cmd --zone=loopback --permanent --add-source=127.0.0.0/8
```

31. Reload the firewall rules.

```
sudo firewall-cmd --reload
```

32. Confirm the rules are applied.

a. Check the firewalld status is active.

```
sudo systemctl status firewalld
```

```
[autorunner@gcp892b829c82864a9aa9b870e795e74383 ~]$ sudo systemctl status firewalld

• firewalld.service - firewalld - dynamic firewall daemon
Loaded: loaded (/usr/lib/systemd/system/firewalld.service; enabled; vendor preset: enabled)
Active: active (running) since Fri 2020-02-14 10:24:12 UTC; 34min ago
Docs: man:firewalld(1)
Main PID: 730 (firewalld)
CGroup: /system.slice/firewalld.service
L730 /usr/bin/python2 -Es /usr/sbin/firewalld --nofork --nopid
```

b. Verify all rules are added in firewalld, all rules should be applied.

sudo firewall-cmd --list-all

Firewall changes for RPM Upgrades from Management Console 20.04 to Management Console 20.07 or newer in IPv4 Deployments

Upgrading from an operational Management Console 20.04 to Management Console 20.07 or newer in an IPv4 environment does not require any firewalld rule changes.

Confirm iptables service has been disabled

It is a good idea to confirm any previous Management Console iptables installation has been removed if your 20.04 version has been previously upgraded from an older version.

Firewalld IPv4 Script

HP has provided instructions to create a script that will apply firewalld rules that allow Management Console to work correctly in an IPv4 environment.

Instructions on creating and executing the script can be found here

Upgrades in IPv6 Environments

Firewall changes required after an Upgrade from Management Console 20.01 or older to Management Console 20.07 or newer in an IPv6 Deployment

When upgrading from a Management Console 20.01 or older installation using RPM, consideration for previous installation firewall rules must be considered. The following steps will remove previously

installed iptables IPv4 rules and add firewalld IPv6 rules so Management Console can operate properly in an IPv6 environment.

- 1. Login to Management Console host operating system console.
- 2. Check iptables status(which should be active).

```
sudo systemctl status iptables
```

```
[admin@ip-10-12-56-215 ~]$ sudo systemctl status iptables
• iptables.service - IPv4 firewall with iptables
Loaded: loaded (/usr/lib/systemd/system/iptables.service; enabled; vendor preset: disabled)
Active: active (exited) since Fri 2020-02-14 11:46:49 UTC; 12min ago
Process: 889 ExecStart=/usr/libexec/iptables/iptables.init start (code=exited, status=0/SUCCESS)
Main PID: 889 (code=exited, status=0/SUCCESS)
CGroup: /system.slice/iptables.service
```

3. Check the applied iptables rules.

```
sudo iptables -L
```

```
hain INPUT (policy ACCEPT)
              prot opt source
tcp -- anywhere
tcp -- anywhere
arget
CCEPT
                                                                                        state NEW tcp dpt:ssh
                                                          anywhere
              tcp -- anywhere
tcp -- anywhere
                                                                                        state NEW tcp dpt:pcsync-https
state NEW tcp dpt:5172
                                                          anywhere
                                                          anywhere
                                                                                        reject-with icmp-port-unreachable state RELATED, ESTABLISHED
                                                          anywhere
anywhere
                                                                                         limit: avg 5/min burst 5 LOG level debug prefix "iptables denied
                                                          anvwhere
Chain FORWARD (policy ACCEPT)
              prot opt source
all -- anywhere
                                                                                        reject-with icmp-port-unreachable
                                                          anywhere
Chain OUTPUT (policy ACCEPT)
              prot opt source
icmp -- anywhere
icmp -- anywhere
all -- anywhere
ACCEPT
ACCEPT
target prot opt source
[admin@ip- ~]$
                                                          destination
```

4. Remove rule which enabled port 8080.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 8080 -j ACCEPT
```

5. Remove rule which enabled port 8443.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 8443 -j ACCEPT
```

6. Remove rule which enabled port 5172.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 5172 -j ACCEPT
```

7. Remove rule which allowed incoming and outgoing pings.

```
sudo iptables -D INPUT -p icmp --icmp-type echo-request -j ACCEPT sudo iptables -D OUTPUT -p icmp --icmp-type echo-reply -j ACCEPT sudo iptables -D OUTPUT -p icmp --icmp-type echo-request -j ACCEPT sudo iptables -D INPUT -p icmp --icmp-type echo-reply -j ACCEPT
```

8. Remove PREROUTING rule.

```
sudo iptables -t nat -D PREROUTING -i `ip addr show | grep "state UP" |
head -1 | awk -F': ' '{print $2}'` -p tcp --dport 443 -j REDIRECT --to-port
8443
```

9. Drop incoming packets to 127/8 from other interfaces other than loopback interface.

```
sudo iptables -D INPUT -i lo -j ACCEPT
sudo iptables -D INPUT -i lo -d 127.0.0.0/8 -j REJECT
```

10. Remove outbound traffic rule.

```
sudo iptables -D OUTPUT -j ACCEPT
```

11. Remove logging rule.

```
sudo iptables -D INPUT -m limit --limit 5/min -j LOG --log-prefix "iptables denied: " --log-level 7
```

12. Remove rule which dropped packets not matching any other rule.

```
sudo iptables -D INPUT -j DROP
sudo iptables -D FORWARD -j REJECT
```

13. Save iptables service to save your changes (should show status OK).

```
sudo service iptables save
```

14. Restart iptables to apply your changes.

```
sudo systemctl restart iptables
```

15. Check iptables rules (should not contain rules which Management Console install previously added).

```
sudo iptables -L
```

```
[admin@ip-10-12-56-215 ~]$ sudo iptables -L
Chain INPUT (policy ACCEPT)
target prot opt source destination
ACCEPT tcp -- anywhere anywhere state NEW tcp dpt:ssh
ACCEPT all -- anywhere anywhere state RELATED, ESTABLISHED

Chain FORWARD (policy ACCEPT)
target prot opt source destination

Chain OUTPUT (policy ACCEPT)
target prot opt source destination

Chain LOGDROP (0 references)
target prot opt source destination

[admin@ip-10-12-56-215 ~]$
```

16. Mask iptables.

```
sudo systemctl mask iptables
```

17. Stop iptables service.

```
sudo systemctl stop iptables
```

18. Unmask firewalld, (should show removed symlink).

```
sudo systemctl unmask firewalld
```

```
[admin@ip- ~]$ sudo systemctl unmask firewalld
Removed symlink /etc/systemd/system/firewalld.service.
[admin@ip- ~]$
```

19. Enable firewalld.

```
sudo systemctl enable firewalld --now
```

20. Start firewalld.

```
sudo systemctl start firewalld
```

21. Check firewalld status (should be active).

```
sudo systemctl status firewalld
```

```
[autorunner@gcp892b829c82864a9aa9b870e795e74383 ~]$ sudo systemctl status firewalld

• firewalld.service - firewalld - dynamic firewall daemon
Loaded: loaded (/usr/lib/systemd/system/firewalld.service; enabled; vendor preset: enabled)
Active: active (running) since Fri 2020-02-14 10:24:12 UTC; 34min ago
Docs: man:firewalld(1)

Main PID: 730 (firewalld)

CGroup: /system.slice/firewalld.service
L730 /usr/bin/python2 -Es /usr/sbin/firewalld --nofork --nopid
```

a. Get the default zone. If the default zone is trusted it will allow all packets. It is recommended that the default zone is set to public.

```
sudo firewall-cmd --get-default
```

If default zone is not public, execute the following commands to set the default zone to public.

```
    i. sudo firewall-cmd --permanent --zone=trusted --remove-service=pcoip-agent
    ii. sudo firewall-cmd --set-default=public
    iii. sudo firewall-cmd --reload
```

22. Get the default zone and assign it to a variable.

```
def_zone=$(firewall-cmd --get-default)
```

23. Set the log.(all denied packets logged together)

```
sudo firewall-cmd --set-log-denied=all
```

24. Add an interface.

```
sudo firewall-cmd --permanent --zone=$(echo $def_zone) --change-
interface=`ip addr show | grep "state UP" | head -1 | awk -F': ' '{print
$2}'`
```

- 25. Enable required ports.
- 26. Open required ports.
 - IPv6 Port 443

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=443 protocol=tcp accept'
```

• IPv6 Port 22

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=22 protocol=tcp accept'
```

• IPv6 Port 5172

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=5172 protocol=tcp accept'
```

• IPv6 Port 80

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=80 protocol=tcp accept'
```

27. Allow pings.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-icmp-
block={echo-reply,echo-request} 2>/dev/null
```

28. Redirect port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8443 protocol=tcp port=443'
```

29. Redirect Port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8080 protocol=tcp port=80'
```

30. Drop incoming packets to 127/8 from other interfaces other than loopback interface.

```
sudo firewall-cmd --permanent --new-zone loopback 2>/dev/null
sudo firewall-cmd --permanent --zone=loopback --change-interface=lo 2>/dev/
null
sudo firewall-cmd --zone=loopback --permanent --set-target=ACCEPT
sudo firewall-cmd --zone=loopback --permanent --add-source=127.0.0.0/8
```

31. Reload the firewall rules.

```
sudo firewall-cmd --reload
```

32. Confirm the rules are applied.

a. Check the firewalld status is active.

b. Verify all rules are added in firewalld, all rules should be applied.

Firewalld Script for IPv6

HP has provided instructions to create a script that removes Management Console iptables rules, stops the iptables service, and enables firewalld with the required rules for Management Console to work correctly in an IPv6 deployment.

The script file is created and executed using the following steps:

1. Copy the script content and save into firewalld.sh

sudo vi firewalld.sh

```
#!/bin/bash
val1=1
if [ $val1 -eq 1 ]; then
systemctl stop iptables || service iptables stop
systemctl enable firewalld --now
def zone=$(firewall-cmd --get-default)
if [ $def zone != "public" ] ; then
    firewall-cmd --permanent --zone=trusted --remove-service=pcoip-agent
    firewall-cmd --set-default=public
    firewall-cmd --reload
    def zone=$(firewall-cmd --get-default)
fi
firewall-cmd --zone=$(echo $def zone) --permanent --remove-
port={22,443,80,5172}/tcp # Closes 22, 443, 80, 5172 port IPv4 rules
firewall-cmd --zone=$(echo $def zone) --permanent --remove-forward-
port=port=443:proto=tcp:toport=8443 # Removes IPv4 internal port
forwarding from 443 to 8443
firewall-cmd --zone=$(echo $def zone) --permanent --remove-forward-
port=port=80:proto=tcp:toport=8080  # Removes IPv4 internal port
forwarding from 80 to 8080
firewall-cmd --set-log-denied=all
firewall-cmd --permanent --zone=$(echo $def zone) --change-interface=`ip
addr show | grep "state UP" | head -1 | awk -F': ' '{print $2}'`
firewall-cmd --zone=$(echo $def zone) --permanent --add-rich-rule='rule
family=ipv6 port port=443 protocol=tcp accept'
                                                                # Open 443
port IPv6 rules
firewall-cmd --zone=$(echo $def zone) --permanent --add-rich-rule='rule
family=ipv6 port port=22 protocol=tcp accept'
                                                                # Open 22
port IPv6 rules
firewall-cmd --zone=$(echo $def zone) --permanent --add-rich-rule='rule
family=ipv6 port port=5172 protocol=tcp accept'
                                                                # Open 5172
port IPv6 rules
firewall-cmd --zone=$(echo $def zone) --permanent --add-rich-rule='rule
family=ipv6 port port=80 protocol=tcp accept'
                                                                # Open 80
port IPv6 rules
firewall-cmd --zone=$(echo $def zone) --permanent --remove-icmp-
block={echo-reply,echo-request}
Allow icmp ping reply and request
firewall-cmd --zone=$(echo $def zone) --permanent --add-rich-rule='rule
family=ipv6 forward-port to-port=8443 protocol=tcp port=443'  # Forward
IPv6 443 port to 8443
firewall-cmd --zone=$(echo $def zone) --permanent --add-rich-rule='rule
family=ipv6 forward-port to-port=8080 protocol=tcp port=80' # Forward
IPv6 80 port to 8080
firewall-cmd --permanent --new-zone loopback
firewall-cmd --permanent --zone=loopback --change-interface=lo
firewall-cmd --zone=loopback --permanent --set-target=ACCEPT
firewall-cmd --zone=loopback --permanent --add-source=127.0.0.0/8 # Not
```

```
removing loopback as some services require loopback address to function properly
firewall-cmd --reload  # Reload the firewall tables
firewall-cmd --list-all
fi 2> /dev/null
```

2. Provide permissions for the script to execute.

```
sudo chmod +x ./firewalld.sh
```

3. Run firewalld.sh:

```
sudo ./firewalld.sh
```

Firewall changes required after an RPM Upgrade from Management Console 20.04 to Management Console 20.07 or newer in an IPv6 Deployment

When upgrading from IPv4 to IPv6, firewalld IPv4 rules must be replaced with IPv6 rules.

Perform the following steps to ensure Management Console only has IPv6 rules enabled after upgrading from an IPv4 environment.

- 1. Login to Management Console operating system console using an SSH client (e.g. PuTTY).
- 2. Ensure firewalld is enabled.

```
sudo systemctl enable firewalld --now
```

3. Get the default zone. If the default zone is trusted it will allow all packets. It is recommended that the default zone is set to public.

```
sudo firewall-cmd --get-default
```

If default zone is not public, execute the following commands to set the default zone to public.

- **a.** sudo firewall-cmd --permanent --zone=trusted --remove-service=pcoip-agent
- b. sudo firewall-cmd --set-default=public
- C. sudo firewall-cmd --reload
- 4. Get the default zone and assign it to a variable.

```
def_zone=$(firewall-cmd --get-default)
```

5. Close IPv4 ports 22, 443, 80, and 5172.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-
port={22,443,80,5172}/tcp
```

6. Remove IPv4 internal port forwarding from 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-forward-
port=port=443:proto=tcp:toport=8443
```

7. Remove IPv4 internal port forwarding from 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-forward-
port=port=80:proto=tcp:toport=8080
```

8. Set the log. (all denied packets are logged together)

```
sudo firewall-cmd --set-log-denied=all
```

9. Add an interface.

```
sudo firewall-cmd --permanent --zone=$(echo $def_zone) --change-
interface=`ip addr show | grep "state UP" | head -1 | awk -F': ' '{print
$2}'`
```

10. Open required ports.

• IPv6 Port 443

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=443 protocol=tcp accept'
```

• IPv6 Port 22

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=22 protocol=tcp accept'
```

• IPv6 Port 5172

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=5172 protocol=tcp accept'
```

• IPv6 Port 80

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=80 protocol=tcp accept'
```

11. Allow pings.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-icmp-
block={echo-reply,echo-request} 2>/dev/null
```

12. Redirect port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8443 protocol=tcp port=443'
```

13. Redirect Port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8080 protocol=tcp port=80'
```

14. Drop incoming packets to 127/8 from other interfaces other than loopback interface.

```
sudo firewall-cmd --permanent --new-zone loopback 2>/dev/null
sudo firewall-cmd --permanent --zone=loopback --change-interface=lo 2>/dev/
null
sudo firewall-cmd --zone=loopback --permanent --set-target=ACCEPT
sudo firewall-cmd --zone=loopback --permanent --add-source=127.0.0.0/8
```

15. Reload the firewall rules.

```
sudo firewall-cmd --reload
```

16. Confirm the rules are applied.

a. Check the firewalld status is active.

```
sudo systemctl status firewalld
```

b. Verify all rules are added in firewalld, all rules should be applied.

```
sudo firewall-cmd --list-all
```

Firewall changes required after updating a Management Console OVA IPv4 deployment to an IPv6 Deployment

To use Management Console OVA in an IPv6 environment, the firewall rules for IPv4 should be removed and the IPv6 rules must be added so Management Console can communicate properly.

Once Management Console 20.07 or newer is deployed, log into it's host operating system console and perform the following steps.

1. Close IPv4 ports 22, 443, 80, and 5172.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-
port={22,443,80,5172}/tcp
```

- 2. Remove IPv4 internal port forwarding rules.
 - From port 443 to 8443.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-forward-
port=port=443:proto=tcp:toport=8443
```

• From port 80 to 8080.

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --remove-forward-
port=port=80:proto=tcp:toport=8080
```

- 3. Open required IPv6 ports.
 - IPv6 Port 443

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=443 protocol=tcp accept'`
```

• IPv6 Port 22

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=22 protocol=tcp accept'
```

• IPv6 Port 5172

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=5172 protocol=tcp accept'
```

• IPv6 Port 80

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 port port=80 protocol=tcp accept'
```

4. Redirect required ports.

Port 443 to 8443

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8443 protocol=tcp port=443'
```

• Port 80 to 8080

```
sudo firewall-cmd --zone=$(echo $def_zone) --permanent --add-rich-
rule='rule family=ipv6 forward-port to-port=8080 protocol=tcp port=80'
```

5. Reload firewall rules.

```
sudo firewall-cmd --reload
```

6. Confirm the rules are applied.

a. Check the firewalld status is active.

```
sudo systemctl status firewalld
```

b. Verify all rules are added in firewalld, all rules should be applied.

sudo firewall-cmd --list-all

Migrating PCoIP Management Console to a Newer Release Using firewalld

HP recommends using firewalld and thus has provisioned scripts and instructions to enable and configure firewalld. The instructions contained in this topic are for administrators who would like to use firewalld with Management Console and are making changes to an existing deployment.

Backup Your Database

Always ensure you have a working backup of your Management Console data when performing a Management Console removal, upgrade, or installation. Considerations should include:

- having a current snapshot of your virtual machine
- having a complete backup or clone of your Linux PC
- having a current backup of your Management Console database.

This topic is separated into different scenarios that differ slightly from one another based on the initial version of Management Console in use. Management Console 20.04 and newer has moved to using firewalld as it's firewall. RPM upgrades to versions 20.04 or newer do not administer any firewall configurations thus leaving the administrator in complete control of the installation. In Management Console releases 19.05 through 20.01, RPM upgrades disabled firewalld, enabled iptables and created rules that allowed Management Console to work as expected.

- Migrating PCoIP Management Console to a Newer Release Using firewalld
- Upgrades in IPv4 Environments
 - To Upgrade from Management Console 20.01 or older to 20.07 or newer in an IPv4 environment perform the following steps:
 - To upgrade from Management Console 20.04 to 20.07 or newer in an IPv4 environment perform the following steps:
- Upgrades in IPv6 Environments
 - To upgrade from Management Console 20.01 or older to 20.07 or newer in an IPv6 environment perform the following steps:
 - To upgrade from Management Console 20.04 to 20.07 or newer in an IPv6 environment perform the following steps:

• <u>To Migrate Management Console 20.07 or newer between IPv4 and IPv6 Networks using a static IP address perform the following steps:</u>

Upgrades in IPv4 Environments

To Upgrade from Management Console 20.01 or older to 20.07 or newer in an IPv4 environment perform the following steps:

The following instructions provide the steps to remove the iptables configuration applied by Management Console and steps to add firewalld rules required by Management Console to operate properly. Additional rules required to comply to your corporate security policy must be added by the administrator.

- 1. Login to the Management Console host operating system console.
- Configure your firewall. See <u>Firewall changes after a RPM Upgrade from Management Console</u> 20.01 or older using IPv4
- 3. Upgrade existing Management Console to 20.07 or newer.

```
sudo dnf install teradicimc-<mc version>.rpm
```

4. Access Management Console Web UI with IPv4 address.

To upgrade from Management Console 20.04 to 20.07 or newer in an IPv4 environment perform the following steps:

Upgrades from an existing Management Console 20.04 deployment should not require additional firewall configurations as new installs use firewalld.

- 1. Login to the Management Console host operating system console.
- 2. Upgrade the existing Management Console to new version using RPM in IPv4 environment.

```
sudo dnf install teradicimc-<mc version>.rpm
```

3. Access Management Console Web UI with IPv4 address.

Upgrades in IPv6 Environments

Loss of Data

When migrating between IPv4 and IPv6, the older unrelated data will be permanently deleted. See Deleted Datafor further details.

To upgrade from Management Console 20.01 or older to 20.07 or newer in an IPv6 environment perform the following steps:

- 1. Login to the Management Console host operating system console.
- 2. Upgrade existing 20.01 or later Management Console to 20.07 or newer.

```
sudo dnf install teradicimc-<mc version>.rpm
```

3. After RPM upgrade, perform the steps <u>Moving between IPv4 and IPv6</u> for switching between IPv4 and IPv6.

Error Message

The error message **connecting to INET family : ipv4 socket. Error No: 101, Reason: Network is unreachable** is expected behavior when upgrading to IPv6. It is OK to ignore this message.

Verify your using the new rpm

Verify your using the new rpm with this command.

```
sudo rpm -qa | grep teradici
```

```
[admin@localhost ~1$ sudo rpm -qa ¦ grep teradici
teradicimc-20.07-11780.el7.x86_64
[admin@localhost ~1$
```

4. Access Management Console Web UI with IPv6 address. Depending on your network configuration, this can be either a manual, DHCP, or SLAAC provided IPv6 address.

To upgrade from Management Console 20.04 to 20.07 or newer in an IPv6 environment perform the following steps:

Deleted data when moving between IP versions

When Management Console migrates between IPv4 to IPv6 using RPM, only the common data between IPv4 and IPv6 will be restored. The rest of the data will be deleted. For further details see <u>Deleted Data When Migrating between IP Protocols</u>

- 1. Login to the Management Console host operating system console.
- 2. Upgrade existing 20.04 Management Console to 20.07 or newer. (See tip above)

sudo dnf install teradicimc-<mc version>.rpm

Error Message

The error message **connecting to INET family : ipv4 socket. Error No: 101, Reason: Network is unreachable** is expected behavior when upgrading to IPv6. It is OK to ignore this message.

- 3. After RPM upgrade, perform the steps <u>Moving between IPv4 and IPv6</u> for switching between IPv4 and IPv6.
- 4. Access Management Console Web UI with a configured IPv6 address. Depending on your network configuration, this can be either a manual, DHCP, or SLAAC provided IPv6 address.

To Migrate Management Console 20.07 or newer between IPv4 and IPv6 Networks using a static IP address perform the following steps:

These steps must be performed in order for Management Console to operate successfully in a pure IPv6 environment when moving from an IPv4 environment.

- 1. Login to the Management Console host operating system console.
- 2. Stop mcconsole and mcdaemon services

```
sudo systemctl stop mcconsole
sudo systemctl stop mcdaemon
```

- 3. Change IP address from IPv4 to IPv6 using nmtui.
- 4. Reboot Management Console host operating system.

```
sudo init 6
```

- 5. Configure your firewall for IPv6
- 6. Run scripts to delete unrelated data.

```
cd /opt/teradici/database
sudo python3.9 mc_env_db.py
```

Error Message when migrating from IPv4 to IPv6

The error message connecting to INET family: ipv4 socket. Error No: 101, Reason: Network is unreachable is expected behavior when migrating from IPv4 to IPv6. It is OK to ignore this message.

7. Start mcconsole and mcdaemon services.

```
sudo systemctl start mcconsole
sudo systemctl start mcdaemon
```

Data deleted

When migrating from IPv4 to IPv6, the data from IPv4 will be deleted during the migration and vice versa.

Deleted data information can be found here

1. Access Management Console Web UI with the address you configured for IPv6 in step 3.

Removing Management Console iptables Configuration

This reference applies to RPM installations and upgrades from Management Console release 20.01 and older as well as all OVA and AMI installations. The following instructions, provide commands to remove the rules created for iptables by Management Console and instructions to disable the iptables service.

To remove the iptables configuration Management Console applied during installation perform these steps:

- 1. Login to Management Console host operating system console.
- 2. Check iptables status (which should be active).

```
sudo systemctl status iptables
```

```
[admin@ip-10-12-56-215 ~]$ sudo systemctl status iptables
• iptables.service - IPv4 firewall with iptables
Loaded: loaded (/usr/lib/systemd/system/iptables.service; enabled; vendor preset: disabled)
Active: active (exited) since Fri 2020-02-14 11:46:49 UTC; 12min ago
Process: 889 ExecStart=/usr/libexec/iptables/iptables.init start (code=exited, status=0/SUCCESS)
Main PID: 889 (code=exited, status=0/SUCCESS)
CGroup: /system.slice/iptables.service
```

3. Check the applied iptables rules.

```
sudo iptables -L
```

```
hain INPUT (policy ACCEPT)
                                                      destination
                                                                                  state NEW top dpt:ssh
state NEW top dpt:pcsync-https
state NEW top dpt:5172
             tcp -- anywhere
tcp -- anywhere
tcp -- anywhere
                                                      anywhere
anywhere
                                                      anywhere
                                                                                  icmp echo-request icmp echo-reply
                                                      anywhere
             all -- anywhere
                                                      anywhere
loopback/8
                                                                                  reject-with icmp-port-unreachable state RELATED, ESTABLISHED
CCEPT
                                                                                   limit: avg 5/min burst 5 LOG level debug prefix "iptables denie
                         anywhere
                                                      anywhere
Chain FORWARD (policy ACCEPT)
             prot opt source
all -- anywhere
                                                      destination
                                                                                  reject-with icmp-port-unreachable
hain OUTPUT (policy ACCEPT)
                                                      destination
                                                                                   icmp echo-reply
                                                      anywhere
             icmp -- anywhere
all -- anywhere
CCEPT
                                                      anywhere
Chain LOGDROP (0 references)
                                                      destination
```

4. Remove rule which enabled port 8080.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 8080 -j ACCEPT
```

5. Remove rule which enabled port 8443.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 8443 -j ACCEPT
```

6. Remove rule which enabled port 5172.

```
sudo iptables -D INPUT -p tcp -m state --state NEW --dport 5172 -j ACCEPT
```

7. Remove rule which allowed incoming and outgoing pings.

```
sudo iptables -D INPUT -p icmp --icmp-type echo-request -j ACCEPT sudo iptables -D OUTPUT -p icmp --icmp-type echo-reply -j ACCEPT sudo iptables -D OUTPUT -p icmp --icmp-type echo-request -j ACCEPT sudo iptables -D INPUT -p icmp --icmp-type echo-reply -j ACCEPT
```

8. Remove PREROUTING rule.

```
sudo iptables -t nat -D PREROUTING -i `ip addr show | grep "state UP" |
head -1 | awk -F': ' '{print $2}'` -p tcp --dport 443 -j REDIRECT --to-port
8443
```

9. Drop incoming packets to 127/8 from other interfaces other than loopback interface.

```
sudo iptables -D INPUT -i lo -j ACCEPT
sudo iptables -D INPUT -i lo -d 127.0.0.0/8 -j REJECT
```

10. Remove outbound traffic rule.

```
sudo iptables -D OUTPUT -j ACCEPT
```

11. Remove logging rule.

```
sudo iptables -D INPUT -m limit --limit 5/min -j LOG --log-prefix "iptables denied: " --log-level 7
```

12. Remove rule which dropped packets not matching any other rule.

```
sudo iptables -D INPUT -j DROP
sudo iptables -D FORWARD -j REJECT
```

13. Save iptable sevice to save your changes (should show status OK).

```
sudo service iptables save
```

14. Restart iptables to apply your changes.

```
sudo systemctl restart iptables
```

15. Check iptables rules (should not contain rules which Management Console install previously added).

sudo iptables -L

```
[admin@ip-10-12-56-215 ~]$ sudo iptables -L
Chain INPUT (policy ACCEPT)
target prot opt source
                                           destination
         tcp -- anywhere
all -- anywhere
                                           anywhere
                                                                   state NEW tcp dpt:ssh
ACCEPT
                                           anywhere
                                                                  state RELATED, ESTABLISHED
Chain FORWARD (policy ACCEPT)
         prot opt source
                                            destination
target
Chain OUTPUT (policy ACCEPT)
          prot opt source
                                            destination
Chain LOGDROP (0 references)
                                            destination
target prot opt source
[admin@ip-10-12-56-215 ~]$
```

16. Mask iptables.

```
sudo systemctl mask iptables
```

17. Stop iptables service.

```
sudo systemctl stop iptables
```


Deleted Data When Migrating between IP Protocols

After migrating from an IPv4 network to an IPv6 network (or vice versa), Management Console deletes data related to the removed IP version.

This table provides descriptions of data that is deleted and uses an example of a migration from IPv4 to IPv6.

✓ IPv6 to IPv4 migrations

Similarly, IPv6 data is deleted when migrating from IPv6 to IPv4.





Tab Name	Display	Display
Migration Behavior	Before Migration	After Migration
All softwares will be restored.	● O Anyone	O ANYWOOD STANDARD STAND STAND STAND STAND STANDARD STAND

PCoIP Management Console Troubleshooting

Troubleshooting

Troubleshooting

The troubleshooting section of this guide allows users to easily find the topics and links that are required for various aspects of troubleshooting your PCoIP Management Console.

• The PCoIP Management Console records logs of its activity on a rotational basis. Logs also have two levels which can be set depending on how much details is required to solve an issue. For further information, see Management Console Logs.

Troubleshooting Endpoints in Recovery Mode

Recovery mode is a special version of the PCoIP Zero Client firmware that takes effect when the client experiences a problem that renders it unable to operate. Recovery mode automatically becomes active under the following conditions:

- · A firmware update fails.
- The client has an invalid configuration.
- The client has been unable to complete its boot sequence after a number of attempts.

This mode lets you correct the configuration, or upload a replacement firmware or certificate file. You can do this directly from a client's AWI or you can use a PCoIP Management Console profile to correct the problem.


Locating Endpoints in Recovery Mode

✓ Note: Recovery mode is only available for PCoIP Zero Clients

Recovery mode is not available on Remote Workstation Cards.

If you have an endpoint in recovery mode, make a note of its firmware version number. You can then locate all endpoints in recovery mode from the PCoIP Management Console ENDPOINTS page by creating a filter to display endpoints running this firmware version.

The following example creates a filter for firmware version earlier than 5.0.0.



Filter criterion for finding endpoints in recovery mode

Recovery Mode Causes and Solutions

The following problems can cause an endpoint to be in recovery mode:

- The client may have been forced into recovery mode by a user repeatedly tapping the power button when turning on the endpoint. If so, rebooting (resetting) the PCoIP Zero Client may return it to the main firmware.
- If the client does not load the main firmware but boots into the recovery image immediately when powered up, then it is likely that a firmware upload operation was interrupted and the client does not contain a valid firmware image. Apply a profile to upload a new firmware image to the PCoIP Zero Client and reboot the client to return to working firmware.
- If the PCoIP Zero Client attempts to boot to the main firmware images a few times (the splash screen is displayed for a bit) but eventually switches to the recovery image, then it is likely that the firmware configuration is not valid. See Resetting Endpoint Properties to Their Defaults to clear this problem and then re-provision the endpoint.

PCoIP Management Console Recovery Mode Examples

Recovery Mode Examples

The following example shows a client with a completed firmware upload status. It may have switched to recovery mode by a user repeatedly tapping its power button. In this case, simply performing a power reset may recover the endpoint.



Client in Recovery Mode with Completed Firmware Upload

The next example shows a client in recovery mode because a firmware upload was interrupted. In this case, applying the profile will download the firmware again and may recover the endpoint.



Client in Recovery Mode with Failed Firmware Upload

Client in Recovery Mode with Failed Firmware Upload

If rebooting a client or uploading firmware again does not recover the endpoint, you must reset parameters to factory defaults and re-provision the endpoint.

Note: Use the client's AWI to reset and configure parameters

You can also use the client's AWI to reset parameters and reconfigure it. See Accessing an Endpoint's AWI.

PCoIP Management Console Troubleshooting DNS

Troubleshooting DNS

This troubleshooting reference provides some steps to perform to ensure that you have the correct PCoIP Management Console information configured in your DNS server.

> N

Note: Instructions are for Windows only

These instructions apply to the Windows platform.

The procedure shown next checks that you have a DNS A record that maps the PCoIP Management Console's host name to its IP address for forward lookups, and a DNS PTR record that maps the PCoIP Management Console's IP address to its host name for reverse lookups. In addition, it checks that a DNS SRV record for **_pcoip-bootstrap** exists, and that the DNS TXT record containing the PCoIP Management Console's certificate fingerprint exists and is located in the right place.

Also note that:

DNS records have a time-to-live value that dictates how long the records are cached. If your nslookup results show old information, please try clearing the PC's DNS cache using the ipconfig /flushdns command before running the nslookup commands in this example again. For example,

C:\Users\username> ipconfig /flushdns

```
Windows IP Configuration
Successfully flushed the DNS Resolver Cache
```

- PCoIP Zero Client endpoints will cache DNS results for the entire time-to-live period. You can clear this cache by power cycling the endpoint.
- The following SHA-256 fingerprint shown is the default PCoIP Management Console certificate fingerprint. If you have created your own certificates, this value will be different.
- The following example uses sample IP addresses and host names for the primary DNS server and PCoIP Management Console. Please substitute your own server and PCoIP Management Console 2 information for these names and addresses.
- The information returned by the **nslookup** commands is shown in gray text after each command.

PCoIP Management Console Troubleshooting DNS

To verify DNS PCoIP Management Console information:

- 1. Log in to your Windows server.
- 2. Launch a command prompt window by clicking the **Start** button and typing **cmd** in the Search box.
- 3. Launch **nslookup** from the command line prompt:

C:\Users\username> nslookup

Default Server: mydnsserver.mydomain.local

Address: 172.15.25.10

4. Instruct **nslookup** to connect to the DNS server under which you created the records. This address should match the primary DNS server address configured in the endpoint's network settings.

> server 172.15.25.10

Default Server: mydnsserver.mydomain.local

Address: 172.15.25.10

5. Enter the FQDN of your PCoIP Management Console to perform a forward lookup to verify that a DNS A record that maps the PCoIP Management Console host name to its IP address is present:

> pcoip-mc.mydomain.local

Server: mydnsserver.mydomain.local

Address: 172.15.25.10

Name: pcoip-mc.mydomain.local

Address: 172.25.15.20

6. Enter the PCoIP Management Console's IP address (found in the previous step) to perform a reverse lookup to verify that a DNS PTR record that maps the PCoIP Management Console IP address to its host name is present:

> 172.25.15.20

Server: mydnsserver.mydomain.local

Address: 172.15.25.10

Name: pcoip-mc.mydomain.local

Address: 172.25.15.20

7. Set the record type to **SRV** and check that a DNS SRV record exists to tell endpoints the FQDN of the PCoIP Management Console. In the second command, the domain name is the domain under which your endpoints are configured:

> set type=srv

> _pcoip-bootstrap._tcp.myendpointdomain.local

PCoIP Management Console Troubleshooting DNS

Server: mydnsserver.mydomain.local

Address: 172.15.25.10:

> _pcoip-bootstrap._tcp.myendpointdomain.local SRV service location:

priority =0 weight =0 port =5172

svr hostname =pcoip-mc.mydomain.local

pcoip-mc.mydomain.local internet address = 172.25.15.20

8. Set the record type to **TXT** and check that a DNS TXT record exists containing the PCoIP Management Console SHA-256 fingerprint. In the second command, the domain name is the domain under which your endpoints are configured.

> set type=txt

> pcoip-mc.myendpointdomain.local

Server: mydnsserver.mydomain.local

Address: 172.15.25.10

pcoip-mc.mydomain.local text = "pcoip-bootstrap-cert=

B7:62:71:01:85:27:46:BB:E3:E9:5C:E2:34:2C:B5:76:7D:7A:F1:7F:6A:4D:5C:DB:AA:2B:

99:BD:D5:A9:28:91"

9. Exit nslookup:

> exit

Viewing License Information via Command Line

If you need to find license information and are having issues using the Management Console web interface, you can use the **mc_view_lic.sh** script to view licensing information such as the **Fulfillment ID** and **Entitlement ID**(activation code).

You can find the script in /opt/teradici/licensing/ folder.

Deactivating and Activating Licenses via Command Line

If you are using PCoIP Management Console Enterprise host operating system console, you can also deactivate the PCoIP Management Console Enterprise license by using the **my_return_lic.sh** script.

To deactivate your Management Console license, run the following command:

```
/opt/teradici/licensing/mc_return_lic.sh -f <fulfillment_ID>
```

To deactivate your Management Console license when it is behind a proxy, run the following command:

```
/opt/teradici/licensing/mc_return_lic.sh -f <fulfillmentId> -p
[<user:password>@] proxyhost:port>
```

To activate your Management Console license, run the following command:

```
/opt/teradici/licensing/mc_activate_lic.sh -k < entitlementID >
```

To activate your Management Console license when it is behind a proxy, run the following command.

```
/opt/teradici/licensing/mc_activate_lic.sh -k <entitlementID> -p
[<user:password>@ <proxyhost:port>
```

PCoIP Management Console FAQ

FAQ

FAQs

The latest PCoIP Management Console FAQs can be found here.

PCoIP Management Console Support

Support

Contacting Support

If you encounter any problems installing, configuring, or running the PCoIP Management Console, you can create a support ticket with HP.

Before creating a ticket, be prepared with the following:

- · A detailed description of the problem
- The version or versions of PCoIP Management Console involved in the problem. See <u>Managing PCoIP Management Console Logs</u>
- Appropriate logs that capture the issue. Locating the PCoIP Management Console's Log Files

The Community Forum

The PCoIP Community Forum enables users to have conversations with other IT professionals to learn how they resolved issues, find answers to common questions, have peer group discussions on various topics, and access the Global Support Service team. HP staff are heavily involved in the forum.

To visit the community, go to https://help.teradici.com/s/discussions.

Finding the PCoIP Management Console Release Number

You can find your PCoIP Manamgement Console release number using the PCoIP Manamgement Console Dashboard.

To find your PCoIP Manamgement Console release number:

Browse to your PCoIP Management Console and view the release number at the bottom of the left of the web interface. It will be in the format of #.#.#@####. For example, 19.05@9507